


Honeywell Zephyr™ Digital Airflow Sensors: HAF Series – High Accuracy



DESCRIPTION

Honeywell Zephyr™ HAF Series sensors provide a digital interface for reading airflow over the specified full-scale flow span and temperature range. The thermally isolated heater and temperature sensing elements help these sensors provide a fast response to air or gas flow.

Zephyr sensors are designed to measure mass flow of air and other non-corrosive gases. Standard flow ranges are available from ± 50 SCCM to ± 750 SCCM. The sensors are fully calibrated and temperature compensated with an onboard Application Specific Integrated Circuit (ASIC).

The HAF Series is compensated over the temperature range of $0\text{ }^{\circ}\text{C}$ to $50\text{ }^{\circ}\text{C}$ [$32\text{ }^{\circ}\text{F}$ to $122\text{ }^{\circ}\text{F}$] and operates across a temperature range of $-20\text{ }^{\circ}\text{C}$ to $70\text{ }^{\circ}\text{C}$ [$-4\text{ }^{\circ}\text{F}$ to $158\text{ }^{\circ}\text{F}$]. The state-of-the-art ASIC-based compensation provides digital (I^2C) outputs with a response time of 1 ms.

FEATURES AND BENEFITS (★ = competitive differentiator)

- ★ Total error band as low as $\pm 2.25\%$ FSS allows for very precise airflow measurement, often ideal for demanding applications with high accuracy requirements
- ★ Wide range of airflows:
 - Zephyr detects presence or absence of airflow from 50 SCCM up to 750 SCCM, increasing the options for integrating the sensor into the application
 - High sensitivity at very low flows
- ★ Full calibration and temperature compensation typically allow customer to remove additional components associated with signal conditioning from the PCB, reducing PCB size as well as costs often associated with those components (e.g., acquisition, inventory, assembly)
- ★ Customizable for specific end-user needs
- ★ High stability reduces errors due to thermal effects and null shift to provide accurate readings over time, often eliminating need for system calibration after PCB mount and periodically over time
- ★ Low pressure drop typically improves patient comfort in medical applications, and reduces noise and system wear on other components such as motors and pumps
- ★ Linear output provides more intuitive sensor signal than the raw output of basic airflow sensors, which can help reduce production costs, design, and implementation time
- ★ Fast response time allows a customer's application to respond quickly to airflow change, important in critical medical (e.g., anesthesia) and industrial (e.g., fume hood) applications
- High 12-bit resolution increases ability to sense small airflow changes, allowing customers to more precisely control their application
- Low 3.3 Vdc operating voltage option and low power consumption allow for use in battery-driven and other portable applications
- ASIC-based I^2C digital output compatibility eases integration to microprocessors or microcontrollers, reducing PCB complexity and component count
- Bidirectional flow sensing capability eliminates the need for two airflow sensors, helping to reduce production costs and implementation time
- Insensitivity to mounting orientation allows customer to position sensor in most optimal point in the system, eliminating concern for positional effects
- Insensitivity to altitude eliminates customer-implemented altitude adjustments in the system, easing integration and reducing production costs by not having to purchase additional sensors for altitude adjustments
- Small size occupies less space on PCB, allowing easier fit and potentially reducing production costs; PCB size may also be reduced for easier fit into space-constrained applications
- RoHS-compliant materials meet Directive 2002/95/EC

Honeywell Zephyr™ Digital Airflow Sensors

POTENTIAL APPLICATIONS

Medical

- Anesthesia delivery machines
- Ventricular assist devices (heart pumps)
- Hospital diagnostics (spectrometry, gas chromatography)
- Nebulizers
- Oxygen concentrators
- Patient monitoring systems (respiratory monitoring)
- Sleep apnea machines
- Spirometers
- Ventilators

Industrial

- Air-to-fuel ratio
- Analytical instrumentation (spectrometry, chromatography)
- Fuel cells
- Gas leak detection
- Gas meters
- HVAC filters
- VAV system on HVAC systems
- Meteorology

Table 1: Absolute Maximum Ratings¹

Characteristic	Parameter
Supply voltage	-0.3 Vdc to 6.0 Vdc
Voltage on output pin	-0.3 V to Vsupply
Storage temperature range	-40 °C to 125 °C [-40 °F to 257 °F]
Maximum flow change	5.0 SLPM/s
Maximum common mode pressure	25 psi at 25 °C [77 °F]
Maximum flow	10 SLPM

CAUTION

IMPROPER USE

Do not use these products to sense liquid flow. Failure to comply with these instructions may result in product damage.

Note 1: Absolute maximum ratings are the extreme limits that the device will withstand without damage to the device. However, the electrical and mechanical characteristics are not guaranteed as the maximum limits (above recommended operating conditions) are approached, nor will the device necessarily operate at absolute maximum ratings.

Table 2: Operating Characteristics

Characteristic	Parameter	Note
Supply voltage	3.3 Vdc ±10%; 5.0 Vdc ±10%	–
Supply current	16 mA max.	–
Power:		–
3.3 Vdc	23 mW typ.	
5.0 Vdc	38 mW typ.	
Operating temperature range	-20 °C to 70 °C [-4 °F to 158 °F]	–
Compensated temperature range	0 °C to 50 °C [32 °F to 122 °F]	1
Accuracy	See Figure 1	2, 4
Total error band (TEB)	See Figure 2	3, 4
Null accuracy	±0.02% FSS	4, 10
Response time	1 ms typ.	5
Resolution	12 bit min.	–
Start up time	17 ms	6
Warm up time	30 ms	7
Calibration media	gaseous nitrogen	8
Bus standards	I ² C, fast mode (400 kHz)	9
Null stability	±0.01% FSS maximum deviation from null output after 1000 hours at 25 °C	–
Reverse polarity protection	no	–

Notes:

1. Custom and extended compensated temperature ranges are possible. Contact Honeywell for details.
2. Accuracy is the maximum deviation from the nominal digital output over the compensated flow range at a reference temperature of 25 °C. Errors include offset, span, non-linearity, hysteresis and non-repeatability (see Figure 1 for the Accuracy Error Band vs Flow).
3. Total error band includes all errors over the compensated flow range including all effects due to temperature over the compensated temperature range (see Figure 2 for the Total Error Band).
4. Full Scale Span (FSS) is the algebraic difference between the digital output at the forward Full Scale (FS) flow and the digital output at the reverse FS flow. Forward flow is defined as flow from P1 to P2 as shown in Figure 2. The references to mass flow (SCCM) refer to gas flows at the standard conditions of 0 °C and atmospheric pressure 760 (101.3 kPa).
5. Response time: time to electrically respond to any mass flow change at the microbridge airflow transducer (response time of the transducer may be affected by the pneumatic interface).
6. Start-up time: time to first valid reading of serial number proceeding streaming 14-bit flow measurements.
7. Warm-up time: time to the first valid flow measurement after power is applied.
8. Default calibration media is dry nitrogen gas. Please contact Honeywell for other calibration options.
9. Refer to Honeywell Technical Note for I²C protocol information.
10. Null accuracy is the maximum deviation in output at 0 SCCM from the ideal transfer function over the compensated temperature range. This includes offset errors, thermal airflow hysteresis and repeatability errors.

HAF Series – High Accuracy

Figure 1. Accuracy Error Band for Bidirectional Forward Flow Optimized





Figure 2. Total Error Band for Bidirectional Forward Flow Optimized



	Applied Flow (SCCM)	Accuracy Error (%FSS)		Applied Flow (SCCM)	Total Error Band (%FSS)
±50 SCCM Sensor Range	-50 to -16.7	±0.06 x flow (±6% reading)	±50 SCCM Sensor Range	-50 to -14.3	±0.07 x flow (±7% reading)
	-16.7 to 0	±1		-14.3 to 0	±1
	0	±0.08		0	±0.08
	0 to 20	±1		0 to 14.3	±1
	20 to 50	±0.05 x flow (±5% reading)		14.3 to 50	±0.07 x flow (±7% reading)
±100 SCCM Sensor Range	-100 to -14.3	±0.035 x flow (±7% reading)	±100 SCCM Sensor Range	-100 to -14.3	±0.035 x flow (±7% reading)
	-14.3 to 0	±0.5		-14.3 to 0	±0.5
	0	±0.04		0	±0.04
	0 to 20	±0.5		0 to 16.7	±0.5
	20 to 100	±0.025 x flow (±5% reading)		16.7 to 100	±0.03 x flow (±6% reading)
±200 SCCM Sensor Range	-200 to -11.1	±0.0225 x flow (±9% reading)	±200 SCCM Sensor Range	-200 to -11.1	±0.0225 x flow (±9% reading)
	-11.1 to 0	±0.25		-11.1 to 0	±0.25
	0	±0.02		0	±0.02
	0 to 40	±0.25		0 to 22.2	±0.25
	40 to 200	±0.006 x flow (±2.5% reading)		22.2 to 200	±0.01125 x flow (±4.5% reading)
±400 SCCM Sensor Range	-400 to -26.7	±0.0112 x flow (±9% reading)	±400 SCCM Sensor Range	-400 to -32	±0.0125 x flow (±10% reading)
	-26.7 to 0	±0.3		-32 to 0	±0.4
	0	±0.02		0	±0.02
	0 to 68.6	±0.3		0 to 71.1	±0.4
	68.6 to 400	±0.0044 x flow (±3.5% reading)		71.1 to 400	±0.00625 x flow (±4.5% reading)
±750 SCCM Sensor Range	-750 to -31.3	±0.008 x flow (±12% reading)	±750 SCCM Sensor Range	-750 to -31.25	±0.008 x flow (±12% reading)
	-31.3 to 0	±0.25		-31.25 to 0	±0.25
	0	±0.02		0	±0.02
	0 to 68.2	±0.25		0 to 50	±0.25
	68.2 to 750	±0.0036 x flow (±5.5% reading)		50 to 750	±0.005 x flow (±7.5% reading)

Table 3. Environmental Characteristics

Characteristic	Parameter
Humidity	0% to 95% RH, non-condensing
Shock	100 g, 11 ms
Vibration	15 g at 20 Hz to 2000 Hz
ESD	Class 3B per MIL-STD 883G
Radiated immunity	Level 3 from (80 MHz to 1000 MHz) per spec IEC61000-4-3

Table 4. Wetted Materials

Characteristic	Parameter
Covers	high temperature polymer
Substrate	PCB
Adhesives	epoxy
Electronic components	silicon, gold

Honeywell Zephyr™ Digital Airflow Sensors

Compliance	RoHS, WEEE
------------	------------

Table 5. Recommended Mounting and Implementation

Characteristic	Parameter
Mounting screw size	5-40
Mounting screw torque	0.68 N m [6 in-lb]
Tubing for long port style	70 durometer, size 0.125 inch inside diameter, 0.250 inch outside diameter silicone tubing
O-ring for short port style	AS568A, Size 7, Silicone, Shore A 70
O-ring for long port style	AS568A, Size 10, Silicone, Shore A 70
Filter recommendation	5-micron filter upstream of the sensor

CAUTION

LARGE PARTICULATE DAMAGE

Use a 5-micron filter upstream of the sensor to keep media flow through the sensor free of condensing moisture and particulates. Large, high-velocity particles or conductive particles may damage the sensing element.

Failure to comply with these instructions may result in product damage.


Figure 3. Nomenclature and Order Guide

<p>Series HAF = High accuracy airflow sensor</p> <p>Flow Direction B = Bidirectional forward flow optimized S = Bidirectional symmetric (coming soon) U = Unidirectional symmetric (coming soon)</p> <p>Port Style L = Long port¹ S = Short port</p> <p>Housing Style F = Fastener mount S = Snap mount¹</p> <p>Flow Range² 0050 = 50 long port style only 0100 = 100 long port style only 0200 = 200 long or short port 0400 = 400 long port style only 0750 = 750 long port style only</p>	<p>HAF B C A X</p>	<p>Supply Voltage 3 = 3.3 Vdc 5 = 5.0 Vdc</p> <p>Reserved for Future Use</p> <p>Transfer Function A = 10% to 90% of Full Scale Output (FSO)</p> <p>Output Format 4 = digital I²C address: 0x49 5 = digital I²C address: 0x59 6 = digital I²C address: 0x69 7 = digital I²C address: 0x79</p> <p>Unit C = SCCM</p>	<p>Example Catalog Listing HAFBLF0200C4AX5 = High accuracy airflow sensor, bidirectional forward flow optimized, long port style, fastener mount housing, 200 SCCM, digital I²C output with address 0x49, 10% to 90% transfer function, 5.0 Vdc supply voltage.</p> <p>Customer-specific Requirements Apart from the general configuration required, other customer-specific requirements are also possible. Please contact Honeywell.</p>
--	--------------------	--	---

Notes:

- The long port **port style** with the snap mount **housing style** is not a valid configuration.
- The 200 SCCM flow range is available in the long and short port styles.

Figure 4. Nominal Digital Output



Ideal Transfer Function

$$\text{Digital Output Code} = 16383 * [0.5 + 0.4 * (\text{Flow Applied}/\text{Full Scale Flow})]$$

$$\text{Flow Applied} = \text{Full Scale Flow} * [(\text{Digital Output Code}/16383) - 0.5]/0.4$$

HAF Series – High Accuracy

Figure 5. Long Port Style Flow vs Pressure




Figure 6. Short Port Style Flow vs Pressure






Figure 7. Wave Solder Profile



Honeywell Zephyr™ Digital Airflow Sensors

Figure 8. Mounting Dimensions (For reference only: mm [in]). Additional port and housing styles available.



⚠ WARNING

PERSONAL INJURY

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell web site, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

⚠ WARNING

MISUSE OF DOCUMENTATION

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

SALES AND SERVICE

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office or:

E-mail: info.sc@honeywell.com

Internet: www.honeywell.com/sensing

Phone and Fax:

Asia Pacific	+65 6355-2828
	+65 6445-3033 Fax
Europe	+44 (0) 1698 481481
	+44 (0) 1698 481676 Fax
Latin America	+1-305-805-8188
	+1-305-883-8257 Fax
USA/Canada	+1-800-537-6945
	+1-815-235-6847
	+1-815-235-6545 Fax

Sensing and Control
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422
www.honeywell.com

008178-5-EN
February 2012
© 2012 Honeywell International Inc.

Honeywell