




TECHNICAL DATA SHEET

Euro Beacon




*Magnetic version shown.



LBB755K

Euro Beacon, 3 bolt


Dimensions: Dia. 143mm H. 163mm



LBB760K

Euro Beacon, Magnetic


Dimensions: Dia. 143mm H. 163mm



LBB722

Euro Beacon, 1 Bolt


Dimensions: Dia. 143mm H. 163mm



LBB749

Euro Beacon, DIN

Dimensions: Dia. 129mm H. 177mm



LBB772

Euro Beacon, Flexi DIN

Dimensions: Dia. 135mm H. 230mm

Features

- Changing the bulb is easier than ever with our new easy to use spring clip.
- Dual voltage 12/24V.
- New rubber Flexi DIN fixing option is designed as a single unit base to provide robust durability for agricultural applications.

Specification

Voltage: 12/24V
 Flash rate: 150 FPM
 Temperature range: -20°C to +50°C
 Lens material: Polycarbonate
 Lens colour: Amber

Approvals

ECE Reg, 65 'E'
 72/245/EEC 'e'



Lucas Warning & Safety
 Victoria Industrial Estate
 Victoria Road
 Leeds
 LS14 2LA.

Tel: 0870 608 0763
 Fax: 0113 237 5630