

MICRO SWITCH™ 914CE Miniature Limit Switch Product Nomenclature



For example, a **914CE29-3** part number would define a 914CE Series miniature limit switch with a panel mount perpendicular top roller plunger and three feet of cable.



914CE	29	—	3		
Switch Type	Actuator Type		Cable Length	Options	Connectors
914CE Series Small Precision Limit Switch	1 Top pin plunger	27 Top pin plunger panel mount	3 3 feet	A Side entry	Q dc type Brad Harrison
	2 Top roller plunger, parallel	28 Top roller plunger, parallel panel mount	6 6 feet	G Gold contacts	Q1 ac type two keyways
	3 Top roller plunger, perp.	29 Top roller plunger, perp. panel mount	9 9 feet	P Top mounting	Q2 dc type plastic
	16 Front rotary	31 Top roller plunger, parallel boot seal	12 12 feet	L1 Low temp. -40 °C, cable not for flexing	
	18 Top pin plunger w/ boot seal	55 Top roller plunger, perp. boot seal	15 15 feet	V Vitron seals/gasket (front rotary only)	
	19 Top adjustable pin plunger	66 Top ball bearing plunger		Bottom exit is standard.	
	20 Coil wobble				
	22 Manually oper. nylon button				

NOTE: not all combinations of model code are available.
Please contact your Honeywell provider/representative for assistance.