

HC-F5V-90L-90LED-WS2813 Specification

I. Product Description

- Every LED works as an individual pixel, it can achieve effects of Full Color Water Running, Chasing and Scanning, which thanks to its high brightness.
 - This LED strip could only be linked up to 3 meters, more than 3 meters is strictly prohibited.
- The diameter of the power wires should be based on the actual maximum current, power, and its cabling length (no more than 3 meters), and the voltage of transmission line.
 - Widely applied to hotel, KTV entertainment place for interior decorative lighting, etc.

II. Physical parameters

Working Voltage: DC5V

LED resource: WS2813 LED (Signal Break-point Continuous Transmission)

LED Type: SMD5050 RGB **LED Quantity**: 90LEDs/Meter

Working Current: 0.06A/Cut; 5.4A/Meter

Width: 10mmLength: 3 Meters per ReelMax. Power: 27Watt/meterViewing Angle: ≥140°CCircuit Board: Double FPCBFPCB Color: White/Black

Package: Anti-static plastic bag

Weight: 250g(Silicone Glue) 120g(Bare board) 235g(Silicone Tube)

IP Grade: IP20/IP60/IP65/IP68
Working Temperature: -40°C ~ 60°C

Storage Temperature: -40 ° ~ 80 ° C

Lifespan: 50000 Hours

Terminal connectors: 4PIN Connector

III. Glowing Effect





HC-F5V-90L-90LED-WS2813 Specification

IV. Distribution wiring diagram

