LEDDEX

PRODUCT DATA

Order code LED Type Luminous efficacy Typical luminous flux, lm Wattage Ingress protection Colometric data, CCT Color rendering index LED strip Dimensions , mm Operating temperature L80 lifetime

LS-LUM24V-15W-XXXXX 2835 180 lm/W 2520 lm/m 15 W/m IP 20 3000/4000/5000/6500 K 85 CRI 5000 x 5 x 2.5 mm -20°C ~ +40°C L80B10 > 36000 hours (@Ta 25 °C) 3 years limited

1.5 mm



15W/M

120 LED/N

RoHS

((

IP 20

DC 24V





Lightsheet Signage Accent lighting Furniture

Warranty



CUT ONLY WHERE IT IS SPECIFIED

SHIPPING INFORMATION

Single bag quantity Carton box quantity 5m 500m

- This product is only suitable for connection to dedicated Class 1 or Class 2 power supplies rated DC24V (± 5%)
- This product is not to draw a total wattage of greater than the secondary (output) rating of the power supply
- This product is suitable for use in dry locations
- Specifications of the products might change without further notice. Make sure to use the most recent

Datasheet last updated on 2018-09

LEDDEX, Ltd. Address Elektrinés str. 8, Vilnius LT-03150, Lithuania Tel./Fax. +370 5 212 7244 Email info@leddex.eu Website www.leddex.eu