



6-557315-2 | MP-88U-R-5  
**Modular Plug, 8P/8C, Unshielded, Round, 500 pcs**

## Body Features

Conductor Type Solid | Stranded

## Configuration Features

Number of Positions 8  
Keyed No

## Contact Features

Contact Base Material Phosphor bronze  
Contact Mating Area Plating Material Gold  
Contact Mating Area Plating Thickness 50.00 µin | 1.27 µm  
Number of Contacts Loaded 8

## Dimensions

Cable Jacket Outside Diameter Range 0.20 in | 5.1 mm  
Conductor Outside Diameter 0.034–0.039 in | 0.86–0.99 mm  
Conductor Wire Size 26–24 AWG

## Housing Features

Housing Material Glass filled polycarbonate

## Industry Standards

UL Flammability Rating UL 1863

## Packaging Features

Packaging Quantity 500

## Product Availability

Region Asia | Australia/New Zealand | EMEA | Latin America | North America

## Product Type Features

Cable Type Round, unshielded  
Performance Category Category 5  
Connector Style Plug  
Jack Type RJ45

6-557315-2 | MP-88UR-5

Latch Style	Standard
Product Type	Connector
Shielded	No

## Termination Features

---

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
----------------------------------	-------------------------------------