



RECOMMENDED MOUNTING HOLE

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 4. PHOSPHOR BRONZE PER QQ-B-750
- 5. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE

1. MAX. PANEL THICKNESS=3.2mm

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES
0.5-6 = ±0.2
6-30 = ±0.4
30-120 = ±0.6
120-315 = ±1
315-1000 = ±1.6
1000-2000 = ±2.4

PART NO. B6351B1-ND3G-50

APPROVED DATE 10-11-01'

CHECKED DATE 10-11-01'

DRAWN DATE 10-11-01'

FILE NO.

**Amphenol**

TITLE BNC BULKHEAD RECEPT. JACK

DRAWING NO. KJ-B6351B1-ND3G-50

ITEM NO.

NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.
6	SOLDER TAG			1	B7310-7
5	HEX NUT			1	HN127-3/8-32 X23
4	LOCK WASHER			1	LW-127/97X05
3	CONTACT PIN			1	B7310-3-50
2	INSULATOR	DELTRIN	NATURAL	1	B7310-2-50-C
1	BODY			1	B7310-1