

		REVISIONS													
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE													
							<p>RECOMMENDED CABLE STRIPPING DIM'S</p>		<p>1. CRIMPED FERRULE HEX CRIMP SIZE .128"</p> <p>2. CONTACT PIN TO SOLDER</p> <p>3. MAX. PANEL THICKNESS=3.2mm</p>						
		<p>1/4-36UNS-2A</p> <p>8 HEX</p> <p>11.4</p> <p>16.3</p>			<p>9.8</p>		<p>9.8</p> <p>0.6</p> <p>1.43</p>		<p>0.6</p> <p>2.7</p>		<p>5.4</p> <p>10.3</p> <p>1</p> <p>1.7</p>				
		<p>6.35 HEX</p> <p>4.5</p> <p>5.2</p>			<p>6</p> <p>10.2</p>		<p>1.6</p>		<p>5.5</p> <p>2.4</p> <p>3.8</p>						
		<p>6</p> <p>6.5</p> <p>6</p>			<p>RECOMMENDED MOUNTING HOLE</p>		<p>19.3</p> <p>3</p> <p>3.6</p>								
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)</p> <p>1. BRASS PER QQ-B-626</p> <p>2. BRASS PER QQ-B-613</p> <p>3. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>4. BERYLLIUM COPPER PER QQ-C-530</p> <p>5. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE</p> <p>6. TEFLON MIL-P-19468</p>															
10	HEAT SHRINK TUBING			1	HT-36/3X193										
9	FERRULE	COPPER	NOTE 3	1	FR-38/24X55C										
8	HEX NUT	NOTE 1	NOTE 3	1	HN8-1/4-36X16										
7	LOCK WASHER	NOTE 2	NOTE 3	1	LW-102/65X05										
6	HEX NUT	NOTE 1	NOTE 3	1	SMA5003-9-635/45										
5	BARREL	NOTE 1	NOTE 3	1	SMA1111G2-8-17/1										
4	INSULATOR	NOTE 6	NATURAL	1	SMA1111G2-7										
3	CONTACT PIN	NOTE 4	NOTE 5	1	SMA6411G2-3-143/06										
2	INSULATOR	NOTE 6	NATURAL	1	SMA6411G2-2T-50										
1	BODY	NOTE 1	NOTE 3	1	SMA7403-1-B										
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	2.5/1	ISSUE	A	FILE NO.					

DIMENSIONS ARE IN MILLIMETERS

UNLESS OTHERWISE SPECIFIED TOLERANCES

0.5-6 = ±0.2

6-30 = ±0.4

30-120 = ±0.6

120-315 = ±1

315-1000 = ±1.6

1000-2000 = ±2.4

PART NO.	SMA6411G2-3GT50G-14-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'
SCALE	2.5/1
ISSUE	A
FILE NO.	

Amphenol

TITLE SMA BULKHEAD CRIMP JACK (FOR 178B/U,196A/U)

DRAWING NO. KJ-SMA6411G2-3GT50G-196A/U-50

ITEM NO