

Ordering Information:



C5080HI -04P-XX




1 2 3

1. Series No.
2. No. of Circuits
3. AWG Of Wire
  - 16 - AWG#16
  - 18 - AWG#18
  - 20 - AWG#20
  - 22 - AWG#22




SPECIFICATIONS

Current Rating: 10A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Terminal: Phosphor Bronze/Tin-plated  
 Material: Nylon 66,UL94V-2  
 Color: Natural(Translucent)

				JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
		UNIT	SCALE	SHEET	TITLE:
		mm		1 of 1	
		DRAWN BY	APPROVED BY		5.08mm PITCH I. D. C. HOUSING
		歐陽小強	董正一		
		2007.04.25	2007.04.25		
		GENERAL TOLERANCE			DRAW NO. : C5080HI -04P-XX
		X. X±0.25	ANGLE±		
		X. XX±0.15			
AO	NEW RELEASE	2007.04.25	X. XXX±0.05		REV. AO
REV.	DESCRIPTION	DATE			



C5080HI-C(Through type)



C5080HI-CA(End type)

SPECIFICATIONS

Current Rating: 10A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-2  
 Color: Natural(Translucent)



JOINT TECH ELECTRONIC IND. CO., LTD.  
 JOY DAY INDUSTRIAL CO., LTD.

UNIT SCALE SHEET  
 mm 1 of 1

DRAWN BY APPROVED BY  
 董正一 董正一  
 2001.02.01 2001.02.01

GENERAL TOLERANCE

X. X±0.25 ANGLE±  
 X. XX±0.15  
 X. XXX±0.05

TITLE:  
 5.08mm PITCH  
 COVER OF I. D. C. HOUSING

BO	NEW RELEASE	2005.12.12	X. XX±0.15	
REV.	DESCRIPTION	DATE	X. XXX±0.05	

DRAW NO. : C5080HI-C(A) REV. B0