Order No. 1693810000 Part designation ZOV 2.5N/3 GE Version Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3 EAN 400819083645 Gly. 60 pc(s). Additional technical data Explosion-tested version "Ex e" No Cross-connector Height 23 mm No. of cross-connected terminals 3 Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type of fixing Plugged Function Cross-connector No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated voltage 0 V Rated current 24 A DOWNICATED 24 A Pownloads 0 V Rated voltage 0 V Rated voltage 0 V Rated voltage 1 (24 A)	General ordering data	
Part designation ZQV 2.5N/3 GE Version Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3 EAN 4008190883645 Oty. 60 pc(s). Additional technical data Explosion-tested version "Ex e" No No Cross-connector Version Tested version "Ex e" Height 23 mm No. of cross-connected terminals 3 Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions V Width 2.8 mm Rated voltage 0 V Rated current 24 A Downloads DXF DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 3.0 ETIM 3.0 EC000489 ETIM 3.0 EC000480		1693810000
Version Cross-connector / link for modular terminal, Cross-connection, No. of poles: 3 EAN 4008190833645 Qty. 60 pc(s). Additional technical data Explosion-tested version "Ex e" No Cross-connector Height 23 mm No. of cross-connected terminals 3 9 Pitch 5.1 mm 1 Rated current, 2-pole 24 A 24 A Rated current, multi-pole 24 A 24 A Rated voltage 0 V 0 Type Cross-connector 7 Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions 3 Width 2.8 mm Rated voltage 0 V Rated voltage 60 V Rated voltage 60 V Resifications 60 V ETIM		
EAN		
Qty. 60 pc(s). Additional technical data Explosion-tested version "Ex e" No Cross-connector Height 23 mm No. of cross-connected terminals 3 Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rating data Rated voltage 0 V		connection, No. of poles: 3
Additional technical data Explosion-tested version "Ex e" No Cross-connector Height 23 mm No. of cross-connected terminals 3 Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rating data Rated voltage 0 V Rated current 24 A Converted to the converted terminals 25 mm Rating data Rated voltage 0 V Rated current 24 A Converted to the converted terminals 25 mm Converted terminals 26 mm Rating data Rated voltage 0 V Rated current 24 A Converted terminals 26 mm Converted terminals 26 mm Converted terminals 26 mm Converted terminals 27 mm Converted terminals 27 mm Converted terminals 27 mm Rating data Rated voltage 10 V Rated current 24 A Converted terminals 27 mm Converted terminals 27 mm Rating data 27 mm Converted terminals 27 mm Rating data	EAN	4008190883645
Explosion-tested version "Ex e" No	Qty.	60 pc(s).
Explosion-tested version "Ex e" No		
Cross-connector		
Height	Explosion-tested version "Ex e"	No
Height		
No. of cross-connected terminals 3 Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ECIass 4.1 27-14-11-99 eClass 5.0 27-14-11-90		
Pitch 5.1 mm Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Rated current, 2-pole 24 A Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Rated current, multi-pole 24 A Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Rated voltage 0 V Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rated voltage Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Type Cross-connector Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rating data Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Type of fixing Plugged Function Cross-connection No. of poles 3 Dimensions Width 2.8 mm Rating data Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	•	
Function Cross-connection No. of poles 3 Dimensions 2.8 mm Rating data 0 V Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
No. of poles 3 Dimensions Width 2.8 mm Rating data Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		••
Dimensions Width 2.8 mm Rating data Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
Width 2.8 mm Rating data 0 V Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	No. of poles	3
Width 2.8 mm Rating data 0 V Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 ETIM 3.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	Dimensions	
Rating data Rated voltage 0 V Rated current 24 A Downloads DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		2.8 mm
Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	viidai	2.0 11111
Rated voltage 0 V Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	Rating data	
Rated current 24 A Downloads 24707_ZQV_2.5N-3_GE_DXF.dxf DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		0 V
DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		24 A
DXF 24707_ZQV_2.5N-3_GE_DXF.dxf STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
STEP 1693810000_24707_ZQV_2.5N-3_STP.stp Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	Downloads	
Classifications ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	DXF	
ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40	STEP	1693810000_24707_ZQV_2.5N-3_STP.stp
ETIM 2.0 EC000489 ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
ETIM 3.0 EC000489 eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
eClass 4.1 27-14-11-99 eClass 5.0 27-14-11-40		
eClass 5.0 27-14-11-40		
eClass 5.1 27-14-11-40		
	eClass 5.1	27-14-11-40

Similar products

1693880000	ZQV 2.5N/10 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 10
1693800000	ZQV 2.5N/2 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 2
1693820000	ZQV 2.5N/4 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 4



1693830000	ZQV 2.5N/5 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 5
1693890000	ZQV 2.5N/50 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 50
1693840000	ZQV 2.5N/6 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 6
1693850000	ZQV 2.5N/7 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 7
1693860000	ZQV 2.5N/8 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 8
1693870000	ZQV 2.5N/9 GE	Cross-connector / link for modular terminal, Cross-connection, No. of poles: 9