



- NOTE
- COMPONENTS OF NO. ④ AND ⑤ ARE APPENDED PRODUCTS.
 - PCB SHALL BE USED FOR CABLE WIRE CONNECTION. LAND OF PCB FOR CABLE WIRE CONNECTION IS PUT IN ONLY HARNESS SIDE. IN ADDITION, THE PRODUCT IS NOT ATTACHED THE PCB.
 - APPLICABLE CABLE : $\phi 4.8 \pm 0.1 \text{mm}$
 - WHITE MARK MIGHT REMAIN. IT IS LUBRICANT AGENT FOR METAL-PEG AT ASSEMBLY. THERE IS NO PROBLEM ON THE PERFORMANCE.
 - PLATING
 CONTACT-AREA GOLD 0.2 μm min.
 LEAD-AREA GOLD 0.03 μm min.
 UNDER-PLATING NICKEL 2 μm min.

2	COPPER ALLOY	⑤	5	STAINLESS STEEL	NICKEL 0.3 μm min.			
1	PA	COLOR:BLACK . UL94V-0	4	STAINLESS STEEL	NICKEL 0.3 μm min.			
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS			
UNITS	mm	SCALE	4 : 1	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
		APPROVED : NM. NISHIMATSU 15.10.27 CHECKED : KN. ICHIKAWA 15.10.27 DESIGNED : TS. ITO 15.10.27 DRAWN : AK. AKIYAMA 15.10.27		DRAWING NO. EDC-125503-30-00 PART NO. GX40-18S(30) CODE NO. CL247-0002-6-30		1/1		