




## Product information GDML 2011 LED 24 VR YE grau/grey

Industrial Connectors:Rectangular connectors GDM-series:Type A EN 175301-803 (DIN 43650) / ISO 4400:Cable socket with electronic insert:GDML 2011 LED 24 VR YE grau/grey


<http://e-catalog.hirschmann.com/link/57078-24228-24309-24310-24314-34980/en/conf/ui/istate>

Name	GDML 2011 LED 24 VR YE grau/grey
	
	function indicator (LED) with freewheeling diode and protective circuit (varistor)
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Description	function indicator (LED) with freewheeling diode and protective circuit (varistor)
Type	GDML 2011 LED 24 VR YE grau/grey
Order No.	933 737-712
Other standard types	transparent housing, cable gland black: Order no. 933 737-212
Number of contacts	2 + PE
Cable gland	PG 11 (grey)
Conductor size	max. 1.5 mm <sup>2</sup>
Standard	DIN EN 175 301-803-A
Housing Color	transparent
Construction type	A
<b>Description of Wiring</b>	
LED color	LED yellow
Suppressor	varistor
Other characteristics	LED-half-wave rectifier
<b>Technical data</b>	
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm
Rated voltage	AC/DC 24 V
Rated current	8 A
Contact resistance	<= 4 mOhm
Type of termination	screw
Suitable cables	4.5 mm to 11 mm diameter
Mounting	central nut
<b>Material</b>	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
<b>Environmental conditions</b>	
Protection class (IEC 60529)	IP 65 (gasket necessary)
Pollution severity	3
Temperature range	-40 °C to +90 °C
<b>Inflammability class</b>	
Housing	94 HB
Contact bearer	94 HB
<b>Packing unit</b>	
Packaging unit	50 pieces
<b>Scope of delivery and accessories</b>	
Accessories to order separately	(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-002; knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001

Industrial Connectors:Rectangular connectors GDM-series:Type A EN 175301-803 (DIN 43650) / ISO 4400:Cable socket with electronic insert:GDML 2011 LED 24 VR YE grau/grey  
<http://e-catalog.hirschmann.com/link/57078-24228-24309-24310-24314-34980/en/conf/ui/state>

Picture

Drawing



**Belden Deutschland GmbH**

Im Gewerbepark 2  
58579 Schalksmühle  
Germany  
Phone: +49 7127/14-1806  
E-Mail: [icos-sales@belden.com](mailto:icos-sales@belden.com)

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.