


REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE



Detailed product Description:
 1. Waterproof connector rating is IP65/IP67
 2. Protected from dust and water during immersion, resistant to many oils and chemical etc
 3. Wire cross section: 0.25mm²

Electrical character:
 1. Rating voltage: 60V AC/DC
 2. Insulation resistance: >100MΩ
 3. Rating current: 4A
 4. Contact resistance of the connector ≤ 10 mΩ

Other Specification:
 1. Contact PIN: Phosphor Copper with Gold plating
 2. Coupling nut/screw: Brass with nickel plating
 3. Insulation plastic: PA66+GF and TPU
 4. Degree of protection: IP65/67
 5. Operating temperature: -25℃~+85℃

Electrical character

Prat Number	Contacts	Rated Voltage		Rated Current	Contact Resistance
		A/C	D/C		
PM-M12A-03P-FF-SL7A01-00B(H)		250V	250V	4A	10mΩ
PM-M12A-04P-FF-SL7A01-00B(H)		250V	250V	4A	10mΩ
PM-M12A-05P-FF-SL7A01-00B(H)		60V	60V	4A	10mΩ
PM-M12A-08P-FF-SL7A01-00B(H)		30V	30V	2A	10mΩ
PM-M12A-12P-FF-SL7A01-00B(H)		30V	30V	1.5A	10mΩ
PM-M12B-05P-FF-SL7A01-00B(H)		60V	60V	4A	10mΩ
PM-M12D-04P-FF-SL7A01-00B(H)		250V	250V	4A	10mΩ

DETACHED LISTS	PART NO.: /		宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD		
	APPD: Alam 9/10/15"		NAME: PM-M12X-XXP-FF-SL7A01-00B(H)		
	CHKD: Aaron 9/2/15"		TITLE: CUSTOMER DRAWING		
	DRFT: CKZ 01/11/15"		REV	DO	
	THIRD ANGLE PROJECTION		DRAWING NO.:	SHEET	1/1
		MM (INCH)	DO NOT SCALE DRAWING	SCALE 1:1	