

EPIC® SENSOR Flush-type M8

sensor/actuator flush-type connectors with TPE single strands for front-mounting (A-coded)



Automation



Industrial machinery and plant engineering



Space requirement



Waterproof

Application range

Connection of enclosures and cabinets

Benefits

Flexible connection solutions for individual device concepts

Simple installation in devices (e.g. cabinet)

Product Make-up

TPE single strands, l = 0.5 m

Core cross section: 0.25 mm²

Product features

M8 fastening thread

Designs for front mounting

PWIS-free

Technical Data

Coding:

A-standard

Material:

Contact: CuSn

Contact surface: Ag

Rated current (A):

4 A

Protection rating:

IP67

Ambient temperature (operation):

Plug/socket

-25°C to +85°C

Note

Copper price basis: inclusive of copper. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs are not to scale and do not represent detailed images of the respective products.



EPIC® SENSOR Flush-type M8

Part number	Article designation	Number of pins	Rated voltage (V)
Panel-mount connector male			
22260100	AB-C3-M8MS-0,5	3	60
22260101	AB-C4-M8MS-0,5	4	30
Panel-mount connector female			
22260102	AB-C3-M8FS-0,5	3	60
22260103	AB-C4-M8FS-0,5	4	30