

CONFIGURATION		PART NUMBER
Male Receptacle, 26 Pin, 20 Awg, Shell 16		RT001626PNH
DIMENSIONS		
<p>The drawing includes the following dimensions and labels:</p> <ul style="list-style-type: none"> <li><b>Side View:</b> O-Ring, Insert, Shell, Seal Gasket, <math>\text{Ø} 23.60</math>, <math>\text{Ø} 25.30</math>, UNEF 15/16-20 THREAD, 11.30, 1.80, 32.5 Max.</li> <li><b>Front View:</b> MASTER KEYWAY, <math>4\text{-}\text{Ø} 3.20</math>, 31.0, 24.60, 24.60, 31.0.</li> <li><b>Panel Cut Out Reference:</b> <math>\text{Ø} 24.60</math> (For Front Panel Mounting), <math>\text{Ø} 28.10</math> (For Rear Panel Mounting), <math>4\text{-}\text{Ø} 3.30</math>.</li> </ul>		
TECHNICAL DATA		
TEMPERATURE RANGE:	-40°C to + 105°C	
PROTECTION:	IP67 in mated condition and in combination with sealed backshell	
VOLTAGE RATING:	150V	
HOUSING BODY:	Zinc Alloy, Nickel Plated	
COUPLING NUT:	-	
INSERT:	Glass-filled Thermoplastic UL94-V0	
SEAL:	NBR	
CURRENT:	5A with Stamped and Formed Contact / 7.5A with Machined Contact	
CONTACT SIZE:	20Awg	
APPROVALS:	UL ECBT2	