

## Product Sheet

**Part Number:** CX 03 4F



<b>Family</b>	modular units series MIXO
<b>Version</b>	crimp connections
<b>Series</b>	CX
<b>Product type</b>	for female contacts 40A
<b>Model</b>	female insert
<b>Reference standard</b>	EN 61984 (2001-11)
<b>No. of poles</b>	3 poles
<b>Voltage (V)</b>	400V/690V
<b>Current (A)</b>	40A (A.C./D.C.)
<b>IP degree of protection</b>	IP20 degree of protection without enclosure; IP65, IP66, IP67, IP68 (EN 60529) and IP69K (DIN 40050 - 9) with enclosure
<b>Fixing centre distance</b>	1 module
<b>Impulse withstand voltage</b>	6kV
<b>Pollution degree</b>	3

The information and the dimensions contained are not binding and may be changed without prior notice.  
The drawing's dimensions are in mm.

**Barcode EAN13**

8015747041706

**Notes**

the modular inserts must be installed in suitable frames which in turn are installed in traditional housings or COB panel support

CX 03 4 inserts:

- characteristics according to EN 61984:  
(40A 400/690V 6kV 3)
- footprint 1 module
- for maximum current load, see the insert load curve section
- for contact crimping instructions, please see the crimping tool section (40A contacts, CXF and CXM series)