



SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 125V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 100MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: PBT,UL94V-0
 Color: Natural(White)

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A1250H-02P	1.25	4.25
A1250H-03P	2.50	5.50
A1250H-04P	3.75	6.75
A1250H-05P	5.00	8.00
A1250H-06P	6.25	9.25
A1250H-07P	7.50	10.50
A1250H-08P	8.75	11.75
A1250H-09P	10.00	13.00
A1250H-10P	11.25	14.25
A1250H-11P	12.50	15.50
A1250H-12P	13.75	16.75
A1250H-13P	15.00	18.00
A1250H-14P	16.25	19.25
A1250H-15P	17.50	20.50
A1250H-16P	18.75	21.75
A1250H-17P	20.00	23.00
A1250H-18P	21.25	24.25

			UNIT	SCALE	SHEET	TITLE:
			mm		1 of 1	
			DRAWN BY		APPROVED BY	
			董正一		董正一	
			2001.02.01		2001.02.01	
			GENERAL TOLERANCE			
			X. X±0.25		ANGLE±	
			X. XX±0.15			
			X. XXX±0.05			
B0	NEW RELEASE	2006.06.23	1.25mm PITCH HOUSING			
REV.	DESCRIPTION	DATE				
			DRAW NO. :			REV.
			A1250H-XP			B0