

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 12/08/11	~	

NOTES:

1. SPECIFICATIONS

- . Current Rating: 1A
- . Insulation Resistance: 500MΩ Min
- . Dielectric Withstanding: 300V AC
- . Contact Resistance: 30mΩ Max
- . Operating Temperature: -40°C to +105°C

2. MATERIALS



- . Contact Material: Copper alloy
- . Insulator: Thermoplastic(UL94 V-0)

3. PART NUMBER: DS1065-07


4. PRODUCT NUMBER CODE:

DS1065-07 - X X X X X

- X: MOUNTING TYPE
V: VERTICAL TYPE
- X: HOUSING COLOR
B: BLACK
- X: CONTACT PLATING
8: FULL GOLD FLASH
- X: CONNECTOR TYPE
S: SOCKET
- X: No. OF CONTACTS
1*1-1*40



N=No.of Contacts



Tel:86-574-63508787

Fax:86-574-63510817

E-mail:sale@zhenqin.com.cn

Http://www.connfly.com

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	FEMALE HEADER PITCH 1.27mm TYPE	
X.	±0.60	X.	±5°	UNITS	mm		SINGLE ROW STRAIGHT	
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1065-07	
.XX	±0.25	.XX	±2°					
DRAWING TYPE		CUSTOMER		晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
SCALE		1:1	SHEET					1 OF 1
DRAWING NO.		C-DS1065-07-XXXXX						