



### SHT W

PTC HEATERS, WIRE CONNECTION



Features	Unit	SHT15W	SHT25W	SHT50W
Heating Capacity*	W	15	25	50
Power supply	V	110-250V AC or DC		
Max. current	A	2A	2A	2A
Heating element type	-	PTC resistor, self regulating		
Electrical connections	-	Silicon cable, 2x0.5 mm <sup>2</sup> , length 400 mm		
Protection class IEC	-	Class II		
Protection degree EN60529	-	IP20		
Operating temperature	°C (°F)	-45/+70 (-49/+158)		
Storage temperature	°C (°F)	-45/+70 (-49/+158)		
Radiator	-	Extruded aluminium profile, anodized		
Mounting	-	Clip for mounting on DIN rail 35 mm EN50022		
Installation position	-	Best efficiency in vertical position		
Dimensions HxWxD	mm	50x50x80	60x50x80	80x50x80
Cable length	mm	400	400	400
Weight	kg	0.20	0.24	0.29
Conformity	-	CE		

\*at 20°C (68°F) ambient temperature

#### Accessories

Thermostat NC 0-60°C	THR2
Double thermostat NC 0-60°C NO 0-60°	THRV22
Hygrothermostat 0-60°C 30-90%RH	ETUH22
Hygrostat 10-90%RH	MUH

