

SPECIFICATIONS

FULLTECH ELECTRIC CO., LTD

ITEM	MODEL	UF-15PE23BWHN
RATED VOLTAGE		AC230V
VOLTAGE RANGE		AC207-253V
SPEED(RPM)		50Hz 2650 RPM±10% 60Hz 2950 RPM±10%
RATED CURRENT		50Hz 0.24 A±10% 60Hz 0.20 A±10%
RATED INPUT		50Hz 36 W±10% 60Hz 33 W±10%
LOCKED CURRENT		50Hz 0.29 A±10% 60Hz 0.25 A±10%
MAX. AIR VOLUME		50Hz 160±10% CFM 60Hz 180±10% CFM
MAX. STATIC PRESSURE		50Hz 0.16±10% inH2O 60Hz 0.18±10% inH2O
OPERATING TEMP.		-40°C~+70 °C
STORAGE TEMP.		-40°C~+80 °C
ROTATING DIRECTION		ANTI-CLOCKWISE DIRECTION
BLOWING DIRECTION		EXHAUST FROM LABEL SIDE
INSULATION RESISTANCE		DC 500 V 100MΩ
DIELECTRIC STRENGTH		AC 1500V / 1MIN.
NOISE		50Hz 48 dB 60Hz 53 dB
SAFETY PROTECTION		IMPEDANCE PROTECTION
INSULATION GRADE		CLASS B
IP RATE		IP55 AT LEAST
BEARING		BALL BEARING
LIFE EXPECTANCY		OVER 40000 HOURS (40°C)
FRAME MATERIAL		ALUMINUM (ADC-12)
IMPELLER		PLASTIC 94V-0 PBT. COVERING GLASS FIBER
DIMENSION		φ 144*49 mm
WEIGHT		0.78 KG.