




# 5 Port Solenoid Valve

Power Consumption  
**0.1 W**  
 With Power Saving Circuit



## SY Series



Cover (stainless steel)

### Improved pilot valve



Pilot valve cover is stronger using stainless steel.  
 Mounting thread is also reinforced from size M1.7 to M2.

#### • Flow Characteristics

| Series | Flow characteristics         |      |      |                |
|--------|------------------------------|------|------|----------------|
|        | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   | Q [ℓ/min(ANR)] |
| SY3000 | 1.1                          | 0.28 | 0.29 | 276            |
| SY5000 | 2.8                          | 0.37 | 0.90 | 746            |
| SY7000 | 4.5                          | 0.28 | 1.4  | 1130           |
| SY9000 | 10                           | 0.29 | 2.5  | 2527           |














# Valve Variations

|  | Series   | Sonic conductance C [dm <sup>3</sup> /(s·bar)]<br>{ 4/2→5/3 }<br>{ (A/B→EA/EB) } | Actuation  |        |               |                |                 | Voltage                                 |  | Electrical entry |                  |                  |              |              | Light/surge voltage suppressor |
|--|----------|--|------------|--------|---------------|----------------|-----------------|---|--|------------------|------------------|------------------|--------------|--------------|--------------------------------|
|  |          |  | 2 position |        | 3 position    |                |                 | DC<br>24 V<br>12 V<br>6 V<br>5 V<br>3 V | AC<br>100 V<br>50/60 Hz<br>110 V<br>50/60 Hz<br>200 V<br>50/60 Hz<br>220 V<br>50/60 Hz | Grommet          | L plug connector | M plug connector | DIN terminal | M8 connector |                                |
|  |          |  | Single     | Double | Closed center | Exhaust center | Pressure center |   |  |                  |                  |                  |              |              |                                |
| Body ported<br>   | P.1      | 0.65   | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY3 □ 20 | 2.4  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY5 □ 20 | 3.3  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY7 □ 20 | 8.6  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
| Base mounted<br> | P.19     | 1.1  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY3 □ 40 | 2.8  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY5 □ 40 | 4.5  | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |
|  | SY7 □ 40 | 10   | ●          | ●      | ●             | ●              | ●               | ●                                       | ●  | ●                | ●                | ●                | ●            | ●            | ●                              |

| Series       | Manual override       |                                |                              | P, EA, EB port size |    |     |     |     | A, B port size |    |     |     |     |     |                   |    |    |     |     | Valve option |    |                  |  |                       |                             |                |                |                     |    |
|--------------|-----------------------|--------------------------------|------------------------------|---------------------|----|-----|-----|-----|----------------|----|-----|-----|-----|-----|-------------------|----|----|-----|-----|--------------|----|------------------|--|-----------------------|-----------------------------|----------------|----------------|---------------------|----|
|              | Non-locking push type | Push-turn locking slotted type | Push-turn locking lever type | Bracket             | M5 | 1/8 | 1/4 | 3/8 | 1/2            | M5 | 1/8 | 1/4 | 3/8 | 1/2 | One-touch fitting |    |    |     |     |              |    | Exhaust throttle | Oil resistant, Other than designated turbine oil | Vacuum specifications | Low pressure specifications | External pilot | Enclosure IP65 | Interface regulator |    |
|              |                       |                                |                              |                     |    |     |     |     |                |    |     |     |     |     | C4                | C6 | C8 | C10 | C12 | N3           | N7 |                  |  |                       |                             |                |                |                     | N9 |
| Body ported  | SY3 □ 20              | ●                              | ●                            | ●                   | ●  | —   | —   | —   | —              | ●  | —   | —   | —   | —   | ●                 | ●  | —  | —   | —   | —            | —  | —                | —  | —                     | —                           | —              | —              | —                   |    |
|              | SY5 □ 20              | ●                              | ●                            | ●                   | ●  | —   | ●   | —   | —              | —  | ●   | —   | —   | —   | ●                 | ●  | ●  | —   | —   | —            | —  | ●                | ▲  | ▲                     | ▲                           | ▲              | ●              | —                   |    |
|              | SY7 □ 20              | ●                              | ●                            | ●                   | ●  | —   | ●   | ●   | —              | —  | —   | ●   | —   | —   | —                 | ●  | ●  | —   | —   | —            | —  | ●                | ●  | ●                     | ●                           | ●              | —              | —                   |    |
|              | SY9 □ 20              | ●                              | ●                            | ●                   | —  | —   | —   | ●   | —              | —  | —   | ●   | ●   | —   | —                 | ●  | ●  | ●   | —   | —            | —  | —                | ●  | ●                     | ●                           | ●              | ●              | —                   |    |
| Base mounted | SY3 □ 40              | ●                              | ●                            | ●                   | —  | —   | ●   | —   | —              | —  | ●   | —   | —   | —   | —                 | —  | —  | —   | —   | —            | —  | —                | —  | —                     | —                           | —              | ●              | —                   |    |
|              | SY5 □ 40              | ●                              | ●                            | ●                   | —  | —   | ●   | —   | —              | —  | —   | ●   | —   | —   | —                 | —  | —  | —   | —   | —            | —  | ●                | ▲  | ●                     | ●                           | ●              | ●              | ●                   | —  |
|              | SY7 □ 40              | ●                              | ●                            | ●                   | —  | —   | ●   | ●   | —              | —  | —   | ●   | ●   | —   | —                 | —  | —  | —   | —   | —            | —  | ●                | —  | ●                     | ●                           | ●              | ●              | ●                   | —  |
|              | SY9 □ 40              | ●                              | ●                            | ●                   | —  | —   | —   | ●   | ●              | —  | —   | —   | ●   | ●   | —                 | —  | —  | —   | —   | —            | —  | —                | ●  | —                     | ●                           | ●              | ●              | ●                   | —  |

- Note 1) All AC voltage models have built-in surge voltage suppressor.
- Note 2) Body ported external pilot style (made to order) is not available for DIN terminal.
- Note 3) Only available for DIN terminal and M8 connector.
- Note 4) SY3000 does not have a DIN terminal which can be connected to a manifold.

# Manifold Variations

| Manifold Variations  |  | Valve Series   | Wiring  |                             |   |  |  |  |           |                          |                 |                 |   |   |
|--|--|--|---|-----------------------------|---|--|--|--|-----------|--------------------------|-----------------|-----------------|---|---|
|  |  |  | Connection  |                             |   |  |  |  |           | Common specifications    |                 |                 |   |   |
|  |  |  | Individual wiring   | Flat ribbon cable (26 pins) | Flat ribbon cable (20 pins) connector box | Plug-in type D-sub connector (25 pins) | Plug-in type flat ribbon cable (26, 20, 10 pins) | Plug-in type terminal block (9, 18 pins) | PC wiring | Serial transmission unit | Positive common | Negative common |   |   |
| Body ported  | <b>Bar stock type Individual wiring</b><br>■ Direct piping to the main unit of a valve. Combination of different fittings is possible. |   | <b>Type 20</b><br>P. 37   | SY3 □ 20                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY5 □ 20                    | —   | ●                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY7 □ 20                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  | <b>Bar stock type Flat ribbon cable</b><br>■ A 26 pins MIL connector permits One-touch wiring of external cables in a bundle.          |   | <b>Type 20P</b><br>P. 47  | SY3 □ 20                    | —   | ●                                      | —  | —  | —         | —                        | —               | ●               | — |   |
|  |  |  |   | SY5 □ 20                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  |  |  |   | SY7 □ 20                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  | <b>Stacking type Individual wiring</b><br>■ Manifold stations can be increased.  |   | <b>Type 23</b><br>P. 43   | SY9 □ 20                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY9 □ 20                    | —   | ●                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  | <b>Stacking type Flat ribbon cable</b><br>■ Manifold stations can be increased.  |                                        | <b>Type 23P</b><br>P. 53  | SY9 □ 20                    | —   | ●                                      | —  | —  | —         | —                        | —               | ●               | — |   |
|  |  |  |   | SY9 □ 20                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  | <b>Cassette type Individual wiring</b><br>■ Size and weight reduced by eliminating the manifold base                                   |                                       | <b>Type 60</b><br>P. 59   | SY3 □ 60                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY5 □ 60                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  |  |  |   | SY7 □ 60                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
|  | Base mounted   | <b>Compact bar stock type Individual wiring</b><br>■ The base mounting facilitates maintenance after valves are changed. |  | <b>Type 41</b><br>P. 79     | SY3 □ 40                                  | ●                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   |                             | SY5 □ 40                                  | —                                      | ●  | —  | —         | —                        | —               | —               | — | — |
| <b>Compact bar stock type Flat ribbon cable</b><br>■ A 26 pins MIL connector permits one-touch wiring of external cables in a bundle.  |  |                                       | <b>Type 41P</b><br>P. 95  | SY3 □ 40                    | —   | ●                                      | —  | —  | —         | —                        | —               | ●               |   |   |
|  |  |  |   | SY5 □ 40                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — | — |
| <b>Bar stock type/Common external EXH Individual wiring</b><br>■ The base mounting facilitates maintenance after valves are changed.<br>■ Vacuum/low pressure combination system is possible.              |  |                                       | <b>Type 42</b><br>P. 79   | SY3 □ 40                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               |   |   |
|  |  |  |   | SY5 □ 40                    | —   | ●                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY7 □ 40                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
| <b>Bar stock type/Common external EXH Flat ribbon cable</b><br>■ A 26 pins MIL connector permits one-touch wiring of external cables in a bundle.<br>■ Vacuum/low pressure combination system is possible. |  |                                       | <b>Type 42P</b><br>P. 95  | SY3 □ 40                    | —   | ●                                      | —  | —  | —         | —                        | —               | ●               |   |   |
|  |  |  |   | SY5 □ 40                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
|  |  |  |   | SY7 □ 40                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
| <b>Stacking type Individual wiring</b><br>■ Manifold stations can be increased.  |  |                                       | <b>Type 43</b><br>P. 89   | SY9 □ 40                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               |   |   |
|  |  |  |   | SY9 □ 40                    | —   | ●                                      | —  | —  | —         | —                        | —               | —               | — |   |
| <b>Stacking type Flat ribbon cable</b><br>■ Manifold stations can be increased.  |  |                                       | <b>Type 43P</b><br>P. 103   | SY9 □ 40                    | —   | ●                                      | —  | —  | —         | —                        | —               | ●               |   |   |
|  |  |  |   | SY9 □ 40                    | —   | —                                      | —  | —  | —         | —                        | —               | —               | — |   |
| <b>Stacking type/DIN rail mounted Individual wiring</b><br>■ Stations can be increased on the DIN rail. Integral mounting of other electric parts is possible, too.  |  |                                       | <b>Type 45</b><br>P. 115  | SY3 □ 40                    | ●   | —                                      | —  | —  | —         | —                        | —               | —               |   |   |
|  | SY5 □ 40   |  |   | —                           | ●   | —                                      | —  | —  | —         | —                        | —               | —               |   |   |
| <b>Stacking type/DIN rail mounted Connector box</b><br>■ Stations can be increased on the DIN rail. The provided connector box permits one-touch connection of electric cables.                            |   | <b>Type 45<sup>A</sup><sub>NA</sub></b><br>P. 127  | SY3 □ 40  | —                           | —   | ●                                      | —  | —  | ●         | —                        | ●               |                 |   |   |
|  |  |  | SY5 □ 40  | —                           | —   | —                                      | —  | —  | ●         | —                        | ●               | ●               |   |   |
| <b>Stacking type/DIN rail mounted Plug-in</b><br>■ Stations can be increased on the DIN rail.<br>■ A variety of centralised wiring methods are possible.   |   | <b>Type 45</b><br>P. 135   | SY3 □ 40  | —                           | —   | —                                      | ●  | ●  | ●         | ●                        | ●               |                 |   |   |
|  |  |  | SY5 □ 40  | —                           | —   | —                                      | —  | —  | ●         | ●                        | ●               | ●               |   |   |

● Standard ● Option ▲ Made to order (Refer to page "Made to Order".)



# 5 Port Solenoid Valve

## Series SY3000/5000/7000/9000

### Body Ported

# Single Unit



Refer to [www.smcworld.com](http://www.smcworld.com) for details of products compatible with overseas standards.

### How to Order

SY 5 1 20 [ ] 5 L [ ] [ ] 01 [ ] [ ] -Q

#### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |
| 9 | SY9000 |

#### Type of actuation

|   |   |
|---|---|
| 1 | 2 position single<br>(A)(B)<br>4 2<br>5 1 3<br>(EA)(P)(EB)          |
| 2 | 2 position double<br>(A)(B)<br>4 2<br>5 1 3<br>(EA)(P)(EB)          |
| 3 | 3 position closed center<br>(A)(B)<br>4 2<br>5 1 3<br>(EA)(P)(EB)   |
| 4 | 3 position exhaust center<br>(A)(B)<br>4 2<br>5 1 3<br>(EA)(P)(EB)  |
| 5 | 3 position pressure center<br>(A)(B)<br>4 2<br>5 1 3<br>(EA)(P)(EB) |

#### Coil specifications

|   |   |
|---|---|
| - | Standard                                    |
| T | With power saving circuit (24, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

#### For DC

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

#### Rated voltage

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D, DO type.

#### Electrical entry

| 24, 12, 6, 5, 3 VDC        |                                   |   |                                      | 24, 12 VDC/<br>100, 110, 200, 220 VAC |
|----------------------------|-----------------------------------|---|--------------------------------------|---------------------------------------|
| Grommet                    | L plug connector                  | M plug connector                        | DIN terminal <small>(Note 2)</small> |                                       |
| G: Lead wire length 300 mm | L: With lead wire (Length 300 mm) | M: With lead wire MN: Without lead wire | D: With connector                    |                                       |
| H: Lead wire length 600 mm | LN: Without lead wire             | LO: Without connector                   | DO: Without connector                |                                       |


#### 24, 12, 6, 5, 3 VDC

##### M8 connector \*

WO: Without connector cable




W□: With connector cable (Note 1)




\* LN, MN type: with 2 sockets.  
\* For DIN terminal of SY3000 series, refer to back page 10.  
\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.  
\* For connector cable of M8 connector, refer to back page 12.  
\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.  
Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.  
Note 2) Except SY3000.

#### Bracket

-: Without bracket  
F1: With foot bracket



F2: With side bracket



\* SY9000 has no bracket.

#### A, B port size

##### Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |
| 02     | 1/4       | SY7000            |
| 02     | 1/4       | SY9000            |
| 03     | 3/8       |                   |

##### One-touch fitting (Metric size)

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  |                   |
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  |                   |
| C8     | One-touch fitting for ø8  | SY7000            |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 | SY9000            |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 |                   |
| C12    | One-touch fitting for ø12 |                   |

##### One-touch fitting (Inch size)

| Symbol | Port size                     | Applicable series |
|--------|-------------------------------|-------------------|
| N3     | One-touch fitting for ø 5/32" | SY3000            |
| N7     | One-touch fitting for ø 1/4"  |                   |
| N3     | One-touch fitting for ø 5/32" | SY5000            |
| N7     | One-touch fitting for ø 1/4"  |                   |
| N9     | One-touch fitting for ø 9/16" | SY7000            |
| N9     | One-touch fitting for ø 9/16" |                   |
| N11    | One-touch fitting for ø 3/8"  | SY9000            |
| N9     | One-touch fitting for ø 9/16" |                   |
| N11    | One-touch fitting for ø 3/8"  |                   |

#### Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* Except for M5

#### Manual override

|                          |                                   |                                 |
|--------------------------|-----------------------------------|---------------------------------|
| -: Non-locking push type | D: Push-turn locking slotted type | E: Push-turn locking lever type |
|                          |                                   |                                 |

#### Light/surge voltage suppressor

##### Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

##### Electrical entry for D (except SY3000)


|   |  |
|---|--|
| - | Without light/surge voltage suppressor |
| S | With surge voltage suppressor          |
| Z | With light/surge voltage suppressor    |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to page 56.)

# SY3000/5000/7000/9000 Body Ported

## Specifications



| Series  |                           | SY3000   | SY5000 | SY7000 | SY9000 |
|---|---------------------------|--|--------|--------|--------|
| Fluid   |                           | Air  |        |        |        |
| Internal pilot<br>Operating pressure<br>range (MPa)                 | 2 position single         | 0.15 to 0.7  |        |        |        |
|   | 2 position double         | 0.1 to 0.7   |        |        |        |
|   | 3 position                | 0.2 to 0.7   |        |        |        |
| Ambient and fluid temperature (°C)                                  |                           | -10 to 50 (No freezing. Refer to back page 3.)   |        |        |        |
| Max. operating<br>frequency (Hz)                                    | 2 Position single, Double | 10   | 5      | 5      | 5      |
|   | 3 position                | 3  | 3      | 3      | 3      |
| Manual override (Manual operation)                                  |                           | Non-locking push type,<br>Push-turn locking slotted type, Push-turn locking lever type |        |        |        |
| Pilot exhaust method  |                           | Common exhaust type for main and pilot valve   |        |        |        |
| Lubrication   |                           | Not required   |        |        |        |
| Mounting orientation  |                           | Unrestricted   |        |        |        |
| Impact/Vibration resistance (m/s <sup>2</sup> ) <small>Note</small> |                           | 150/30   |        |        |        |
| Enclosure   |                           | Dust proof (* DIN terminal and M8 connector: IP65)                                     |        |        |        |



\* Based on IEC60529)

Note) Impact resistance: No malfunction occurred when it is tested in the axial direction and at the right angles to the main valve and armature in both energised and de-energised states every once for each condition. (Values at the initial period)

Vibration resistance: No malfunction occurred in a one-sweep test between 45 and 2000 Hz. Test was performed at both energised and de-energised states in the axial direction and at the right angles to the main valve and armature. (Values at the initial period)



**Made to Order**

(For details, refer to pages 199 through to 213.)

## Solenoid Specifications

| Electrical entry                  |             | Grommet (G), (H)<br>L plug connector (L)<br>M plug connector (M) |  | DIN terminal (D)<br>M8 connector (W)                                     |  |
|-----------------------------------|-------------|--|--|--|--|
|                                   |             | G, H, L, M, W  |  | D  |  |
| Coil rated<br>voltage (V)         | DC          | 24, 12, 6, 5, 3  |  | 24, 12   |  |
|                                   | AC 50/60 Hz | 100, 110   |  | 200, 220   |  |
| Allowable voltage fluctuation (%) |             | ±10% of rated voltage *  |  |  |  |
| Power<br>consumption (W)          | DC          | Standard   | 0.35 (With indicator light: 0.4 DIN terminal with indicator light: 0.45) |  |  |
|                                   |             | With power saving circuit  | 0.1 (With indicator light only)  |  |  |
| Apparent power<br>(VA) *          | AC          | 100 V  | -  | 0.78 (With indicator light: 0.87)  |  |
|                                   |             | 110 V  | -  | 0.86 (With indicator light: 0.97)  |  |
|                                   |             | [115 V]  | -  | [0.94 (With indicator light: 1.07)]                                      |  |
|                                   |             | 200 V  | -  | 1.15 (With indicator light: 1.30)  |  |
|                                   |             | 220 V<br>[230 V]   | -  | 1.27 (With indicator light: 1.46)<br>[1.39 (With indicator light: 1.60)] |  |
| Surge voltage suppressor          |             | Diode (Varistor is for DIN terminal and Non-polar type.)         |  |  |  |
| Indicator light                   |             | LED (AC of DIN connector is neon light.)                         |  |  |  |



\* In common between 110 VAC and 115 VAC, and between 220 VAC and 230 VAC.

\* For 115 VAC and 230 VAC, the allowable voltage is -15% to +5% of rated voltage.

\* S, Z and T type (with power saving circuit) should be used within the following allowable voltage fluctuation range due to a voltage drop caused by the internal circuit.

S and Z type: 24 VDC: -7% to +10%

12 VDC: -4% to +10%

T type: 24 VDC: -8% to +10%

12 VDC: -6% to +10%

## Response Time



Note) Based on dynamic performance test, JIS B 8375-1981. (Coil temperature: 20°C, at rated voltage, without surge suppressor)

### SY3000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                                     |            |
|----------------------|---|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor       | With light/surge voltage suppressor |            |
|                      |   | Type S, Z                           | Type R, U  |
| 2 position single    | 12 or less                                      | 15 or less                          | 12 or less |
| 2 position double    | 10 or less                                      | 13 or less                          | 10 or less |
| 3 position           | 15 or less                                      | 20 or less                          | 16 or less |

### SY7000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                                     |            |
|----------------------|---|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor       | With light/surge voltage suppressor |            |
|                      |   | Type S, Z                           | Type R, U  |
| 2 position single    | 31 or less                                      | 38 or less                          | 33 or less |
| 2 position double    | 27 or less                                      | 30 or less                          | 28 or less |
| 3 position           | 50 or less                                      | 56 or less                          | 50 or less |

### SY5000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                                     |            |
|----------------------|---|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor       | With light/surge voltage suppressor |            |
|                      |   | Type S, Z                           | Type R, U  |
| 2 position single    | 19 or less                                      | 26 or less                          | 19 or less |
| 2 position double    | 18 or less                                      | 22 or less                          | 18 or less |
| 3 position           | 32 or less                                      | 38 or less                          | 32 or less |

### SY9000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                                     |            |
|----------------------|---|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor       | With light/surge voltage suppressor |            |
|                      |   | Type S, Z                           | Type R, U  |
| 2 position single    | 35 or less                                      | 41 or less                          | 35 or less |
| 2 position double    | 35 or less                                      | 41 or less                          | 35 or less |
| 3 position           | 62 or less                                      | 64 or less                          | 62 or less |

# Body Ported

## Flow Characteristics/Weight

### Series SY3000

| Valve model     | Type of actuation | Port size              |                | Flow characteristics       |      |      |               |                            |      |      |               | Weight (g)   |                          |                      |    |
|-----------------|-------------------|------------------------|----------------|----------------------------|------|------|---------------|----------------------------|------|------|---------------|--------------|--------------------------|----------------------|----|
|                 |                   | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1→4/2 (P→A/B)              |      |      |               | 4/2→5/3 (A/B→EA/EB)        |      |      |               | Gro-<br>mmet | L/M<br>plug<br>connector | W<br>M8<br>connector |    |
|                 |                   |                        |                | C (dm <sup>2</sup> /s·bar) | b    | Cv   | Q(l/min(ANR)) | C (dm <sup>2</sup> /s·bar) | b    | Cv   | Q(l/min(ANR)) |              |                          |                      |    |
| SY3□20<br>-□-M5 | 2 position        | Single                 | M5 x 0.8       | 0.61                       | 0.44 | 0.16 | 171           | 0.64                       | 0.45 | 0.18 | 181           | 51           | 53                       | 57                   |    |
|                 |                   | Double                 |                | 0.48                       | 0.46 | 0.13 | 137           | 0.47                       | 0.43 | 0.13 | 131           | 68           | 74                       | 82                   |    |
|                 | 3 position        | Closed center          |                | 0.47                       | 0.42 | 0.13 | 130           | 0.47                       | 0.41 | 0.13 | 129           | 71           | 76                       | 84                   |    |
|                 |                   | Exhaust center         |                | 0.50                       | 0.48 | 0.15 | 145           | 0.47                       | 0.43 | 0.13 | 131           |              |                          |                      |    |
| SY3□20<br>-□-C4 | 2 position        | Single                 |                | M5 x 0.8                   | 0.72 | 0.29 | 0.18          | 182                        | 0.64 | 0.34 | 0.17          | 167          | 60                       | 63                   | 67 |
|                 |                   | Double                 |                |                            | 0.59 | 0.28 | 0.15          | 148                        | 0.59 | 0.30 | 0.15          | 150          | 78                       | 83                   | 91 |
|                 | 3 position        | Closed center          |                |                            | 0.63 | 0.35 | 0.16          | 166                        | 0.42 | 0.34 | 0.11          | 110          | 81                       | 86                   | 94 |
|                 |                   | Exhaust center         |                |                            | 0.76 | 0.42 | 0.21          | 210                        | 0.59 | 0.29 | 0.15          | 149          |                          |                      |    |
| SY3□20<br>-□-C6 | 2 position        | Single                 | M5 x 0.8       |                            | 0.76 | 0.30 | 0.19          | 193                        | 0.65 | 0.39 | 0.17          | 176          | 56                       | 59                   | 63 |
|                 |                   | Double                 |                |                            | 0.76 | 0.55 | 0.24          | 233                        | 0.60 | 0.33 | 0.16          | 156          | 74                       | 79                   | 87 |
|                 | 3 position        | Closed center          |                |                            | 0.65 | 0.32 | 0.16          | 167                        | 0.64 | 0.31 | 0.17          | 164          | 77                       | 82                   | 90 |
|                 |                   | Exhaust center         |                |                            | 0.77 | 0.34 | 0.21          | 201                        | 0.61 | 0.34 | 0.16          | 159          |                          |                      |    |
|                 |                   | Pressure center        |                |                            |      |      |               |                            |      |      |               |              |                          |                      |    |

Note ( ): denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Series SY5000

| Valve model     | Type of actuation | Port size              |                | Flow characteristics       |      |      |               |                            |      |      |               | Weight (g)   |                          |                 |                      |     |
|-----------------|-------------------|------------------------|----------------|----------------------------|------|------|---------------|----------------------------|------|------|---------------|--------------|--------------------------|-----------------|----------------------|-----|
|                 |                   | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1→4/2 (P→A/B)              |      |      |               | 4/2→5/3 (A/B→EA/EB)        |      |      |               | Gro-<br>mmet | L/M<br>plug<br>connector | DIN<br>terminal | W<br>M8<br>connector |     |
|                 |                   |                        |                | C (dm <sup>2</sup> /s·bar) | b    | Cv   | Q(l/min(ANR)) | C (dm <sup>2</sup> /s·bar) | b    | Cv   | Q(l/min(ANR)) |              |                          |                 |                      |     |
| SY5□20<br>-□-01 | 2 position        | Single                 | 1/8            | 1.9                        | 0.35 | 0.49 | 499           | 2.4                        | 0.39 | 0.61 | 648           | 70           | 72                       | 93              | 76                   |     |
|                 |                   | Double                 |                | 1.7                        | 0.43 | 0.45 | 473           | 1.8                        | 0.35 | 0.46 | 473           | 88           | 93                       | 135             | 101                  |     |
|                 | 3 position        | Exhaust center         |                | 1.5                        | 0.44 | 0.41 | 420           | 2.5                        | 0.32 | 0.59 | 644           | 93           | 98                       | 140             | 106                  |     |
|                 |                   | Pressure center        |                | 2.2                        | 0.46 | 0.61 | 626           | 1.8                        | 0.38 | 0.46 | 483           |              |                          |                 |                      |     |
| SY5□20<br>-□-C4 | 2 position        | Single                 |                | 1/8                        | 0.75 | 0.43 | 0.20          | 209                        | 0.85 | 0.64 | 0.30          | 285          | 94                       | 96              | 117                  | 100 |
|                 |                   | Double                 |                |                            | 0.74 | 0.40 | 0.19          | 201                        | 0.84 | 0.57 | 0.28          | 263          | 111                      | 117             | 159                  | 125 |
|                 | 3 position        | Closed center          |                |                            | 0.75 | 0.36 | 0.19          | 198                        | 0.84 | 0.64 | 0.30          | 281          | 117                      | 122             | 164                  | 130 |
|                 |                   | Exhaust center         |                |                            | 0.78 | 0.44 | 0.21          | 219                        | 0.84 | 0.57 | 0.27          | 263          |                          |                 |                      |     |
| SY5□20<br>-□-C6 | 2 position        | Single                 | 1/8            |                            | 1.5  | 0.33 | 0.33          | 389                        | 2.0  | 0.37 | 0.52          | 533          | 88                       | 91              | 112                  | 95  |
|                 |                   | Double                 |                |                            | 1.3  | 0.31 | 0.33          | 333                        | 1.6  | 0.32 | 0.39          | 412          | 106                      | 111             | 153                  | 119 |
|                 | 3 position        | Closed center          |                |                            | 1.3  | 0.33 | 0.33          | 337                        | 1.8  | 0.35 | 0.44          | 473          | 111                      | 116             | 158                  | 124 |
|                 |                   | Exhaust center         |                |                            | 1.7  | 0.31 | 0.42          | 435                        | 1.7  | 0.33 | 0.44          | 441          |                          |                 |                      |     |
| SY5□20<br>-□-C8 | 2 position        | Single                 |                | 1/8                        | 1.9  | 0.21 | 0.45          | 458                        | 2.3  | 0.29 | 0.57          | 581          | 80                       | 82              | 103                  | 86  |
|                 |                   | Double                 |                |                            | 1.6  | 0.29 | 0.39          | 404                        | 1.7  | 0.38 | 0.46          | 456          | 98                       | 103             | 145                  | 111 |
|                 | 3 position        | Closed center          |                |                            | 1.4  | 0.38 | 0.39          | 375                        | 2.0  | 0.37 | 0.52          | 533          | 103                      | 108             | 150                  | 116 |
|                 |                   | Exhaust center         |                |                            | 2.2  | 0.32 | 0.56          | 567                        | 1.8  | 0.41 | 0.50          | 493          |                          |                 |                      |     |
|                 |                   | Pressure center        |                |                            |      |      |               |                            |      |      |               |              |                          |                 |                      |     |

Note ( ): denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

# SY3000/5000/7000/9000 Body Ported

## Series SY7000

| Valve model     | Type of actuation | Port size            |                                    | Flow characteristics             |                |                |                |                            |                |                |                | Weight (g)   |                          |                 |                      |     |     |     |     |     |
|-----------------|-------------------|----------------------|------------------------------------|----------------------------------|----------------|----------------|----------------|----------------------------|----------------|----------------|----------------|--------------|--------------------------|-----------------|----------------------|-----|-----|-----|-----|-----|
|                 |                   | 1, 5, 3<br>P, EA, EB | 4, 2<br>(A, B)                     | 1→4/2 (P→A/B)                    |                |                |                | 4/2→5/3 (A/B→EA/EB)        |                |                |                | Gro-<br>mmet | L/M<br>plug<br>connector | DIN<br>terminal | W<br>M8<br>connector |     |     |     |     |     |
|                 |                   |                      |                                    | C (dm <sup>3</sup> /s·bar)       | b              | Cv             | Q [l/min(ANR)] | C (dm <sup>3</sup> /s·bar) | b              | Cv             | Q [l/min(ANR)] |              |                          |                 |                      |     |     |     |     |     |
| SY7□20<br>-□-02 | 2 position        | Single               | 1/4                                | 4.1                              | 0.23           | 0.93           | 999            | 3.3                        | 0.33           | 0.81           | 855            | 101          | 104                      | 125             | 108                  |     |     |     |     |     |
|                 |                   | Double               |                                    | 2.9                              | 0.31           | 0.70           | 742            | 2.4                        | 0.38           | 0.63           | 644            | 120          | 125                      | 167             | 133                  |     |     |     |     |     |
|                 | 3 position        | Exhaust center       |                                    | 2.5                              | 0.39           | 0.65           | 675            | 3.4<br>(2.1)               | 0.35<br>(0.38) | 0.82<br>(0.54) | 893<br>(563)   | 128          | 133                      | 175             | 141                  |     |     |     |     |     |
|                 |                   | Pressure center      |                                    | 4.3<br>(2.4)                     | 0.23<br>(0.32) | 0.97<br>(0.61) | 1048<br>(618)  | 2.2                        | 0.39           | 0.58           | 594            |              |                          |                 |                      |     |     |     |     |     |
| SY7□20<br>-□-08 | 2 position        | Single               |                                    | C8<br>(One-touch fitting for ø8) | 3.2            | 0.26           | 0.77           | 794                        | 3.2            | 0.37           | 0.82           |              |                          |                 |                      | 852 | 107 | 110 | 131 | 114 |
|                 |                   | Double               |                                    |                                  | 2.6            | 0.24           | 0.63           | 637                        | 2.4            | 0.31           | 0.62           |              |                          |                 |                      | 614 | 126 | 132 | 174 | 140 |
|                 | 3 position        | Closed center        |                                    |                                  | 2.4            | 0.25           | 0.57           | 592                        | 2.6<br>(1.9)   | 0.42<br>(0.46) | 0.70<br>(0.56) | 718<br>(541) | 134                      | 140             | 182                  | 148 |     |     |     |     |
|                 |                   | Exhaust center       |                                    |                                  | 3.3<br>(2.4)   | 0.28<br>(0.22) | 0.78<br>(0.57) | 829<br>(581)               | 2.2            | 0.34           | 0.60           | 574          |                          |                 |                      |     |     |     |     |     |
|                 |                   | Pressure center      | 3.8                                |                                  | 0.26           | 0.86           | 943            | 3.2                        | 0.34           | 0.82           | 835            | 103          |                          |                 |                      |     | 105 | 126 | 109 |     |
|                 |                   |                      | 2.8                                |                                  | 0.27           | 0.67           | 699            | 2.4                        | 0.21           | 0.59           | 578            | 122          |                          |                 |                      |     | 127 | 169 | 135 |     |
| SY7□20<br>-□-10 | 2 position        | Single               | C10<br>(One-touch fitting for ø10) | 2.5                              | 0.25           | 0.59           | 616            | 2.7<br>(2.0)               | 0.38<br>(0.38) | 0.70<br>(0.56) | 724<br>(536)   | 130          | 135                      | 177             | 143                  |     |     |     |     |     |
|                 |                   | Double               |                                    | 3.8<br>(2.4)                     | 0.25<br>(0.31) | 0.89<br>(0.61) | 937<br>(614)   | 2.3                        | 0.38           | 0.61           | 617            |              |                          |                 |                      |     |     |     |     |     |
|                 | 3 position        | Exhaust center       |                                    | 3.8                              | 0.26           | 0.86           | 943            | 3.2                        | 0.34           | 0.82           | 835            |              |                          |                 |                      | 103 | 105 | 126 | 109 |     |
|                 |                   | Pressure center      |                                    | 2.8                              | 0.27           | 0.67           | 699            | 2.4                        | 0.21           | 0.59           | 578            |              |                          |                 |                      | 122 | 127 | 169 | 135 |     |



Note ( ): denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Series SY9000

| Valve model     | Type of actuation | Port size            |                                    | Flow characteristics               |                |                |                |                            |                |                |                | Weight (g)     |                          |                 |                      |      |     |     |     |     |
|-----------------|-------------------|----------------------|------------------------------------|------------------------------------|----------------|----------------|----------------|----------------------------|----------------|----------------|----------------|----------------|--------------------------|-----------------|----------------------|------|-----|-----|-----|-----|
|                 |                   | 1, 5, 3<br>P, EA, EB | 4, 2<br>(A, B)                     | 1→4/2 (P→A/B)                      |                |                |                | 4/2→5/3 (A/B→EA/EB)        |                |                |                | Gro-<br>mmet   | L/M<br>plug<br>connector | DIN<br>terminal | W<br>M8<br>connector |      |     |     |     |     |
|                 |                   |                      |                                    | C (dm <sup>3</sup> /s·bar)         | b              | Cv             | Q [l/min(ANR)] | C (dm <sup>3</sup> /s·bar) | b              | Cv             | Q [l/min(ANR)] |                |                          |                 |                      |      |     |     |     |     |
| SY9□20<br>-□-02 | 2 position        | Single               | 1/4                                | 7.0                                | 0.33           | 1.7            | 1815           | 7.6                        | 0.35           | 2.0            | 1997           | 241            | 244                      | 265             | 248                  |      |     |     |     |     |
|                 |                   | Double               |                                    | 6.7                                | 0.37           | 1.7            | 1784           | 6.4                        | 0.34           | 1.6            | 1670           | 260            | 266                      | 308             | 274                  |      |     |     |     |     |
|                 | 3 position        | Exhaust center       |                                    | 6.4                                | 0.36           | 1.6            | 1693           | 8.3<br>(4.1)               | 0.41<br>(0.27) | 2.2<br>(0.91)  | 2274<br>(1023) | 284            | 290                      | 332             | 298                  |      |     |     |     |     |
|                 |                   | Pressure center      |                                    | 8.0<br>(3.2)                       | 0.27<br>(0.34) | 1.8<br>(0.76)  | 1997<br>(835)  | 6.5                        | 0.22           | 1.4            | 1575           |                |                          |                 |                      |      |     |     |     |     |
| SY9□20<br>-□-03 | 2 position        | Single               |                                    | 3/8                                | 8.0            | 0.29           | 1.9            | 2021                       | 8.0            | 0.33           | 2.0            |                |                          |                 |                      | 2074 | 236 | 239 | 260 | 243 |
|                 |                   | Double               |                                    |                                    | 7.9            | 0.33           | 1.9            | 2048                       | 6.6            | 0.27           | 1.6            |                |                          |                 |                      | 1647 | 255 | 261 | 303 | 269 |
|                 | 3 position        | Exhaust center       |                                    |                                    | 8.0            | 0.33           | 1.9            | 2074                       | 8.7<br>(8.3)   | 0.34<br>(0.40) | 2.2<br>(2.3)   | 2270<br>(2258) | 279                      | 285             | 327                  | 293  |     |     |     |     |
|                 |                   | Pressure center      |                                    |                                    | 8.9<br>(3.3)   | 0.34<br>(0.40) | 2.2<br>(0.82)  | 2323<br>(898)              | 6.5            | 0.25           | 1.5            | 1603           |                          |                 |                      |      |     |     |     |     |
| SY9□20<br>-□-08 | 2 position        | Single               | C8<br>(One-touch fitting for ø8)   | 4.3                                | 0.28           | 0.96           | 1080           | 7.1                        | 0.32           | 1.7            | 1829           | 293            |                          |                 |                      |      | 296 | 317 | 300 |     |
|                 |                   | Double               |                                    | 4.3                                | 0.31           | 0.99           | 1100           | 6.1                        | 0.28           | 1.4            | 1532           | 312            |                          |                 |                      |      | 318 | 360 | 326 |     |
|                 | 3 position        | Exhaust center       |                                    | 4.3                                | 0.3            | 0.99           | 1093           | 7.4<br>(3.8)               | 0.36<br>(0.29) | 1.9<br>(0.86)  | 1957<br>(960)  | 336            | 342                      | 384             | 350                  |      |     |     |     |     |
|                 |                   | Pressure center      |                                    | 4.4<br>(3.2)                       | 0.35<br>(0.26) | 1.0<br>(0.71)  | 1156<br>(794)  | 2.1                        | 0.41           | 0.53           | 575            |                |                          |                 |                      |      |     |     |     |     |
| SY9□20<br>-□-10 | 2 position        | Single               |                                    | C10<br>(One-touch fitting for ø10) | 6.1            | 0.28           | 1.4            | 1532                       | 7.9            | 0.33           | 1.9            |                |                          |                 |                      | 2048 | 279 | 282 | 303 | 286 |
|                 |                   | Double               |                                    |                                    | 5.9            | 0.30           | 1.4            | 1500                       | 6.5            | 0.26           | 1.5            |                |                          |                 |                      | 1612 | 298 | 304 | 346 | 312 |
|                 | 3 position        | Exhaust center       |                                    |                                    | 5.8            | 0.25           | 1.3            | 1430                       | 8.4<br>(4.1)   | 0.33<br>(0.27) | 2.0<br>(0.93)  | 2178<br>(1023) | 322                      | 328             | 370                  | 336  |     |     |     |     |
|                 |                   | Pressure center      |                                    |                                    | 6.3<br>(3.2)   | 0.29<br>(0.29) | 1.5<br>(0.72)  | 1592<br>(809)              | 6.4            | 0.25           | 1.5            | 1578           |                          |                 |                      |      |     |     |     |     |
| SY9□20<br>-□-12 | 2 position        | Single               | C12<br>(One-touch fitting for ø12) | 7.0                                | 0.25           | 1.6            | 1726           | 8.6                        | 0.41           | 2.2            | 2356           | 265            |                          |                 |                      |      | 268 | 289 | 272 |     |
|                 |                   | Double               |                                    | 6.9                                | 0.24           | 1.6            | 1691           | 7.0                        | 0.33           | 1.7            | 1815           | 284            |                          |                 |                      |      | 290 | 332 | 298 |     |
|                 | 3 position        | Exhaust center       |                                    | 6.6                                | 0.23           | 1.4            | 1608           | 9.4<br>(4.5)               | 0.48<br>(0.32) | 2.6<br>(1.0)   | 2718<br>(1159) | 308            | 314                      | 356             | 322                  |      |     |     |     |     |
|                 |                   | Pressure center      |                                    | 7.4<br>(3.2)                       | 0.25<br>(0.34) | 1.7<br>(0.74)  | 1825<br>(835)  | 6.6                        | 0.23           | 1.5            | 1608           |                |                          |                 |                      |      |     |     |     |     |








Note ( ): denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.


# Body Ported

## Construction

### Series SY



### 3 position closed center / exhaust center / pressure center



(This figure shows a closed center type.)

### Component Parts

| No. | Description          | Material   | Note                    |
|-----|----------------------|--|-------------------------|
| 1   | Body                 | Aluminum die-casted<br>(SY3000: Zinc die-casted) | White                   |
| 2   | Adapter plate        | Resin  | White<br>(SY9000: Gray) |
| 3   | End plate            | Resin  | White                   |
| 4   | Piston               | Resin  | —                       |
| 5   | Spool valve assembly | Aluminum, HNBR                                   | —                       |

### Replacement Parts

| No. | Description            | No.   |
|-----|------------------------|---|
| 6   | Pilot valve assembly   | Refer to "How to Order Pilot Valve Assembly" on page 5. |
| 7   | M5 port block assembly | Refer to "How to Order Port Block Assembly" on page 6.  |

### Bracket Assembly No.


| Description      | No.   |
|------------------|---|
| Bracket (For F1) | SX <sup>3</sup> 000-16-2A (with mounting screw) |
| Bracket (For F2) | SX <sup>3</sup> 000-16-1A (with mounting screw) |

\* SY9000 has no bracket.

### How to Change Port Block Assembly

If using body port type, both A and B port sizes can be changed by replacing the port block assembly mounted on the body. When changing this block assembly, the correct screw torque must be achieved to avoid possible air leakage.

#### For SY5000



### Caution

#### Mounting screw tightening torques

SY3000 (M2): 0.12 N·m  
SY<sup>5</sup>000 (M3): 0.6 N·m  
SY9000 (M4): 1.4 N·m

\* Refer to "How to Order Port Block Assembly" on page 6 for part no.

# SY3000/5000/7000/9000 Body Ported

## How to Order Pilot Valve Assembly

## How to Order Connector Assembly for L/M Plug Connector

V111  5 G

**Coil specifications**

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W  type.

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

**Light/surge voltage suppressor**

|     |  |
|-----|--|
| Nil | Without light/surge voltage suppressor               |
| S   | With surge voltage suppressor                        |
| Z   | With light/surge voltage suppressor                  |
| R   | With surge voltage suppressor (Non-polar type)       |
| U   | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry**

|                            |                           |                               |
|----------------------------|---------------------------|-------------------------------|
| G                          | Grommet, 300 mm lead wire |                               |
| H                          | Grommet, 600 mm lead wire |                               |
| L                          | L plug connector          | With lead wire                |
| LN                         |                           | Without lead wire             |
| LO                         |                           | Without connector             |
| M                          | M plug connector          | With lead wire                |
| MN                         |                           | Without lead wire             |
| MO                         |                           | Without connector             |
| WO                         | M8                        | Without connector cable       |
| W <input type="checkbox"/> | connector                 | With connector cable (Note 1) |

\* For connector cable of M8 connector, refer to back page 12.  
Note 1) Enter the cable length symbols in . Please be sure to fill in the blank referring to back page 13.

For DC: SY100-30-4A-

Without lead wire: SY100-30-A  
(with connector and 2 of sockets only)

**Lead wire length**

|    |         |
|----|---------|
| -  | 300 mm  |
| 6  | 600 mm  |
| 10 | 1000 mm |
| 15 | 1500 mm |
| 20 | 2000 mm |
| 25 | 2500 mm |
| 30 | 3000 mm |
| 50 | 5000 mm |

## How to Order M8 Connector Cable

### ■ Straight type

V100-49-1-

**Cable length**

|   |         |
|---|---------|
| 1 | 300 mm  |
| 2 | 500 mm  |
| 3 | 1000 mm |
| 4 | 2000 mm |
| 7 | 5000 mm |

### ■ DIN terminal type

V115-5 D

**Rated voltage**

|   |   |
|---|---|
| 5 | 24 VDC  |
| 6 | 12 VDC  |
| 1 | 100 VAC <sup>50/60</sup> Hz                               |
| 2 | 200 VAC <sup>50/60</sup> Hz                               |
| 3 | 110 VAC <sup>50/60</sup> Hz [115 VAC <sup>50/60</sup> Hz] |
| 4 | 220 VAC <sup>50/60</sup> Hz [230 VAC <sup>50/60</sup> Hz] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.

**Light/surge voltage suppressor**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**

|    |          |                   |
|----|----------|-------------------|
| D  | DIN      | With connector    |
| DO | terminal | Without connector |

Note) Do not replace V111 (G, H, L, M) to V115 (DIN terminal) and vice versa when replacing pilot valve assembly only.

## How to Order Port Block Assembly

SY  000-6A-

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |
| 9 | SY9000 |

**Thread type**

|     |      |
|-----|------|
| Nil | Rc   |
| F   | G    |
| N   | NPT  |
| T   | NPTF |

\* Except for M5

### ● A, B port size Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |
| 02     | 1/4       | SY7000            |
| 02     | 1/4       | SY9000            |
| 03     | 3/8       |                   |

### One-touch fitting (Metric size)


| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  |                   |
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  |                   |
| C8     | One-touch fitting for ø8  |                   |
| C8     | One-touch fitting for ø8  | SY7000            |
| C10    | One-touch fitting for ø10 |                   |
| C8     | One-touch fitting for ø8  | SY9000            |
| C10    | One-touch fitting for ø10 |                   |
| C12    | One-touch fitting for ø12 |                   |

### One-touch fitting (Inch size)

| Symbol | Port size                     | Applicable series |
|--------|-------------------------------|-------------------|
| N3     | One-touch fitting for ø 5/32" | SY3000            |
| N7     | One-touch fitting for ø 1/4"  |                   |
| N3     | One-touch fitting for ø 5/32" | SY5000            |
| N7     | One-touch fitting for ø 1/4"  |                   |
| N9     | One-touch fitting for ø 5/16" |                   |
| N9     | One-touch fitting for ø 5/16" | SY7000            |
| N11    | One-touch fitting for ø 3/8"  |                   |
| N9     | One-touch fitting for ø 5/16" | SY9000            |
| N11    | One-touch fitting for ø 3/8"  |                   |

\* Only replacement of the fittings assembly is possible.

| Metric size |                           | Inch size       |        |                               |                 |
|-------------|---------------------------|-----------------|--------|-------------------------------|-----------------|
| SY3000      | One-touch fitting for ø4  | VVQ1000-50A-C4  | SY3000 | One-touch fitting for ø 5/32" | VVQ1000-50A-N3  |
|             | One-touch fitting for ø6  | VVQ1000-50A-C6  |        | One-touch fitting for ø 1/4"  | VVQ1000-50A-N7  |
|             | One-touch fitting for ø4  | VVQ1000-51A-C4  |        | One-touch fitting for ø 5/32" | VVQ1000-51A-N3  |
| SY5000      | One-touch fitting for ø6  | VVQ1000-51A-C6  | SY5000 | One-touch fitting for ø 1/4"  | VVQ1000-51A-N7  |
|             | One-touch fitting for ø8  | VVQ1000-51A-C8  |        | One-touch fitting for ø 5/16" | VVQ1000-51A-N9  |
| SY7000      | One-touch fitting for ø8  | VVQ2000-51A-C8  | SY7000 | One-touch fitting for ø 5/16" | VVQ2000-51A-N9  |
|             | One-touch fitting for ø10 | VVQ2000-51A-C10 |        | One-touch fitting for ø 3/8"  | VVQ2000-51A-N11 |
| SY9000      | One-touch fitting for ø8  | VVQ4000-50B-C8  | SY9000 | One-touch fitting for ø 5/16" | VVQ4000-50B-N9  |
|             | One-touch fitting for ø10 | VVQ4000-50B-C10 |        | One-touch fitting for ø 3/8"  | VVQ4000-50B-N11 |
|             | One-touch fitting for ø12 | VVQ4000-50B-C12 |        |                               |                 |




# Body Ported

## Dimensions: Series SY3000


### 2 position single

Grommet (G), (H): SY3120-□<sub>G</sub>□□-C<sub>4</sub>, N<sub>3</sub>  
C<sub>6</sub>, N<sub>7</sub>-(F<sub>2</sub>)-Q




### Foot bracket

SY3120-□<sub>G</sub>□□-C<sub>4</sub>, N<sub>3</sub>  
C<sub>6</sub>, N<sub>7</sub>-F<sub>1</sub>-Q




SY3120-□<sub>G</sub>□□-M5-(F<sub>2</sub>)-Q




### L plug connector (L):

SY3120-□<sub>L</sub>□□-C<sub>4</sub>, N<sub>3</sub>  
C<sub>6</sub>, N<sub>7</sub>-(F<sub>1</sub>)-Q




### M plug connector (M):

SY3120-□<sub>M</sub>□□-C<sub>4</sub>, N<sub>3</sub>  
C<sub>6</sub>, N<sub>7</sub>-(F<sub>1</sub>)-Q



### M8 connector (WO):

SY3120-□<sub>WO</sub>□□-C<sub>4</sub>, N<sub>3</sub>  
C<sub>6</sub>, N<sub>7</sub>-(F<sub>1</sub>)-Q





Note) Refer to back page 12 for dimensions of connector types.

## Dimensions: Series SY3000

### 2 position double


Grommet (G), (H): SY3220-□<sub>G</sub>□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>(-F<sub>2</sub>)-Q

SY3220-□<sub>G</sub>□□-M5(-F<sub>2</sub>)-Q





G: Approx. 300


H: Approx. 600




Applicable tubing O.D.: ø4, ø5/32"  
: ø6, ø1/4"




L plug connector (L):  
SY3220-□L□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>(-F<sub>1</sub>)-Q



M plug connector (M):  
SY3220-□M□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>(-F<sub>2</sub>)-Q



M8 connector (WO):  
SY3220-WO□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>(-F<sub>2</sub>)-Q






Note) Refer to back page 12 for dimensions of connector types.

# Body Ported


## Dimensions: Series SY3000

3 position closed center / exhaust center / pressure center

Grommet (G), (H): SY3<sup>3</sup>/<sub>5</sub>20-□G□□-C<sub>4</sub>, N<sub>3</sub>/<sub>C<sub>6</sub>, N<sub>7</sub></sub>(-F2)-Q




SY3<sup>3</sup>/<sub>5</sub>20-□H□□-M5(-F2)-Q




L plug connector (L):

SY3<sup>3</sup>/<sub>5</sub>20-□L□□-C<sub>4</sub>, N<sub>3</sub>/<sub>C<sub>6</sub>, N<sub>7</sub></sub>(-F2)-Q




M plug connector (M):

SY3<sup>3</sup>/<sub>5</sub>20-□M□□-C<sub>4</sub>, N<sub>3</sub>/<sub>C<sub>6</sub>, N<sub>7</sub></sub>(-F2)-Q



M8 connector (WO):

SY3<sup>3</sup>/<sub>5</sub>20-□WO□□-C<sub>4</sub>, N<sub>3</sub>/<sub>C<sub>6</sub>, N<sub>7</sub></sub>(-F2)-Q




Note) Refer to back page 12 for dimensions of connector types.

## Dimensions: Series SY5000


### 2 position single

Grommet (G), (H): SY5120-□<sup>G</sup>□□-<sup>C4, N3</sup>□□-<sup>C6, N7</sup>□□(-F<sub>2</sub>)-Q  
<sup>C8, N9</sup>




### Foot bracket

SY5120-□<sup>G</sup>□□-<sup>C4, N3</sup>□□-<sup>C6, N7</sup>□□(-F<sub>1</sub>)-Q  
<sup>C8, N9</sup>




SY5120-□<sup>G</sup>□□-01□(-F<sub>2</sub>)-Q




### L plug connector: L

SY5120-□L□□-<sup>C4, N3</sup>□□(-F<sub>2</sub>)-Q  
<sup>C6, N7</sup>□□  
<sup>C8, N9</sup>




### M plug connector: M

SY5120-□M□□-<sup>C4, N3</sup>□□(-F<sub>2</sub>)-Q  
<sup>C6, N7</sup>□□  
<sup>C8, N9</sup>




### DIN terminal (D):

SY5120-□D□□-<sup>C4, N3</sup>□□(-F<sub>2</sub>)-Q  
<sup>C6, N7</sup>□□  
<sup>C8, N9</sup>



### M8 connector (WO):

SY5120-□WO□□-<sup>C4, N3</sup>□□(-F<sub>2</sub>)-Q  
<sup>C6, N7</sup>□□  
<sup>C8, N9</sup>



Note) Refer to back page 12 for dimensions of connector types.



# Body Ported

## Dimensions: Series SY5000

2 position double


Grommet (G), (H): SY5220-□<sup>G</sup>□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>□(-F2)-Q  
C<sub>8</sub>, N<sub>9</sub>

SY5220-□<sup>H</sup>□□-01□(-F2)-Q



G: Approx. 300  
H: Approx. 600

(Lead wire length)



L plug connector (L):

SY5220-□L□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>□(-F2)-Q  
C<sub>8</sub>, N<sub>9</sub>

M plug connector (M):





SY5220-□M□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>□(-F2)-Q  
C<sub>8</sub>, N<sub>9</sub>

DIN terminal (D):

SY5220-□D□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>□(-F2)-Q  
C<sub>8</sub>, N<sub>9</sub>

M8 connector (WO):

SY5220-□WO□□-C<sub>4</sub>, N<sub>3</sub>-C<sub>6</sub>, N<sub>7</sub>□(-F2)-Q  
C<sub>8</sub>, N<sub>9</sub>






Note) Refer to back page 12 for dimensions of connector types.

# SY3000/5000/7000/9000 Body Ported

## Dimensions: Series SY5000

3 position closed center / exhaust center / pressure center

Grommet (G), (H): SY5<sup>3</sup><sub>5</sub>420-□<sup>G</sup>□□<sup>C4, N3</sup>□□<sup>C6, N7</sup>□□(-F2)-Q  
C8, N9



G: Approx. 300  
H: Approx. 600  
(Lead wire length)

L plug connector (L):

SY5<sup>3</sup><sub>5</sub>420-□L□□<sup>C4, N3</sup>□□<sup>C6, N7</sup>□□(-F2)-Q  
C8, N9

M plug connector (M):





SY5<sup>3</sup><sub>5</sub>420-□M□□<sup>C4, N3</sup>□□<sup>C6, N7</sup>□□(-F2)-Q  
C8, N9

DIN terminal (D):

SY5<sup>3</sup><sub>5</sub>420-□D□□<sup>C4, N3</sup>□□<sup>C6, N7</sup>□□(-F2)-Q  
C8, N9

M8 connector (WO):

SY5<sup>3</sup><sub>5</sub>420-□WO□□<sup>C4, N3</sup>□□<sup>C6, N7</sup>□□(-F2)-Q  
C8, N9




Note) Refer to back page 12 for dimensions of connector types.

# Body Ported


## Dimensions: Series SY7000

### 2 position single


Grommet (G), (H): SY7120-□G□□-C8, N9  
C10, N11 □(-F2)-Q



SY7120-□G□□-C8, N9  
C10, N11 □(-F1)-Q



SY7120-□G□□-02□(-F2)-Q



L plug connector (L):

SY7120-□L□□-C8, N9  
C10, N11 □(-F2<sub>1</sub>)-Q

M plug connector (M):





SY7120-□M□□-C8, N9  
C10, N11 □(-F2<sub>2</sub>)-Q

DIN terminal (D):

SY7120-□D□□-C8, N9  
C10, N11 □(-F2<sub>1</sub>)-Q

M8 connector (WO):

SY7120-□WO□□-C8, N9  
C10, N11 □(-F2<sub>1</sub>)-Q



Note) Refer to back page 12 for dimensions of connector types.



# SY3000/5000/7000/9000 Body Ported

## Dimensions: Series SY7000

### 2 position double

Grommet (G), (H): SY7220-□<sup>G</sup>□□-C8, N9 □(-F2)-Q  
C10, N11

SY7220-□<sup>G</sup>□□-02□(-F2)-Q



### L plug connector (L):

SY7220-□<sup>L</sup>□□-C8, N9 □(-F2)-Q  
C10, N11

### M plug connector (M):





SY7220-□<sup>M</sup>□□-C8, N9 □(-F2)-Q  
C10, N11

### DIN terminal (D):

SY7220-□<sup>D</sup>□□-C8, N9 □(-F2)-Q  
C10, N11

### M8 connector (WO):

SY7220-□<sup>WO</sup>□□-C8, N9 □(-F2)-Q  
C10, N11





Note) Refer to back page 12 for dimensions of connector types.

# Body Ported

## Dimensions: Series SY7000


3 position closed center / exhaust center / pressure center  
 Grommet (G), (H): SY7<sup>3</sup>/<sub>5</sub>20-□<sup>G</sup>□□□-C<sub>8, N<sub>9</sub></sub>-C<sub>10, N<sub>11</sub></sub>□(-F2)-Q

SY7<sup>3</sup>/<sub>5</sub>20-□<sup>G</sup>□□□-02□(-F2)-Q




### L plug connector (L):

SY7<sup>3</sup>/<sub>5</sub>20-□<sup>L</sup>□□□-C<sub>8, N<sub>9</sub></sub>-C<sub>10, N<sub>11</sub></sub>□(-F2)-Q




### M plug connector (M):

SY7<sup>3</sup>/<sub>5</sub>20-□<sup>M</sup>□□□-C<sub>8, N<sub>9</sub></sub>-C<sub>10, N<sub>11</sub></sub>□(-F2)-Q




### DIN terminal (D):

SY7<sup>3</sup>/<sub>5</sub>20-□<sup>D</sup>□□□-C<sub>8, N<sub>9</sub></sub>-C<sub>10, N<sub>11</sub></sub>□(-F2)-Q



### M8 connector (WO):

SY7<sup>3</sup>/<sub>5</sub>20-□<sup>WO</sup>□□□-C<sub>8, N<sub>9</sub></sub>-C<sub>10, N<sub>11</sub></sub>□(-F2)-Q



Note) Refer to back page 12 for dimensions of connector types.




# SY3000/5000/7000/9000 Body Ported

## Dimensions: Series SY9000

### 2 position single

Grommet (G), (H): SYJ9120-□<sup>G</sup>□□□□<sup>C8, N9</sup>-□□□□<sup>C10, N11</sup>-□□<sup>C12</sup>-Q

SY9120-□<sup>G</sup>□□□□-02□□-Q







**L plug connector (L):**  
SY9120-□L□□□□<sup>C8, N9</sup>-□□□□<sup>C10, N11</sup>-□□<sup>C12</sup>-Q

**M plug connector (M):**  
SY9120-□M□□□□<sup>C8, N9</sup>-□□□□<sup>C10, N11</sup>-□□<sup>C12</sup>-Q

**DIN terminal (D):**  
SY9120-□D□□□□<sup>C8, N9</sup>-□□□□<sup>C10, N11</sup>-□□<sup>C12</sup>-Q

**M8 connector (WO):**  
SY9120-□WO□□□□<sup>C8, N9</sup>-□□□□<sup>C10, N11</sup>-□□<sup>C12</sup>-Q



Note) Refer to back page 12 for dimensions of connector types.



# Body Ported

## Dimensions: Series SY9000

### 2 position double

Grommet (G), (H): SY9220-□<sub>G</sub>□□□<sub>C8, N9</sub>-□□□<sub>C10, N11</sub>-□□□<sub>C12</sub>-Q

SY9220-□<sub>G</sub>□□□<sub>02</sub>□□□<sub>03</sub>-Q



### L plug connector (L):

SY9220-□L□□□<sub>C8, N9</sub>-□□□<sub>C10, N11</sub>-□□□<sub>C12</sub>-Q

### M plug connector (M):





SY9220-□M□□□<sub>C8, N9</sub>-□□□<sub>C10, N11</sub>-□□□<sub>C12</sub>-Q

### DIN terminal (D):

SY9220-□D□□□<sub>C8, N9</sub>-□□□<sub>C10, N11</sub>-□□□<sub>C12</sub>-Q

### M8 connector (WO):

SY9220-□WO□□□<sub>C8, N9</sub>-□□□<sub>C10, N11</sub>-□□□<sub>C12</sub>-Q



Note) Refer to back page 12 for dimensions of connector types.



# SY3000/5000/7000/9000 Body Ported

## Dimensions: Series SY9000


3 position closed center / exhaust center / pressure

Grommet (G), (H): SY9<sup>3</sup>/<sub>5</sub>420-□<sup>G</sup>□□-C<sup>C8, N9</sup><sub>10, N11</sub>□-Q  
C12

SY9<sup>3</sup>/<sub>5</sub>420-□<sup>G</sup>□□-02□-Q



G: Approx. 300  
H: Approx. 600  
(Lead wire length)



One-touch fitting [4 (A), 2 (B) port]  
Applicable tubing O.D. : ø8, ø5/16"  
: ø10, ø3/8"  
: ø12

L plug connector (L):

SY9<sup>3</sup>/<sub>5</sub>420-□L□□-C<sup>C8, N9</sup><sub>10, N11</sub>□-Q  
C12

M plug connector (M):





SY9<sup>3</sup>/<sub>5</sub>420-□M□□-C<sup>C8, N9</sup><sub>10, N11</sub>□-Q  
C12

DIN terminal (D):

SY9<sup>3</sup>/<sub>5</sub>420-□D□□-C<sup>C8, N9</sup><sub>10, N11</sub>□-Q  
C12

M8 connector (WO):

SY9<sup>3</sup>/<sub>5</sub>420-□WO□□-C<sup>C8, N9</sup><sub>10, N11</sub>□-Q  
C12



Note) Refer to back page 12 for dimensions of connector types.

# 5 Port Solenoid Valve

## Series SY3000/5000/7000/9000

### Base Mounted

# Single Unit



Refer to [www.smcworld.com](http://www.smcworld.com) for details of products compatible with overseas standards.

### How to Order

SY **5** **2** 40 **5** **L** **-Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |
| 9 | SY9000 |

**Type of actuation**

|   |                                |
|---|--------------------------------|
| 1 | 2 position single<br>          |
| 2 | 2 position double<br>          |
| 3 | 3 position closed center<br>   |
| 4 | 3 position exhaust center<br>  |
| 5 | 3 position pressure center<br> |

**Pilot type**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

**Coil specifications**

|   |   |
|---|---|
| - | Standard                                    |
| T | With power saving circuit (24, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

**Rated voltage**

| For DC |        |
|--------|--------|
| 5      | 24 VDC |
| 6      | 12 VDC |
| V      | 6 VDC  |
| S      | 5 VDC  |
| R      | 3 VDC  |

**For AC (50/60 Hz)**

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D, DO type.


**Port size**

| Symbol | Port size          | Applicable series |
|--------|--------------------|-------------------|
| -      | Without sub-plate  |                   |
| 01     | 1/8 With sub-plate | SY3000            |
| 02     | 1/4 With sub-plate | SY5000<br>SY7000  |
| 03     | 3/8 With sub-plate | SY7000<br>SY9000  |
| 04     | 1/2 With sub-plate | SY9000            |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**Manual override**



**(Light/surge voltage suppressor)**

**Electrical entry for G, H, L, M, W**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry for D (Except SY3000)**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**

| 24, 12, 6, 5, 3 VDC               |  |  |                              | 24, 12 VDC/<br>100, 110, 200, 220 VAC        | 24, 12, 6, 5, 3 VDC                      |
|-----------------------------------|--|--|------------------------------|--|--|
| Grommet                           | L plug connector                         | M plug connector                         |                              | DIN terminal                                 | M8 connector *                           |
| <p>G: Lead wire length 300 mm</p> | <p>L: With lead wire (Length 300 mm)</p> | <p>M: With lead wire (Length 300 mm)</p> | <p>MN: Without lead wire</p> | <p>(Except SY3000)<br/>D: With connector</p> | <p>W□: Without connector cable</p>       |
| <p>H: Lead wire length 600 mm</p> | <p>LN: Without lead wire</p>             | <p>LO: Without connector</p>             | <p>MO: Without connector</p> | <p>DO: Without connector</p>                 | <p>W□: With connector cable (Note 1)</p> |

\* LN, MN type: with 2 sockets.  
\* For DIN terminal of SY3000 series, refer to back page 10.

\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.

\* For connector cable of M8 connector, refer to back page 12.  
\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.

Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.

# SY3000/5000/7000/9000 Base Mounted

## Specifications



**Made to Order**

(For details, refer to pages 199 through to 213.)

| Series   |                            | SY3000   | SY5000          | SY7000 | SY9000 |
|--|----------------------------|--|-----------------|--------|--------|
| Fluid  |                            | Air  |                 |        |        |
| Internal pilot<br>Operating pressure<br>range(MPa)                   | 2 position single          | 0.15 to 0.7  |                 |        |        |
|  | 2 position double          | 0.1 to 0.7   |                 |        |        |
|  | 3 position                 | 0.2 to 0.7   |                 |        |        |
| External pilot<br>Operating pressure<br>range(MPa)                   | Operating pressure range   |  | -100 kPa to 0.7 |        |        |
|  | Pilot<br>pressure<br>range | 2 position single  | 0.25 to 0.7     |        |        |
|  |                            | 2 position double  | 0.25 to 0.7     |        |        |
|  |                            | 3 position   | 0.25 to 0.7     |        |        |
| Ambient and fluid temperature (°C)                                   |                            | -10 to 50 (No freezing. Refer to back page 3.)   |                 |        |        |
| Max. operating<br>frequency (Hz)                                     | 2 Position single, Double  | 10   | 5               | 5      | 5      |
|  | 3 position                 | 3  | 3               | 3      | 3      |
| Manual override<br>(Manual operation)                                |                            | Non-locking push type,<br>Push-turn locking slotted type, Push-turn locking lever type |                 |        |        |
| Pilot exhaust<br>method  | Internal pilot             | Common exhaust type for main and pilot valve   |                 |        |        |
|  | External pilot             | Pilot valve individual exhaust   |                 |        |        |
| Lubrication  |                            | Not required   |                 |        |        |
| Mounting orientation   |                            | Unrestricted   |                 |        |        |
| Impact/Vibration resistance (m/s <sup>2</sup> ) <small>Note)</small> |                            | 150/30   |                 |        |        |
| Enclosure  |                            | Dust proof (* DIN terminal and M8 connector: IP65)                                     |                 |        |        |



\* Based on IEC60529)

Note) Impact resistance: No malfunction occurred when it is tested in the axial direction and at the right angles to the main valve and armature in both energised and de-energised states every once for each condition. (Values at the initial period)

Vibration resistance: No malfunction occurred in a one-sweep test between 45 and 2000 Hz. Test was performed at both energised and de-energised states in the axial direction and at the right angles to the main valve and armature. (Values at the initial period)

## Response Time



Note) Based on dynamic performance test, JIS B 8375-1981. (Coil temperature: 20°C, at rated voltage)

### SY3000

| Type of<br>actuation | Response time (ms)<br>(at the pressure of 0.5 MPa) |                                     |            |
|----------------------|--|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor          | With light/surge voltage suppressor |            |
|                      |  | Type S, Z                           | Type R, U  |
| 2 position single    | 12 or less   | 15 or less                          | 12 or less |
| 2 position double    | 10 or less   | 13 or less                          | 10 or less |
| 3 position           | 15 or less   | 20 or less                          | 16 or less |

### SY5000

| Type of<br>actuation | Response time (ms)<br>(at the pressure of 0.5 MPa) |                                     |            |
|----------------------|--|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor          | With light/surge voltage suppressor |            |
|                      |  | Type S, Z                           | Type R, U  |
| 2 position single    | 19 or less   | 26 or less                          | 19 or less |
| 2 position double    | 18 or less   | 22 or less                          | 18 or less |
| 3 position           | 32 or less   | 38 or less                          | 32 or less |

### SY7000

| Type of<br>actuation | Response time (ms)<br>(at the pressure of 0.5 MPa) |                                     |            |
|----------------------|--|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor          | With light/surge voltage suppressor |            |
|                      |  | Type S, Z                           | Type R, U  |
| 2 position single    | 31 or less   | 38 or less                          | 33 or less |
| 2 position double    | 27 or less   | 30 or less                          | 28 or less |
| 3 position           | 50 or less   | 56 or less                          | 50 or less |

### SY9000

| Type of<br>actuation | Response time (ms)<br>(at the pressure of 0.5 MPa) |                                     |            |
|----------------------|--|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor          | With light/surge voltage suppressor |            |
|                      |  | Type S, Z                           | Type R, U  |
| 2 position single    | 35 or less   | 41 or less                          | 35 or less |
| 2 position double    | 35 or less   | 41 or less                          | 35 or less |
| 3 position           | 62 or less   | 64 or less                          | 62 or less |

## Solenoid Specifications

| Electrical entry                  | Grommet (G), (H)<br>L plug connector (L)<br>M plug connector (M) |                           | DIN terminal (D)<br>M8 connector (W)  |
|-----------------------------------|--|---------------------------|---|
|                                   | G, H, L, M, W  |                           | D   |
| Coil rated<br>voltage (V)         | DC   | 24, 12, 6, 5, 3           | 24, 12  |
|                                   | AC 50/60 Hz  | 100, 110                  | 200, 220  |
| Allowable voltage fluctuation (%) | ±10% of rated voltage *  |                           |   |
| Power<br>consumption (W)          | DC   | Standard                  | 0.35 (With indicator light: 0.4 DIN terminal with indicator light: 0.45)      |
|                                   |  | With power saving circuit | 0.1 (With indicator light only)   |
| Apparent power<br>(VA) *          | AC   | 100 V                     | -<br>0.78 (With indicator light: 0.87)  |
|                                   |  | 110 V                     | -<br>0.86 (With indicator light: 0.97)  |
|                                   |  | [115 V]                   | -<br>[0.94 (With indicator light: 1.07)]                                      |
|                                   |  | 200 V                     | -<br>1.15 (With indicator light: 1.30)  |
|                                   |  | 220 V<br>[230 V]          | -<br>1.27 (With indicator light: 1.46)<br>[1.39 (With indicator light: 1.60)] |
| Surge voltage suppressor          | Diode (Varistor is for DIN terminal and Non-polar type.)         |                           |   |
| Indicator light                   | LED (AC of DIN connector is neon light.)                         |                           |   |



\* In common between 110 VAC and 115 VAC, and between 220 VAC and 230 VAC.

\* For 115 VAC and 230 VAC, the allowable voltage is -15% to +5% of rated voltage.

\* S, Z and T type (with power saving circuit) should be used within the following allowable voltage fluctuation range due to a voltage drop caused by the internal circuit.

S and Z type: 24 VDC: -7% to +10%

12 VDC: -4% to +10%

T type: 24 VDC: -8% to +10%

12 VDC: -6% to +10%

# Base Mounted

## Flow Characteristics/Weight

### Series SY3000

| Valve model | Type of actuation |                 | Port size | Flow characteristics <sup>Note 1)</sup> |             |             |                            |                              |             |             |                            | Weight (g) <sup>Note 2)</sup> |                                       |                   |
|-------------|-------------------|-----------------|-----------|---|-------------|-------------|----------------------------|------------------------------|-------------|-------------|----------------------------|-------------------------------|---------------------------------------|-------------------|
|             |                   |                 |           | 1 → 4/2 (P → A/B)                       |             |             |                            | 4/2 → 5/3 (A/B → EA/EB)      |             |             |                            | Grommet                       | L plug connector,<br>M plug connector | W<br>M8 connector |
|             |                   |                 |           | C (dm <sup>3</sup> /(s·bar))            | b           | Cv          | Q <sub>l</sub> /(min(ANR)) | C (dm <sup>3</sup> /(s·bar)) | b           | Cv          | Q <sub>l</sub> /(min(ANR)) |                               |                                       |                   |
| SY3□40-□-01 | 2 position        | Single          | 1/8       | 1.0                                     | 0.30        | 0.24        | 254                        | 1.1                          | 0.30        | 0.26        | 280                        | 104 [69]                      | 109 [74]                              | 117 [82]          |
|             |                   | Double          |           |   |             |             |                            |                              |             |             |                            |                               |                                       |                   |
|             | 3 position        | Closed center   |           | 0.77                                    | 0.28        | 0.18        | 193                        | 0.85                         | 0.30        | 0.19        | 216                        |                               |                                       |                   |
|             |                   | Exhaust center  |           | 0.73                                    | 0.31        | 0.18        | 187                        | 1.1 (0.55)                   | 0.26 (0.52) | 0.24 (0.16) | 273 (164)                  |                               |                                       |                   |
|             |                   | Pressure center |           | 1.2 (0.51)                              | 0.24 (0.45) | 0.29 (0.14) | 294 (144)                  | 0.89                         | 0.47        | 0.24        | 255                        |                               |                                       |                   |



Note 1) [ ]: denotes the normal position. Note 2) [ ]: denotes without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Series SY5000

| Valve model | Type of actuation |                 | Port size | Flow characteristics <sup>Note 1)</sup> |             |             |                            |                              |             |             |                            | Weight (g) <sup>Note 2)</sup> |                                       |              |                   |
|-------------|-------------------|-----------------|-----------|---|-------------|-------------|----------------------------|------------------------------|-------------|-------------|----------------------------|-------------------------------|---------------------------------------|--------------|-------------------|
|             |                   |                 |           | 1 → 4/2 (P → A/B)                       |             |             |                            | 4/2 → 5/3 (A/B → EA/EB)      |             |             |                            | Grommet                       | L plug connector,<br>M plug connector | DIN terminal | W<br>M8 connector |
|             |                   |                 |           | C (dm <sup>3</sup> /(s·bar))            | b           | Cv          | Q <sub>l</sub> /(min(ANR)) | C (dm <sup>3</sup> /(s·bar)) | b           | Cv          | Q <sub>l</sub> /(min(ANR)) |                               |                                       |              |                   |
| SY5□40-□-02 | 2 position        | Single          | 1/4       | 2.4                                     | 0.41        | 0.64        | 658                        | 2.8                          | 0.29        | 0.66        | 707                        | 144 [82]                      | 150 [87]                              | 192 [129]    | 158 [95]          |
|             |                   | Double          |           |   |             |             |                            |                              |             |             |                            |                               |                                       |              |                   |
|             | 3 position        | Closed center   |           | 1.8                                     | 0.47        | 0.50        | 516                        | 1.8                          | 0.40        | 0.47        | 490                        |                               |                                       |              |                   |
|             |                   | Exhaust center  |           | 1.4                                     | 0.55        | 0.44        | 430                        | 3.0 (1.2)                    | 0.33 (0.48) | 0.72 (0.37) | 778 (347)                  |                               |                                       |              |                   |
|             |                   | Pressure center |           | 3.3 (0.84)                              | 0.36 (0.60) | 0.85 (0.28) | 873 (270)                  | 1.8                          | 0.40        | 0.48        | 490                        |                               |                                       |              |                   |



Note 1) [ ]: denotes the normal position. Note 2) [ ]: denotes without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Series SY7000

| Valve model | Type of actuation |                 | Port size | Flow characteristics <sup>Note 1)</sup> |             |            |                            |                              |             |            |                            | Weight (g) <sup>Note 2)</sup> |                                       |              |                   |
|-------------|-------------------|-----------------|-----------|---|-------------|------------|----------------------------|------------------------------|-------------|------------|----------------------------|-------------------------------|---------------------------------------|--------------|-------------------|
|             |                   |                 |           | 1 → 4/2 (P → A/B)                       |             |            |                            | 4/2 → 5/3 (A/B → EA/EB)      |             |            |                            | Grommet                       | L plug connector,<br>M plug connector | DIN terminal | W<br>M8 connector |
|             |                   |                 |           | C (dm <sup>3</sup> /(s·bar))            | b           | Cv         | Q <sub>l</sub> /(min(ANR)) | C (dm <sup>3</sup> /(s·bar)) | b           | Cv         | Q <sub>l</sub> /(min(ANR)) |                               |                                       |              |                   |
| SY7□40-□-02 | 2 position        | Single          | 1/4       | 4.1                                     | 0.41        | 1.1        | 1123                       | 4.1                          | 0.29        | 1.0        | 1036                       | 239 [110]                     | 245 [116]                             | 287 [158]    | 253 [124]         |
|             |                   | Double          |           |   |             |            |                            |                              |             |            |                            |                               |                                       |              |                   |
|             | 3 position        | Closed center   |           | 3.0                                     | 0.43        | 0.80       | 834                        | 2.6                          | 0.41        | 0.72       | 712                        |                               |                                       |              |                   |
|             |                   | Exhaust center  |           | 2.6                                     | 0.42        | 0.71       | 718                        | 4.7 (1.7)                    | 0.35 (0.48) | 1.1 (0.49) | 1235 (492)                 |                               |                                       |              |                   |
|             |                   | Pressure center |           | 5.3 (2.3)                               | 0.39 (0.49) | 1.3 (0.65) | 1431 (670)                 | 2.2                          | 0.49        | 0.63       | 641                        |                               |                                       |              |                   |



Note 1) [ ]: denotes the normal position. Note 2) [ ]: denotes without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Series SY9000

| Valve model | Type of actuation |                 | Port size | Flow characteristics <sup>Note 1)</sup> |             |            |                            |                              |             |            |                            | Weight (g) <sup>Note 2)</sup> |                                       |              |                   |
|-------------|-------------------|-----------------|-----------|---|-------------|------------|----------------------------|------------------------------|-------------|------------|----------------------------|-------------------------------|---------------------------------------|--------------|-------------------|
|             |                   |                 |           | 1 → 4/2 (P → A/B)                       |             |            |                            | 4/2 → 5/3 (A/B → EA/EB)      |             |            |                            | Grommet                       | L plug connector,<br>M plug connector | DIN terminal | W<br>M8 connector |
|             |                   |                 |           | C (dm <sup>3</sup> /(s·bar))            | b           | Cv         | Q <sub>l</sub> /(min(ANR)) | C (dm <sup>3</sup> /(s·bar)) | b           | Cv         | Q <sub>l</sub> /(min(ANR)) |                               |                                       |              |                   |
| SY9□40-□-03 | 2 position        | Single          | 3/8       | 7.9                                     | 0.34        | 2.0        | 2062                       | 9.6                          | 0.43        | 2.6        | 2670                       | 512[215]                      | 518[221]                              | 560[263]     | 526[229]          |
|             |                   | Double          |           |   |             |            |                            |                              |             |            |                            |                               |                                       |              |                   |
|             | 3 position        | Closed center   |           | 7.5                                     | 0.33        | 1.8        | 1944                       | 7.3                          | 0.30        | 1.7        | 1856                       |                               |                                       |              |                   |
|             |                   | Exhaust center  |           | 7.2                                     | 0.34        | 1.7        | 1879                       | 13 (4.0)                     | 0.23 (0.41) | 2.8 (0.95) | 3168 (1096)                |                               |                                       |              |                   |
|             |                   | Pressure center |           | 12 (3.3)                                | 0.26 (0.41) | 2.8 (0.84) | 2977 (904)                 | 6.7                          | 0.40        | 1.9        | 1823                       |                               |                                       |              |                   |




Note 1) [ ]: denotes the normal position. Note 2) [ ]: denotes without sub-plate.



\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Construction



### Series SY






2 position single



2 position double



3 position closed center / exhaust center / pressure center



(This figure shows a closed center type.)

### Component Parts

| No. | Description          | Material   | Note                    |
|-----|----------------------|--|-------------------------|
| 1   | Body                 | Aluminum die-casted<br>(SY3000: Zinc die-casted) | White                   |
| 2   | Adapter plate        | Resin  | White<br>(SY9000: Gray) |
| 3   | End plate            | Resin  | White                   |
| 4   | Piston               | Resin  | -                       |
| 5   | Spool valve assembly | Aluminum, HNBR                                   | -                       |

### Replacement Parts

| No. | Description                  | Part No.   |                              |  |  | Note                                       |
|-----|------------------------------|--|------------------------------|--|--|--|
|     |                              | SY3□40   | SY5□40                       | SY7□40   | SY9□40   |  |
| 6   | Sub-plate                    | SY3000-27-1* <sup>1</sup> -Q                             | SY5000-27-1* <sup>1</sup> -Q | 1/4: SY7000-27-1* <sup>1</sup> -Q<br>3/8: SY7000-27-2* <sup>1</sup> -Q | 3/8: SY9000-27-1* <sup>1</sup> -Q<br>1/2: SY9000-27-2* <sup>1</sup> -Q | Aluminum die-casted                        |
| 7   | Pilot valve assembly         | Refer to "How to Order Pilot Valve Assembly" on page 23. |                              |  |  |  |
| 8   | Gasket                       | SY3000-11-25   | SY5000-11-15                 | SY7000-11-11   | SY9000-11-2  | H-NBR                                      |
| -   | Round head combination screw | SY3000-23-4<br>(M2 x 21)                                 | M3 x 26                      | M4 x 31  | SY9000-18-2<br>(M3 x 42)   | For valve mounting<br>(Matt nickel plated) |

\* Thread type

### Caution

Mounting screw  
tightening torques

M2: 0.16 N·m

M3: 0.8 N·m

M4: 1.4 N·m

# Base Mounted

## How to Order Pilot Valve Assembly

V111  5  G

### Coil specifications

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W  type.

### Rated voltage

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

### Light/surge voltage suppressor

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

### Electrical entry

|                            |                           |   |
|----------------------------|---------------------------|---|
| G                          | Grommet, 300 mm lead wire |   |
| H                          | Grommet, 600 mm lead wire |   |
| L                          | L plug connector          | With lead wire                          |
| LN                         |                           | Without lead wire                       |
| LO                         |                           | Without connector                       |
| M                          | M plug connector          | With lead wire                          |
| MN                         |                           | Without lead wire                       |
| MO                         |                           | Without connector                       |
| WO                         | M8                        | Without connector cable                 |
| W <input type="checkbox"/> | connector                 | With connector cable <sup>Note 1)</sup> |

\* For connector cable of M8 connector, refer to back page 12.  
Note 1) Enter the cable length symbols in . Please be sure to fill in the blank referring to back page 13.

## ■ DIN terminal type

V115  5  D

### Rated voltage

|   |  |
|---|--|
| 5 | 24 VDC   |
| 6 | 12 VDC   |
| 1 | 100 VAC <sup>50/60</sup> Hz                                  |
| 2 | 200 VAC <sup>50/60</sup> Hz                                  |
| 3 | 110 VAC <sup>50/60</sup> Hz<br>[115 VAC <sup>50/60</sup> Hz] |
| 4 | 220 VAC <sup>50/60</sup> Hz<br>[230 VAC <sup>50/60</sup> Hz] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.

### Light/surge voltage suppressor

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

### Electrical entry

|    |          |                   |
|----|----------|-------------------|
| D  | DIN      | With connector    |
| DO | terminal | Without connector |

Note) Do not replace V111 (G, H, L, M) to V115 (DIN terminal) and vice versa when replacing pilot valve assembly only.

## How to Order Connector Assembly for L/M Plug Connector

For DC: SY100-30-4A

Without lead wire: SY100-30-A

Only connector and sockets (x 2 pcs.)

### Lead wire length

|    |         |
|----|---------|
| -  | 300 mm  |
| 6  | 600 mm  |
| 10 | 1000 mm |
| 15 | 1500 mm |
| 20 | 2000 mm |
| 25 | 2500 mm |
| 30 | 3000 mm |
| 50 | 5000 mm |

## How to Order M8 Connector Cable

### ■ Straight type

V100-49-1

### Cable length

|   |         |
|---|---------|
| 1 | 300 mm  |
| 2 | 500 mm  |
| 3 | 1000 mm |
| 4 | 2000 mm |
| 7 | 5000 mm |

## How to Order Interface Regulator

### Series SY3000

**ARBY3000-05-P-2**


Pressure gauge connection port

|           |                            |
|-----------|----------------------------|
| <b>05</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |


Regulating port

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

ARBY3000-05-□-2



ARBY3000-M1-□-2



### Series SY5000

**ARBY5000-00-P-2**


Pressure gauge connection port

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |


Regulating port

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

ARBY5000-00-□-2



ARBY5000-M1-□-2



### Series SY7000

**ARBY7000-00-P-2**


Pressure gauge connection port

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |


Regulating port

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

ARBY7000-00-□-2



ARBY7000-M1-□-2



## Accessory

| Series          | Round head combination screw     | Gasket      |
|-----------------|----------------------------------|-------------|
| <b>ARBY3000</b> | SY3000-23-10<br>(M2 x 36)        | SX3000-57-4 |
| <b>ARBY5000</b> | M3 x 48.5,<br>Matt nickel plated | SX5000-57-6 |
| <b>ARBY7000</b> | M4 x 57,<br>Matt nickel plated   | SX7000-57-4 |

## ⚠ Caution

Mounting screw  
tightening torques

**M2: 0.16 N·m**

**M3: 0.8 N·m**


**M4: 1.4 N·m**

# Base Mounted


## Dimensions: Series SY3000

### 2 position single


Grommet (G), (H): SY3140(R)-□<sup>G</sup>□□-01□-Q




### With interface regulator




L plug connector (L):  
SY3140(R)-□L□□-01□-Q



M plug connector (M):  
SY3140(R)-□M□□-01□-Q



M8 connector (WO):  
SY3140(R)-□WO□□-01□-Q




Note) Refer to back page 12 for dimensions of connector types.

# SY3000/5000/7000/9000 Base Mounted


## Dimensions: Series SY3000

2 position double


Grommet (G), (H): SY3240(R)-□<sup>G</sup><sub>H</sub>□□-01□-Q




With interface regulator




L plug connector (L):  
 SY3240(R)-□L□□-01□-Q



M plug connector (M):  
 SY3240(R)-□M□□-01□-Q



M8 connector (WO):  
 SY3240(R)-□WO□□-01□-Q




Note) Refer to back page 12 for dimensions of connector types.

# Base Mounted


## Dimensions: Series SY3000

3 position closed center / exhaust center / pressure center


Grommet (G), (H): SY3<sup>3</sup>/<sub>5</sub>40(R)-□<sup>G</sup>□□-01□-Q




L plug connector (L):  
SY3<sup>3</sup>/<sub>5</sub>40(R)-□L□□-01□-Q



M plug connector (M):  
SY3<sup>3</sup>/<sub>5</sub>40(R)-□M□□-01□-Q



M8 connector (WO):  
SY3<sup>3</sup>/<sub>5</sub>40(R)-□WO□□-01□-Q




Note) Refer to back page 12 for dimensions of connector types.

# SY3000/5000/7000/9000 Base Mounted


## Dimensions: Series SY5000

2 position single

Grommet (G), (H): SY5140(R)-□<sup>G</sup><sub>H</sub>□□-02□-Q



With interface regulator




L plug connector (L):  
SY5140(R)-□L□□-02□-Q

M plug connector (M):  
SY5140(R)-□M□□-02□-Q

DIN terminal (D):  
SY5140(R)-□D□□-02□-Q

M8 connector (WO):  
SY5140(R)-□WO□□-02□-Q




Note) Refer to back page 12 for dimensions of connector types.

# Base Mounted



## Dimensions: Series SY5000

2 position double

Grommet (G), (H): SY5240(R)-□<sup>G</sup>□□-02□-Q



With interface regulator







L plug connector (L): SY5240(R)-□L□□-02□-Q

M plug connector (M): SY5240(R)-□M□□-02□-Q

DIN terminal (D): SY5240(R)-□D□□-02□-Q

M8 connector (WO): SY5240(R)-□WO□□-02□-Q



Note) Refer to back page 12 for dimensions of connector types.






# SY3000/5000/7000/9000 Base Mounted


## Dimensions: Series SY7000

2 position double

Grommet (G), (H): SY7240(R)-□<sup>G</sup>□□-02□-Q



With interface regulator




L plug connector: L  
SY7240(R)-□L□□-02□-Q

M plug connector: M  
SY7240(R)-□M□□-02□-Q

DIN terminal (D):  
SY7240(R)-□D□□-02□-Q

M8 connector (WO):  
SY7240(R)-□WO□□-02□-Q




Note) Refer to back page 12 for dimensions of connector types.

# Base Mounted


## Dimensions: Series SY7000

3 position closed center / exhaust center / pressure center

Grommet (G), (H): SY7<sup>3</sup>/<sub>5</sub>40(R)-□<sup>G</sup>/<sub>H</sub>□□-02<sup>03</sup>□-Q



With interface regulator



L plug connector: L

SY7<sup>3</sup>/<sub>5</sub>40(R)-□L□□-02<sup>03</sup>□-Q

M plug connector: M


SY7<sup>3</sup>/<sub>5</sub>40(R)-□M□□-02<sup>03</sup>□-Q

DIN terminal (D):

SY7<sup>3</sup>/<sub>5</sub>40(R)-□D□□-02<sup>03</sup>□-Q

M8 connector (WO):

SY7<sup>3</sup>/<sub>5</sub>40(R)-□WO□□-02<sup>03</sup>□-Q




Note) Refer to back page 12 for dimensions of connector types.

# SY3000/5000/7000/9000 Base Mounted

## Dimensions: Series SY9000

2 position single

Grommet (G), (H): SYJ9140-□<sup>G</sup>□□-<sup>03</sup>□□-<sup>04</sup>□-Q




**L plug connector (L):**  
SY9140(R)-□L□□-<sup>03</sup>□□-<sup>04</sup>□-Q

**M plug connector (M):**  
SY9140(R)-□M□□-<sup>03</sup>□□-<sup>04</sup>□-Q

**DIN terminal (D):**  
SY9140(R)-□D□□-<sup>03</sup>□□-<sup>04</sup>□-Q

**M8 connector (WO):**  
SY9140(R)-□WO□□-<sup>03</sup>□□-<sup>04</sup>□-Q




Note) Refer to back page 12 for dimensions of connector types.

# Base Mounted

## Dimensions: Series SY9000

2 position double  
Grommet (G), (H): SY9240(R)-□G□□-03□-Q




**L plug connector (L):**  
SY9240(R)-□L□□-03□-Q

**M plug connector (M):**  
SY9240(R)-□M□□-03□-Q

**DIN terminal (D):**  
SY9240(R)-□D□□-03□-Q

**M8 connector (WO):**  
SY9240(R)-□WO□□-03□-Q




Note) Refer to back page 12 for dimensions of connector types.

# SY3000/5000/7000/9000 Base Mounted

## Dimensions: Series SY9000

3 position closed center / exhaust center / pressure center

Grommet (G), (H): SY9<sup>3</sup>/<sub>4</sub>40-□<sup>G</sup>□□-<sup>03</sup>/<sub>04</sub>□-Q




L plug connector (L):  
SY9<sup>3</sup>/<sub>4</sub>40(R)-□L□□-<sup>03</sup>/<sub>04</sub>□-Q

M plug connector (M):  
SY9<sup>3</sup>/<sub>4</sub>40(R)-□M□□-<sup>03</sup>/<sub>04</sub>□-Q

DIN terminal (D):  
SY9<sup>3</sup>/<sub>4</sub>40(R)-□D□□-<sup>03</sup>/<sub>04</sub>□-Q

M8 connector (WO):  
SY9<sup>3</sup>/<sub>4</sub>40(R)-□WO□□-<sup>03</sup>/<sub>04</sub>□-Q



Note) Refer to back page 12 for dimensions of connector types.

# 5 Port Solenoid Valve

## Series SY3000/5000/7000

Body Ported

# Bar Stock Type/Individual Wiring

### How to Order Manifold

SS5Y **5** - 20 - **05** - **□** - Q

• **Manifold series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

• **Thread type**

|     |      |
|-----|------|
| -   | Rc   |
| 00F | G    |
| 00N | NPT  |
| 00T | NPTF |

• **Stations**

|    |             |
|----|-------------|
| 02 | 2 stations  |
| ⋮  | ⋮           |
| 20 | 20 stations |




\* This also includes the number of blanking plate assemblies.

### How to Order Valve Manifold Assembly (Example)

**Example**

Cylinder port size  
C6: With one-touch fitting for ø6



- SS5Y3-20-05-Q 1 set (Type 20, 5 station manifold base part no.)
- \* SY3000-26-19A-Q 1 set (Blanking plate assembly part no.)
- \* SY3120-5G-C6-Q 2 sets (Single solenoid part no.)
- \* SY3220-5G-C6-Q 2 sets (Double solenoid part no.)

→ The asterisk denotes the symbol for assembly.  
Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number.  
In the case of complex arrangement, specify them on the manifold specification sheet.

## How to Order Valve

SY 5 1 20   5 L     01   -Q

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Coil specifications**

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

**Rated voltage**

| For DC |        | AC (50/60 Hz) |                   |
|--------|--------|---------------|-------------------|
| 5      | 24 VDC | 1             | 100 VAC           |
| 6      | 12 VDC | 2             | 200 VAC           |
| V      | 6 VDC  | 3             | 110 VAC [115 VAC] |
| S      | 5 VDC  | 4             | 220 VAC [230 VAC] |
| R      | 3 VDC  |               |                   |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D and DO type.

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**  
Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry for D (SY5000/7000 only)**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**A, B port size**  
Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |
| 02     | 1/4       | SY7000            |

**One-touch fitting (Metric size)**

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  | SY5000            |
| C4     | One-touch fitting for ø4  |                   |
| C6     | One-touch fitting for ø6  | SY7000            |
| C8     | One-touch fitting for ø8  |                   |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 |                   |

**One-touch fitting (Inch size)**


| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N3     | One-touch fitting for ø5/32" | SY5000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N9     | One-touch fitting for ø5/16" |                   |
| N11    | One-touch fitting for ø3/8"  |                   |

### Electrical entry

| 24, 12, 6, 5, 3 VDC                                      |   |   | 24, 12 VDC/<br>100, 110, 200,<br>220 VAC   | 24, 12, 6, 5, 3 VDC  |
|--|---|---|--|--|
| Grommet  | L plug connector  | M plug connector  | DIN terminal <small>Note2)</small>         | M8 connector *   |
| G: Lead wire length 300 mm<br>H: Lead wire length 600 mm | L: With lead wire (Length 300 mm)<br>LN: Without lead wire<br>LO: Without connector | M: With lead wire (Length 300 mm)<br>MN: Without lead wire<br>MO: Without connector | D: With connector<br>DO: Without connector | WO: Without connector cable<br>W□: With connector cable <small>Note 1)</small> |

- \* LN, MN type: with 2 sockets.
- \* For DIN terminal of SY3000 series, refer to back page 10.
- \* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.
- \* For connector cable of M8 connector, refer to back page 12.
- \* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.
- Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.
- Note2) SY5000/7000 only).

Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to catalogue in page 56.)



## Manifold Specifications

| Model                                     | SS5Y3-20                           | SS5Y5-20   | SS5Y7-20   |   |
|---|------------------------------------|--|--|---|
| Applicable valve                          | SY3□20                             | SY5□20   | SY7□20   |   |
| Manifold type                             | Single base/B mount                |  |  |   |
| P (SUP)/R (EXH)                           | Common SUP, Common EXH             |  |  |   |
| Valve stations                            | 2 to 20 stations <sup>Note1)</sup> |  |  |   |
| A, B port location                        | Valve                              |  |  |   |
| Port size                                 | P, EA, EB port                     | 1/8  | 1/4  | 1/4   |
|   | A, B port                          | M5<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | 1/8<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | 1/4<br>C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10) |
| Manifold base weight W (g)<br>n: Stations | W = 13n + 35                       | W = 36n + 64   | W = 43n + 64   |   |

-  Note 1) For more than 10 stations (more than 5 stations in case of SS5Y7), supply pressure to P port on both sides and exhaust from EA/EB port on both sides.  
 Note 2) Refer to "Manifold Option" on page 56.

## Flow Characteristics

| Model    | Port size              |                | Flow characteristics         |      |      |                 |                              |      |      |                 |
|----------|------------------------|----------------|------------------------------|------|------|-----------------|------------------------------|------|------|-----------------|
|          | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |      |                 | 4/2 → 5/3 (A/B → EA/EB)      |      |      |                 |
|          |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* |
| SS5Y3-20 | 1/8                    | C6             | 0.72                         | 0.29 | 0.18 | 182             | 0.80                         | 0.36 | 0.21 | 212             |
| SS5Y5-20 | 1/4                    | C8             | 1.9                          | 0.28 | 0.48 | 477             | 2.2                          | 0.20 | 0.53 | 527             |
| SS5Y7-20 | 1/4                    | C10            | 3.6                          | 0.31 | 0.93 | 921             | 3.6                          | 0.27 | 0.88 | 898             |


-  Note) The value is for manifold base with 5 stations and individually operated 2 position type.  
 \* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.



**SY5000: SS5Y5-20- Stations - -Q**





**Grommet (G)**

Dimensions when mounting individual EXH spacer




Dimensions when mounting individual SUP spacer


(SUP port is at the end plate of single solenoid.)




**L plug connector (L)**




**M plug connector (M)**



**DIN terminal (D)**



**M8 connector (WO)**




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4  | 5   | 6   | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15  | 16  | 17  | 18  | 19  | 20 stations |
|------------|------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------|
| L1         | 60         | 76 | 92 | 108 | 124 | 140 | 156 | 172 | 188 | 204 | 220 | 236 | 252 | 268 | 284 | 300 | 316 | 332 | 348         |
| L2         | 40         | 56 | 72 | 88  | 104 | 120 | 136 | 152 | 168 | 184 | 200 | 216 | 232 | 248 | 264 | 280 | 296 | 312 | 328         |




## SY7000: SS5Y7-20-Stations -   -Q

### Grommet (G)


Dimensions when mounting individual EXH spacer




Dimensions when mounting individual SUP spacer  
(SUP port is at the end plate of single solenoid.)




### L plug connector (L)




### M plug connector (M)



### DIN terminal (D)



### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4   | 5   | 6   | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15  | 16  | 17  | 18  | 19  | 20 stations |
|------------|------------|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------|
| L1         | 66         | 85 | 104 | 123 | 142 | 161 | 180 | 199 | 218 | 237 | 256 | 275 | 294 | 313 | 332 | 351 | 370 | 389 | 408         |
| L2         | 46         | 65 | 84  | 103 | 122 | 141 | 160 | 179 | 198 | 217 | 236 | 255 | 274 | 293 | 312 | 331 | 350 | 369 | 388         |

# 5 Port Solenoid Valve

Series **SY9000**

Body Ported

# Stacking Type/Individual Wiring

## How to Order Manifold

**SS5Y 9 — 23 — 05** [ ] [ ] -Q

• **Manifold series**

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

• **Valve stations**

| Symbol | Stations    |
|--------|-------------|
| 02     | 2 stations  |
| ⋮      | ⋮           |
| 20     | 20 stations |



\* This also includes the number of blanking plate assemblies.

• **Thread type**

|     |      |
|-----|------|
| -   | Rc   |
| 00F | G    |
| 00N | NPT  |
| 00T | NPTF |


• **Option**

| Symbol | Mounting  |
|--------|---|
| -      | Direct mounting   |
| D      | DIN rail mounting (with DIN rail)   |
| D0     | DIN rail mounting (without DIN rail)  |
| D*     | When a longer DIN rail is desired than the specified stations, specify the station number to be required into * mark. |

\* Type 23 manifold of Series SY9000 is concurrently used for the internal and external pilot.

## How to Order Valve Manifold Assembly (Example)

### Example



- SS5Y9-23-05-Q** 1 set (Type 23, 5 station manifold base part no.)  
 \* **SY9000-26-1A-Q** 1 set (Blanking plate assembly part no.)  
 \* **SY9120-5LOZ-C12-Q** 2 sets (Single solenoid part no.)  
 \* **SY9220-5LOZ-C12-Q** 2 sets (Double solenoid part no.)

↳ The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

## How to Order Valve

SY 9 1 20     5 L     02   -Q

**Series**

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Pilot specifications**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

*\* In the case of external pilot specifications, it cannot be used as a single unit.*

**Coil specifications**

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

*\* Power saving circuit is not available in the case of D, DO or W□ type.*

**Rated voltage**

| For DC |        | For AC (50/60 Hz) |                   |
|--------|--------|-------------------|-------------------|
| 5      | 24 VDC | 1                 | 100 VAC           |
| 6      | 12 VDC | 2                 | 200 VAC           |
| V      | 6 VDC  | 3                 | 110 VAC [115 VAC] |
| S      | 5 VDC  | 4                 | 220 VAC [230 VAC] |
| R      | 3 VDC  |                   |                   |

*\* DC specifications of type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D and DO type.*

**Thread type**

|     |      |
|-----|------|
| Nil | Rc   |
| F   | G    |
| N   | NPT  |
| T   | NPTF |

**A, B port size Thread piping**

| Symbol | Port size |
|--------|-----------|
| 02     | 1/4       |
| 03     | 3/8       |

**One-touch fitting (Metric size)**

| Symbol | Port size                 |
|--------|---------------------------|
| C8     | One-touch fitting for ø8  |
| C10    | One-touch fitting for ø10 |
| C12    | One-touch fitting for ø12 |

**One-touch fitting (Inch size)**

| Symbol | Port size                    |
|--------|------------------------------|
| N9     | One-touch fitting for ø5/16" |
| N11    | One-touch fitting for ø3/8"  |

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**  
Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

*\* Power saving circuit is only available in the "Z" type.*

**Electrical entry for D**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor |
| S | With surge voltage suppressor          |
| Z | With light/surge voltage suppressor    |


*\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.*

### Electrical entry

| 24, 12, 6, 5, 3 VDC           |                                      |                                      | 24, 12 VDC/<br>100, 110, 200,<br>220 VAC | 24, 12, 6,<br>5, 3 VDC                             |
|-------------------------------|--------------------------------------|--------------------------------------|--|--|
| Grommet                       | L plug connector                     | M plug connector                     | DIN terminal                             | M8 connector *                                     |
| G: Lead wire<br>length 300 mm | L: With lead wire<br>(Length 300 mm) | M: With lead wire<br>(Length 300 mm) | D: With connector                        | WO: Without connector<br>cable                     |
| H: Lead wire<br>length 600 mm | LN: Without lead wire                | MN: Without lead wire                | DO: Without connector                    | W□: With connector<br>cable <small>Note 1)</small> |
|                               | LO: Without connector                | MO: Without connector                |  |  |

- \* LN, MN type: with 2 sockets.*
- \* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.*
- \* For connector cable of M8 connector, refer to back page 12.*
- \* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.*
- Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.*

*Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. For details, refer to page 56.*



## Manifold Specifications

|   |                                     |   |
|---|-------------------------------------|---|
| Model                                     | <b>SS5Y9-23</b>                     |   |
| Applicable valve                          | <b>SY9□20</b>                       |   |
| Manifold type                             | Stacking type                       |   |
| P (SUP)/R (EXH)                           | Common SUP, Common EXH              |   |
| Valve stations                            | 2 to 20 stations <sup>Note 1)</sup> |   |
| A, B port location                        | Valve                               |   |
| Port size                                 | P, EA, EB port                      | 3/8   |
|   | A, B port                           | 1/4<br>3/8<br>C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10)<br>C12 (One-touch fitting for ø12) |
| Manifold base weight W (g)<br>n: Stations | W = 66n + 246                       |   |



Note 1) For more than 10 stations, supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) Refer to "Manifold Option" on page 56.

## Flow Characteristics

| Model           | Port size              |                | Flow characteristics         |      |     |                |                              |      |     |                |
|-----------------|------------------------|----------------|------------------------------|------|-----|----------------|------------------------------|------|-----|----------------|
|                 | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1→4/2 (P→A/B)                |      |     |                | 4/2→5/3 (A/B→EA/EB)          |      |     |                |
|                 |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q[l/min/ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q[l/min/ANR)]* |
| <b>SS5Y9-23</b> | 3/8                    | C12            | 6.3                          | 0.20 | 1.5 | 1509           | 8.2                          | 0.28 | 1.9 | 2059           |




Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## SY9000: SS5Y9-23- Stations -(D)-□(D)-Q

### Grommet (G)




### L plug connector (L)

### M plug connector (M)

### DIN terminal (D)

### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 123        | 148   | 173   | 198   | 223   | 248   | 273   | 298   | 323   | 335.5 | 360.5 | 385.5 | 410.5 | 435.5 | 460.5 | 485.5 | 510.5 | 535.5 | 560.5       |
| <b>L2</b>  | 112.5      | 137.5 | 162.5 | 187.5 | 212.5 | 237.5 | 262.5 | 287.5 | 312.5 | 325   | 350   | 375   | 400   | 425   | 450   | 475   | 500   | 525   | 550         |
| <b>L3</b>  | 96         | 120   | 144   | 168   | 192   | 216   | 240   | 264   | 288   | 312   | 336   | 360   | 384   | 408   | 432   | 456   | 480   | 504   | 528         |
| <b>L4</b>  | 13.5       | 14    | 14.5  | 15    | 15.5  | 16    | 16.5  | 17    | 17.5  | 12    | 12.5  | 13    | 13.5  | 14    | 14.5  | 15    | 15.5  | 16    | 16.5        |
| <b>L5</b>  | 66         | 90    | 114   | 138   | 162   | 186   | 210   | 234   | 258   | 282   | 306   | 330   | 354   | 378   | 402   | 426   | 450   | 474   | 498         |

Note) In the case of direct mounting without DIN rail, total width of manifold is **L3**.

Type **20P**


# 5 Port Solenoid Valve

Series **SY3000/5000/7000**

Body Ported


# Bar Stock Type/Flat Ribbon Cable

## How to Order Manifold



## How to Order Valve Manifold Assembly (Example)

### Example



- |                           |   |
|---------------------------|---|
| <b>SS5Y3-20P-06-Q</b>     | 1 set (Type 20P, 6 station manifold part no.) |
| * <b>SY3000-26-20A-Q</b>  | 1 set (Blanking plate assembly part no.)      |
| * <b>SY3120-5LOU-C6-Q</b> | 3 sets (Single solenoid part no.)             |
| * <b>SY3220-5LOU-C6-Q</b> | 2 sets (Double solenoid part no.)             |
| * <b>SY3000-37-3A</b>     | 3 sets (Connector assembly part no.)          |
| * <b>SY3000-37-4A</b>     | 2 sets (Connector assembly part no.)          |
- The asterisk denotes the symbol for assembly.  
Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

## How to Order Valve

**For DC: SY 5 1 20 - 5 LO Z [ ] - 01 [ ] - Q**

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |

**Light/surge voltage suppressor**

|   |  |
|---|--|
| Z | With light/surge voltage suppressor                  |
| U | With light/surge voltage suppressor (Non-polar type) |

Note) Z: Positive common specifications only.

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* Except for M5

**A, B port size**

**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |
| 02     | 1/4       | SY7000            |

**One-touch fitting (Metric size)**

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  | SY3000            |
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  | SY5000            |
| C8     | One-touch fitting for ø8  | SY5000            |
| C8     | One-touch fitting for ø8  | SY7000            |
| C10    | One-touch fitting for ø10 | SY7000            |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* Except for M5

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  | SY3000            |
| N3     | One-touch fitting for ø5/32" | SY5000            |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" | SY5000            |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N11    | One-touch fitting for ø3/8"  | SY7000            |


**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Note)** When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary.  
(For details, refer to page 56.)

- Multiple valve wiring is simplified through the use of the flat cable connector
- Clean appearance

In the case of a flat ribbon cable type, each valve is wired on the print board of manifold base to allow the external wiring to be piped all together with 26 pins MIL connector.



## Manifold Specifications

| Model                                     | SS5Y3-20P   | SS5Y5-20P   | SS5Y7-20P  |   |
|---|---|---|--|---|
| Applicable valve                          | SY3□20  | SY5□20  | SY7□20   |   |
| Manifold type                             | Single base/B mount   |   |  |   |
| P (SUP)/R (EXH)                           | Common SUP, Common EXH  |   |  |   |
| Valve stations                            | 4 to 12 stations <sup>(1)</sup>   | 3 to 12 stations <sup>Note 1)</sup>                                   |  |   |
| A, B port location                        | Valve   |   |  |   |
| Port size                                 | P, EA, EB port  | 1/8   | 1/4  | 1/4   |
|   | A, B port   | M5,<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | 1/8<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | 1/4<br>C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10) |
| Manifold base weight W (g)<br>n: Stations | W = 19n + 45  | W = 43n + 77  | W = 51n + 81   |   |
| Applicable flat ribbon cable connector    | Flat ribbon cable connector, Socket: 26 pins MIL type with strain relief, Conforming to MIL-C-83503 |   |  |   |
| Internal wiring                           | In common between +COM and -COM (Z type: +COM only).  |   |  |   |
| Rated voltage                             | 12, 24 VDC  |   |  |   |

Note 1) For more than 10 stations (more than 5 stations in case of SS5Y7), supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) The withstand voltage specification for the wiring unit section is JIS C 0704, Grade 1 or its equivalent.

Note 3) Refer to "Manifold Option" on page 56.

## Flow Characteristics

| Model     | Port size              |                | Flow characteristics         |      |      |                  |                              |      |      |                 |
|-----------|------------------------|----------------|------------------------------|------|------|------------------|------------------------------|------|------|-----------------|
|           | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |      |                  | 4/2 → 5/3 (A/B → EA/EB)      |      |      |                 |
|           |                        |                | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   | Q [l/min(ANR)]*C | C [dm <sup>3</sup> /(s·bar)] | b    | Cv   | Q [l/min(ANR)]* |
| SS5Y3-20P | 1/8                    | C6             | 0.72                         | 0.29 | 0.18 | 182              | 0.80                         | 0.36 | 0.21 | 212             |
| SS5Y5-20P | 1/4                    | C8             | 1.9                          | 0.28 | 0.48 | 477              | 2.2                          | 0.20 | 0.53 | 527             |
| SS5Y7-20P | 1/4                    | C10            | 3.6                          | 0.31 | 0.93 | 921              | 3.6                          | 0.27 | 0.88 | 898             |

Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## How to Order Connector Assembly


### For 12, 24 VDC

| For DC                                  | For SY3000   | For SY5000/7000 |
|---|--------------|-----------------|
| For single solenoid:                    | SY3000-37-3A | SY5000-37-3A    |
| Double solenoid, 3 position type        | SY3000-37-4A | SY5000-37-4A    |
| Single with spacer assembly             | SY5000-37-3A | SY5000-37-5A    |
| Double, 3 position with spacer assembly | SY3000-37-6A | SY5000-37-6A    |


### Caution

- For non-polar (U) valves, the electrical DC connections can be used with either positive and negative COM. For type (Z), only use with positive COM as the valve does not operate correctly when used with negative COM.


## Internal Wiring of Manifold (Non-polar type)



- For more than 10 stations, both poles of the common should be wired.
- For single solenoid, connect to the solenoid A side.
- The maximum number of stations that can be accommodated is 12. For more stations, please contact SMC.





## SY3000: SS5Y3-20P- Stations -□-Q




| Stations n | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|------|----|------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 72.5 | 85 | 97.5 | 110 | 122.5 | 135 | 147.5 | 160 | 172.5 |
| <b>L2</b>  | 64.5 | 77 | 89.5 | 102 | 114.5 | 127 | 139.5 | 152 | 164.5 |

**SY5000: SS5Y5-20P-Stations-Q**



| Stations n | 3  | 4    | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|----|------|-----|-------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 77 | 94.5 | 112 | 129.5 | 147 | 164.5 | 182 | 199.5 | 217 | 234.5 |
| <b>L2</b>  | 67 | 84.5 | 102 | 119.5 | 137 | 154.5 | 172 | 189.5 | 207 | 224.5 |

## SY7000: SS5Y7-20P- Stations -□-Q



| Stations n | 3  | 4     | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|----|-------|-----|-------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 88 | 108.5 | 129 | 149.5 | 170 | 190.5 | 211 | 231.5 | 252 | 272.5 |
| <b>L2</b>  | 68 | 88.5  | 109 | 129.5 | 150 | 170.5 | 191 | 211.5 | 232 | 252.5 |

Type **23P**

# 5 Port Solenoid Valve

## Series SY9000

### Body Ported

# Stacking Type/Flat Ribbon Cable

### How to Order Manifold

**SS5Y 9 — 23P — 05** — [ ] — [ ] — **-Q**

**Manifold series**

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

**Thread type**

|     |      |
|-----|------|
| -   | Rc   |
| 00F | G    |
| 00N | NPT  |
| 00T | NPTF |

**Valve stations**

| Symbol | Stations    |
|--------|-------------|
| 04     | 4 stations  |
| ⋮      | ⋮           |
| 12     | 12 stations |

\* This also includes the number of blanking plate assemblies.

**Option**

| Symbol | Mounting  |
|--------|---|
| -      | Direct mounting   |
| D      | DIN rail mounting (with DIN rail)   |
| D0     | DIN rail mounting (without DIN rail)  |
| D*     | When a longer DIN rail is desired than the specified stations, specify the station number to be required into * mark. |

\* Type 23P manifold of Series SY9000 is concurrently used for the internal and external pilot.

### How to Order Valve Manifold Assembly (Example)

**Example**

Cylinder port Port size  
C12: One-touch fitting for  $\phi 12$

(Single solenoid) Connector assembly  
SY9000-37-1A

(Double solenoid) Connector assembly  
SY9000-37-2A

SY9220-5LOU-C12-Q (2 sets)  
Double solenoid (24 VDC)

SY9120-5LOU-C12-Q (2 sets)  
Single solenoid (24 VDC)

Blanking plate assembly  
SY9000-26-3A-Q (1 set)

Manifold base (5 stations)  
SS5Y9-23P-05-Q

Stations --- 3 2 1

**SS5Y9-23P-05-Q** 1 set (Type 23, 5 station manifold base part no.)

\* **SY9000-26-3A-Q** 1 set (Blanking plate assembly part no.)

\* **SY9120-5LOU-C12-Q** 2 sets (Single solenoid part no.)

\* **SY9220-5LOU-C12-Q** 2 sets (Double solenoid part no.)

\* **SY9000-37-1A** 2 sets (Connector assembly part no.)

\* **SY9000-37-2A** 2 sets (Connector assembly part no.)

↳ The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

### How to Order Valve

**For DC: SY 9 1 20** — [ ] — **5 LO Z** — [ ] — **02** — [ ] — **-Q**

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |

**Series**

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Pilot specifications**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

\* Type 23P manifolds can be used for both internal and external pilots.

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**

|   |  |
|---|--|
| Z | With light/surge voltage suppressor                  |
| U | With light/surge voltage suppressor (Non-polar type) |

Note) Z: Positive common specifications only.

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**A, B port size**

**Thread piping**

| Symbol | Port size |
|--------|-----------|
| 02     | 1/4       |
| 03     | 3/8       |

**One-touch fitting (Metric size)**

| Symbol | Port size                       |
|--------|---------------------------------|
| C8     | One-touch fitting for $\phi 8$  |
| C10    | One-touch fitting for $\phi 10$ |
| C12    | One-touch fitting for $\phi 12$ |

**One-touch fitting (Inch size)**

| Symbol | Port size                          |
|--------|------------------------------------|
| N9     | One-touch fitting for $\phi 5/16"$ |
| N11    | One-touch fitting for $\phi 3/8"$  |


Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to page 56.)

## Manifold Specifications

- Multiple valve wiring is simplified through the use of the flat cable connector.

### • Clean appearance

In the case of a flat ribbon cable type, each valve is wired on the print board of manifold base to allow the external wiring to be piped all together with 26 pins MIL connector.



|   |  |   |
|---|--|---|
| Model                                     | <b>SS5Y9-23P</b>   |   |
| Applicable valve                          | <b>SY9□20</b>  |   |
| Manifold type                             | Stacking type  |   |
| P (SUP)/R (EXH)                           | Common SUP, Common EXH   |   |
| Valve stations                            | 4 to 12 stations <small>Note1)</small>   |   |
| A, B port location                        | Valve  |   |
| Port size                                 | P, EA, EB port   | 3/8   |
|   | A, B port  | 1/4   |
|   |  | 3/8   |
|   |  | C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10)<br>C12 (One-touch fitting for ø12) |
| Manifold base weight W (g)<br>n: Stations | W = 73n + 259  |   |
| Applicable flat ribbon cable connector    | Flat ribbon cable connector, Socket: 26 pins MIL with strain relief, Conforming to MIL-C-83503 |   |
| Internal wiring                           | In common between +COM and -COM (Z type: +COM only)  |   |
| Rated voltage                             | 12, 24 VDC   |   |

- Note 1)** For more than 10 stations, supply pressure to P port on both sides and exhaust from EA/EB port on both sides.  
**Note 2)** The withstand voltage specification for the wiring unit section is JIS C 0704, Grade 1 or its equivalent.  
**Note 3)** Refer to "Manifold Option" on page 56.

## How to Order Connector Assembly

### For 12, 24 VDC


| Specifications                             | For SY9000   |
|--|--------------|
| For single solenoid                        | SY9000-37-1A |
| Double solenoid<br>3 position              | SY9000-37-2A |
| Single<br>with spacer assembly             | SY9000-37-3A |
| Double, 3 position<br>with spacer assembly | SY9000-37-4A |

## Flow Characteristics

| Model            | Port size              |                | Flow characteristics         |      |     |                 |                              |      |     |                 |
|------------------|------------------------|----------------|------------------------------|------|-----|-----------------|------------------------------|------|-----|-----------------|
|                  | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |     |                 | 4/2 → 5/3 (A/B → EA/EB)      |      |     |                 |
|                  |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q [l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q [l/min(ANR)]* |
| <b>SS5Y9-23P</b> | 3/8                    | C12            | 6.3                          | 0.20 | 1.5 | 1509            | 8.2                          | 0.28 | 1.9 | 2059            |

- Note)** The value is for manifold base with 5 stations and individually operated 2 position type.  
 \* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.


## Internal Wiring of Manifold (Non-polar type)



## ⚠ Caution


- For non-polar (U) valves, the electrical DC connections can be used with either positive and negative COM. For type (Z), only use with positive COM as the valve does not operate correctly when used with negative COM.

- For more than 10 stations, both poles of the common should be wired.
- For single solenoid, connect to the solenoid A side.
- The maximum number of stations that can be accommodated is 12. For more stations, please contact SMC.



**SY9000: SS5Y9-23P- Stations- -(D)-Q**

**Grommet (G)**




| Stations n | 4 stations | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 173        | 198   | 223   | 248   | 273   | 298   | 323   | 335.5 | 360.5       |
| <b>L2</b>  | 162.5      | 187.5 | 212.5 | 237.5 | 262.5 | 287.5 | 312.5 | 325   | 350         |
| <b>L3</b>  | 144        | 168   | 192   | 216   | 240   | 264   | 288   | 312   | 336         |
| <b>L4</b>  | 14.5       | 15    | 15.5  | 16    | 16.5  | 17    | 17.5  | 12    | 12.5        |
| <b>L5</b>  | 114        | 138   | 162   | 186   | 210   | 234   | 258   | 282   | 306         |

Note) In the case of direct mounting without DIN rail, total width of manifold is L3.


## Manifold Option

### ■ Type 20, 23 Blanking plate assembly




| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SY3000-26-19A-Q   |
| SY5000 | SY5000-26-1A-Q    |
| SY7000 | SY7000-26-1A-Q    |
| SY9000 | SY9000-26-1A-Q    |

### ■ Type 20P, 23P Blanking plate assembly



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SY3000-26-20A-Q   |
| SY5000 | SY5000-26-3A-Q    |
| SY7000 | SY7000-26-3A-Q    |
| SY9000 | SY9000-26-3A      |


### ■ Gasket assembly part no.



| Series | Gasket assembly |
|--------|-----------------|
| SY3000 | SY3000-GS-1     |
| SY5000 | SY5000-GS-1     |
| SY7000 | SY7000-GS-1     |
| SY9000 | SY9000-GS-1     |

Note) Gasket assembly consists of mounting screws and a gasket.


### ■ Individual SUP spacer assembly



| Series | Assembly part no. | Port size | t    |
|--------|-------------------|-----------|------|
| SY3000 | SY3000-38-20A-Q   | M5        | 10.5 |
| SY5000 | SY5000-38-1*A-Q   | 1/8       | 15   |
| SY7000 | SY7000-38-1*A-Q   | 1/4       | 18   |
| SY9000 | SY9000-38-1*A-Q   | 1/4       | 20   |

Note) • The SUP port of SY3000/5000/7000 may be either on the lead wire side or on the end plate side. (An assembly is shipped under the conditions shown in the figure.)  
• The end plate side is only available to SY9000.


### ■ Individual EXH spacer assembly



| Series | Assembly part no. | Port size | t    |
|--------|-------------------|-----------|------|
| SY3000 | SY3000-39-20A-Q   | M5        | 10.5 |
| SY5000 | SY5000-39-1*A-Q   | 1/8       | 15   |
| SY7000 | SY7000-39-1*A-Q   | 1/4       | 18   |
| SY9000 | SY9000-39-1*A-Q   | 1/4       | 20   |

Note) In case of 20P and 23P, for protection of the wiring unit section from drainage, piping at the EA port should be arranged so that it will not be directly exposed to exhaust from the valve.

### ■ Individual SUP spacer assembly + Individual EXH spacer assembly (Double spacer)



[●: Available X: Not available]

| Series | Individual SUP + Individual EXP Assemble part no. | Port size | Applicable manifold types |     |
|--------|---|-----------|---------------------------|-----|
|        |   |           | 20                        | 20P |
| SY3000 | SY3000-120-1A-Q                                   | M5        | ●                         | X   |
| SY5000 | SY5000-75-2*A-Q                                   | 1/8       | ●                         | X   |
| SY7000 | SY7000-73-3*A-Q                                   | 1/4       | ●                         | X   |

Note) The SUP spacer's port does not have an orientation. As for the EXH ports, adjust the symbol "5" to the pilot valve side. Also, please make sure to connect the individual ports to protect the wiring section of the pilot valve from drainage, etc. The individual SUP spacer and EXH spacer can be mounted either on the upper side or lower side. (The above illustration shows the condition when the product is shipped out from a factory already assembled.)

## ⚠ Caution

### Mounting screw tightening torques

M2: 0.16 N·m  
M3: 0.8 N·m  
M4: 1.4 N·m

## ⚠ Warning

When mounting a valve or spacer on the manifold base or sub-plate, etc., those mounting directions are determined. If mounted in the wrong direction, the equipment to be connected may cause malfunction. Refer to external dimensions, and then mount it.

### \* Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**Manifold Option**

■ **SUP blocking disk (For SY9000)**

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold.



| Series        | No.          |
|---------------|--------------|
| <b>SY9000</b> | SY9000-61-2A |

■ **EXH blocking disk (For SY9000)**

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to divide both exhausts.)





| Series        | No.          |
|---------------|--------------|
| <b>SY9000</b> | SY9000-61-2A |

■ **Label for blocking disk (For SY9000)**

The labels shown below are used on manifold stations containing SUP/EXH blocking disk(s) to show their location. (3 pcs. each)

**VZ3000-123-1A**

Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk




\* When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.

■ **DIN Rail Dimensions/Weight for SY9000**

**VZ1000-11-4-** □

● **Refer to L dimensions**

\* Fill in □ with an appropriate no. listed on the table of DIN rail dimensions shown below.




|             |      |       |      |       |       |       |      |       |       |       |
|-------------|------|-------|------|-------|-------|-------|------|-------|-------|-------|
| No.         | 0    | 1     | 2    | 3     | 4     | 5     | 6    | 7     | 8     | 9     |
| L Dimension | 98   | 110.5 | 123  | 135.5 | 148   | 160.5 | 173  | 185.5 | 198   | 210.5 |
| Weight (g)  | 24.8 | 28    | 31.1 | 34.3  | 37.4  | 40.6  | 43.8 | 46.9  | 50.1  | 53.3  |
| No.         | 10   | 11    | 12   | 13    | 14    | 15    | 16   | 17    | 18    | 19    |
| L Dimension | 223  | 235.5 | 248  | 260.5 | 273   | 285.5 | 298  | 310.5 | 323   | 335.5 |
| Weight (g)  | 56.4 | 59.6  | 62.7 | 65.9  | 69.1  | 72.2  | 75.4 | 78.6  | 81.7  | 84.9  |
| No.         | 20   | 21    | 22   | 23    | 24    | 25    | 26   | 27    | 28    | 29    |
| L Dimension | 348  | 360.5 | 373  | 385.5 | 398   | 410.5 | 423  | 435.5 | 448   | 460.5 |
| Weight (g)  | 88   | 91.2  | 94.4 | 97.5  | 100.7 | 103.9 | 107  | 110.2 | 113.3 | 116.5 |

Note) - For DIN rail, refer to page 223.  
- Refer to **L1** dimension on pages starting with page 55 for lengths that correspond to the number of manifold stations.

■ **Cable assembly (For 20P, 23P)**

**AXT100-FC26-1**



**Connector Assembly for Flat Ribbon Cables**

| Cable length (L) | Assembly part no. | Note                   |
|------------------|-------------------|------------------------|
| 1.5 m            | AXT100-FC26-1     | Cable 26 core x 28 AWG |
| 3 m              | AXT100-FC26-2     |                        |
| 5 m              | AXT100-FC26-3     |                        |


\* For other commercial connectors, use a 26 pins with strain relief conforming to MIL-C-83503.

**Connector manufacturers' example**

- Hirose Electric Company
- Japan Aviation Electronics Industry, Ltd.
- Sumitomo 3M Limited
- J.S.T. Mfg. Co., Ltd.
- Fujitsu Limited

■ **Plug (white)**

These are inserted in unused cylinder ports and SUP, EXH ports.  
Note) Purchasing order is available in units of 10 pieces.



**Dimensions**

| Applicable fittings size ød | Model          | A    | L    | D    |
|-----------------------------|----------------|------|------|------|
| 4                           | <b>KQ2P-04</b> | 16   | 32   | 6    |
| 6                           | <b>KQ2P-06</b> | 18   | 35   | 8    |
| 8                           | <b>KQ2P-08</b> | 20.5 | 39   | 10   |
| 10                          | <b>KQ2P-10</b> | 22   | 43   | 12   |
| 12                          | <b>KQ2P-12</b> | 24   | 44.5 | 14   |
| 1/8"                        | <b>KQ2P-01</b> | 16   | 31.5 | 5    |
| 5/32"                       | <b>KQ2P-03</b> | 16   | 32   | 6    |
| 1/4"                        | <b>KQ2P-07</b> | 18   | 35   | 8.5  |
| 5/16"                       | <b>KQ2P-09</b> | 20.5 | 39   | 10   |
| 3/8"                        | <b>KQ2P-11</b> | 22   | 43   | 11.5 |

## How to Increase Manifold Bases (Series SY9000 only) Manifold case can be added at any location.

When a type 23 manifold base is added, tension bolts as well as manifold block assembly will be required. Order the tension bolt suitable for the stations after a station was increased (decreased), since the length of a tension bolt differs by the number of stations. (For changing the number of stations for a type 23P manifold, wiring unit for the stations and lead assembly will be required.)

- 1 Loosen the tension bolts ⑤ connecting the manifold base, and pull out both of 2 tension bolts.  
(When equipped with a DIN rail, loosen one DIN rail holding screw on either U side or D side.)
- 2 Separate the blocks at the location where station expansion is desired.
- 3 Mount additional manifold block assembly.
- 4 Press block-to-block so that there's no gap. After connection, insert a tension bolt for desired stations and then tighten it.


**⚠ Caution** (Tightening torque: 2.9 N·m)  
(When equipped with a DIN rail, be sure to tighten the DIN rail holding screws after tightening the tension bolts. Tightening torque: 1.4 N·m)

### ⚠ Caution

1. Be sure to shut off the power and air supplies before disassembly. Furthermore, since air may remain inside the actuator, piping and manifold, confirm that the air is completely exhausted before performing any work.
2. When disassembly and assembly are performed, air leakage may result if connections between blocks and tightening of the end block's holding screw, is inadequate.
3. By adding wiring unit assembly to type 23 manifold, it can be changed to type 23P manifold, too.

## Body Ported Manifold Exploded View, 23/23P Common

As for body ported manifold, it is available only for Series SY9000 to disassemble or increase the manifold.



### Replacement Parts

| No. | Description                   | No.           | Note  |
|-----|-------------------------------|---------------|---|
| 1   | Manifold block assembly       | SY9000-50-1A  |   |
| 2   | D side SUP/EXH block assembly | SY9000-51-2A  | Common use for the internal pilot and external pilot  |
| 3   | U side SUP/EXH block          | SY9000-51-4   | Common use for the internal pilot and external pilot  |
| 4   | Hexagon nut                   | SY9000-25-1   | M5 x 0.8  |
| 5   | Tension bolt                  | SY9000-23-□   | Since □ at the end of part number corresponds with the number of stations, fill in the same number as the number of stations. |
| 6   | SUP Block bush assembly       | SY9000-61-1A  | Included in the Manifold block assembly and the D side SUP/EXH block assembly.  |
| 7   | SUP Block bush assembly       | SY9000-61-3A  | Included in the Manifold block assembly and the D side SUP/EXH block assembly.  |
| 8   | Round head combination screw  | SY9000-18-2   | Included in the Manifold block assembly.  |
| 9   | Manifold gasket               | SY9000-11-1   | Included in the Manifold block assembly.  |
| 10  | Clamp sub assembly            | SY9000-29-1A  |   |
| 11  | DIN rail                      | VZ1000-11-4-□ | Refer to p. 57.   |
| 12  | Wiring unit assembly          | SY9000-36-□A  | Since □ in part number corresponds with the number of stations, fill in the number of stations (4 to 12).                     |
| 13  | Connector assembly            | SY9000-37-□□  | Refer to page 54.   |


# 5 Port Solenoid Valve

## Series SY3000/5000/7000

### Body Ported

# Cassette Type

Type **60**



### How to Order

SS5Y **3** — 60 — **05** **D** — **-Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

**Valve stations**

|    |             |
|----|-------------|
| 02 | 2 stations  |
| ⋮  | ⋮           |
| 20 | 20 stations |

**Option**

When a DIN rail longer than standard is required, enter the number of manifold stations that corresponds with the length of DIN rail needed. Max. 20 stations


**SUP/EXH block assembly mounting position**

| Symbol    | Mounting position | Applicable stations |
|-----------|-------------------|---------------------|
| <b>U</b>  | U side            | 2 to 10 stations    |
| <b>D</b>  | D side            |                     |
| <b>B</b>  | Both sides        | 2 to 20 stations    |
| <b>M*</b> | Special location  |                     |

\* For special specifications, indicate separately by the manifold specification sheet.

### How to Order Valve Manifold Assembly (Example)

**Example**



SS5Y3-60-04U-Q  
 \* SY3260-5G-C6-Q  
 \* SY3160-5G-M5-Q

1 set (Type 60, 4 station manifold base part no.)  
 2 sets (Double solenoid part no.)  
 2 sets (Single solenoid part no.)

→ The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

## Manifold Specifications

| Model   | SS5Y3-60                            | SS5Y5-60   | SS5Y7-60   |   |
|---|-------------------------------------|--|--|---|
| Applicable valve  | SY3□60                              | SY5□60   | SY7□60   |   |
| Manifold type   | Stacking type/DIN rail mounted      |  |  |   |
| P (SUP)/R (EXH)   | Common SUP/Common EXH               |  |  |   |
| Valve stations  | 2 to 20 stations <sup>Note 1)</sup> |  |  |   |
| A, B port location  | Valve                               |  |  |   |
| Port size   | P, R port                           | C8 (One-touch fitting for ø8)  | C10 (One-touch fitting for ø10)  | C12 (One-touch fitting for ø12)   |
|   | A, B port                           | M5<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | 1/8<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | 1/4<br>C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10) |
| Manifold base weight W (g) <sup>Note 2)</sup><br>(n: Number of SUP/EXH blocks, m: Weight of DIN rail) | W = 13n + m + 36                    | W = 41.2n + m + 77.6   | W = 65.4n + m + 128.2  |   |

Note 1) In cases such as those where many valves are operated simultaneously, use “-[station]B (SUP/EXH block on both sides)” (both sides SUP/EXH), applying pressure to the P ports on both sides and exhausting from the R ports on both sides.

Note 2) For DIN rail weight, refer to page 67.

## Flow Characteristics

| Model    | Port size      |              | Flow characteristics         |      |      |                |                              |      |      |                |
|----------|----------------|--------------|------------------------------|------|------|----------------|------------------------------|------|------|----------------|
|          | 1,5/3<br>(P,R) | 4,2<br>(A,B) | 1 → 4/2(P → A/B)             |      |      |                | 4/2 → 5/3(A/B → R)           |      |      |                |
|          |                |              | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q[l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q[l/min(ANR)]* |
| SS5Y3-60 | C8             | M5           | 0.55                         | 0.29 | 0.14 | 139            | 0.72                         | 0.24 | 0.18 | 176            |
|          |                | C4           | 0.57                         | 0.24 | 0.14 | 140            | 0.71                         | 0.20 | 0.17 | 170            |
|          |                | C6           | 0.68                         | 0.28 | 0.17 | 171            | 0.77                         | 0.24 | 0.19 | 189            |
| SS5Y5-60 | C10            | 1/8          | 1.8                          | 0.24 | 0.44 | 441            | 2.1                          | 0.17 | 0.47 | 495            |
|          |                | C6           | 1.5                          | 0.30 | 0.37 | 381            | 2.0                          | 0.16 | 0.46 | 469            |
|          |                | C8           | 1.8                          | 0.20 | 0.45 | 431            | 2.2                          | 0.17 | 0.50 | 518            |
| SS5Y7-60 | C12            | 1/4          | 3.7                          | 0.25 | 0.96 | 912            | 3.8                          | 0.19 | 0.94 | 905            |
|          |                | C8           | 3.2                          | 0.26 | 0.81 | 794            | 4.0                          | 0.18 | 0.96 | 947            |
|          |                | C10          | 3.7                          | 0.28 | 0.98 | 929            | 4.1                          | 0.19 | 1.0  | 977            |

Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## How to Order Valve

**SY 3 1 60** **5 L** **C6 -Q**

### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

### Type of actuation

|   |                            |  |
|---|----------------------------|--|
| 1 | 2 position single          |  |
|   | 2 position double          |  |
| 3 | 3 position closed center   |  |
|   | 3 position exhaust center  |  |
| 5 | 3 position pressure center |  |

### Coil specifications

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

### A, B port size

#### Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| O1     | 1/8       | SY5000            |
| O2     | 1/4       | SY7000            |


#### One-touch fitting (Metric size)

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  | SY3000            |
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  | SY5000            |
| C8     | One-touch fitting for ø8  | SY7000            |
| C10    | One-touch fitting for ø10 | SY7000            |

#### One-touch fitting (Inch size)

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  | SY3000            |
| N3     | One-touch fitting for ø5/32" | SY5000            |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N11    | One-touch fitting for ø3/8"  | SY7000            |

### Manual override



### Light/surge voltage suppressor

#### Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With light/surge voltage suppressor                  |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

#### Electrical entry for D (SY5000/7000 only)

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.  
\* DOZ is not available.

### Electrical entry

| 24, 12, 6, 5, 3 VDC                   |  |  |                                  | 24, 12 VDC/<br>100, 110, 200, 220 VAC | 24, 12, 6, 5, 3 VDC                          |
|---------------------------------------|--|--|----------------------------------|---------------------------------------|--|
| Grommet                               | L plug connector                             | M plug connector                             |                                  | DIN terminal<br>(SY5000, 7000)        | M8 connector *                               |
| <b>G:</b> Lead wire length 300 mm<br> | <b>L:</b> With lead wire (Length 300 mm)<br> | <b>M:</b> With lead wire (Length 300 mm)<br> | <b>MN:</b> Without lead wire<br> | <b>D:</b> With connector<br>          | <b>WO:</b> Without connector cable<br>       |
| <b>H:</b> Lead wire length 600 mm<br> | <b>LN:</b> Without lead wire<br>             | <b>LO:</b> Without connector<br>             | <b>MO:</b> Without connector<br> | <b>DO:</b> Without connector<br>      | <b>W□:</b> With connector cable (Note 1)<br> |

\* LN, MN type: with 2 sockets.

\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.

\* For connector cable of M8 connector, refer to back page 12.

\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.

Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.

### Rated voltage

#### For DC

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

#### For AC (50/60Hz)

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.

\* AC specification is only available with D and DO type.

## Specifications

| Series  |                   | SY3000  | SY5000     | SY7000 |
|---|-------------------|---|------------|--------|
| Fluid   |                   | Air   |            |        |
| Internal pilot<br>Operating pressure<br>range (MPa) | 2 position single | 0.15 to 0.7   |            |        |
|   | 2 position double | 0.1 to 0.7  |            |        |
|   |                   | 3 position  | 0.2 to 0.7 |        |
| Ambient and fluid temperature (°C)                  |                   | Max. 50   |            |        |
| Max. operating<br>frequency (Hz)                    | 2 position double | 10  | 5          | 5      |
|   | 3 position        | 3   | 3          | 3      |
| Manual override<br>(Manual operation)               |                   | Non-locking push type,<br>Push-turn locking slotted type,<br>Push-turn locking lever type |            |        |
| Pilot exhaust method                                |                   | Common exhaust type for main and pilot valve  |            |        |
| Lubrication   |                   | Not required  |            |        |
| Mounting position                                   |                   | Unrestricted  |            |        |
| Impact/Vibration resistance <small>Note</small>     |                   | 150/30  |            |        |
| Enclosure   |                   | Dust proof (* DIN terminal, M8 connector: IP65)   |            |        |

**Note)** Impact resistance: No malfunction occurred when it is tested in the axial direction and at the right angles to the main valve and armature in both energised and de-energised states every once for each condition.

Vibration resistance: No malfunction occurred in a one-sweep test between 45 and 2000 Hz. Test was performed at both energised and de-energised states in the axial direction and at the right angles to the main valve and armature. (Values in the initial stage)

\* Based on IEC60529

## Solenoid Specifications

|                                   |             |  |   |
|-----------------------------------|-------------|--|---|
| Electrical entry                  |             | Grommet (G), (H)<br>L plug connector (L)<br>M plug connector (M)<br>DIN terminal (D)<br>M8 connector (W) |   |
|                                   |             | G, H, L, M, W  | D   |
| Coil rated<br>voltage (V)         | DC          | 24, 12, 6, 5, 3  | 24, 12  |
|                                   | AC 50/60 Hz | 100, 110   | 200, 220  |
| Allowable voltage fluctuation (%) |             | ±10% of rated voltage *  |   |
| Power<br>consumption<br>(W)       | DC          | Standard   | 0.35 [With indicator light: 0.4<br>(DIN terminal with indicator light: 0.45)] |
|                                   |             | With power<br>saving circuit   | 0.1 (With indicator light only)   |
| Apparent<br>power<br>(VA) *       | AC          | 100 V  | -<br>0.78 (With indicator light: 0.87)  |
|                                   |             | 110 V<br>[115 V]   | -<br>0.86 (With indicator light: 0.97)<br>[0.94 (With indicator light: 1.07)] |
|                                   |             | 200 V  | -<br>1.15 (With indicator light: 1.30)  |
|                                   |             | 220 V<br>[230 V]   | -<br>1.27 (With indicator light: 1.46)<br>[1.39 (With indicator light: 1.60)] |
| Surge voltage suppressor          |             | Diode (Varistor is for DIN terminal<br>and non-polar)  |   |
| Indicator light                   |             | LED (AC of DIN connector is neon light.)   |   |

\* In common between 110 VAC and 115 VAC, and between 220 VAC and 230 VAC.

\* For 115 VAC and 230 VAC, the allowable voltage is -15% to +5% of rated voltage.

\* S, Z and T type (with power saving circuit) should be used within the following allowable voltage fluctuation range due to a voltage drop caused by the internal circuit.

S and Z type: 24 VDC: -7% to +10%

12 VDC: -4% to +10%

T type: 24 VDC: -8% to +10%

12 VDC: -6% to +10%

## Response Time

**Note)** Based on dynamic performance test, JIS B 8375-1981. (Coil temperature: 20°C, at rated voltage)

### SY3000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                               |            |
|----------------------|---|-------------------------------|------------|
|                      | Without surge voltage<br>suppressor             | With surge voltage suppressor |            |
|                      |   | S, Z type                     | R, U type  |
| 2 position single    | 12 or less                                      | 15 or less                    | 12 or less |
| 2 position double    | 10 or less                                      | 13 or less                    | 10 or less |
| 3 position           | 15 or less                                      | 20 or less                    | 16 or less |

### SY5000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                               |            |
|----------------------|---|-------------------------------|------------|
|                      | Without surge voltage<br>suppressor             | With surge voltage suppressor |            |
|                      |   | S, Z type                     | R, U type  |
| 2 position single    | 19 or less                                      | 26 or less                    | 19 or less |
| 2 position double    | 18 or less                                      | 22 or less                    | 18 or less |
| 3 position           | 32 or less                                      | 38 or less                    | 32 or less |

### SY7000

| Type of<br>actuation | Response time (ms) (at the pressure of 0.5 MPa) |                                     |            |
|----------------------|---|-------------------------------------|------------|
|                      | Without light/surge<br>voltage suppressor       | With light/surge voltage suppressor |            |
|                      |   | S, Z type                           | R, U type  |
| 2 position single    | 31 or less                                      | 38 or less                          | 33 or less |
| 2 position double    | 27 or less                                      | 30 or less                          | 28 or less |
| 3 position           | 50 or less                                      | 56 or less                          | 50 or less |

**Weight**

**Series SY3000**

| Valve model | Type of actuation |                 | Port size                        | Weight (g) |                    |              |
|-------------|-------------------|-----------------|----------------------------------|------------|--------------------|--------------|
|             |                   |                 | A, B                             | Gro-mmet   | L/M plug connector | M8 Connector |
| SY3□60-□-M5 | 2 position        | Single          | M5                               | 49         | 51                 | 55           |
|             |                   | Double          |                                  | 70         | 73                 | 81           |
|             | 3 position        | Closed center   |                                  | 73         | 76                 | 84           |
|             |                   | Exhaust center  |                                  |            |                    |              |
|             |                   | Pressure center |                                  |            |                    |              |
| SY3□60-□-C4 | 2 position        | Single          | C4<br>(One-touch fitting for ø4) | 62         | 61                 | 65           |
|             |                   | Double          |                                  | 80         | 83                 | 91           |
|             | 3 position        | Closed center   |                                  | 82         | 86                 | 94           |
|             |                   | Exhaust center  |                                  |            |                    |              |
|             |                   | Pressure center |                                  |            |                    |              |
| SY3□60-□-C6 | 2 position        | Single          | C6<br>(One-touch fitting for ø6) | 55         | 57                 | 61           |
|             |                   | Double          |                                  | 76         | 79                 | 87           |
|             | 3 position        | Closed center   |                                  | 78         | 82                 | 90           |
|             |                   | Exhaust center  |                                  |            |                    |              |
|             |                   | Pressure center |                                  |            |                    |              |

 Note) [ ]: denotes normal position.

**Series SY7000**

| Valve model  | Type of actuation |                 | Port size                          | Weight (g) |                    |              |              |
|--------------|-------------------|-----------------|------------------------------------|------------|--------------------|--------------|--------------|
|              |                   |                 | A, B                               | Gro-mmet   | L/M plug connector | DIN terminal | M8 Connector |
| SY7□60-□-02  | 2 position        | Single          | 1/4                                | 103        | 105                | 126          | 109          |
|              |                   | Double          |                                    | 125        | 128                | 170          | 136          |
|              | 3 position        | Closed center   |                                    | 133        | 136                | 178          | 144          |
|              |                   | Exhaust center  |                                    |            |                    |              |              |
|              |                   | Pressure center |                                    |            |                    |              |              |
| SY7□60-□-C8  | 2 position        | Single          | C8<br>(One-touch fitting for ø8)   | 138        | 139                | 160          | 143          |
|              |                   | Double          |                                    | 160        | 163                | 205          | 171          |
|              | 3 position        | Closed center   |                                    | 168        | 171                | 213          | 179          |
|              |                   | Exhaust center  |                                    |            |                    |              |              |
|              |                   | Pressure center |                                    |            |                    |              |              |
| SY7□60-□-C10 | 2 position        | Single          | C10<br>(One-touch fitting for ø10) | 123        | 125                | 146          | 129          |
|              |                   | Double          |                                    | 145        | 149                | 191          | 157          |
|              | 3 position        | Closed center   |                                    | 153        | 157                | 199          | 165          |
|              |                   | Exhaust center  |                                    |            |                    |              |              |
|              |                   | Pressure center |                                    |            |                    |              |              |

**Series SY5000**

| Valve model | Type of actuation |                 | Port size                        | Weight (g) |                    |              |              |
|-------------|-------------------|-----------------|----------------------------------|------------|--------------------|--------------|--------------|
|             |                   |                 | A, B                             | Gro-mmet   | L/M plug connector | DIN terminal | M8 Connector |
| SY5□60-□-01 | 2 position        | Single          | 1/8                              | 67         | 69                 | 90           | 71           |
|             |                   | Double          |                                  | 91         | 94                 | 136          | 102          |
|             | 3 position        | Closed center   |                                  | 97         | 100                | 142          | 108          |
|             |                   | Exhaust center  |                                  |            |                    |              |              |
|             |                   | Pressure center |                                  |            |                    |              |              |
| SY5□60-□-C4 | 2 position        | Single          | C4<br>(One-touch fitting for ø4) | 91         | 93                 | 114          | 97           |
|             |                   | Double          |                                  | 113        | 116                | 158          | 124          |
|             | 3 position        | Closed center   |                                  | 119        | 122                | 164          | 130          |
|             |                   | Exhaust center  |                                  |            |                    |              |              |
|             |                   | Pressure center |                                  |            |                    |              |              |
| SY5□60-□-C6 | 2 position        | Single          | C6<br>(One-touch fitting for ø6) | 86         | 88                 | 109          | 92           |
|             |                   | Double          |                                  | 108        | 111                | 153          | 119          |
|             | 3 position        | Closed center   |                                  | 114        | 117                | 159          | 125          |
|             |                   | Exhaust center  |                                  |            |                    |              |              |
|             |                   | Pressure center |                                  |            |                    |              |              |
| SY5□60-□-C8 | 2 position        | Single          | C8<br>(One-touch fitting for ø8) | 78         | 80                 | 101          | 84           |
|             |                   | Double          |                                  | 100        | 103                | 145          | 111          |
|             | 3 position        | Closed center   |                                  | 106        | 109                | 151          | 117          |
|             |                   | Exhaust center  |                                  |            |                    |              |              |
|             |                   | Pressure center |                                  |            |                    |              |              |

### How to Order Pilot Valve Assembly

V111  — 5 — G

**Coil specifications**

|     |   |
|-----|---|
| Nil | Standard  |
| T   | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W  type.

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

**Light/surge voltage suppressor**

|     |  |
|-----|--|
| Nil | Without light/surge voltage suppressor               |
| S   | With surge voltage suppressor                        |
| Z   | With light/surge voltage suppressor                  |
| R   | With surge voltage suppressor (Non-polar type)       |
| U   | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry**

|                            |                           |   |
|----------------------------|---------------------------|---|
| G                          | Grommet, 300 mm lead wire |   |
| H                          | Grommet, 600 mm lead wire |   |
| L                          | L plug connector          | With lead wire                          |
| LN                         |                           | Without lead wire                       |
| LO                         | Without connector         |   |
| M                          | M plug connector          | With lead wire                          |
| MN                         |                           | Without lead wire                       |
| MO                         | Without connector         |   |
| WO                         | M8                        | Without connector cable                 |
| W <input type="checkbox"/> | connector                 | With connector cable <sup>Note 1)</sup> |

\* For connector cable of M8 connector, refer to back page 12.

Note 1) Enter the cable length symbols in . Please be sure to fill in the blank referring to back page 13.

**■ DIN terminal type**

V115 — 5 — D

**Rated voltage**

|   |  |
|---|--|
| 5 | 24 VDC   |
| 6 | 12 VDC   |
| 1 | 100 VAC <sup>50/60</sup> Hz                                  |
| 2 | 200 VAC <sup>50/60</sup> Hz                                  |
| 3 | 110 VAC <sup>50/60</sup> Hz<br>[115 VAC <sup>50/60</sup> Hz] |
| 4 | 220 VAC <sup>50/60</sup> Hz<br>[230 VAC <sup>50/60</sup> Hz] |

\* DC specifications of Type D and DO is only available with 12 and 24 VDC.

**Light/surge voltage suppressor**

|     |  |
|-----|--|
| Nil | Without light/surge voltage suppressor               |
| S   | With surge voltage suppressor (Non-polar type)       |
| Z   | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**

|    |              |                   |
|----|--------------|-------------------|
| D  | DIN terminal | With connector    |
| DO | terminal     | Without connector |

Note) Do not replace V111 (G, H, L, M) to V115 (DIN terminal) and vice versa when replacing pilot valve assembly only.

### How to Order Connector Assembly for L/M Plug Connector

For DC: SY100-30-4A

Without lead wire: SY100-30-A

Only connector and sockets (x 2 pcs.)

**Lead wire length**

|     |         |
|-----|---------|
| Nil | 300 mm  |
| 6   | 600 mm  |
| 10  | 1000 mm |
| 15  | 1500 mm |
| 20  | 2000 mm |
| 25  | 2500 mm |
| 30  | 3000 mm |
| 50  | 5000 mm |

### How to Order M8 Connector Cable

V100-49-1

**Cable length**

|   |         |
|---|---------|
| 1 | 300 mm  |
| 2 | 500 mm  |
| 3 | 1000 mm |
| 4 | 2000 mm |
| 7 | 5000 mm |

\* For details, refer to back page 5.

## How to Order Port Block Assembly

SY **3** 000 — 6A — **C4**

• Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

• A, B port size

Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| O1     | 1/8       | SY5000            |
| O2     | 1/4       | SY7000            |

### One-touch fitting (Metric size)

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  |                   |
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  |                   |
| C8     | One-touch fitting for ø8  | SY7000            |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 |                   |

### One-touch fitting (Inch size)

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N3     | One-touch fitting for ø5/32" | SY5000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N9     | One-touch fitting for ø5/16" |                   |
| N11    | One-touch fitting for ø3/8"  |                   |

## How to Change Port Block Assembly

Connecting port size of A and B can be changed by replacing port block assembly mounted on body. When changing block assembly, correct screw torque must be achieved to avoid trouble; e.g. air leakage.


With the one-touch fitting port block assembly, it is only necessary to change the fitting and not the whole block. Refer to following part numbers.

### One-touch fitting (Metric size)

| Port size                 | Fitting assembly part no. | Applicable series |
|---------------------------|---------------------------|-------------------|
| One-touch fitting for ø4  | VVQ1000-50A-C4            | SY3000            |
| One-touch fitting for ø6  | VVQ1000-50A-C6            |                   |
| One-touch fitting for ø4  | VVQ1000-51A-C4            | SY5000            |
| One-touch fitting for ø6  | VVQ1000-51A-C6            |                   |
| One-touch fitting for ø8  | VVQ1000-51A-C8            | SY7000            |
| One-touch fitting for ø8  | VVQ2000-51A-C8            |                   |
| One-touch fitting for ø10 | VVQ2000-51A-C10           |                   |

### One-touch fitting (Inch size)

| Port size                    | Fitting assembly part no. | Applicable series |
|------------------------------|---------------------------|-------------------|
| One-touch fitting for ø5/32" | VVQ1000-50A-N3            | SY3000            |
| One-touch fitting for ø1/4"  | VVQ1000-50A-N7            |                   |
| One-touch fitting for ø5/32" | VVQ1000-51A-N3            | SY5000            |
| One-touch fitting for ø1/4"  | VVQ1000-51A-N7            |                   |
| One-touch fitting for ø5/16" | VVQ1000-51A-N9            | SY7000            |
| One-touch fitting for ø1/4"  | VVQ2000-51A-N9            |                   |
| One-touch fitting for ø3/8"  | VVQ2000-51A-N11           |                   |



### ⚠ Caution

Torque for mounting screws


SY3000(M2): 0.12 N·m

SY5000, 7000 (M3): 0.6 N·m

\* Refer to "How to Change Port Block Assembly" for part numbers.

## Manifold Option

### Individual SUP block assembly




#### One-touch fitting (Metric size)

| Port size                 | Assembly part no. | Applicable series |
|---------------------------|-------------------|-------------------|
| One-touch fitting for ø6  | SY3000-54-2C-Q    | SY3000            |
| One-touch fitting for ø8  | SY3000-54-1C-Q    |                   |
| One-touch fitting for ø10 | SY5000-54-1C-Q    | SY5000            |
| One-touch fitting for ø12 | SY7000-54-1C-Q    | SY7000            |

#### One-touch fitting (Inch size)

| Port size                    | Assembly part no. | Applicable series |
|------------------------------|-------------------|-------------------|
| One-touch fitting for ø5/16" | SY3000-54-3C-Q    | SY3000            |
| One-touch fitting for ø3/8"  | SY5000-54-2C-Q    | SY5000            |
| One-touch fitting for ø3/8"  | SY7000-54-3C-Q    | SY7000            |

### Individual EXH block assembly



#### One-touch fitting (Metric size)

| Port size                 | Assembly part no. | Applicable series |
|---------------------------|-------------------|-------------------|
| One-touch fitting for ø8  | SY3000-55-1B-Q    | SY3000            |
| One-touch fitting for ø10 | SY5000-55-1B-Q    | SY5000            |
| One-touch fitting for ø12 | SY7000-55-1B-Q    | SY7000            |


#### One-touch fitting (Inch size)

| Port size                    | Assembly part no. | Applicable series |
|------------------------------|-------------------|-------------------|
| One-touch fitting for ø5/16" | SY3000-55-2B-Q    | SY3000            |
| One-touch fitting for ø3/8"  | SY5000-55-2B-Q    | SY5000            |
| One-touch fitting for ø3/8"  | SY7000-55-3B-Q    | SY7000            |

#### [When supplying the manifold with 2 different supply pressures.]

Specify arrangement of individual SUP block assembly on the manifold specification sheet. (When using SS5Y□-60-□□D, blocking disk is assembled on D side.)


<Manifold model no.: SS5Y<sub>3</sub>□-60-□□D>



#### [When 2 different EXH passages are required.]

Specify arrangement of individual EXH block assembly on the manifold specification sheet. (When using SS5Y□-60-□□D, blocking disk is assembled on D side.)


<Manifold model no.: SS5Y<sub>3</sub>□-60-□□D>



#### [When a different supply pressure is required for only a middle valve.]

Specify arrangement of individual SUP block assembly and SUP blocking disk on the manifold specification sheet.


(Applicable manifold model no.: SS5Y□-60-□□B)



#### [When a separate exhaust passage is needed on only a middle valve.]

Specify arrangement of individual EXH block assembly and EXH blocking disk on the manifold specification sheet.

(Applicable manifold model no.: SS5Y□-60-□□B)



## Manifold Option

### ■ SUP blocking disk

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold. (This is the same block disk used with the individual SUP block assembly.)



| Series        | No.          |
|---------------|--------------|
| <b>SY3000</b> | SY3000-52-6A |
| <b>SY5000</b> | SY5000-52-4A |
| <b>SY7000</b> | SY7000-70-2A |

### ■ EXH blocking disk

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to separate both EXH passages. It is the same block disk that is used in the individual EXH block assembly.)





| Series        | No.          |
|---------------|--------------|
| <b>SY3000</b> | SY3000-52-6A |
| <b>SY5000</b> | SY5000-52-4A |
| <b>SY7000</b> | SY7000-70-2A |

### ■ Label for block disk


The labels shown below are used on manifold stations containing SUP/EXH blocking disk(s) to show their location. (3 pcs. each)

#### VZ3000-123-1A

Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk




\* When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.



### ■ Silencer with One-touch fitting


The silencer plugs directly into the One-touch fittings of the manifold.



| Series                  | Model      | Effective area     | A   | B  | C    |
|-------------------------|------------|--------------------|-----|----|------|
| <b>SY3000</b> (for ø8)  | AN203-KM8  | 14 mm <sup>2</sup> | ø16 | 26 | 51   |
| <b>SY5000</b> (for ø10) | AN200-KM10 | 26 mm <sup>2</sup> | ø22 | 54 | 80.8 |
|                         | AN300-KM10 | 30 mm <sup>2</sup> | ø25 | 70 | 97   |
| <b>SY7000</b> (for ø12) | AN300-KM12 | 41 mm <sup>2</sup> | ø25 | 70 | 98   |

### ■ Plug (white)

These are inserted in unused cylinder ports and SUP, EXH ports. Purchasing order is available in units of 10 pieces.



#### Dimensions


| Applicable fittings size ød | Model          | A    | L    | D    |
|-----------------------------|----------------|------|------|------|
| 4                           | <b>KQ2P-04</b> | 16   | 32   | 6    |
| 6                           | <b>KQ2P-06</b> | 18   | 35   | 8    |
| 8                           | <b>KQ2P-08</b> | 20.5 | 39   | 10   |
| 10                          | <b>KQ2P-10</b> | 22   | 43   | 12   |
| 12                          | <b>KQ2P-12</b> | 24   | 45.5 | 14   |
| 5/32"                       | <b>KQ2P-03</b> | 16   | 32   | 6    |
| 1/4"                        | <b>KQ2P-07</b> | 18   | 35   | 8.5  |
| 5/16"                       | <b>KQ2P-09</b> | 20.5 | 39   | 10   |
| 3/8"                        | <b>KQ2P-11</b> | 22   | 43   | 11.5 |

### ■ DIN Rail Dimensions/Weight for SY3000/5000

#### VZ1000-11-1-□

• Refer to the L dimension tables

\* Enter a number from the DIN rail dimension table below in them.



| No.         |      |       |      |       |      |       |      |       |      |       |
|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
| L dimension | 108  | 110.5 | 123  | 135.5 | 148  | 160.5 | 173  | 185.5 | 198  | 210.5 |
| Weight (g)  | 17.6 | 19.9  | 22.1 | 24.4  | 26.6 | 28.9  | 31.1 | 33.4  | 35.6 | 37.9  |

| No.         |      |       |      |       |      |       |      |       |      |       |
|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
| L dimension | 223  | 235.5 | 248  | 260.5 | 273  | 285.5 | 298  | 310.5 | 323  | 335.5 |
| Weight (g)  | 40.1 | 42.4  | 44.6 | 46.9  | 49.1 | 51.4  | 53.6 | 55.9  | 58.1 | 60.4  |


| No.         |      |       |      |       |      |       |      |       |      |       |
|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
| L dimension | 348  | 360.5 | 373  | 385.5 | 398  | 410.5 | 423  | 435.5 | 448  | 460.5 |
| Weight (g)  | 62.6 | 64.9  | 67.1 | 69.4  | 71.6 | 73.9  | 76.1 | 78.4  | 80.6 | 82.9  |

### ■ DIN Rail Dimensions/Weight for SY7000

#### VZ1000-11-4-□

• Refer to the L dimension tables

\* Enter a number from the DIN rail dimension table below in them.



| No.         |      |       |      |       |      |       |      |       |      |       |
|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
| L dimension | 198  | 110.5 | 123  | 135.5 | 148  | 160.5 | 173  | 185.5 | 198  | 210.5 |
| Weight (g)  | 24.8 | 28    | 31.1 | 34.3  | 37.4 | 40.6  | 43.8 | 46.9  | 50.1 | 53.3  |

| No.         |      |       |      |       |      |       |      |       |      |       |
|-------------|------|-------|------|-------|------|-------|------|-------|------|-------|
| L dimension | 223  | 235.5 | 248  | 260.5 | 273  | 285.5 | 298  | 310.5 | 323  | 335.5 |
| Weight (g)  | 56.4 | 59.6  | 62.7 | 65.9  | 69.1 | 72.2  | 75.4 | 78.6  | 81.7 | 84.9  |

| No.         |     |       |      |       |       |       |     |       |       |       |
|-------------|-----|-------|------|-------|-------|-------|-----|-------|-------|-------|
| L dimension | 348 | 360.5 | 373  | 385.5 | 398   | 410.5 | 423 | 435.5 | 448   | 460.5 |
| Weight (g)  | 88  | 91.2  | 94.4 | 97.5  | 100.7 | 103.9 | 107 | 110.2 | 113.3 | 116.5 |


Note) For DIN rail mounting, refer to page 226.

## Construction


### Series SY

#### JIS Symbol

2 position single




#### 2 position single




#### JIS Symbol

2 position double




#### 2 position double




#### JIS Symbol


3 position closed center




3 position exhaust center



3 position pressure center



#### 3 position closed center / exhaust center / pressure center



(This figure shows a closed center type.)

### Component Parts

| No. | Description          | Material  | Note  |
|-----|----------------------|---|-------|
| 1   | Body                 | Aluminum die-casted<br>(SY3000:<br>Zinc die-casted) | White |
| 2   | Adapter plate        | Resin   | White |
| 3   | End plate            | Resin   | White |
| 4   | Piston               | Resin   | —     |
| 5   | Spool valve assembly | Aluminum/NBR  | —     |

### Replacement Parts

| No. | Description                           | No.  |
|-----|---------------------------------------|--|
| 6   | Pilot valve assembly                  | Refer to "How to Order Pilot Valve Assembly" on page 64.               |
| 7   | Port block assembly                   | Refer to "How to Order Port Block Assembly" on page 65.                |
| 8   | Bottom cover assembly <sup>Note</sup> | SY3000-41-2A (with screw, gasket)<br>SY5000-41-2A (with screw, gasket) |


Note) There is no bottom cover assembly available for SY7000.




## SS5Y3-60- Stations B-Q

| Stations  | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|-----------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b> | 110.5      | 123   | 135.5 | 148   | 160.5 | 173   | 173   | 185.5 | 198         |
| <b>L2</b> | 100        | 112.5 | 125   | 137.5 | 150   | 162.5 | 162.5 | 175   | 187.5       |
| <b>L3</b> | 86         | 96.5  | 107   | 117.5 | 128   | 138.5 | 149   | 159.5 | 170         |
| <b>L4</b> | 12         | 13    | 14    | 15    | 16    | 17    | 12    | 13    | 14          |


| Stations  | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|-----------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b> | 210.5       | 223   | 235.5 | 235.5 | 248   | 260.5 | 273   | 285.5 | 298   | 310.5       |
| <b>L2</b> | 200         | 212.5 | 225   | 225   | 237.5 | 250   | 262.5 | 275   | 287.5 | 300         |
| <b>L3</b> | 180.5       | 191   | 201.5 | 212   | 222.5 | 233   | 243.5 | 254   | 264.5 | 275         |
| <b>L4</b> | 15          | 16    | 17    | 11.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |




### L plug connector (L)



### M plug connector (M)



### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.






## SS5Y5-60- Stations B-Q

| Stations | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|----------|------------|-------|-------|-------|-------|-------|------------|
| L1       | 135.5      | 160.5 | 173   | 185.5 | 210.5 | 223   | 235.5      |
| L2       | 125        | 150   | 162.5 | 175   | 200   | 212.5 | 225        |
| L3       | 112        | 128   | 144   | 160   | 176   | 192   | 208        |
| L4       | 11.5       | 16    | 14.5  | 12.5  | 17.5  | 15.5  | 13.5       |

| Stations | 9 stations | 10    | 11    | 12    | 13    | 14    | 15 stations |
|----------|------------|-------|-------|-------|-------|-------|-------------|
| L1       | 248        | 273   | 285.5 | 298   | 323   | 335.5 | 348         |
| L2       | 237.5      | 262.5 | 275   | 287.5 | 312.5 | 325   | 337.5       |
| L3       | 224        | 240   | 256   | 272   | 288   | 304   | 320         |
| L4       | 12         | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14          |

| Stations | 16 stations | 17    | 18    | 19    | 20 stations |
|----------|-------------|-------|-------|-------|-------------|
| L1       | 360.5       | 385.5 | 398   | 410.5 | 435.5       |
| L2       | 350         | 375   | 387.5 | 400   | 425         |
| L3       | 336         | 352   | 368   | 384   | 400         |
| L4       | 12          | 16.5  | 15    | 13    | 17.5        |







L plug connector (L)

M plug connector (M)

DIN terminal (D)

M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

## Dimensions


### SS5Y7-60- Stations U-Q

| Stations  | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|-----------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b> | 135.5      | 148   | 173   | 185.5 | 210.5 | 223   | 248   | 260.5 | 285.5       |
| <b>L2</b> | 125        | 137.5 | 162.5 | 175   | 200   | 212.5 | 237.5 | 250   | 275         |
| <b>L3</b> | 103        | 122   | 141   | 160   | 179   | 198   | 217   | 236   | 255         |
| <b>L4</b> | 16         | 13    | 16    | 12.5  | 15.5  | 12.5  | 15.5  | 12    | 15          |



### SS5Y7-60- Stations D-Q

| Stations  | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|-----------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b> | 135.5      | 148   | 173   | 185.5 | 210.5 | 223   | 248   | 260.5 | 285.5       |
| <b>L2</b> | 125        | 137.5 | 162.5 | 175   | 200   | 212.5 | 237.5 | 250   | 275         |
| <b>L3</b> | 103        | 122   | 141   | 160   | 179   | 198   | 217   | 236   | 255         |
| <b>L4</b> | 16         | 13    | 16    | 12.5  | 15.5  | 12.5  | 15.5  | 12    | 15          |




## SS5Y7-60- Stations B-Q


| Stations | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|----------|------------|-------|-------|-------|-------|-------|------------|
| L1       | 160.5      | 173   | 198   | 210.5 | 235.5 | 248   | 273        |
| L2       | 150        | 162.5 | 187.5 | 200   | 225   | 237.5 | 262.5      |
| L3       | 128        | 147   | 166   | 185   | 204   | 223   | 242        |
| L4       | 16         | 13    | 16    | 12.5  | 15.5  | 12.5  | 15.5       |

| Stations | 9 stations | 10    | 11    | 12    | 13    | 14    | 15 stations |
|----------|------------|-------|-------|-------|-------|-------|-------------|
| L1       | 285.5      | 310.5 | 323   | 348   | 360.5 | 385.5 | 410.5       |
| L2       | 275        | 300   | 312.5 | 337.5 | 350   | 375   | 400         |
| L3       | 261        | 280   | 299   | 318   | 337   | 356   | 375         |
| L4       | 12         | 15    | 12    | 15    | 11.5  | 14.5  | 17.5        |


| Stations | 16 stations | 17    | 18    | 19    | 20 stations |
|----------|-------------|-------|-------|-------|-------------|
| L1       | 423         | 448   | 460.5 | 485.5 | 498         |
| L2       | 412.5       | 437.5 | 450   | 475   | 487.5       |
| L3       | 394         | 413   | 432   | 451   | 470         |
| L4       | 14.5        | 17.5  | 14    | 17    | 14          |




### L plug connector (L)




### M plug connector (M)



### DIN terminal (D)




### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.

### DIN Rail Manifold Exploded View

**SY3000**  
Type 60




#### Replacement Parts

| No. | Description            | No.  | Note   |
|-----|------------------------|--|--|
| 1   | Valve                  | SY3□60-□□-□-□-□                            | □ at the end of part number denotes A. B port size: M5, C4, C6, N3, N7. Includes bushing assembly (SY3000-52-5A) 3 pcs.  |
| 2   | SUP/EXH block assembly | SY3000-55- <sup>1</sup> / <sub>2</sub> A-Q | P, R port (1: One-touch fitting for ø8, 2: One-touch fitting for ø5/16") Includes bushing assembly (SY3000-52-5A) 3 pcs. |
| 3   | End block assembly     | SY3000-56-1A-Q                             | For D side (Bushing assembly: Not available for SY3000-52-5A)  |
| 4   | End block assembly     | SY3000-56-1B-Q                             | For U side (Bushing assembly: Not available for SY3000-52-5A)  |
| 5   | Bushing assembly       | SY3000-52-5A                               |  |
| 6   | DIN rail               | VZ1000-11-1-□                              | Refer to page 67.  |



## DIN Rail Manifold Exploded View

**SY7000**  
Type 60



### Replacement Parts

| No. | Description            | No.                          | Note  |
|-----|------------------------|------------------------------|---|
| 1   | Valve                  | SY7□60-□□-□-□-□              | □ at the end of part number denotes A. B port size: 02, C8, C10, N9, N11. Includes bushing assembly (SY7000-70-1A) 3 pcs. |
| 2   | SUP/EXH block assembly | SY7000-75- $\frac{1}{3}$ A-Q |   |
| 3   | End block assembly     | SY7000-56-1A-Q               | In common for D side and U side (Bushing assembly: Not available for SY7000-70-1A.)                                       |
| 4   | Bushing assembly       | SY7000-70-1A                 |   |
| 5   | DIN rail               | VZ1000-11-4-□                | Refer to page 67.   |

### How to Add Additional Valves to the DIN Rail

Valves can be added at any station on the rail.

- 1 Loosen the rail holding screw (a) at both of 2 locations which holds the manifold base either in the U side or D side.  
When removing the end block assembly from the DIN rail, loosen the holding screws for DIN rail at first, then slide it to the edge of the rail.
- 2 Separate the valves at the point where more valves are to be added.
- 3 Mount the additional valves on the DIN rail as shown in Fig. 1.
- 4 Connect them together while pressing the block assemblies toward each others, and tighten the 2 holding screws (a) for DIN rail alternately (2 to 3 times) with the prescribed torque (1.4 N·m) to fix them to the DIN rail.

#### ⚠ Caution

**Tightening torque**  
SY7000: 1.4 N·m

(While lightly holding the blocks after fixing an end block on one side, tighten the other end block for better sealing after no gap between valves is confirmed.)

- Bushing assembly must be seated properly to each valve block in order to prevent air leaks from occurring.
- Refer to the fig. 2 when dismantling the valve from the DIN rail.

Fig. 1 Manifold mounting procedure





Fig. 2 Manifold dismantling procedure



#### ⚠ Caution

When clamping screw (a) of the end block is not sufficiently tightened during reassembly, air leakage may result. Before supplying air, check that there are no gaps between valves and that the end block is firmly secured to the DIN rail in order to ensure air supply without leakage.



Type **41**  
Type **42**

# 5 Port Solenoid Valve

## Series SY3000/5000/7000

### Base Mounted

# Bar Stock Type/Individual Wiring

### How to Order Manifold

#### Type 41/Compact style

**SS5Y 5 - 41 - 05 - C8 - Q**

**Manifold series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Stations**

|    |             |
|----|-------------|
| 02 | 2 stations  |
| :  | :           |
| 20 | 20 stations |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* This also includes the number of blanking plate assemblies.

\* Except for M5

**A, B port size**  
**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| C6     | One-touch fitting for ø6 | SY5000            |
| C8     | One-touch fitting for ø8 |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" |                   |

#### Type 42/External pilot capable

**SS5Y 5 - 42 - 05 - C8 - Q**

**Manifold series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

**Stations**

|    |             |
|----|-------------|
| 02 | 2 stations  |
| :  | :           |
| 20 | 20 stations |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**A, B port size**  
**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| 01     | 1/8       | SY3000            |
| 02     | 1/4       | SY5000            |
| 02     | 1/4       | SY7000            |

**One-touch fitting (Metric size)**


| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  |                   |
| C6     | One-touch fitting for ø6  | SY5000            |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 | SY7000            |

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" |                   |
| N11    | One-touch fitting for ø3/8"  | SY7000            |

### How to Order Valve Manifold Assembly (Example)

#### Example



**SS5Y3-41-05-C6-Q 1 set (Type 41, 5 stations manifold base part no.)**  
 \* SY3240-5G-Q 2 sets (Double solenoid part no.)  
 \* SY3140-5G-Q 2 sets (Single solenoid part no.)  
 \* SY3000-26-9A-Q 1 set (Blanking plate assembly part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

How to Order Valve

SY 5 2 40 □ □ — 5 L □ □ -Q

Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

Type of actuation

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

Pilot type

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

Coil specifications

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

Rated voltage

For DC

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

For AC (50/60 Hz)

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of Type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D and DO type.

Manual override

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

Light/surge voltage suppressor

Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

Electrical entry for D (SY5000/7000 only)


|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

Electrical entry

| 24, 12, 6, 5, 3 VDC   |   |  | 24, 12 VDC/<br>100, 110, 200,<br>220 VAC                    | 24, 12, 6, 5, 3 VDC  |
|---|---|--|---|--|
| Grommet   | L plug connector  | M plug connector   | DIN terminal <sup>Note2</sup>                               | M8 connector *   |
| <b>G:</b> Lead wire length<br>300 mm lead<br><b>H:</b> Lead wire length<br>600 mm | <b>L:</b> With lead wire<br>(Length 300 mm)<br><b>LN:</b> Without lead wire<br><b>LO:</b> Without | <b>M:</b> With lead wire<br>(Length 300 mm)<br><b>MN:</b> Without lead | <b>D:</b> With connector<br><b>DO:</b> Without<br>connector | <b>WO:</b> Without connector<br>cable<br><b>W□:</b> With connector<br>cable <sup>Note 1)</sup> |

\* LN, MN type: with 2 sockets.  
\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.  
\* For connector cable of M8 connector, refer to back page 12.  
\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.  
Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.  
Note 2) SY5000/7000 only.



## Manifold Specifications

|   |                                     |   |   |   |   |
|---|-------------------------------------|---|---|---|---|
| Model                                     | <b>SS5Y3-41</b>                     | <b>SS5Y3-42</b>   | <b>SS5Y5-41</b>   | <b>SS5Y5-42</b>   | <b>SS5Y7-42</b>   |
| Applicable valve                          | <b>SY3□40</b>                       |   | <b>SY5□40</b>   |   | <b>SY7□40</b>   |
| Manifold type                             | Single base/B mount                 |   |   |   |   |
| P(SUP)/R(EXH)                             | Common SUP, Common EXH              |   |   |   |   |
| Valve stations                            | 2 to 20 stations <sup>Note 1)</sup> |   |   |   |   |
| A, B port                                 | Base                                |   |   |   |   |
| Porting specifications                    | Side                                |   |   |   |   |
| Port size                                 | P, EA, EB port                      | 1/8   |   | 1/4   |   |
|   | A, B port                           | M5,<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | 1/8<br>C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | 1/8<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | 1/4<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) |
| Manifold base weight<br>W (g) n: Stations | W = 30n + 50                        | W = 37n + 63  | W = 61n + 101   | W = 79n + 127   | W = 100n + 151  |



Note 1) For more than 10 stations (more than 5 stations in case of SS5Y7), supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) Refer to "Manifold Option" on page 109.

## Flow Characteristics

| Model           | Port size              |                | Flow characteristics         |      |      |                 |                              |      |      |                 |
|-----------------|------------------------|----------------|------------------------------|------|------|-----------------|------------------------------|------|------|-----------------|
|                 | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |      |                 | 4/2 → 5/3 (A/B → EA/EB)      |      |      |                 |
|                 |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* |
| <b>SS5Y3-41</b> | 1/8                    | C6             | 0.75                         | 0.19 | 0.18 | 179             | 0.81                         | 0.23 | 0.20 | 197             |
| <b>SS5Y3-42</b> | 1/8                    | C6             | 0.75                         | 0.20 | 0.18 | 180             | 0.82                         | 0.20 | 0.20 | 196             |
| <b>SS5Y5-41</b> | 1/4                    | C8             | 1.8                          | 0.23 | 0.44 | 439             | 1.9                          | 0.16 | 0.45 | 445             |
| <b>SS5Y5-42</b> | 1/4                    | C8             | 1.9                          | 0.20 | 0.46 | 455             | 1.9                          | 0.12 | 0.43 | 436             |
| <b>SS5Y7-42</b> | 1/4                    | C10            | 3.0                          | 0.25 | 0.75 | 740             | 3.0                          | 0.12 | 0.66 | 688             |



Note) The value is for manifold base with 5 stations and individually operated 2 position type.


\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## SY3000: SS5Y3-41- Stations -M5, <sup>C4,N3</sup> <sup>C6,N7</sup> -Q


Grommet (G)

With interface regulator (with gauge)


For M5




### L plug connector (L)



### M plug connector (M)



### M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4    | 5  | 6    | 7  | 8     | 9   | 10    | 11  | 12    | 13  | 14    | 15  | 16    | 17  | 18    | 19  | 20 stations |
|------------|------------|----|------|----|------|----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------------|
| L1         | 38.5       | 49 | 59.5 | 70 | 80.5 | 91 | 101.5 | 112 | 122.5 | 133 | 143.5 | 154 | 164.5 | 175 | 185.5 | 196 | 206.5 | 217 | 227.5       |
| L2         | 30.5       | 41 | 51.5 | 62 | 72.5 | 83 | 93.5  | 104 | 114.5 | 125 | 135.5 | 146 | 156.5 | 167 | 177.5 | 188 | 198.5 | 209 | 219.5       |

**SY5000: SS5Y5-41- Stations -01, C6, N7 C8, N9 -Q**

**Grommet (G)**

For 1/8




**L plug connector: L**

**M plug connector: M**

**DIN terminal (D)**

**M8 connector (WO)**




Note) Refer to back page 12 for dimensions of connector types.


| Stations n | 2 stations | 3    | 4    | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|------------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 52.5       | 68.5 | 84.5 | 100.5 | 116.5 | 132.5 | 148.5 | 164.5 | 180.5 | 196.5 | 212.5 | 228.5 | 244.5 | 260.5 | 276.5 | 292.5 | 308.5 | 324.5 | 340.5       |
| <b>L2</b>  | 42         | 58   | 74   | 90    | 106   | 122   | 138   | 154   | 170   | 186   | 202   | 218   | 234   | 250   | 266   | 282   | 298   | 314   | 330         |

SY3000: SS5Y3-42- Stations - C4, N3 -Q  
C6, N7


Grommet (G)




L plug connector (L)



M plug connector (M)



M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4    | 5  | 6    | 7  | 8     | 9   | 10    | 11  | 12    | 13  | 14    | 15  | 16    | 17  | 18    | 19  | 20 stations |
|------------|------------|----|------|----|------|----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------------|
| L1         | 38.5       | 49 | 59.5 | 70 | 80.5 | 91 | 101.5 | 112 | 122.5 | 133 | 143.5 | 154 | 164.5 | 175 | 185.5 | 196 | 206.5 | 217 | 227.5       |
| L2         | 30.5       | 41 | 51.5 | 62 | 72.5 | 83 | 93.5  | 104 | 114.5 | 125 | 135.5 | 146 | 156.5 | 167 | 177.5 | 188 | 198.5 | 209 | 219.5       |


**SY3000: SS5Y3-42- Stations -01 -Q**

**Grommet (G)**


(Station 1) ----- (Station n)




**L plug connector (L)**



**M plug connector (M)**



**M8 connector (WO)**




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    | 13  | 14    | 15  | 16    | 17  | 18    | 19  | 20 stations |
|------------|------------|----|------|----|------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------------|
| <b>L1</b>  | 47.5       | 60 | 72.5 | 85 | 97.5 | 110 | 122.5 | 135 | 147.5 | 160 | 172.5 | 185 | 197.5 | 210 | 222.5 | 235 | 247.5 | 260 | 272.5       |
| <b>L2</b>  | 39.5       | 52 | 64.5 | 77 | 89.5 | 102 | 114.5 | 127 | 139.5 | 152 | 164.5 | 177 | 189.5 | 202 | 214.5 | 227 | 239.5 | 252 | 264.5       |

## SY5000: SS5Y5-42- Stations C4, N3 C6, N7 -Q

### Grommet (G)




### L plug connector (L)

### M plug connector (M)

### DIN terminal (D)

### M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4  | 5   | 6   | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15  | 16  | 17  | 18  | 19  | 20 stations |
|------------|------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------|
| <b>L1</b>  | 52         | 68 | 84 | 100 | 116 | 132 | 148 | 164 | 180 | 196 | 212 | 228 | 244 | 260 | 276 | 292 | 308 | 324 | 340         |
| <b>L2</b>  | 42         | 58 | 74 | 90  | 106 | 122 | 138 | 154 | 170 | 186 | 202 | 218 | 234 | 250 | 266 | 282 | 298 | 314 | 330         |

**SY5000: SS5Y5-42- Stations -02 -Q**

**Grommet (G)**




**L plug connector (L)**

**M plug connector (M)**

**DIN terminal (D)**

**M8 connector (WO)**




Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4    | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    | 13  | 14    | 15  | 16    | 17  | 18    | 19  | 20 stations |
|------------|------------|----|------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|-------------|
| <b>L1</b>  | 59.5       | 77 | 94.5 | 112 | 129.5 | 147 | 164.5 | 182 | 199.5 | 217 | 234.5 | 252 | 269.5 | 287 | 304.5 | 322 | 339.5 | 357 | 374.5       |
| <b>L2</b>  | 49.5       | 67 | 84.5 | 102 | 119.5 | 137 | 154.5 | 172 | 189.5 | 207 | 224.5 | 242 | 259.5 | 277 | 294.5 | 312 | 329.5 | 347 | 364.5       |

**SY7000: SS5Y7-42- Stations -02, C10, N11 -Q**

**Grommet (G)**




**L plug connector (L)**

**M plug connector (M)**

**DIN terminal (D)**

**M8 connector (WO)**



Note) Refer to back page 12 for dimensions of connector types.

| Stations n | 2 stations | 3  | 4  | 5   | 6   | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15  | 16  | 17  | 18  | 19  | 20 stations |
|------------|------------|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-------------|
| <b>L1</b>  | 61         | 80 | 99 | 118 | 137 | 156 | 175 | 194 | 213 | 232 | 251 | 270 | 289 | 308 | 327 | 346 | 365 | 384 | 403         |
| <b>L2</b>  | 49         | 68 | 87 | 106 | 125 | 144 | 163 | 182 | 201 | 220 | 239 | 258 | 277 | 296 | 315 | 334 | 353 | 372 | 391         |

# 5 Port Solenoid Valve

## Series SY9000

### Base Mounted

# Stacking Type/Individual Wiring

### How to Order Manifold

SS5Y9-43-05U-C8-Q

Manifold series  
9 SY9000

#### Valve stations

| Symbol | Stations    |
|--------|-------------|
| 02     | 2 stations  |
| ⋮      | ⋮           |
| 20     | 20 stations |

\* This also includes the number of blanking plate assemblies.

#### P, R port outlets

| Symbol | Port outlet | Applicable stations |
|--------|-------------|---------------------|
| U      | U side      | 2 to 10 stations    |
| D      | D side      |                     |
| B      | Both sides  | 2 to 20 stations    |

#### SUP/EXH block assembly specifications

| Symbol | Specifications                        |
|--------|---------------------------------------|
| -      | Standard/Internal pilot specification |
| R      | External pilot specification          |
| S      | Internal pilot/Built-in silencer      |
| RS     | External pilot/Built-in silencer      |

#### Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

#### Option

| Symbol | Mounting  |
|--------|---|
| -      | Direct mounting   |
| D      | DIN rail mounting (with DIN rail)   |
| DO     | DIN rail mounting (without DIN rail)  |
| D*     | When a longer DIN rail is desired than the specified stations, specify the station number to be required into * mark. |

#### A, B port size

| Symbol | Port size |
|--------|-----------|
| 02     | 1/4       |
| 03     | 3/8       |

#### One-touch fitting (Metric size)

| Symbol | Port size                 |
|--------|---------------------------|
| C8     | One-touch fitting for ø8  |
| C10    | One-touch fitting for ø10 |
| C12    | One-touch fitting for ø12 |
| M      | Mixed                     |


#### One-touch fitting (Inch size)

| Symbol | Port size                    |
|--------|------------------------------|
| N9     | One-touch fitting for ø5/16" |
| N11    | One-touch fitting for ø3/8"  |
| M      | Mixed                        |

\* In the case of mixed specifications (M), indicate separately on the manifold specification sheet.

### How to Order Valve Manifold Assembly (Example)

#### Example



SS5Y9-43-05B-C12-Q 1 set (Type 43, 5 station manifold base part no.)  
 \* SY9000-26-2A-Q 1 set (Blanking plate assembly part no.)  
 \* SY9140-5LOZ-Q 2 sets (Single solenoid part no.)  
 \* SY9220-5LOZ-Q 2 sets (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

**How to Order Valve**

SY 9 2 40 □ □ 5 L □ □ -Q

**Series**

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Pilot type**

|     |                |
|-----|----------------|
| Nil | Internal pilot |
| R   | External pilot |

**Coil specifications**

|     |   |
|-----|---|
| Nil | Standard                                    |
| T   | With power saving circuit (24, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

**Rated voltage**

**For DC**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

**For AC ( 50/60 Hz)**

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of Type D and DO is only available with 12 and 24 VDC.

\* AC specification is only available with D and DO type.

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**

**Electrical entry for G, H, L, M, W**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With indicator light and surge voltage suppressor    |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |



\* Power saving circuit is only available in the "Z" type.

**Electrical entry for D**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |



\* DOZ is not available.

\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**

| 24, 12, 6, 5, 3 VDC        |                                   |                                   | 24, 12 VDC/<br>100, 110, 200,<br>220 VAC | 24, 12, 6, 5, 3 VDC                         |
|----------------------------|-----------------------------------|-----------------------------------|--|---|
| Grommet                    | L plug connector                  | M plug connector                  | DIN terminal                             | M8 connector *                              |
| G: Lead wire length 300 mm | L: With lead wire (Length 300 mm) | M: With lead wire (Length 300 mm) | D: With connector                        | WO: Without connector cable                 |
| H: Lead wire length 600 mm | LN: Without lead wire             | MN: Without lead wire             | DO: Without connector                    | W□: With connector cable <sup>Note 1)</sup> |
|                            | LO: Without connector             | MO: Without connector             |  |   |




\* LN, MN type: with 2 sockets.

\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.

\* For connector cable of M8 connector, refer to back page 12.

\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.

Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.



## Manifold Specifications

|  |                |   |  |
|--|----------------|---|--|
| Model                                      |                | <b>SS5Y9-43</b>   |  |
| Applicable valve                           |                | <b>SY9□40</b>   |  |
| Manifold type                              |                | Stacking type   |  |
| P(SUP)/R(EXH)                              |                | Common SUP, Common EXH  |  |
| Valve stations                             |                | 2 to 20 stations <sup>(1)</sup>   |  |
| A, B port                                  | Location       | Base  |  |
| Porting specifications                     | Direction      | Side  |  |
| Port size                                  | P, EA, EB port | C12 (One-touch fitting for ø12)   |  |
|  | A, B port      | $\frac{1}{4}$<br>$\frac{3}{8}$<br>C8 (One-touch fitting for ø8)<br>C10 (One-touch fitting for ø10)<br>C12 (One-touch fitting for ø12) |  |
| Manifold base weight<br>W (g), n: Stations |                | W = 107n + 330  |  |



Note 1) For more than 10 stations, supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) Refer to "Manifold Option" on page 109.

## Flow Characteristics

| Model           | Port size              |                | Flow characteristics       |      |     |                |                            |      |     |                |
|-----------------|------------------------|----------------|----------------------------|------|-----|----------------|----------------------------|------|-----|----------------|
|                 | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1→4/2 (P→A/B)              |      |     |                | 4/2→5/3 (A/B→EA/EB)        |      |     |                |
|                 |                        |                | C (dm <sup>3</sup> /s·bar) | b    | Cv  | Q[l/min(ANR)]* | C (dm <sup>3</sup> /s·bar) | b    | Cv  | Q[l/min(ANR)]* |
| <b>SS5Y9-43</b> | C12                    | C12            | 6.4                        | 0.29 | 1.6 | 1617           | 7.3                        | 0.29 | 1.8 | 1845           |




Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## SY9000: SS5Y9-43- Stations D 02, C8, N9 03, C10, N11 C12 (-D)-Q

### Grommet (G)


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 198   | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5       |
| L2         | 137.5      | 162.5 | 187.5 | 212.5 | 237.5 | 250   | 275   | 300   | 325         |
| L3         | 117        | 141   | 165   | 189   | 213   | 237   | 261   | 285   | 309         |
| L4         | 15.5       | 16    | 16.5  | 17    | 17.5  | 12    | 12.5  | 13    | 13.5        |
| L5         | 103        | 127   | 151   | 175   | 199   | 223   | 247   | 271   | 295         |




DIN rail holding screw  
 <When attaching the DIN rail>  
 Tightening torque: 0.55 to 0.65N·m

\* When P, R port outlets are indicated on the D side, the P, R ports on the opposite side are plugged.


### With External Pilot Specifications




\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the D side.




### L plug connector (L)




### M plug connector (M)



### DIN terminal (D)



### M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

SY9000: SS5Y9-43- Stations U 02 C9, N9  
-03 C10, N11   (-D)-Q


Grommet (G)

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 198   | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5       |
| L2         | 137.5      | 162.5 | 187.5 | 212.5 | 237.5 | 250   | 275   | 300   | 325         |
| L3         | 117        | 141   | 165   | 189   | 213   | 237   | 261   | 285   | 309         |
| L4         | 15.5       | 16    | 16.5  | 17    | 17.5  | 12    | 12.5  | 13    | 13.5        |
| L5         | 103        | 127   | 151   | 175   | 199   | 223   | 247   | 271   | 295         |




\* When P, R port outlets are indicated on the U side, the P, R ports on the opposite side are plugged.


With External Pilot Specifications




\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the D side.




Silencer (Air discharge port) (with built-in silencer specifications)




L plug connector (L)




M plug connector (M)



DIN terminal (D)



M8 connector (WO)




Note) Refer to back page 12 for dimensions of connector types.

## SY9000: SS5Y9-43- Stations B 02, C8, N9 03, C10, N11 (-D)-Q

### Grommet (G)

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 198   | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5       |
| L2         | 137.5      | 162.5 | 187.5 | 212.5 | 237.5 | 250   | 275   | 300   | 325         |
| L3         | 117        | 141   | 165   | 189   | 213   | 237   | 261   | 285   | 309         |
| L4         | 15.5       | 16    | 16.5  | 17    | 17.5  | 12    | 12.5  | 13    | 13.5        |
| L5         | 103        | 127   | 151   | 175   | 199   | 223   | 247   | 271   | 295         |


| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 360.5       | 385.5 | 410.5 | 435.5 | 460.5 | 485.5 | 510.5 | 535.5 | 560.5 | 573         |
| L2         | 350         | 375   | 400   | 425   | 450   | 475   | 500   | 525   | 550   | 562.5       |
| L3         | 333         | 357   | 381   | 405   | 429   | 453   | 477   | 501   | 525   | 549         |
| L4         | 14          | 14.5  | 15    | 15.5  | 16    | 16.5  | 17    | 17.5  | 18    | 12          |
| L5         | 319         | 343   | 367   | 391   | 415   | 439   | 463   | 487   | 511   | 535         |





DIN rail holding screw  
 <When attaching the DIN rail>  
 Tightening torque: 0.55 to 0.65 N·m

\* When P, R port outlets are indicated on the B side, the P, R ports on the both sides are in the open state.


### With External Pilot Specifications




\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the B side (both sides).




### L plug connector (L)




### M plug connector (M)



### DIN terminal (D)



### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.

Type **41P**  
Type **42P**

# 5 Port Solenoid Valve

## Series SY3000/5000/7000

### Base Mounted

# Bar Stock Type/Flat Ribbon Cable

### How to Order Manifold

#### Type 41P/Compact style

**SS5Y 5-41P-05-C8-□-Q**

Manifold series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

Stations

|    |             |
|----|-------------|
| 03 | 3 stations  |
| :  | :           |
| 12 | 12 stations |

Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* SS5Y3 has 4 to 12 stations.

\* Except for M5

#### A, B port size Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| 01     | 1/8       | SY5000            |

#### One-touch fitting (Metric size)

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| C6     | One-touch fitting for ø6 | SY5000            |
| C8     | One-touch fitting for ø8 |                   |

#### One-touch fitting (Inch size)

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" |                   |

#### Type 42P/Common external pilot

**SS5Y 5-42P-05-C8-□-Q**

Manifold series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |

Stations

|    |             |
|----|-------------|
| 03 | 3 stations  |
| :  | :           |
| 12 | 12 stations |

Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* SS5Y3 has 4 to 12 stations.

#### A, B port size Thread piping

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| 01     | 1/8       | SY3000            |
| 02     | 1/4       | SY5000            |
| 02     | 1/4       | SY7000            |

#### One-touch fitting (Metric size)


| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY3000            |
| C6     | One-touch fitting for ø6  |                   |
| C6     | One-touch fitting for ø6  | SY5000            |
| C8     | One-touch fitting for ø8  |                   |
| C10    | One-touch fitting for ø10 | SY7000            |

#### One-touch fitting (Inch size)

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY3000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N7     | One-touch fitting for ø1/4"  | SY5000            |
| N9     | One-touch fitting for ø5/16" |                   |
| N9     | One-touch fitting for ø5/16" | SY7000            |

### How to Order Valve Manifold Assembly (Example)

#### Example




- SS5Y3-41P-06-C6-Q** 1 set (Type 41, 6 stations manifold base part no.)
- \* **SX3000-26-10A-Q** 1 set (Blanking plate assembly part no)
- \* **SY3140-5LOU-Q** 3 sets (Single solenoid part no.)
- \* **SY3240-5LOU-Q** 2 sets (Double solenoid part no.)
- \* **SY3000-37-3A** 3 sets (Connector assembly part no.)
- \* **SY3000-37-4A** 2 sets (Connector assembly part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

**How to Order Valve**



**How to Order Connector Assembly**

**For 12, 24 VDC**


| For DC                                  | For SY3000   | For SY5000/7000 |
|---|--------------|-----------------|
| For single solenoid                     | SY3000-37-3A | SY5000-37-3A    |
| Double solenoid, 3 position type        | SY3000-37-4A | SY5000-37-4A    |
| Single with spacer assembly             | SY5000-37-3A | SY5000-37-5A    |
| Double, 3 position with spacer assembly | SY3000-37-6A | SY5000-37-6A    |

## Flat Ribbon Cable Manifold Specifications

• Multiple valve wiring is simplified through the use of the flat cable connector.

• Clean appearance

In the case of a flat ribbon cable type, each valve is wired on the print board of manifold base to allow the external wiring to be piped all together with 26 pins MIL connector.



| Model                                  | SS5Y3-41P   | SS5Y3-42P  | SS5Y5-41P  | SS5Y5-42P  | SS5Y7-42P  |                                 |
|--|---|--|--|--|--|---------------------------------|
| Applicable valve                       | SY3□40  |  | SY5□40   |  | SY7□40   |                                 |
| Manifold type                          | Single base/B mount   |  |  |  |  |                                 |
| P(SUP)/R(EXH)                          | Common SUP, Common EXH  |  |  |  |  |                                 |
| Valve stations                         | 4 to 12 stations <sup>(1)</sup>   |  | 3 to 12 stations <sup>Note 1)</sup>                            |  |  |                                 |
| A, B port                              | Location  |  |  |  |  |                                 |
|  | Direction   |  |  |  |  |                                 |
| Porting specifications                 | 1/8   |  | 1/4  |  | 1/4  |                                 |
|  | P, EA, EB port  | M5   | 1/8  | 1/8  | 1/4  | 1/4                             |
| Port size                              | A, B port   | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) | C10 (One-touch fitting for ø10) |
|  | Manifold base weight W (g), n: Stations   | W = 39n + 83   | W = 48n + 99   | W = 67n + 118  | W = 88n + 151  | W = 109n + 174                  |
| Applicable flat ribbon cable connector | Flat ribbon cable connector, Socket: 26 pins MIL type with strain relief, Conforming to MIL-C-83503 |  |  |  |  |                                 |
| Internal wiring                        | In common between +COM and -COM (Z type: +COM only).  |  |  |  |  |                                 |
| Rated voltage                          | 12, 24 VDC  |  |  |  |  |                                 |

Note 1) For more than 10 stations (more than 5 stations in case of SS5Y7), supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) The withstand voltage specification for the wiring unit section is JIS C 0704, Grade 1 or its equivalent.

Note 3) Refer to "Manifold Option" on page 109.


## Flow Characteristics

| Model     | Port size              |                | Flow characteristics |      |      |                |                         |      |      |                |
|-----------|------------------------|----------------|----------------------|------|------|----------------|-------------------------|------|------|----------------|
|           | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)    |      |      |                | 4/2 → 5/3 (A/B → EA/EB) |      |      |                |
|           |                        |                | C (dm³/(s·bar))      | b    | Cv   | Q(l/min(ANR))* | C (dm³/(s·bar))         | b    | Cv   | Q(l/min(ANR))* |
| SS5Y3-41P | 1/8                    | C6             | 0.75                 | 0.19 | 0.18 | 179            | 0.81                    | 0.23 | 0.20 | 197            |
| SS5Y3-42P | 1/8                    | C6             | 0.75                 | 0.20 | 0.18 | 180            | 0.82                    | 0.20 | 0.20 | 196            |
| SS5Y5-41P | 1/4                    | C8             | 1.8                  | 0.23 | 0.44 | 439            | 1.9                     | 0.16 | 0.45 | 445            |
| SS5Y5-42P | 1/4                    | C8             | 1.9                  | 0.20 | 0.46 | 455            | 1.9                     | 0.12 | 0.43 | 436            |
| SS5Y7-42P | 1/4                    | C10            | 3.0                  | 0.25 | 0.75 | 740            | 3.0                     | 0.12 | 0.66 | 688            |


Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Internal Wiring of Manifold (Non-polar type)



- For more than 10 stations, both poles of the common should be wired.
- For single solenoid, connect to the solenoid A side.
- The maximum number of stations that can be accommodated is 12. For more stations, please contact SMC.







### Caution



- For non-polar (U) valves, the electrical DC connections can be used with either positive and negative COM. For type (Z), only use with positive COM as the valve does not operate correctly when used with negative COM.

## SY3000: SS5Y3-41P- Stations -M5, <sup>C4, N3</sup><sub>C6, N7</sub> -Q

With interface regulator (with gauge)




For M5




| Stations n | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|------|----|------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 72.5 | 85 | 97.5 | 110 | 122.5 | 135 | 147.5 | 160 | 172.5 |
| <b>L2</b>  | 64.5 | 77 | 89.5 | 102 | 114.5 | 127 | 139.5 | 152 | 164.5 |

**SY5000: SS5Y5-41P- Stations -01, C6,N7 C8,N9 -Q**







**With interface regulator (with gauge)**





| Stations n | 3  | 4    | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|----|------|-----|-------|-----|-------|-----|-------|-----|-------|
| L1         | 77 | 94.5 | 112 | 129.5 | 147 | 164.5 | 182 | 199.5 | 217 | 234.5 |
| L2         | 67 | 84.5 | 102 | 119.5 | 137 | 154.5 | 172 | 189.5 | 207 | 224.5 |

## SY3000: SS5Y3-42P- Stations -01, <sup>C4, N3</sup><sub>C6, N7</sub> -Q

With interface regulator (with gauge)



For 1/8




| Stations n | 4    | 5  | 6    | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|------|----|------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 72.5 | 85 | 97.5 | 110 | 122.5 | 135 | 147.5 | 160 | 172.5 |
| <b>L2</b>  | 64.5 | 77 | 89.5 | 102 | 114.5 | 127 | 139.5 | 152 | 164.5 |

**SY5000: SS5Y5-42P- Stations -02, <sup>C6, N7</sup><sub>C8, N9</sub> -Q**

**Grommet (G)**

With interface regulator (with gauge)






| Stations n | 3  | 4    | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|----|------|-----|-------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 77 | 94.5 | 112 | 129.5 | 147 | 164.5 | 182 | 199.5 | 217 | 234.5 |
| <b>L2</b>  | 67 | 84.5 | 102 | 119.5 | 137 | 154.5 | 172 | 189.5 | 207 | 224.5 |

## SY7000: SS5Y7-42P- Stations -02, C10, N11 □ -Q



### Grommet (G)

#### With interface regulator (with gauge)



<In the case of external pilot type solenoid valve>

#### For 1/4



| Stations n | 3  | 4     | 5   | 6     | 7   | 8     | 9   | 10    | 11  | 12    |
|------------|----|-------|-----|-------|-----|-------|-----|-------|-----|-------|
| <b>L1</b>  | 88 | 108.5 | 129 | 149.5 | 170 | 190.5 | 211 | 231.5 | 252 | 272.5 |
| <b>L2</b>  | 76 | 96.5  | 117 | 137.5 | 158 | 178.5 | 199 | 219.5 | 240 | 260.5 |

# 5 Port Solenoid Valve

## Series SY9000

### Base Mounted

# Stacking Type/Flat Ribbon Cable

### How to Order Manifold

**SS5Y9 - 43P - 05 U - C8 - Q**

Manifold series

|   |        |
|---|--------|
| 9 | SY9000 |
|---|--------|

Valve stations

| Symbol | Stations    |
|--------|-------------|
| 04     | 4 stations  |
| ⋮      | ⋮           |
| 12     | 12 stations |

\* This also includes the number of blanking plate assemblies.

#### P, R port outlets

| Symbol | Port outlet | Applicable stations |
|--------|-------------|---------------------|
| U      | U side      | 4 to 10 stations    |
| D      | D side      |                     |
| B      | Both sides  | 4 to 12 stations    |

#### SUP/EXH block assembly specifications

| Symbol | Specifications                        |
|--------|---------------------------------------|
| -      | Standard/Internal pilot specification |
| R      | External pilot specification          |
| S      | Internal pilot/Built-in silencer      |
| RS     | External pilot/Built-in silencer      |

#### Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

#### Option

| Symbol | Mounting  |
|--------|---|
| -      | Direct mounting   |
| D      | DIN rail mounting (with DIN rail)   |
| D0     | DIN rail mounting (without DIN rail)  |
| D*     | When a longer DIN rail is desired than the specified stations, specify the station number to be required into * mark. |

#### A, B port size

##### Thread piping

| Symbol | Port size |
|--------|-----------|
| 02     | 1/4       |
| 03     | 3/8       |

##### One-touch fitting (Metric size)

| Symbol | Port size                 |
|--------|---------------------------|
| C8     | One-touch fitting for ø8  |
| C10    | One-touch fitting for ø10 |
| C12    | One-touch fitting for ø12 |
| M      | Mixed                     |


##### One-touch fitting (Inch size)

| Symbol | Port size                    |
|--------|------------------------------|
| N9     | One-touch fitting for ø5/16" |
| N11    | One-touch fitting for ø3/8"  |
| M      | Mixed                        |

\* In the case of mixed specifications (M), indicate separately on the manifold specification sheet.

### How to Order Valve Manifold Assembly (Example)

#### Example




- |                     |   |
|---------------------|---|
| SS5Y9-43P-05B-C12-Q | 1 set (Type 43, 5 station manifold base part no.) |
| * SY9000-26-4A-Q    | 1 set (Blanking plate assembly part no.)          |
| * SY9140-5LOU-Q     | 2 sets (Single solenoid part no.)                 |
| * SY9240-5LOU-Q     | 2 sets (Double solenoid part no.)                 |
| * SY9000-37-1A      | 2 sets (Connector assembly part no.)              |
| * SY9000-37-2A      | 2 sets (Connector assembly part no.)              |
| * SY9000-41-1       | 1 set (Lead wire cover)                           |

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

**How to Order Valve**



**How to Order Connector Assembly**


**For 12, 24 VDC**

| For DC                                  | For SY9000   |
|---|--------------|
| For single solenoid                     | SY9000-37-1A |
| Double solenoid, 3 position type        | SY9000-37-2A |
| Single with spacer assembly             | SY9000-37-3A |
| Double, 3 position with spacer assembly | SY9000-37-4A |

• Multiple valve wiring is simplified through the use of the flat cable connector.

• Clean appearance

In the case of a flat ribbon cable type, each valve is wired on the print board of manifold base to allow the external wiring to be piped all together with 26 pins MIL connector.



## Flat Ribbon Cable Manifold Specifications

|  |   |  |
|--|---|--|
| Model                                  | SS5Y9-43P   |  |
| Applicable valve                       | SY9□40  |  |
| Manifold type                          | Stacking type   |  |
| P (SUP)/R (EXH)                        | Common SUP, Common EXH  |  |
| Valve stations                         | 4 to 12 stations <sup>Note 1)</sup>   |  |
| A, B port Porting specifications       | Location  | Base   |
|  | Direction   | Side   |
| Port size                              | P, EA, EB port  | C12 (One-touch fitting for $\phi 12$ )   |
|  | A, B port   | $\frac{1}{4}$<br>$\frac{3}{8}$<br>C8 (One-touch fitting for $\phi 8$ )<br>C10 (One-touch fitting for $\phi 10$ )<br>C12 (One-touch fitting for $\phi 12$ ) |
| Manifold base weight W (g) n: Stations | W = 114n + 343  |  |
| Applicable flat ribbon cable connector | Flat ribbon cable connection, Socket: 26 pins MIL with strain relief, Conforming to MIL-C-83503 |  |
| Internal wiring                        | In common between +COM and -COM (Z type: +COM only)   |  |
| Rated voltage                          | 12, 24 VDC  |  |



Note 1) For more than 10 stations, supply pressure to P port on both sides and exhaust from EA/EB port on both sides.

Note 2) The withstand voltage specification for the wiring unit section is JIS C 0704, Grade 1 or its equivalent.

Note 3) Refer to "Manifold Option" on page 109.

## Flow Characteristics


| Model     | Port size              |                | Flow characteristics         |      |     |                           |                              |      |     |                           |
|-----------|------------------------|----------------|------------------------------|------|-----|---------------------------|------------------------------|------|-----|---------------------------|
|           | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |     |                           | 4/2 → 5/3 (A/B → EA/EB)      |      |     |                           |
|           |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q <sub>l</sub> /min(ANR)* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv  | Q <sub>l</sub> /min(ANR)* |
| SS5Y9-43P | C12                    | C12            | 6.4                          | 0.29 | 1.6 | 1617                      | 7.3                          | 0.29 | 1.8 | 1845                      |



Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Internal Wiring of Manifold (Non-polar type)




### Caution

- For non-polar (U) valves, the electrical DC connections can be used with either positive and negative COM. For type (Z), only use with positive COM as the valve does not operate correctly when used with negative COM.




- For more than 10 stations, both poles of the common should be wired.
- For single solenoid, connect to the solenoid A side.
- The maximum number of stations that can be accommodated is 12. For more stations, please contact SMC.






SY9000: SS5Y9-43P- Stations D 02 C8, N9 -03 C10, N11 C12 (-D)-Q

\* When P, R port outlets are indicated on the D side, the P, R ports on the opposite side are plugged.

### With External Pilot Specifications



\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the D side.




| Stations n | 4 stations | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------------|
| L1         | 198        | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5       |
| L2         | 187.5      | 212.5 | 237.5 | 250   | 275   | 300   | 325         |
| L3         | 165        | 189   | 213   | 237   | 261   | 285   | 309         |
| L4         | 16.5       | 17    | 17.5  | 12    | 12.5  | 13    | 13.5        |
| L5         | 151        | 175   | 199   | 223   | 247   | 271   | 295         |




SY9000: SS5Y9-43P- Stations U  <sup>02</sup> <sub>-03</sub> <sup>C8, N9</sup> <sub>C10, N11</sub>  (-D)-Q <sub>C12</sub>

 \* When P, R port outlets are indicated on the U side, the P, R ports on the opposite side are plugged.

**With External Pilot Specifications**



\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the U side.




| Stations n | 4 stations | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------------|
| L1         | 198        | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5       |
| L2         | 187.5      | 212.5 | 237.5 | 250   | 275   | 300   | 325         |
| L3         | 165        | 189   | 213   | 237   | 261   | 285   | 309         |
| L4         | 16.5       | 17    | 17.5  | 12    | 12.5  | 13    | 13.5        |
| L5         | 151        | 175   | 199   | 223   | 247   | 271   | 295         |



SY9000: SS5Y9-43P- Stations B  <sup>02</sup> <sub>03</sub> C8, N9 C10, N11 C12  (-D)-Q

 \* When P, R port outlets are indicated on the B side, the P, R ports on the both sides are in the open state.

## With External Pilot Specifications




\* Air discharge port on the built-in silencer type and the external pilot's extracting position are in the B side (both sides).



| Stations n | 4 stations | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 198        | 223   | 248   | 260.5 | 285.5 | 310.5 | 335.5 | 360.5 | 385.5       |
| L2         | 187.5      | 212.5 | 237.5 | 250   | 275   | 300   | 325   | 350   | 375         |
| L3         | 165        | 189   | 213   | 237   | 261   | 285   | 309   | 333   | 357         |
| L4         | 16.5       | 17    | 17.5  | 12    | 12.5  | 13    | 13.5  | 14    | 14.5        |
| L5         | 151        | 175   | 199   | 223   | 247   | 271   | 295   | 319   | 343         |


Manifold Option

■ Type 41, 42, 43  
Blanking plate assembly




| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SY3000-26-9A-Q    |
| SY5000 | SY5000-26-20A-Q   |
| SY7000 | SY7000-26-22A-Q   |
| SY9000 | SY9000-26-2A-Q    |

■ Type 41P, 42P, 43P  
Blanking plate assembly



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SY3000-26-10A-Q   |
| SY5000 | SY5000-26-21A-Q   |
| SY7000 | SY7000-26-23A-Q   |
| SY9000 | SY9000-26-4A-Q    |


■ Gasket assembly part no.



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SY3000-GS-2       |
| SY5000 | SY5000-GS-2-Q     |
| SY7000 | SY7000-GS-2-Q     |
| SY9000 | SY9000-GS-2       |

Note) Gasket assembly consists of mounting screws and a gasket.


■ Individual SUP spacer assembly



| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-38-2A-Q    | M5        | 11 |
| SY5000 | SY5000-38-16*A-Q  | 1/8       | 15 |
| SY7000 | SY7000-38-16*A-Q  | 1/4       | 18 |
| SY9000 | SY9000-38-2*A-Q   | 1/4       | 20 |

Note) • The SUP port of SY3000, 5000 and 7000 may be either on the lead wire side or on the end plate side. (An assembly is shipped under the condition shown in the figure.)  
• The end plate side is only available to SY9000.


■ Individual EXH spacer assembly



| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-39-2A-Q    | M5        | 11 |
| SY5000 | SY5000-39-16*A-Q  | 1/8       | 15 |
| SY7000 | SY7000-39-16*A-Q  | 1/4       | 18 |
| SY9000 | SY9000-39-2*A-Q   | 1/4       | 20 |

Note) In case of 41P, 42P and 43P, for protection of the wiring unit section from drainage, piping at the EA port should be arranged so that it will not be directly exposed to exhaust from the valve.

■ Individual SUP spacer assembly + Individual EXH spacer assembly (Double spacer)



●: Available ×: Not available —: Nonapplicable manifold]

| Series | Individual SUP + Individual EXP Assemble part no. | Port size | Applicable manifold types |     |    |     |    |               |     |
|--------|---|-----------|---------------------------|-----|----|-----|----|---------------|-----|
|        |   |           | 41                        | 41P | 42 | 42P | 45 | 45-A<br>45-NA | 45□ |
| SY3000 | SY3000-120-2A-Q                                   | M5        | ●                         | ×   | ●  | ×   | ●  | ×             | ×   |
| SY5000 | SY5000-75-1*A-Q                                   | 1/8       | ●                         | ×   | ●  | ×   | ●  | ×             | ×   |
| SY7000 | SY7000-73-1*A-Q                                   | 1/4       | ●                         | ×   | ●  | ×   | —  | —             | —   |

Note) The port on a spacer can be directed to the pilot valve side or end plate side. For mounting the port to the pilot valve side, please make sure to connect the ports to protect the pilot valve wiring section from drainage.  
The individual SUP spacer and EXH spacer can be mounted either on the upper side or lower side. (The above illustration shows the condition when the product is shipped out from a factory already assembled.)

⚠ Caution

Mounting screw tightening torques

M2: 0.16 N·m  
M3: 0.8 N·m  
M4: 1.4 N·m

\* Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

⚠ Warning

When mounting a valve or spacer on the manifold base or sub-plate, etc., those mounting directions are determined. If mounted in the wrong direction, the equipment to be connected may cause malfunction. Refer to external dimensions, and then mount it.

## Manifold Option

### ■ SUP blocking disk (For SY9000)

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold.



| Series | No.          |
|--------|--------------|
| SY9000 | SY9000-57-1A |

### ■ EXH blocking disk (For SY9000)

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to divide both exhausts.)




| Series | No.          |
|--------|--------------|
| SY9000 | SY9000-57-1A |

### ■ Label for block disk (For SY9000)

The labels shown below are used on manifold stations containing SUP/EXH block disk(s) to show their location. (3 pcs. each)

#### VZ3000-123-1A


Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk



Note) When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.

### ■ Silencer with One-touch fitting (For SY9000)

The silencer plugs directly into the One-touch fittings of the manifold R (exhaust) port.




| For Series   | Model      | Effective area     | A   | B  | C  |
|--------------|------------|--------------------|-----|----|----|
| SY9000 (ø12) | AN300-KM12 | 41 mm <sup>2</sup> | ø25 | 70 | 98 |

### ■ DIN Rail Dimensions/Weight for SY9000

VZ1000-11-4-□

#### Refer to L dimensions

\* Fill in □ with an appropriate no. listed on the table of DIN rail dimensions shown below.




|             |      |       |      |       |       |       |      |       |       |       |
|-------------|------|-------|------|-------|-------|-------|------|-------|-------|-------|
| No.         | 0    | 1     | 2    | 3     | 4     | 5     | 6    | 7     | 8     | 9     |
| L Dimension | 98   | 110.5 | 123  | 135.5 | 148   | 160.5 | 173  | 185.5 | 198   | 210.5 |
| Weight (g)  | 24.8 | 28    | 31.1 | 34.3  | 37.4  | 40.6  | 43.8 | 46.9  | 50.1  | 53.3  |
| No.         | 10   | 11    | 12   | 13    | 14    | 15    | 16   | 17    | 18    | 19    |
| L Dimension | 223  | 235.5 | 248  | 260.5 | 273   | 285.5 | 298  | 310.5 | 323   | 335.5 |
| Weight (g)  | 56.4 | 59.6  | 62.7 | 65.9  | 69.1  | 72.2  | 75.4 | 78.6  | 81.7  | 84.9  |
| No.         | 20   | 21    | 22   | 23    | 24    | 25    | 26   | 27    | 28    | 29    |
| L Dimension | 348  | 360.5 | 373  | 385.5 | 398   | 410.5 | 423  | 435.5 | 448   | 460.5 |
| Weight (g)  | 88   | 91.2  | 94.4 | 97.5  | 100.7 | 103.9 | 107  | 110.2 | 113.3 | 116.5 |

Note) • For DIN rail, refer to back page 10.  
• Refer to L1 dimension on pages starting with pages 106 through 108 for lengths that correspond to the number of manifold stations.

### ■ Cable assembly

AXT100-FC26- $\frac{1}{3}$



### Connector Assembly for Flat Ribbon Cables

| Cable length (L) | Ass'y part no. | Note                   |
|------------------|----------------|------------------------|
| 1.5m             | AXT100-FC26-1  | Cable 26 core x 28 AWG |
| 3m               | AXT100-FC26-2  |                        |
| 5m               | AXT100-FC26-3  |                        |


\* For other commercial connectors, use a 20 pins with strain relief conforming to MIL-C-83503.

### Connector manufacturers' example

- Hirose Electric Company
- Japan Aviation Electronics Industry, Ltd.
- Sumitomo 3M Limited
- J.S.T. Mfg. Co., Ltd.
- Fujitsu Limited

### ■ Plug (white)

These are inserted in unused cylinder ports and SUP, EXH ports. Purchasing order is available in units of 10 pieces.



### Dimensions

| Applicable fittings size ød | Model   | A    | L    | D    |
|-----------------------------|---------|------|------|------|
| 4                           | KQ2P-04 | 16   | 32   | 6    |
| 6                           | KQ2P-06 | 18   | 35   | 8    |
| 8                           | KQ2P-08 | 20.5 | 39   | 10   |
| 10                          | KQ2P-10 | 22   | 43   | 12   |
| 12                          | KQ2P-12 | 24   | 44.5 | 14   |
| 1/8"                        | KQ2P-01 | 16   | 31.5 | 5    |
| 5/32"                       | KQ2P-03 | 16   | 32   | 6    |
| 1/4"                        | KQ2P-07 | 18   | 35   | 8.5  |
| 5/16"                       | KQ2P-09 | 20.5 | 39   | 10   |
| 3/8"                        | KQ2P-11 | 22   | 43   | 11.5 |

## Manifold Option

### How to Order Interface Regulator

#### Series SY3000

**ARBY3000-05-P-2**

**Pressure gauge connection port**

|           |                            |
|-----------|----------------------------|
| <b>05</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |



Note In the case of mounting an ARBY3000 with a pressure gauge onto a manifold, use caution that the part numbers are different between the odd no. stations and the even no. stations to avoid the gauges from interfering with each other.

**Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

#### Series SY5000

**ARBY5000-00-P-2**

**Pressure gauge connection port**

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |

**Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |






**ARBY3000-05-□-2**  
(For odd number stations)

**ARBY3000-06-□-2**  
(For even number stations)

**ARBY3000-M1-□-2**

**ARBY5000-00-□-2**

**ARBY5000-M1-□-2**



#### Series SY7000

**ARBY7000-00-P-2**

**Pressure gauge connection port**



|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |

**Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

**ARBY7000-00-□-2**

**ARBY7000-M1-□-2**



### Accessory


| Series          | Round head combination screw  | Gasket      |
|-----------------|-------------------------------|-------------|
| <b>ARBY3000</b> | SY3000-23-10 (M2336)          | SX3000-57-4 |
| <b>ARBY5000</b> | M3 x 48.5, Matt nickel plated | SX5000-57-6 |
| <b>ARBY7000</b> | M4 x 57, Matt nickel plated   | SX7000-57-4 |

### Caution

Mounting screw tightening torques

- M2: 0.16 N·m
- M3: 0.8 N·m
- M4: 1.4 N·m

**Base Mounted Manifold Exploded View**




**Replacement Parts**

| No. | Description                  | No.              | Note  |
|-----|------------------------------|------------------|---|
| 1   | Manifold block assembly      | SY9000-50-2A-C8  | C8: A, B port with one-touch fitting for ø8   |
|     |                              | SY9000-50-2A-C10 | C10: A, B port with one-touch fitting for ø10   |
|     |                              | SY9000-50-2A-C12 | C12: A, B port with one-touch fitting for ø12   |
|     |                              | SY9000-50-2A-N9  | N9: A, B port with one-touch fitting for ø5/16"   |
|     |                              | SY9000-50-2A-N11 | N11: A, B port with one-touch fitting for ø3/8"   |
|     |                              | SY9000-50-2A-O2* | O2: A, B port 1/4" (* thread type)  |
|     |                              | SY9000-50-2A-O3* | O3: A, B port 3/8" (* thread type)  |
| 4   | Round head combination screw | SY9000-18-2      | M3 x 42, Matt nickel plated   |
| 5   | Gasket                       | SY9000-11-2      |   |
| 6   | Tension bolt                 | SY9000-23-□      | □ at the end of part number corresponds with the number of manifold station. Specify the same number as the number of stations.                   |
| 7   | Hexagon nut                  | SY9000-25-1      |   |
| 8   | DIN rail                     | VZ1000-11-4-□    | Refer to page 110.  |
| 9   | Wiring unit assembly         | SY9000-36-□A     | □ at the end of part number corresponds with the number of manifold station. Specify the same number as the number of stations (4 to 12 stations) |
| 10  | Connector assembly           | SY9000-37-□□     | Refer to page 104.  |
| 11  | Lead wire cover              | SY9000-41-1      |   |
| 12  | Clamp sub assembly           | SY9000-30-1A     | Included only with the DIN rail mounting type.  |

**⑪ How to assemble lead wire cover**

Lead wire cover is only usable for double solenoid valves. Lead wire is inserted into the lead wire cover as magnifying figure, then push it until it touches the valve body.



**⚠ Caution**

For type 43P (Flat cable manifold) of Series SY9000, the lead wire cover is attached for bundling the lead wires for each solenoid. In case such as adding double solenoid valve, etc., order separately lead wire cover as well.

**② SUP/EXH block assembly no. (D side mounting)**

- Direct mount type: **SY9000-70-** □ **A-** □
- DIN rail mount type: **SY9000-72-** □ **A-** □

• P, R port

|            |                             |
|------------|-----------------------------|
| <b>C12</b> | One-touch fitting for ø12   |
| <b>N11</b> | One-touch fitting for ø3/8" |
| <b>00</b>  | Plug                        |

**• Specifications**

|          |   |
|----------|---|
| <b>1</b> | Internal pilot type                     |
| <b>3</b> | External pilot type                     |
| <b>4</b> | Internal pilot / Built-in silencer type |
| <b>5</b> | External pilot / Built-in silencer type |

**③ SUP/EXH block assembly no. (U side mounting)**

- Direct mount type: **SY9000-71-** □ **A-** □
- DIN rail mount type: **SY9000-73-** □ **A-** □

• P, R port

|            |                             |
|------------|-----------------------------|
| <b>C12</b> | One-touch fitting for ø12   |
| <b>N11</b> | One-touch fitting for ø3/8" |
| <b>00</b>  | Plug                        |

**• Specifications**

|          |   |
|----------|---|
| <b>1</b> | Internal pilot type                     |
| <b>3</b> | External pilot type                     |
| <b>4</b> | Internal pilot / Built-in silencer type |
| <b>5</b> | External pilot / Built-in silencer type |

**How to Increase Manifold Bases (Series SY9000 only) Manifold case can be added at any location.**

When a type 43 manifold base is added, tension bolts as well as manifold block assembly will be required. Order the tension bolt suitable for the stations after a station was increased (decreased), since the length of a tension bolt differs by the number of stations. (For changing the number of stations for a type 43P manifold, wiring unit for the stations and lead assembly will be required.)


- 1 Loosen the tension bolts connecting the manifold base, and pull out both of 2 tension bolts.  
(When equipped with a DIN rail, loosen one DIN rail holding screw on either U side or D side.)
- 2 Separate the blocks at the location where station expansion is desired.
- 3 Mount additional manifold block assembly.
- 4 Press block-to-block so that there's no gap. After connection, insert a tension bolt for desired stations and then tighten it.  
 ⚠ **Caution** (Tightening torque: 2.9 N·m)  
 (When equipped with a DIN rail, be sure to tighten the DIN rail holding screws after tightening the tension bolts. Tightening torque: 1.4 N·m)

**⚠ Caution**

1. Be sure to shut off the power and air supplies before disassembly. Furthermore, since air may remain inside the actuator, piping and manifold, confirm that the air is completely exhausted before performing any work.
2. When disassembly and assembly are performed, air leakage may result if connections between blocks and tightening of the end block's holding screw, is inadequate.
3. By adding wiring unit assembly to type 43 manifold, it can be changed to type 43P manifold, too.

**How to Replace A, B Port Fitting Assembly**

By replacing manifold block fitting assemblies or the threaded port block assembly of a type 43(P) manifold, the port size of the A and B ports can be changed. To replace these parts, remove the clip with a flat head screwdriver after the valve has been removed. Insert the fitting assemblies or threaded port block assembly, and then reinsert the clip so that it does not protrude from the manifold block.



**Fitting Assembly Part No.**

| Port size                                | No.             | Note  |
|--|-----------------|---|
| One-touch fitting assembly for $\phi 8$  | VVQ4000-50B-C8  |   |
| One-touch fitting assembly for $\phi 10$ | VVQ4000-50B-C10 |   |
| One-touch fitting assembly for $\phi 12$ | VVQ4000-50B-C12 |   |
| One-touch fitting for $\phi 5/16$ "      | VVQ4000-50B-N9  |   |
| One-touch fitting for $\phi 3/8$ "       | VVQ4000-50B-N11 |   |
| 1/4 threaded type port block assembly    | SY9000-58A-02*  | -* at the end of part number denotes the thread type. |
| 3/8 threaded type port block assembly    | SY9000-58A-03*  | -* at the end of part number denotes the thread type. |
| Plug assembly                            | SY9000-62-1A    |   |

Note 1) Be careful to avoid damage or contamination of O-rings, as this can cause air leakage.  
 Note 2) Although replacing the One-touch fittings of P, R port is possible, use caution in the case where solenoid valves are used at the same time when using the smaller sized fittings than the standard size ( $\phi 12$ ). Because they may not be able to supply or exhaust air sufficiently in comparison to the valve performance. Also, although the fittings used for A, B port are the same as for P, R port, it is not possible to use the threaded type port block assembly.



# 5 Port Solenoid Valve Series SY3000/5000 Base Mounted Stacking Type/DIN Rail Mounted Individual Wiring

## How to Order Manifold

**SS5Y 3 - 45 - 05 U - C6 - -Q**

| Series   | Valve stations |
|----------|----------------|
| 3 SY3000 | 02 2 stations  |
| 5 SY5000 | ⋮ ⋮            |
|          | 20 20 stations |

### SUP/EXH block assembly mounting position

| Symbol | Mounting position      | Applicable no. of stations |
|--------|------------------------|----------------------------|
| U      | U side                 | 2 to 10 stations           |
| D      | D side                 |                            |
| B      | (Both sides)           | 2 to 20 stations           |
| M*     | Special specifications |                            |

\* For special specifications, indicate separately by the manifold specification sheet.

### A, B port size

#### One-touch fitting (Metric size)

| Symbol | Port size                      | Applicable series |
|--------|--------------------------------|-------------------|
| C4     | One-touch fitting for $\phi 4$ | SY3000            |
| C6     | One-touch fitting for $\phi 6$ |                   |
| M      | Mixed                          | SY5000            |
| C4     | One-touch fitting for $\phi 4$ |                   |
| C6     | One-touch fitting for $\phi 6$ |                   |
| C8     | One-touch fitting for $\phi 8$ |                   |
| M      | Mixed                          |                   |

#### One-touch fitting (Inch size)

| Symbol | Port size                           | Applicable series |
|--------|-------------------------------------|-------------------|
| N3     | One-touch fitting for $\phi 5/32$ " | SY3000            |
| N7     | One-touch fitting for $\phi 1/4$ "  |                   |
| M      | Mixed                               | SY5000            |
| N3     | One-touch fitting for $\phi 5/32$ " |                   |
| N7     | One-touch fitting for $\phi 1/4$ "  |                   |
| N9     | One-touch fitting for $\phi 5/16$ " |                   |
| M      | Mixed                               |                   |

\* In the case of mixed specifications (M), indicate separately on the manifold specification sheet.

### Option


When a longer DIN rail is desired than the specified stations, specify the station number to be required. (20 stations at maximum)



For external pilot specifications and built-in silencer, refer to page 205.

## How to Order Valve Manifold Assembly (Example)

### Example



**SS5Y3-45-05D-C6-Q** 1 set (Type 45, 5 station manifold base part no.)  
 \***SX3000-75-1A-Q** 1 set (Blanking plate assembly part no.)  
 \***SY3140-5G-Q** 2 sets (Single solenoid part no.)  
 \***SY3240-5G-Q** 2 sets (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of SUP/EXH block assembly. In ordering, specify the part nos. in the order from the 1st. station on D side. Besides, when the arrangement will be complicated, fill out the manifold specification sheet to instruct us.

## How to Order Valve

SY **5** **2** 40  **5** **L**   **-Q**

### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

### Type of actuation

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

### Coil specifications

|   |   |
|---|---|
| - | Standard                                    |
| T | With power saving circuit (24, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

### Rated voltage

#### For DC

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |
| V | 6 VDC  |
| S | 5 VDC  |
| R | 3 VDC  |

#### AC (Hz) 50/60

|   |                   |
|---|-------------------|
| 1 | 100 VAC           |
| 2 | 200 VAC           |
| 3 | 110 VAC [115 VAC] |
| 4 | 220 VAC [230 VAC] |

\* DC specifications of type D and DO is only available with 12 and 24 VDC.

\* AC specification is only available with D and DO type.

\* D and DO only available for SY5000.

### Manual override

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

### Light/surge voltage suppressor

#### Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With indicator light and surge voltage suppressor    |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |



\* Power saving circuit is only available in the "Z" type.

#### Electrical entry for D (SY5000 only)

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor (Non-polar type)       |
| Z | With light/surge voltage suppressor (Non-polar type) |



\* DOZ is not available.

\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

### Electrical entry

| 24, 12, 6, 5, 3 VDC  |  |  | 24, 12 VDC/<br>100, 110, 200,<br>220 VAC   | 24, 12, 6, 5, 3 VDC  |
|--|--|--|--|--|
| Grommet  | L plug connector   | M plug connector   | DIN terminal   | M8 connector *   |
| <b>G:</b> Lead wire length 300 mm<br><b>H:</b> Lead wire length 600 mm | <b>L:</b> With lead wire (Length 300 mm)<br><b>LN:</b> Without lead wire<br><b>LO:</b> Without connector | <b>M:</b> With lead wire (Length 300 mm)<br><b>MN:</b> Without lead wire<br><b>MO:</b> Without connector | <b>(SY5000 only)</b><br><b>D:</b> With connector<br><b>DO:</b> Without connector | <b>WO:</b> Without connector cable<br><b>W□:</b> With connector cable <sup>Note 1)</sup> |



\* LN, MN type: with 2 sockets.


\* D and DO only available for SY5000.

\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.

\* For connector cable of M8 connector, refer to back page 12.

\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.

Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.



## Manifold Specifications

|                        |  |   |   |
|------------------------|--|---|---|
| Model                  |  | <b>SS5Y3-45</b>   | <b>SS5Y5-45</b>   |
| Applicable valve       |  | <b>SY3□40</b>   | <b>SY5□40</b>   |
| Manifold type          |  | Stacking type/DIN rail mounted                                      |   |
| P (SUP)/R (EXH)        |  | Common SUP, Common EXH  |   |
| Valve stations         |  | 2 to 20 stations <sup>Note 1)</sup>                                 |   |
| A, B port              | Location                                   | Base  |   |
| Porting specifications | Direction                                  | Side  |   |
|                        | P, R port                                  | C8 (One-touch fitting for ø8)                                       | C10 (One-touch fitting for ø10)   |
| Port size              | A, B port                                  | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)      | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) |
|                        | Manifold base weight<br>W (g), n: Stations | 2 to 10 stations: W = 22n + 118<br>11 to 20 stations: W = 22n + 140 | 2 to 10 stations: W = 47n + 156<br>11 to 20 stations: W = 47n + 190                             |



Note 1) For more than 11 stations, supply pressure to P port on both sides and exhaust from R port on both sides.

## Flow Characteristics

| Model           | Port size          |              | Flow characteristics        |      |      |                |                             |      |      |                |
|-----------------|--------------------|--------------|-----------------------------|------|------|----------------|-----------------------------|------|------|----------------|
|                 | 1,5,3<br>(P,EA,EB) | 4,2<br>(A,B) | 1 → 4/2 (P → A/B)           |      |      |                | 4/2 → 5/3 (A/B → EA/EB)     |      |      |                |
|                 |                    |              | C (dm <sup>3</sup> /(sbar)) | b    | Cv   | Q(l/min(ANR))* | C (dm <sup>3</sup> /(sbar)) | b    | Cv   | Q(l/min(ANR))* |
| <b>SS5Y3-45</b> | C8                 | C6           | 0.88                        | 0.21 | 0.22 | 212            | 0.95                        | 0.18 | 0.22 | 225            |
| <b>SS5Y5-45</b> | C10                | C8           | 2.2                         | 0.24 | 0.53 | 539            | 2.5                         | 0.18 | 0.58 | 592            |




Note) The value is for manifold base with 5 stations and individually operated 2 position type.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Manifold Option

### Individual SUP spacer assembly ■ Individual EXH spacer assembly




| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-38-2A-Q    | M5        | 11 |
| SY5000 | SY5000-38-16*A-Q  | 1/8       | 15 |

Note) The SUP port may be either on the lead wire side or on the end plate side.

| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-39-2A-Q    | M5        | 11 |
| SY5000 | SY5000-39-16*A-Q  | 1/8       | 15 |

Note) The EXH port may be either on the lead wire side or on the end plate side.

### Blanking plate assembly



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SX3000-75-1A-Q    |
| SY5000 | SX5000-76-5A-Q    |

#### \* Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

### Caution

Mounting screw tightening torques


M2: 0.16 N·m  
M3: 0.8 N·m  
M4: 1.4 N·m

### Dimensions/DIN rail

VZ1000-11-1-□

#### Refer to L dimensions

\* Fill in □ with an appropriate no. listed on the table of DIN rail dimensions shown below.



|             |       |       |       |       |       |       |       |       |       |       |       |
|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| No.         | 0     | 1     | 2     | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    |
| L Dimension | 98    | 110.5 | 123   | 135.5 | 148   | 160.5 | 173   | 185.5 | 198   | 210.5 | 223   |
| No.         | 11    | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20    | 21    |
| L Dimension | 235.5 | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 323   | 335.5 | 348   | 360.5 |
| No.         | 22    | 23    | 24    | 25    | 26    | 27    | 28    | 29    | 30    | 31    | 32    |
| L Dimension | 373   | 385.5 | 398   | 410.5 | 423   | 435.5 | 448   | 460.5 | 473   | 485.5 | 498   |
| No.         | 33    | 34    | 35    | 36    | 37    | 38    | 39    | 40    | 41    | 42    | 43    |
| L Dimension | 510.5 | 523   | 535.5 | 548   | 560.5 | 573   | 585.5 | 598   | 610.5 | 623   | 635.5 |
| No.         | 44    | 45    | 46    | 47    | 48    | 49    | 50    | 51    | 52    | 53    | 54    |
| L Dimension | 648   | 660.5 | 673   | 685.5 | 698   | 710.5 | 723   | 735.5 | 748   | 760.5 | 773   |
| No.         | 55    | 56    | 57    | 58    | 59    | 60    | 61    | 62    | 63    | 64    | 65    |
| L Dimension | 785.5 | 798   | 810.5 | 823   | 835.5 | 848   | 860.5 | 873   | 885.5 | 898   | 910.5 |
| No.         | 66    | 67    | 68    | 69    | 70    | 71    |       |       |       |       |       |
| L Dimension | 923   | 935.5 | 948   | 960.5 | 973   | 985.5 |       |       |       |       |       |

\* Refer to L1 dimension on pages starting with page 121 for lengths that correspond to the number of manifold stations.

### ■ SUP blocking disk

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold.



| Series | No.          |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

### ■ EXH blocking disk

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to divide both exhausts.)






| Series | No.          |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

### ■ Label for block disk

The labels shown below are used on manifold stations containing SUP/EXH blocking disk(s) to show their location. (3 pcs. each)

#### VZ3000-123-1A


Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk



Note) When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.

### ■ Silencer with One-touch fitting


The silencer plugs directly into the One-touch fittings of the manifold.



| Series           | Model      | Effective area     | A   | B    | C    |
|------------------|------------|--------------------|-----|------|------|
| For SY3000 (ø8)  | AN203-KM8  | 14 mm <sup>2</sup> | ø16 | 26   | 51   |
|                  | AN200-KM10 | 26 mm <sup>2</sup> | ø22 | 53.8 | 80.8 |
| For SY5000 (ø10) | AN300-KM10 | 30 mm <sup>2</sup> | ø25 | 70   | 97   |

### ■ Plug (white)

These are inserted in unused cylinder ports and SUP, EXH ports. Purchasing order is available in units of 10 pieces.



### Dimensions

| Applicable fittings size øD | Model   | A    | L    | D   |
|-----------------------------|---------|------|------|-----|
| 4                           | KQ2P-04 | 16   | 32   | 6   |
| 6                           | KQ2P-06 | 18   | 35   | 8   |
| 8                           | KQ2P-08 | 20.5 | 39   | 10  |
| 10                          | KQ2P-10 | 22   | 43   | 12  |
| 1/8"                        | KQ2P-01 | 16   | 31.5 | 5   |
| 5/32"                       | KQ2P-03 | 16   | 32   | 6   |
| 1/4"                        | KQ2P-07 | 18   | 35   | 8.5 |
| 5/16"                       | KQ2P-09 | 20.5 | 39   | 10  |

**Manifold Option**

▪ How to Order Interface Regulator (SY3000, 5000 only)

**Series SY3000**

**ARBY3000-05-P-2**

• **Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

• **Pressure gauge connection port**

|           |  |
|-----------|--|
| <b>05</b> | Pressure gauge (G15-10-01) [for odd number station]  |
| <b>06</b> | Pressure gauge (G15-10-01) [for even number station] |
| <b>M1</b> | Plug (M-5P)  |

\* In the case of mounting an ARBY3000 with a pressure gauge onto a manifold, use caution that the part numbers are different between the odd no. stations and the even no. stations to avoid gauges interfering with each others.

**Series SY5000**

**ARBY5000-00-P-2**


• **Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |


• **Pressure gauge connection port**

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |


**ARBY3000-05-□-2**  
(For mounting odd number stations)




**ARBY3000-06-□-2**  
(For mounting even number stations)




**ARBY3000-M1-□-2**



**ARBY5000-00-□-2**



**ARBY5000-M1-□-2**



**Accessory**

| Series          | Round head combination screw     | Gasket      |
|-----------------|----------------------------------|-------------|
| <b>ARBY3000</b> | SY3000-23-10<br>(M2 x 36)        | SX3000-57-4 |
| <b>ARBY5000</b> | M3 x 48.5,<br>Matt nickel plated | SX5000-57-6 |

**Caution**

**Mounting screw tightening torques**

M2: 0.17 N·m  
M3: 0.8 N·m




Dimensions: Series SY3000


SS5Y3-45- Stations D- C4, N3  
C6, N7 -Q

SS5Y3-45- Stations U- C4, N3  
C6, N7 -Q

(Station n) (Station 1)




With interface regulator (with gauge)




## Dimensions: Series SY3000


### SS5Y3-45- Stations B-C4, N3-Q C6, N7




#### L plug connector




#### M plug connector



#### M8 connector (WO)



Note) Refer to back page 12 for dimensions of connector types.



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 110.5      | 123   | 135.5 | 148   | 160.5 | 173   | 185.5 | 185.5 | 198         |
| <b>L2</b>  | 100        | 112.5 | 125   | 137.5 | 150   | 162.5 | 175   | 175   | 187.5       |
| <b>L3</b>  | 87         | 97.5  | 108   | 118.5 | 129   | 139.5 | 150   | 160.5 | 171         |
| <b>L4</b>  | 11.5       | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5        |



  

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 210.5       | 223   | 235.5 | 248   | 248   | 260.5 | 273   | 285.5 | 298   | 310.5       |
| <b>L2</b>  | 200         | 212.5 | 225   | 237.5 | 237.5 | 250   | 262.5 | 275   | 287.5 | 300         |
| <b>L3</b>  | 181.5       | 192   | 202.5 | 213   | 223.5 | 234   | 244.5 | 255   | 265.5 | 276         |
| <b>L4</b>  | 14.5        | 15.5  | 16.5  | 17.5  | 12    | 13    | 14    | 15    | 16    | 17          |

**Dimensions: Series SY5000**


SS5Y5-45- Stations D- C4, N3  
C6, N7-Q  
C8, N9

SS5Y5-45- Stations U- C4, N3  
C6, N7-Q  
C8, N9



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 110.5      | 135.5 | 148   | 160.5 | 173   | 198   | 210.5 | 223   | 235.5       |
| L2         | 100        | 125   | 137.5 | 150   | 162.5 | 187.5 | 200   | 212.5 | 225         |
| L3         | 84         | 100   | 116   | 132   | 148   | 164   | 180   | 196   | 212         |
| L4         | 13         | 17.5  | 16    | 14    | 12.5  | 17    | 15    | 13.5  | 11.5        |


**With interface regulator (with gauge)**





**DIN Rail Manifold Exploded View**

Type 45



**Replacement Parts**

| No. | Description                  | No.   |   | Note  |
|-----|------------------------------|---|---|---|
|     |                              | SY3000  | SY5000  |   |
| 1   | Manifold block assembly      | SX3000-50-1A-□□-Q   | SX5000-50-1A-□□-Q   | □□: SY3000 (Metric size) C4: With one-touch fitting for $\phi 4$ (Inch size) N3: With one-touch fitting for $\phi 5/32$ "<br>SY5000 (Metric size) C6: With one-touch fitting for $\phi 6$ (Inch size) N7: With one-touch fitting for $\phi 1/4$ "<br>C4: With one-touch fitting for $\phi 4$ (Inch size) N3: With one-touch fitting for $\phi 5/32$ "<br>C6: With one-touch fitting for $\phi 6$ N7: With one-touch fitting for $\phi 1/4$ "<br>C8: With one-touch fitting for $\phi 8$ N9: With one-touch fitting for $\phi 5/16$ "<br>(Gasket 6 is supplied as an accessory.) |
| 2   | SUP/EXH block assembly       | (Metric size)<br>SX3000-51-1A<br>(Inch size)<br>SX3000-51-15A | (Metric size)<br>SX5000-51-1A<br>(Inch size)<br>SX5000-51-15A | P, R port SY3000 (Metric size) With one-touch fitting for $\phi 8$<br>(Inch size) With one-touch fitting for $\phi 5/16$ "<br>P, R port SY5000 (Metric size) With one-touch fitting for $\phi 10$<br>(Inch size) With one-touch fitting for $\phi 3/8$ "  |
| 3   | End block assembly R         | SX3000-52-1A-Q  | SX5000-52-1A-Q  | For D side  |
| 4   | End block assembly R         | SX3000-53-1A-Q  | SX5000-53-1A-Q  | For U side  |
| 5   | Round head combination screw | SY3000-23-4   | M3 x 26<br>(Matt nickel plated)                               |   |
| 6   | Gasket                       | SX3000-57-4   | SX5000-57-6   |   |
| 7   | DIN rail                     | VZ1000-11-1-□   |   | Refer to page 118.  |

## DIN Rail Manifold Exploded View

### How to Increase Manifold Bases Station expansion is possible at any position.


- 1 Loosen DIN rail holding screw (a) fixing the manifold base until it begins to turn idly. (While pressing DIN rail releasing buttons (c), at two locations, separate the manifold base from the DIN rail.)
- 2 Press manifold block assembly dividing button (b), that are at the location where manifold bases are to be added, until button (b) locks, and then separate the block assemblies.
- 3 Mount additional manifold block assembly on the DIN rail as shown in the figure 1.
- 4 Press the block assemblies until a click sound is produced, and tighten the DIN rail holding screw (a) to fix them to the DIN rail.  
**⚠ Caution** (Tightening torque: 1.4 N·m)  
 (While lightly holding the blocks after fixing an end block on one side, tighten the other end block for for better sealing.)

#### ⚠ Caution

Note 1) When there are 10 or fewer manifold block assemblies, and more are added to make a total of 11 or more, a supply/exhaust block assembly must also be added.


Note 2) When disassembly and assembly are performed, air leakage may result if connections between blocks and tightening of the end block's holding screw, is inadequate. Before supplying air, confirm that there are no gaps, etc. between blocks, and that manifold blocks are securely fastened to the DIN rail. Then supply air and confirm that there is no air leakage before operating.

Fig. (1) Block mounting procedure



Hook the DIN rail here and press down in the direction of the arrow until a click sound is heard.

### How to Change Fitting Assembly



Type 45 manifold permits change in the A and B port sizes by changing the manifold block fitting assembly. After removing the valve, remove the clip with a screwdriver, etc. For mounting a new fitting assembly, insert it and then insert a clip until it will not come out of the manifold block.

### Fitting Assembly Part No.

#### Metric size

|        |                                |                |
|--------|--------------------------------|----------------|
| SY3000 | One-touch fitting for $\phi 4$ | VVQ1000-50A-C4 |
|        | One-touch fitting for $\phi 6$ | VVQ1000-50A-C6 |
| SY5000 | One-touch fitting for $\phi 4$ | VVQ1000-51A-C4 |
|        | One-touch fitting for $\phi 6$ | VVQ1000-51A-C6 |
|        | One-touch fitting for $\phi 8$ | VVQ1000-51A-C8 |

#### Inch size

|        |                                     |                |
|--------|-------------------------------------|----------------|
| SY3000 | One-touch fitting for $\phi 5/32''$ | VVQ1000-50A-N3 |
|        | One-touch fitting for $\phi 1/4''$  | VVQ1000-50A-N7 |
| SY5000 | One-touch fitting for $\phi 5/32''$ | VVQ1000-51A-N3 |
|        | One-touch fitting for $\phi 1/4''$  | VVQ1000-51A-N7 |
|        | One-touch fitting for $\phi 5/16''$ | VVQ1000-51A-N9 |



Note 1) P and R ports cannot be changed.

Note 2) Use caution that O-rings must be free from scratches and dust. Otherwise, air leakage may result.

Type **45-A**  
NA

# 5 Port Solenoid Valve

## Series SY3000/5000

### Base Mounted

### Stacking Type/DIN Rail Mounted

# Connector Box

### How to Order Manifold

SS5Y **3** -45- **A** **U** -05 **D** -C6 -□ -Q

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Specifications**

| Symbol | Specifications                  |
|--------|---------------------------------|
| A      | With connector box (+COM spec.) |
| NA     | With connector box (-COM spec.) |

The style of attached lead wire assembly is different.

**Connector box mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**Valve stations**

| Symbol | Stations    | Note                                 |
|--------|-------------|--------------------------------------|
| 02     | 2 stations  | Applicable up to 16 solenoid valves. |
| ⋮      | ⋮           |                                      |
| 16     | 16 stations |                                      |

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Applicable stations |
|--------|------------------------|---------------------|
| U      | U side                 | 2 to 10 stations    |
| D      | D side                 |                     |
| B      | Both sides             | 2 to 16 stations    |
| M*     | Special specifications |                     |

\* For special specifications, indicate separately by the manifold specification sheet.

**A/B port size**

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size  | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY3000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| M      | Mixed  |                   |
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY5000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| N9     | One-touch fitting for ø <sup>9</sup> / <sub>32</sub> " |                   |
| M      | Mixed  |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.


**Option**

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (Max. 20 stations)

For external pilot specifications and built-in silencer, refer to page 205.

### How to Order Valve Manifold Assembly (Example)

**Example (SY3000, +COM, U side)**



- SS5Y3-45-AU-05D-C6-Q 1 set (Type 45, 5 station manifold base part no.)  
 \* SX3000-75-1A-Q 1 set (Blanking plate assembly part no.)  
 \* SY3140-5LOU-Q 2 sets (Single solenoid part no.)  
 \* SY3240-5LOU-Q 2 sets (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of connector box. In ordering, specify the part nos. in the order from the 1st. station on D side. Besides, when the arrangement will be complicated, fill out the manifold specification sheet to instruct us.

SS5Y<sup>3</sup>-45-A<sup>U</sup>-□□-C□ is assembled with solenoid valve and lead wire assembly when shipping. When ordering manifold only (without valves/wires/options), refer to how to order on page 115 and list the connector box (VZ3000-106-1A) and the rail stopper (TXE1-SMC) below the manifold to allow for the connector box mounting at U side. (Be sure to order DIN rail 3 station longer than number of the manifold stations.) In this case, please note that dimensions, L1 and L2 on pages 131 and 132 may vary slightly.) For other components, refer to page 133.

### How to Order Valve

SY **5** **2** 40 - 5 LOU □ -Q

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |


**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
|---|--------|

## Manifold Specifications



|  |   |  |   |  |
|--|---|--|---|--|
| Model                                  | <b>SS5Y3-45-A<sub>NA</sub></b>  |  | <b>SS5Y5-45-A<sub>NA</sub></b>  |  |
| Applicable valve                       | <b>SY3□40</b>   |  | <b>SY5□40</b>   |  |
| Manifold type                          | Stacking type/DIN rail mounted  |  |   |  |
| P (SUP)/R (EXH)                        | Common SUP, Common EXH  |  |   |  |
| Valve stations                         | 2 to 16 stations <sup>Note 1, 2)</sup>  |  |   |  |
| A, B port                              | Base  |  |   |  |
| Porting specifications                 | Location  | Side   |   |  |
|  | Direction   | Side   |   |  |
| Port size                              | P, R port   | C8 (One-touch fitting for ø8)                                  | C10 (One-touch fitting for ø10)   |  |
|  | A, B port   | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6) | C4 (One-touch fitting for ø4)<br>C6 (One-touch fitting for ø6)<br>C8 (One-touch fitting for ø8) |  |
| Manifold base weight W (g)             | 2 to 10 stations: W = 26n + 207<br>11 to 20 stations: W = 26n + 229                               |  | 2 to 10 stations: W = 52n + 245<br>11 to 16 stations: W = 52n + 279                             |  |
| n: Stations                            |   |  |   |  |
| Applicable flat ribbon cable connector | Flat ribbon cable connector Socket: 20 pins MIL type with strain relief conforming to MIL-C-83503 |  |   |  |
| Wiring specifications                  | +COM specifications (Type 45-A), -COM specifications (Type 45-NA)                                 |  |   |  |


Note 1) For more than 11 stations, supply pressure to P port on both sides and exhaust from R port on both sides.  
 Note 2) There is a limit depending on the number of solenoids. Refer to "How to Order".

## Flow Characteristics

| Model             | Port size              |                | Flow characteristics         |      |      |                |                              |      |      |                |
|-------------------|------------------------|----------------|------------------------------|------|------|----------------|------------------------------|------|------|----------------|
|                   | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |      |                | 4/2 → 5/3 (A/B → EA/EB)      |      |      |                |
|                   |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q(l/min(ANR))* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q(l/min(ANR))* |
| <b>SS5Y3-45-□</b> | C8                     | C6             | 0.88                         | 0.21 | 0.22 | 212            | 0.95                         | 0.18 | 0.22 | 225            |
| <b>SS5Y5-45-□</b> | C10                    | C8             | 2.2                          | 0.24 | 0.53 | 539            | 2.5                          | 0.18 | 0.58 | 592            |


Note) The value is for manifold base with 5 stations and individually operated 2 position type.  
 \* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Manifold Wiring Diagram (Circuit diagram for the reference layout)



**Manifold Option**

▪ Individual SUP spacer assembly ▪ Individual EXH spacer assembly




| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-38-2A-Q    | M5        | 11 |
| SY5000 | SY5000-38-16*A-Q  | 1/8"      | 15 |

Note) The SUP port may be either on the lead wire side or on the end plate side. (An assembly is shipped under the condition shown in the figure.)

| Series | Assembly part no. | Port size | t  |
|--------|-------------------|-----------|----|
| SY3000 | SY3000-39-2A-Q    | M5        | 11 |
| SY5000 | SY5000-39-16*A-Q  | 1/8"      | 15 |

Note) The EXH port may be either on the lead wire side or on the end plate side. (An assembly is shipped under the condition shown in the figure.)

▪ Blanking plate assembly



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SX3000-75-1A-Q    |
| SY5000 | SX5000-76-5A-Q    |

\* Thread type


|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**Caution**

Mounting screw tightening torques

M2: 0.16 N·m  
M3: 0.8 N·m  
M4: 1.4 N·m

▪ Cable assembly  
AXT100-FC20-<sup>1</sup>/<sub>3</sub>



**Connector Assembly for Flat Ribbon Cables**

| Cable length (L) | Assembly part no. | Note                   |
|------------------|-------------------|------------------------|
| 1.5 m            | AXT100-FC20-1     | Cable 20 core x 22 AWG |
| 3 m              | AXT100-FC20-2     |                        |
| 5 m              | AXT100-FC20-3     |                        |

\* For other commercial connectors, use a 20 pins with strain relief conforming to MIL-C-83503.

**Connector manufacturers' example**

- Sumitomo 3M Limited
- Fujitsu Limited
- Japan Aviation Electronics Industry, Ltd.
- J.S.T. Mfg. Co., Ltd.

**Warning**

When mounting a valve or spacer on the manifold base or sub-plate, etc., those mounting directions are determined. If mounted in the wrong direction, the equipment to be connected may cause malfunction. Refer to external dimensions, and then mount it.

▪ SUP blocking disk

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold.



| Series | Part no.     |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

▪ EXH blocking disk

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to divide both exhausts.)




| Series | Part no.     |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

▪ Label for block disk

The labels shown below are used on manifold stations containing SUP/EXH blocking disk(s) to show their location. (3 pcs. each)

VZ3000-123-1A


Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk



Note) When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.

▪ Silencer with One-touch fitting


The silencer plugs directly into the One-touch fittings of the manifold.



| Series           | Model      | Effective area     | A   | B    | C    |
|------------------|------------|--------------------|-----|------|------|
| For SY3000 (ø8)  | AN203-KM8  | 14 mm <sup>2</sup> | ø16 | 26   | 51   |
| For SY5000 (ø10) | AN200-KM10 | 26 mm <sup>2</sup> | ø22 | 53.8 | 80.8 |
|                  | AN300-KM10 | 30 mm <sup>2</sup> | ø25 | 70   | 97   |

▪ Plug (white)

These are inserted in unused cylinder ports and SUP, EXH ports. Purchasing order is available in units of 10 pieces.



**Dimensions**

| Applicable fittings size ød | Model   | A    | L    | D   |
|-----------------------------|---------|------|------|-----|
| 4                           | KQ2P-04 | 16   | 32   | 6   |
| 6                           | KQ2P-06 | 18   | 35   | 8   |
| 8                           | KQ2P-08 | 20.5 | 39   | 10  |
| 10                          | KQ2P-10 | 22   | 43   | 12  |
| 1/8"                        | KQ2P-01 | 16   | 31.5 | 5   |
| 5/32"                       | KQ2P-03 | 16   | 32   | 6   |
| 1/4"                        | KQ2P-07 | 18   | 35   | 8.5 |
| 5/16"                       | KQ2P-09 | 20.5 | 39   | 10  |

## Manifold Option

▪ How to Order Interface regulator (SY3000, 5000 only)

### Series SY3000

**ARBY3000-05-P-2**

• **Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

• **Pressure gauge connection port**

|           |  |
|-----------|--|
| <b>05</b> | Pressure gauge (G15-10-01) [for odd number station]  |
| <b>06</b> | Pressure gauge (G15-10-01) [for even number station] |
| <b>M1</b> | Plug (M-5P)  |

\* In the case of mounting an ARBY3000 with a pressure gauge onto a manifold, use caution that the part numbers are different between the odd no. stations and the even no. stations to avoid the gauges from interfering with each other.

### Series SY5000

**ARBY5000-00-P-2**

• **Regulating port**

|           |   |
|-----------|---|
| <b>P</b>  | P port  |
| <b>A1</b> | A port (P controlled type, A port regulation) |
| <b>B1</b> | B port (P controlled type, B port regulation) |

• **Pressure gauge connection port**

|           |                            |
|-----------|----------------------------|
| <b>00</b> | Pressure gauge (G15-10-01) |
| <b>M1</b> | Plug (M-5P)                |






**ARBY3000-05-□-2**  
(For odd number stations)

**ARBY3000-06-□-2**  
(For even number stations)

**ARBY3000-M1-□-2**

**ARBY5000-00-□-2**

**ARBY5000-M1-□-2**



### Accessory

| Series          | Round head combination screw     | Gasket      |
|-----------------|----------------------------------|-------------|
| <b>ARBY3000</b> | SY3000-23-10<br>(M2 x 36)        | SX3000-57-4 |
| <b>ARBY5000</b> | M3 x 48.5,<br>Matt nickel plated | SX5000-57-6 |

### ⚠ Caution


**Mounting screw tightening torques**

**M2: 0.16 N·m**


**M3: 0.8 N·m**

**Dimensions: Series SY3000**


**SS5Y3-45-AU- Stations D- C4, N3 C6, N7 -Q**



**With interface regulator (with gauge)**



**SS5Y3-45-AD- Stations U- C4, N3 C6, N7 -Q**




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    | 13    | 14    | 15    | 16 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 160.5 | 173   | 185.5 | 198   | 210.5 | 210.5 | 223   | 235.5 | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5       |
| L2         | 137.5      | 150   | 162.5 | 175   | 187.5 | 200   | 200   | 212.5 | 225   | 250   | 262.5 | 275   | 287.5 | 300   | 300         |
| L3         | 70.5       | 81    | 91.5  | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 181.5 | 192   | 202.5 | 213   | 223.5 | 234         |
| L4         | 12         | 13    | 14    | 15    | 16    | 17    | 12    | 13    | 14    | 13    | 14    | 15    | 16    | 17    | 11.5        |


\* Two SUP/EXH blocks are provided for models with 11 stations or more.

## Dimensions: Series SY5000


### SS5Y5-45-AU- Stations D- C4, N3 C6, N7 C8, N9



Applicable connector: 20 pins MIL type  
With strain relief  
(Conforming to MIL-C-83503)




### With interface regulator (with gauge)





One-touch fitting (A, B port)

Applicable tubing O.D.:  $\varnothing 4$ ,  $\varnothing 5/32$ "  
 $\varnothing 6$ ,  $\varnothing 1/4$ "  
 $\varnothing 8$ ,  $\varnothing 5/16$ "



### SS5Y5-45-AD- Stations U- C4, N3 C6, N7 C8, N9


(Station n) --- (Station 1)



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    | 11    | 12    | 13    | 14    | 15    | 16 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 160.5      | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 273   | 298   | 323   | 348   | 360.5 | 373   | 398   | 410.5       |
| L2         | 150        | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 262.5 | 287.5 | 312.5 | 337.5 | 350   | 362.5 | 387.5 | 400         |
| L3         | 84         | 100   | 116   | 132   | 148   | 164   | 180   | 196   | 212   | 246   | 262   | 278   | 294   | 310   | 326         |
| L4         | 11.5       | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5  | 12    | 16.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5        |


\* Two SUP/EXH blocks are provided for models with 11 stations or more.

Applicable connector:  
20 pins MIL type  
With strain relief  
(Conforming to MIL-C-83503)



DIN Rail Manifold Exploded View

Type 45-NA




Replacement Parts

| No. | Description                  | No.   |   | Note   |
|-----|------------------------------|---|---|--|
|     |                              | SY3000  | SY5000  |  |
| 1   | Manifold block assembly      | SX3000-50-1A-□□-Q                                       | SX5000-50-1A-□□-Q                                       | •SY3000 (Metric size) (Inch size)<br>C4: With one-touch fitting for ø4 N3: With one-touch fitting for ø5/32"<br>C6: With one-touch fitting for ø6 N7: With one-touch fitting for ø1/4"<br>For SY5000 (Metric size) (Inch size)<br>C4: With one-touch fitting for ø4 N3: With one-touch fitting for ø5/32"<br>C6: With one-touch fitting for ø6 N7: With one-touch fitting for ø1/4"<br>C8: With one-touch fitting for ø8 N9: With one-touch fitting for ø5/16"<br>(Gasket 10 is supplied as an accessory.) |
| 2   | SUP/EXH block assembly       | (Metric size) SX3000-51-1A<br>(Inch size) SX3000-51-15A | (Metric size) SX5000-51-1A<br>(Inch size) SX5000-51-15A | P, R port SY3000 (Metric size) With one-touch fitting for ø8<br>(Inch size) With one-touch fitting for ø5/16"<br>P, R port SY5000 (Metric size) With one-touch fitting for ø10<br>(Inch size) With one-touch fitting for ø3/8"   |
| 3   | End block assembly R         | SX3000-52-1A-Q  | SX5000-52-1A-Q  | For D side   |
| 4   | End block assembly L         | SX3000-53-1A-Q  | SX5000-53-1A-Q  | For U side   |
| 5   | Connector box                | VZ3000-106-1A   |   | For 24 VDC only  |
| 6   | Rail stopper                 | TXE1-SMC  |   | Made by Kasuga Electric Works  |
| 7   | Connecter assembly           | SY3000-43-1A-□  | SY3000-43-2A-□  | +COM Type D, 2 to 8 stations<br>Type U, 9 to 16 stations   |
|     |                              | SY3000-43-2A-□  | SY3000-43-3A-□  | +COM Type D, 9 to 16 stations<br>Type U, 2 to 8 stations   |
|     |                              | SY3000-43-1NA-□   | SY3000-43-2NA-□   | -COM Type D, 2 to 8 stations<br>Type U, 9 to 16 stations   |
|     |                              | SY3000-43-2NA-□   | SY3000-43-3NA-□   | -COM Type D, 9 to 16 stations<br>Type U, 2 to 8 stations   |
| 8   | Dust cap                     | VZ3000-63-2   |   |  |
| 9   | Round head combination screw | SY3000-23-4   | M3 x 26, Matt nickel plated                             |  |
| 10  | Gasket                       | SX3000-57-4   | SX5000-57-6   |  |
| 11  | DIN rail                     | VZ1000-11-1-□   |   | Refer to page 118.   |

## How to Increase Manifold Bases Station expansion is possible at any position.

- 1 Loosen DIN rail holding screw (a) fixing the manifold base until it begins to turn idly. (While pressing DIN rail releasing buttons (c), at two locations, separate the manifold base from the DIN rail.)
- 2 Press manifold block assembly dividing button (b), that are at the location where manifold bases are to be added, until button (b) locks, and then separate the block assemblies.
- 3 Mount additional manifold block assembly on the DIN rail as shown in the figure 1.
- 4 Press the block assemblies until a click sound is produced, and tighten the DIN rail holding screw (a) to fix them to the DIN rail.  
**⚠Caution** (Tightening torque: 1.4 N·m)  
 (While lightly holding the blocks after fixing an end block on one side, tighten the other end block for for better sealing.)
- 5 Untighten the rail stopper bolt (d) to demount the connector box from the DIN rail, and when remounting it, tighten the bolt while pressing it against the rail.

Fig. (1) Block mounting procedure



### ⚠Caution

- Note 1) When there are 10 or fewer manifold block assemblies, and more are added to make a total of 11 or more, a supply/exhaust block assembly must also be added.
- Note 2) When disassembly and assembly are performed, air leakage may result if connections between blocks and tightening of the end block's holding screw, is inadequate. Before supplying air, confirm that there are no gaps, etc. between blocks, and that manifold blocks are securely fastened to the DIN rail. Then supply air and confirm that there is no air leakage before operating.
- Note 3) One connector assembly is necessary for one solenoid.  
 When a number is necessary for the connector assembly mark tube, suffix the number to the part no. (0 to 15 are provided as mark tube numbers.)  
 Ex) +COM spec.: D type for 2 to 8 stations: No. 10  
**SY3000-43-1A-10**

## How to Change Fitting Assembly

Type 45 manifold permits change in the A and B port sizes by changing the manifold block fitting assembly.  
 After removing the valve, remove the clip with a screwdriver, etc. For mounting a new fitting assembly, insert it and then insert a clip until it will not come out of the manifold block.

### Fitting Assembly Part No.


#### Metric size

|        |                                |                |
|--------|--------------------------------|----------------|
| SY3000 | One-touch fitting for $\phi 4$ | VVQ1000-50A-C4 |
|        | One-touch fitting for $\phi 6$ | VVQ1000-50A-C6 |
| SY5000 | One-touch fitting for $\phi 4$ | VVQ1000-51A-C4 |
|        | One-touch fitting for $\phi 6$ | VVQ1000-51A-C6 |
|        | One-touch fitting for $\phi 8$ | VVQ1000-51A-C8 |

#### Inch size

|        |                                     |                |
|--------|-------------------------------------|----------------|
| SY3000 | One-touch fitting for $\phi 5/32$ " | VVQ1000-50A-N3 |
|        | One-touch fitting for $\phi 1/4$ "  | VVQ1000-50A-N7 |
| SY5000 | One-touch fitting for $\phi 5/32$ " | VVQ1000-51A-N3 |
|        | One-touch fitting for $\phi 1/4$ "  | VVQ1000-51A-N7 |
|        | One-touch fitting for $\phi 5/16$ " | VVQ1000-51A-N9 |

- ⦿ Note 1) P and R ports cannot be changed.  
 Note 2) Use caution that O-rings must be free from scratches and dust. Otherwise, air leakage may result.



# 5 Port Solenoid Valve

## Series SY3000/5000

### Base Mounted

### Stacking Type/DIN Rail Mounted

# Plug-in

Type 45

### How to Order Manifold

Type 45F (D-sub connector, 25 pins)

SS5Y 3-45 F D-05 U-C4 -Q

#### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

#### Common specifications

|   |                 |
|---|-----------------|
| - | Positive common |
| N | Negative common |

#### Connector mounting position

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

#### Valve stations

| Symbol | Stations    | Note   |
|--------|-------------|--|
| 02     | 2 stations  | Single wiring spec. (Applicable up to 20 solenoid valves.) |
| ⋮      | ⋮           |  |
| 20     | 20 stations |  |

- \* This also includes the number of blanking plate assemblies.
- \* Two stations are necessary for the double and 3 position solenoid valves (Dual body type).

#### SUP/EXH block assembly mounting position

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | (Both sides)           | 2 to 20 stations |
| M      | Special specifications |                  |

- \* For special specifications, indicate separately by the manifold specification

#### A, B port size

##### One-touch fitting (Metric size)

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    | SY5000            |
| C4     | One-touch fitting for ø4 |                   |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

##### One-touch fitting (Inch size)

| Symbol | Port size                                | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY3000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| M      | Mixed                                    | SY5000            |
| N3     | One-touch fitting for ø $\frac{5}{32}$ " |                   |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| N9     | One-touch fitting for ø $\frac{5}{16}$ " |                   |
| M      | Mixed                                    |                   |

- \* In the case of mixed specifications (M), indicate separately on the manifold specification sheet.

#### Voltage

|     |        |
|-----|--------|
| -   | 24 VDC |
| 12V | 12 VDC |

#### Option


When a longer DIN rail is desired than the specified stations, specify the station number to be required. (20 stations at maximum)



For external pilot specifications and built-in silencer, refer to page 208.

### How to Order Valve Manifold Assembly (Example)

#### Example (Type 45F/D-sub connector (25 pin))



SS5Y3-45FD-05U-C6-Q 1 set (Type 45F, D-sub connector 5 port manifold base part no.)  
 \* SX3000-75-2A-Q 1 set (Blanking plate assembly part no.)  
 \* SY3140-5FU-Q 2 sets (Single solenoid part no.)  
 \* SY3245-5FU-Q 1 set (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

- The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of connector box.
- When ordering double solenoid valves/3 position (Dual body type), please keep in mind that they require two manifold stations.

### How to Order Valve

(Type 45F, 45P□, 45T, 45T1)

2 position single SY 3 1 4 0 - 5 FU □ -Q

Double and 3 position SY 3 2 4 5 - 5 FU □ -Q

#### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

#### Type of actuation

|   |                            |
|---|----------------------------|
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

Dual body type (Double, 3 position)

#### Rated voltage

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |

#### Manual override

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

## How to Order Manifold

### Type 45P (Flat ribbon cable)

**SS5Y 3-45 P D-05 U-C4 -Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Common specifications**

|   |                 |
|---|-----------------|
| - | Positive common |
| N | Negative common |

**Connector poles**

| Symbol | Poles | Stations         |
|--------|-------|------------------|
| -      | 26    | 2 to 20 stations |
| G      | 20    | 2 to 16 stations |
| H      | 10    | 2 to 8 stations  |

**Connector mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**A, B port size**

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                                | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY3000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| M      | Mixed                                    |                   |
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY5000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| N9     | One-touch fitting for ø $\frac{5}{16}$ " |                   |
| M      | Mixed                                    |                   |

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | Both sides             | 2 to 20 stations |
| M      | Special specifications |                  |

**Option**  
When a longer DIN rail is desired than the specified stations, specify the station number to be required. (20 stations at maximum)

**Voltage**

|     |        |
|-----|--------|
| -   | 24 VDC |
| 12V | 12 VDC |

\* For special specifications, indicate separately on the manifold specification sheet.

Valve stations (Blanking plate assemblies are included.)

### 26 pins (P) connector

| Symbol | Stations    | Note   |
|--------|-------------|--|
| 02     | 2 stations  | Single wiring spec. (Applicable up to 20 solenoid valves.) |
| :      | :           |  |
| 20     | 20 stations |  |

### 20 pins (PG) connector

| Symbol | Stations    | Note   |
|--------|-------------|--|
| 02     | 2 stations  | Single wiring spec. (Applicable up to 16 solenoid valves.) |
| :      | :           |  |
| 16     | 16 stations |  |

### 10 pins (PH) connector

| Symbol | Stations   | Note   |
|--------|------------|--|
| 02     | 2 stations | Single wiring spec. (Applicable up to 8 solenoid valves) |
| :      | :          |  |
| 08     | 8 stations |  |

Two stations are necessary for the double, 3 position (Dual body type).

### Type 45T (9 pins terminal block)

**SS5Y 3-45T D-05 U-C4 -Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Terminal block mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**Valve stations**

| Symbol | Stations   | Note   |
|--------|------------|--|
| 02     | 2 stations | Single wiring spec. (Applicable up to 8 solenoid valves) |
| :      | :          |  |
| 08     | 8 stations |  |

\* This also includes the number of blanking plate assemblies.  
\* Two stations are necessary for the double, 3 position (Dual body type).

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Stations        |
|--------|------------------------|-----------------|
| U      | U side                 | 2 to 8 stations |
| D      | D side                 | 2 to 8 stations |
| B      | Both sides             | 2 to 8 stations |
| M      | Special specifications |                 |

**A, B port size**

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                                | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY3000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| M      | Mixed                                    |                   |
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY5000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| N9     | One-touch fitting for ø $\frac{5}{16}$ " |                   |
| M      | Mixed                                    |                   |

**Option**  
When a longer DIN rail is desired than the specified stations, specify the station number to be required.

\* For special specifications, indicate separately by the manifold specification sheet.

### Type 45T1 (18 pins terminal block)

**SS5Y 3-45T1 D-15 B-C4 -Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Terminal block mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**Valve stations**

| Symbol | Stations    | Note   |
|--------|-------------|--|
| 02     | 2 stations  | Single wiring spec. (Applicable up to 17 solenoid valves.) |
| :      | :           |  |
| 17     | 17 stations |  |

\* This also includes the number of blanking plate assemblies.  
\* Two stations are necessary for the double, 3 position (Dual body type).

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | Both sides             | 2 to 17 stations |
| M      | Special specifications |                  |

**A, B port size**

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                                | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY3000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| M      | Mixed                                    |                   |
| N3     | One-touch fitting for ø $\frac{5}{32}$ " | SY5000            |
| N7     | One-touch fitting for ø $\frac{1}{4}$ "  |                   |
| N9     | One-touch fitting for ø $\frac{5}{16}$ " |                   |
| M      | Mixed                                    |                   |

**Option**  
When a longer DIN rail is desired than the specified stations, specify the station number to be required.

\* For special specifications, indicate separately by the manifold specification sheet.

Note) The terminal block (45T) manifold has no common polarity. It can be used for both positive and negative common.

## How to Order Manifold

Type 45G (Flat cable, PC Wiring System compatible)

**SS5Y 3-45G D-05 U C4 -Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Connector mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**Valve stations**

| Symbol | Stations    | Note  |
|--------|-------------|---|
| 02     | 2 stations  | Single wiring spec.<br>(Applicable up to 16 solenoid valves.) |
| ⋮      | ⋮           |   |
| 16     | 16 stations |   |

\* Two stations are necessary for the double, 3 position (Dual body type).  
\* This also includes the number of blanking plate assemblies.

**Option**

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (20 stations at maximum)

**A, B port size**

| One-touch fitting (Metric size) |                          |                   |
|---------------------------------|--------------------------|-------------------|
| Symbol                          | Port size                | Applicable series |
| C4                              | One-touch fitting for ø4 | SY3000            |
| C6                              | One-touch fitting for ø6 |                   |
| M                               | Mixed                    |                   |
| C4                              | One-touch fitting for ø4 | SY5000            |
| C6                              | One-touch fitting for ø6 |                   |
| M                               | Mixed                    |                   |

| One-touch fitting (Inch size) |                              |                   |
|-------------------------------|------------------------------|-------------------|
| Symbol                        | Port size                    | Applicable series |
| N3                            | One-touch fitting for ø5/32" | SY3000            |
| N7                            | One-touch fitting for ø1/4"  |                   |
| M                             | Mixed                        |                   |
| N3                            | One-touch fitting for ø5/32" | SY5000            |
| N7                            | One-touch fitting for ø1/4"  |                   |
| M                             | Mixed                        |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.

**SUP/EXH block assembly specifications**

| Symbol | Specifications                     |
|--------|------------------------------------|
| -      | Internal pilot specifications      |
| R      | External pilot specifications      |
| S      | Internal pilot / Built-in silencer |
| RS     | External pilot / Built-in silencer |

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | Both sides             | 2 to 16 stations |
| M      | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification sheet.

## How to Order Valve

2 position single **SY 3 1 4 0** - 5 FU -Q

Double, 3 position **SY 3 2 4 5** - 5 FU -Q

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Dual body type (Double, 3 position)**

**Pilot type**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

**Rated voltage**



|   |        |
|---|--------|
| 5 | 24 VDC |
|---|--------|

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

## Manifold Option

Individual EXP spacer assembly    Individual SUP spacer assembly



| Series | Assembly part no. | Port no. | t  |
|--------|-------------------|----------|----|
| SY3000 | SY3000-39-3A      | M5       | 11 |
| SY5000 | SY5000-39-17*A-Q  | 1/8      | 15 |

Note) Please be careful because the dual body type (double solenoid, 3-position) requires two pieces. In this case, the exhaust is performed in the direction of the arrow mark indicated on the valve surface.

| Series | Assembly part no. | Port no. | t  |
|--------|-------------------|----------|----|
| SY3000 | SY3000-38-3A      | M5       | 11 |
| SY5000 | SY5000-38-17*A-Q  | 1/8      | 15 |


Note) Please be careful because the dual body type (double solenoid, 3-position) requires two pieces. In this case, both supply ports require the piping.

\* Thread type

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

## Manifold Specifications

| Model                                    | D-sub connector<br>Type 45F                                   | Flat ribbon cable Type 45P□  |  |  | Terminal block                   |                                   | Flat ribbon cable<br>PC wiring system compatible<br>Type 45G   |
|--|---|--|--|--|----------------------------------|-----------------------------------|--|
|  |   | Type 45P   | Type 45PG  | Type 45PH  | Type 45T                         | Type 45T1                         |  |
| Manifold                                 | Plug-in   |  |  |  |                                  |                                   |  |
| P (SUP)/R (EXH)                          | Common SUP, Common EXH  |  |  |  |                                  |                                   |  |
| Valve stations <small>Note 1, 2)</small> | 2 to 20 stations  | 2 to 16 stations   | 2 to 8 stations  | 2 to 17 stations   | 2 to 16 stations                 |                                   |  |
| A, B port                                | Location  | Base   |  |  |                                  |                                   |  |
| Porting specifications                   | Direction   | Side   |  |  |                                  |                                   |  |
| Port size                                | P, R port   | C8 (One-touch fitting for ø8)  |  |  |                                  |                                   |  |
|  |   | SY3000 C10 (One-touch fitting for ø10)   |  |  |                                  |                                   |  |
|  | A, B port   | SY3000 C4 (One-touch fitting for ø4)/C6 (One-touch fitting for ø6)   |  |  |                                  |                                   |  |
|  |   | SY5000 C4 (One-touch fitting for ø4)/C6 (One-touch fitting for ø6)/C8 (One-touch fitting for ø8)           |  |  |                                  |                                   |  |
| Applicable connector                     | D-sub connector<br>Complies with<br>MIL-C-24308<br>JIS-X-5101 | Flat ribbon cable connector<br>Socket: 26 pins MIL type<br>with strain relief<br>Conforming to MIL-C-83503 | Flat ribbon cable connector<br>Socket: 20 pins MIL type<br>with strain relief<br>Conforming to MIL-C-83503 | Flat ribbon cable connector<br>Socket: 10 pins MIL type<br>with strain relief<br>Conforming to MIL-C-83503 | Terminal block<br>(M3)<br>9 pins | Terminal block<br>(M3)<br>18 pins | Flat ribbon cable connector<br>Socket: 20 pins MIL type<br>with strain relief<br>Conforming to MIL-C-83503 |
| Internal wiring                          | +COM (Type 45□), -COM (Type 45N□)                             |  |  |  | In common between +COM and -COM. |                                   | + COM  |
| Manifold base weight w (g)               | SY3000  | 2 to 10 stations: W = 26n + 172  |  |  |                                  |                                   |  |
| n: Stations<br>(D-sub connector)         |   | 11 to 20 stations: W = 26n + 199   |  |  |                                  |                                   |  |
|  | SY5000  | 2 to 10 stations: W = 54n + 227  |  |  |                                  |                                   |  |
|  |   | 11 to 20 stations: W = 52n + 264   |  |  |                                  |                                   |  |



Note 1) For more than 11 stations, supply pressure to P port on both sides and exhaust from R port on both sides.  
Note 2) There is a limit depending on the number of solenoids. Refer to "How to Order".


## Flow Characteristics

| Model     | Port size              |                | Flow characteristics         |      |      |                 |                              |      |      |                 |
|-----------|------------------------|----------------|------------------------------|------|------|-----------------|------------------------------|------|------|-----------------|
|           | 1, 5, 3<br>(P, EA, EB) | 4, 2<br>(A, B) | 1 → 4/2 (P → A/B)            |      |      |                 | 4/2 → 5/3 (A/B → EA/EB)      |      |      |                 |
|           |                        |                | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b    | Cv   | Q [l/min(ANR)]* |
| SS5Y3-45□ | C8                     | C6             | 0.88                         | 0.21 | 0.22 | 212             | 0.95                         | 0.18 | 0.22 | 225             |
| SS5Y5-45□ | C10                    | C8             | 2.2                          | 0.24 | 0.53 | 539             | 2.5                          | 0.18 | 0.58 | 592             |

Note) The value is for manifold base with 5 stations and individually operated 2 position type.  
\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Manifold Option

### Blanking plate assembly



| Series | Assembly part no. |
|--------|-------------------|
| SY3000 | SX3000-75-2A-Q    |
| SY5000 | SX5000-76-2A-Q    |

Note) • When mounting blanking plate, be sure to mount a short cap.  
• Two stations are necessary for the double, 3 position (Dual body type).

### SUP blocking disk

By installing a SUP blocking disk in the pressure supply passage of a manifold valve, it is possible to supply two or more different high and low pressures to one manifold.



| Series | No.          |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

### EXH blocking disk

By installing an EXH blocking disk in the exhaust passage of a manifold valve, it is possible to divide the valve's exhaust so that it does not affect another valve. (Two blocking disks are needed to divide both exhausts.)





| Series | No.          |
|--------|--------------|
| SY3000 | SX3000-77-1A |
| SY5000 | SX5000-77-1A |

### Label for block disk

The labels shown below are used on manifold stations containing SUP/EXH block disk(s) to show their location. (3 pcs. each)  
**VZ3000-123-1A** (In common with SY3000, 5000)


Label for SUP block disk    Label for EXH block disk    Label for SUP/EXH block disk



Note) When a block disk is concurrently ordered by specifying on the manifold specification sheet, etc., a label will be stuck on the position where block disk is mounted.

### Silencer with One-touch fi


The silencer plugs directly into the C touch fittings of the manifold.



| Series           | Model      | Effective area     | A   | B    | C    |
|------------------|------------|--------------------|-----|------|------|
| For SY3000 (ø8)  | AN203-KM8  | 14 mm <sup>2</sup> | ø16 | 26   | 51   |
|                  | AN200-KM10 | 26 mm <sup>2</sup> | ø22 | 53.8 | 80.8 |
| For SY5000 (ø10) | AN300-KM10 | 30 mm <sup>2</sup> | ø25 | 70   | 97   |

### Plug (white)

These are inserted in unused cylinder ports and SUP, EXH ports. Purchasing order is available in units of 10 pieces.



## Dimensions

| Applicable fittings size ød | Model   | A    | L    | D   |
|-----------------------------|---------|------|------|-----|
| 4                           | KQ2P-04 | 16   | 32   | 6   |
| 6                           | KQ2P-06 | 18   | 35   | 8   |
| 8                           | KQ2P-08 | 20.5 | 39   | 10  |
| 10                          | KQ2P-10 | 22   | 43   | 12  |
| 1/8"                        | KQ2P-01 | 16   | 31.5 | 5   |
| 5/32"                       | KQ2P-03 | 16   | 32   | 6   |
| 1/4"                        | KQ2P-07 | 18   | 35   | 8.5 |
| 5/16"                       | KQ2P-09 | 20.5 | 39   | 10  |

## Caution

### Mounting screw tightening torques



M2: 0.17 N·m  
M3: 0.8 N·m  
M4: 1.4 N·m

**Manifold Option**

▪ **D-sub connector (25 pins)/Cable assembly**

GVVZS3000-21A-<sup>1</sup>/<sub>2</sub>-<sup>2</sup>/<sub>3</sub>-<sup>3</sup>/<sub>4</sub>-<sup>4</sup>/<sub>5</sub>S-60

(The D-sub connector cable ass'y can be ordered individually or included in a specific manifold model no. Refer to "How to Order Manifold".)



D-sub connector cable ass'y

| Cable length (L) | Ass'y No.         |
|------------------|-------------------|
| 1m*              | GVVZS3000-21A-1-□ |
| 3m               | GVVZS3000-21A-2-□ |
| 5m               | GVVZS3000-21A-3-□ |
| 8m               | GVVZS3000-21A-4-□ |
| 20m              | GVVZS3000-21A-5S  |

\* Standard type is not available for the cable length of 1m.

| Model | Shielded cable | 60° connector | Standard |
|-------|----------------|---------------|----------|
| Model | S              | 60            | -        |

**Electric characteristics**

| Item                            | Characteristics |
|---------------------------------|-----------------|
| Conductor resistance Ω/km, 20°C | 57 or less      |
| Voltage limit V, 5min, AC       | 1500            |
| Insulation resistance MΩ/km     | 20              |


Wire color table by terminal number of D-sub connector cable assembly

| Terminal No. | Lead wire colour | Dot marking |
|--------------|------------------|-------------|
| 1            | White            | -           |
| 2            | Brown            | -           |
| 3            | Green            | -           |
| 4            | Yellow           | -           |
| 5            | Grey             | -           |
| 6            | Pink             | -           |
| 7            | Blue             | -           |
| 8            | Red              | -           |
| 9            | Black            | -           |
| 10           | Violet           | -           |
| 11           | Grey             | Pink        |
| 12           | Red              | Blue        |
| 13           | White            | Green       |
| 14           | Brown            | Green       |
| 15           | White            | Yellow      |
| 16           | Yellow           | Brown       |
| 17           | White            | Grey        |
| 18           | Grey             | Brown       |
| 19           | White            | Pink        |
| 20           | Pink             | Brown       |
| 21           | White            | Blue        |
| 22           | Brown            | Blue        |
| 23           | White            | Red         |
| 24           | Brown            | Red         |
| 25           | White            | Black       |

\* Connector made in conformity with DIN47100.

▪ **Flat Ribbon Cable Connector/Cable assembly**

AXT100-FC-<sup>1</sup>/<sub>3</sub>



**Flat Ribbon Cable Assembly**

| Cable length (L)    | 10 pins       | 20 pins       | 26 pins       |
|---------------------|---------------|---------------|---------------|
| 1.5 m               | AXT100-FC10-1 | AXT100-FC20-1 | AXT100-FC26-1 |
| 3 m                 | AXT100-FC10-2 | AXT100-FC20-2 | AXT100-FC26-2 |
| 5 m                 | AXT100-FC10-3 | AXT100-FC20-3 | AXT100-FC26-3 |
| Connector width (W) | 17.2          | 30            | 37.5          |

\* For other commercial connectors, use a type with strain relief that conform to MIL-C-83503.

**Connector manufacturers' example**


- Hirose Electric Co., Ltd.
- Sumitomo 3M Limited
- Fujitsu Limited
- Japan Aviation Electronics Industry, Ltd.
- J.S.T. Mfg. Co., Ltd.

▪ **Dimensions/DIN rail**

VZ100-11-1-□

Refer to L dimensions

\* Fill in □ with an appropriate no. listed on the table of DIN rail dimensions shown below.




| No.         | 0     | 1     | 2     | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10    |
|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| L Dimension | 98    | 110.5 | 123   | 135.5 | 148   | 160.5 | 173   | 185.5 | 198   | 210.5 | 223   |
| No.         | 11    | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20    | 21    |
| L Dimension | 235.5 | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 323   | 335.5 | 348   | 360.5 |
| No.         | 22    | 23    | 24    | 25    | 26    | 27    | 28    | 29    | 30    | 31    | 32    |
| L Dimension | 373   | 385.5 | 398   | 410.5 | 423   | 435.5 | 448   | 460.5 | 473   | 485.5 | 498   |
| No.         | 33    | 34    | 35    | 36    | 37    | 38    | 39    | 40    | 41    | 42    | 43    |
| L Dimension | 510.5 | 523   | 535.5 | 548   | 560.5 | 573   | 585.5 | 598   | 610.5 | 623   | 635.5 |
| No.         | 44    | 45    | 46    | 47    | 48    | 49    | 50    | 51    | 52    | 53    | 54    |
| L Dimension | 648   | 660.5 | 673   | 685.5 | 698   | 710.5 | 723   | 735.5 | 748   | 760.5 | 773   |
| No.         | 55    | 56    | 57    | 58    | 59    | 60    | 61    | 62    | 63    | 64    | 65    |
| L Dimension | 785.5 | 798   | 810.5 | 823   | 835.5 | 848   | 860.5 | 873   | 885.5 | 898   | 910.5 |
| No.         | 66    | 67    | 68    | 69    | 70    | 71    |       |       |       |       |       |
| L Dimension | 923   | 935.5 | 948   | 960.5 | 973   | 985.5 |       |       |       |       |       |

\* Refer to L1 dimension on pages starting with page 145 for lengths that correspond to the number of manifold stations.


## Manifold Internal Wiring

### 45(N)F/D-sub Connector


A D-sub connector used for electric wiring reduces labor during wiring operation. Connectors conforming to MIL are used for interchangeability.



#### <For positive common (45F)>




#### <For negative common (45NF)>




- The power source terminal is used for connecting to an external power source.
- The maximum number of stations that can be accommodated is 20 manifold stations, with up to 20 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.

### Type 45(N)P/Flat Ribbon Cable (26 pins)


A flat cable connector used for electric wiring reduces labor during wiring operation. Connectors conforming to MIL are used for interchangeability.




#### <For positive common (45P)>



#### <For negative common (45NP)>






- The power source terminal is used for connecting to an external power source.
- The maximum number of stations that can be accommodated is 20 manifold stations, with up to 20 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.



## Manifold Internal Wiring

### Type 45(N)PG/Flat Ribbon Cable (20 pins)




A flat cable connector used for electric wiring reduces labor during wiring operation. Connectors conforming to MIL are used for interchangeability.



- The power source terminal is used for connecting to an external power source.
- The maximum number of stations that can be accommodated is 16 manifold stations, with up to 16 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.

### Type 45(N)PH/Flat Ribbon Cable (10 pins)

A flat cable connector used for electric wiring reduces labor during wiring operation. Connectors conforming to MIL are used for interchangeability.





- The power source terminal is used for connecting to an external power source.
- The maximum number of stations that can be accommodated is 8 manifold stations, with up to 8 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.

## Manifold Internal Wiring



### Type 45T/Terminal Block

A terminal block style permits direct cable connection without treatment of lead wires.



- The maximum number of stations that can be accommodated is 8 manifold stations, with up to 8 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.
- There is no polarity in the COM wiring. Supply positive power for +COM spec. and negative power for -COM spec.

### Type 45T1/Terminal Block




- The maximum number of stations that can be accommodated is 17 manifold stations, with up to 17 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.
- There is no polarity in the COM wiring. Supply positive power for +COM spec. and negative power for -COM spec.


## Manifold Internal Wiring

### Type 45G Flat Ribbon Cable (PC Wiring System compatible)

It's the manifold for 20 pins flat ribbon cable connector which is compliant for PC wiring system.



Electric circuit diagram  
(Below wiring is the case of all double solenoid connections.)




- The maximum number of stations that can be accommodated is 16 manifold stations, with up to 16 solenoids. (For more stations, please contact SMC.)
- Regardless of the connector mounting position, stations are to be counted from D side as the 1st one.

( For details about the PC wiring system, refer to )  
catalogue CAT.ES02-20 separately.


## How to Connect SS5Y□-45□ (Plug-in)

Power terminal is equipped with plug-in manifold of Series SY as standard.  
Power terminal enables the power supply to valve from either of manifold or controller side.

### 1. Wiring example when using manifold power supply terminals



### 2. Wiring example when not using manifold power supply terminals (Power is supplied to the controller side or along the wiring, etc.)




### ⚠ Caution

- Single wire, COM position, etc. of PLC are different from each manufacturer. When connecting with PLC, read the specifications carefully and understand the electrical circuit. Poor wiring could cause damage to PLC, power source, etc. as well as manifold and valve.


**SY3000: D-sub Connector/Plug-in**

**SS5Y3-45FU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q**  
C<sub>6</sub>, N<sub>7</sub>

(Station n) --- (Station 1)  
(Light/surge voltage suppressor)




Equivalent to the applicable D-sub connector (JIS-X-5101, MIL-C-24308)




Note) The L1 to L4 dimensions of **SS5Y3-45FU- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q** are identical to those of **SS5Y3-45FU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| <b>L2</b>  | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |



**SS5Y3-45FU- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q**  
C<sub>6</sub>, N<sub>7</sub>


Equivalent to the applicable D-sub connector (JIS-X-5101, MIL-C-24308)



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| <b>L2</b>  | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| <b>L4</b>  | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 235.5       | 248   | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5 | 323         |
| <b>L2</b>  | 225         | 237.5 | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300   | 312.5       |
| <b>L3</b>  | 202.5       | 213   | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5 | 297         |
| <b>L4</b>  | 16.5        | 17.5  | 12    | 13    | 14    | 15    | 16    | 17    | 12    | 13          |




**SY3000: D-sub Connector/Plug-in**

**SS5Y3-45FD- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q**  
C<sub>6</sub>, N<sub>7</sub>



Note) The L1 to L4 dimensions of **SS5Y3-45FD- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q** are identical to those of **SS5Y3-45FD- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q**.


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| <b>L2</b>  | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |



**SS5Y3-45FD- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q**  
C<sub>6</sub>, N<sub>7</sub>


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| <b>L2</b>  | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| <b>L4</b>  | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 235.5       | 248   | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5 | 323         |
| <b>L2</b>  | 225         | 237.5 | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300   | 312.5       |
| <b>L3</b>  | 202.5       | 213   | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5 | 297         |
| <b>L4</b>  | 16.5        | 17.5  | 12    | 13    | 14    | 15    | 16    | 17    | 12    | 13          |




**SY5000: D-sub Connector/Plug-in**

**SS5Y5-45FU- Stations D-<sup>C4, N3</sup>  
C6, N7 -Q  
C8, N9**




Equivalent to the applicable D-sub connector (JIS-X-5101, MIL-C-24308)




Note) The L1 to L4 dimensions of SS5Y5-45FU- Stations U-<sup>C4, N3</sup>  
C6, N7 -Q are identical to those of SS5Y5-45FU- Stations D-<sup>C4, N3</sup>  
C6, N7 -Q.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| L2         | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| L3         | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| L4         | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |




**SS5Y5-45FU- Stations B-<sup>C4, N3</sup>  
C6, N7 -Q  
C8, N9**

Equivalent to the applicable D-sub connector (JIS-X-5101, MIL-C-24308)



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| L2         | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| L3         | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| L4         | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 298         | 310.5 | 323   | 348   | 360.5 | 373   | 398   | 410.5 | 423   | 435.5       |
| L2         | 287.5       | 300   | 312.5 | 337.5 | 350   | 362.5 | 387.5 | 400   | 412.5 | 425         |
| L3         | 267         | 283   | 299   | 315   | 331   | 347   | 363   | 379   | 395   | 411         |
| L4         | 15.5        | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |




## SY5000: D-sub Connector/Plug-in

**SS5Y5-45FD- [Stations] U-** <sup>C4, N3</sup>  
<sup>C6, N7 -Q</sup>  
<sup>C8, N9</sup>



Note) The L1 to L4 dimensions of **SS5Y5-45FD-**  
**[Stations] D-** <sup>C4, N3</sup>  
<sup>C6, N7 -Q</sup> are identical to those of  
**SS5Y5-45FD- [Stations] U-** <sup>C4, N3</sup>  
<sup>C6, N7 -Q</sup>, <sup>C8, N9</sup>

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| <b>L2</b>  | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| <b>L4</b>  | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |




**SS5Y5-45FD- [Stations] B-** <sup>C4, N3</sup>  
<sup>C6, N7 -Q</sup>  
<sup>C8, N9</sup>

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| <b>L2</b>  | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| <b>L4</b>  | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 298         | 310.5 | 323   | 348   | 360.5 | 373   | 398   | 410.5 | 423   | 435.5       |
| <b>L2</b>  | 287.5       | 300   | 312.5 | 337.5 | 350   | 362.5 | 387.5 | 400   | 412.5 | 425         |
| <b>L3</b>  | 267         | 283   | 299   | 315   | 331   | 347   | 363   | 379   | 395   | 411         |
| <b>L4</b>  | 15.5        | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |




**SY3000: Flat Ribbon Cable/Plug-in**



**SS5Y3-45PU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q (26 pins)**



Note) The L1 to L4 dimensions of SS5Y3-45P□U- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q are identical to those of SS5Y3-45PIU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q.



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| L2         | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| L3         | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| L4         | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |




**SS5Y3-45PU- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q (26 pins)**

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| L2         | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| L3         | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| L4         | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |


  

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 235.5       | 248   | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5 | 323         |
| L2         | 225         | 237.5 | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300   | 312.5       |
| L3         | 202.5       | 213   | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5 | 297         |
| L4         | 16.5        | 17.5  | 12    | 13    | 14    | 15    | 16    | 17    | 12    | 13          |



## SY3000: Flat Ribbon Cable/Plug-in


### SS5Y3-45PD- Stations U-C<sub>4</sub>,N<sub>3</sub>-Q (26 pins) C<sub>6</sub>,N<sub>7</sub>-Q



Note) The L1 to L4 dimensions of **SS5Y3-45P□D-**  
**Stations D-C<sub>4</sub>,N<sub>3</sub>-Q** are identical to those of  
**SS5Y3-45P□D- Stations U-C<sub>4</sub>,N<sub>3</sub>-Q.**

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| <b>L2</b>  | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |

### SS5Y3-45PD- Stations B-C<sub>4</sub>,N<sub>3</sub>-Q (26 pins) C<sub>6</sub>,N<sub>7</sub>-Q



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| <b>L2</b>  | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| <b>L4</b>  | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |



| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 235.5       | 248   | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5 | 323         |
| <b>L2</b>  | 225         | 237.5 | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300   | 312.5       |
| <b>L3</b>  | 202.5       | 213   | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5 | 297         |
| <b>L4</b>  | 16.5        | 17.5  | 12    | 13    | 14    | 15    | 16    | 17    | 12    | 13          |

**SY5000: Flat Ribbon Cable/Plug-in**


**SS5Y5-45PU- Stations D-C<sub>6</sub>, N<sub>3</sub>-Q (26 pins)**



Note) The L1 to L4 dimensions of SS5Y5-45P□U- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q are identical to those of SS5Y5-45P□U- Stations D-C<sub>6</sub>, N<sub>3</sub>-Q.




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| L2         | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| L3         | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| L4         | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |



**SS5Y5-45PU- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q (26 pins)**

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| L2         | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| L3         | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| L4         | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 298         | 310.5 | 323   | 348   | 360.5 | 373   | 398   | 410.5 | 423   | 435.5       |
| L2         | 287.5       | 300   | 312.5 | 337.5 | 350   | 362.5 | 387.5 | 400   | 412.5 | 425         |
| L3         | 267         | 283   | 299   | 315   | 331   | 347   | 363   | 379   | 395   | 411         |
| L4         | 15.5        | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |




## SY5000: Flat Ribbon Cable/Plug-in


### SS5Y5-45PD- Stations U-C<sub>4, N3</sub>, N7-Q (26 pins) C<sub>8, N9</sub>




Note) The L1 to L4 dimensions of SS5Y5-45PD- Stations D-C<sub>4, N3</sub>, N7-Q are identical to those of SS5Y3-45PD- Stations U-C<sub>4, N3</sub>, N7-Q.



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| L2         | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| L3         | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| L4         | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |




### SS5Y5-45PD- Stations B-C<sub>4, N3</sub>, N7-Q (26 pins) C<sub>8, N9</sub>



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| L2         | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| L3         | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| L4         | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |


| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16    | 17    | 18    | 19    | 20 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 298         | 310.5 | 323   | 348   | 360.5 | 373   | 398   | 410.5 | 423   | 435.5       |
| L2         | 287.5       | 300   | 312.5 | 337.5 | 350   | 362.5 | 387.5 | 400   | 412.5 | 425         |
| L3         | 267         | 283   | 299   | 315   | 331   | 347   | 363   | 379   | 395   | 411         |
| L4         | 15.5        | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |



**SY3000: 9 Pins Terminal Block/Plug-in**

**SS5Y3-45TU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q (9 pins)**


(Light/surge voltage suppressor) (Station n) --- (Station 1)



Note) The L1 to L4 dimensions of **SS5Y3-45TU- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q, SS5Y3-45TD- Stations U-C<sub>4</sub>, N<sub>3</sub>-Q**, **SS5Y3-45TD- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q** are identical those of **SS5Y3-45TU- Stations D-C<sub>4</sub>, N<sub>3</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|------------|------------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5      |
| <b>L2</b>  | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175        |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5      |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5       |

**SS5Y3-45TU- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q (9 pins)**




Note) The L1 to L4 dimensions of **SS5Y3-45TD- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q** are identical to those of **SS5Y3-45TU- Stations B-C<sub>4</sub>, N<sub>3</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|------------|------------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198        |
| <b>L2</b>  | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5      |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171        |
| <b>L4</b>  | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5       |


## SY5000: 9 Pins Terminal Block/Plug-in

**SS5Y5-45TU- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (9 pins)**




Note) The L1 to L4 dimensions of **SS5Y5-45TU-<sup>C4, N3</sup><sub>C6, N7</sub>-Q, SS5Y5-45TD-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of SS5Y5-45TU-<sup>C4, N3</sup><sub>C6, N7</sub>-Q.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|------------|------------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5      |
| <b>L2</b>  | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225        |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201        |
| <b>L4</b>  | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17         |



**SS5Y5-45TU- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (9 pins)**




Note) The L1 to L4 dimensions of **SS5Y5-45TD-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of SS5Y5-45TU-<sup>C4, N3</sup><sub>C6, N7</sub>-Q.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8 stations |
|------------|------------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248        |
| <b>L2</b>  | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5      |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219        |
| <b>L4</b>  | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5       |

**SY3000: 18 Pins Terminal Block/Plug-in**


**SS5Y3-45T1U- [Stations] D-<sup>C4, N3</sup><sub>C6, N7</sub> -Q (18 pins)**



Note) The L1 to L4 dimensions of **SS5Y3-45T1U- [Stations] U-<sup>C4, N3</sup><sub>C6, N7</sub> -Q** are identical to those of **SS5Y3-45T1U- [Stations] D-<sup>C4, N3</sup><sub>C6, N7</sub> -Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 148   | 160.5 | 173   | 185.5 | 198   | 210.5 | 210.5 | 223         |
| <b>L2</b>  | 137.5      | 137.5 | 150   | 162.5 | 175   | 187.5 | 200   | 200   | 212.5       |
| <b>L3</b>  | 112.5      | 123   | 133.5 | 144   | 154.5 | 165   | 175.5 | 186   | 196.5       |
| <b>L4</b>  | 17.5       | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5  | 12    | 13          |

**SS5Y3-45T1U- [Stations] B-<sup>C4, N3</sup><sub>C6, N7</sub> -Q (18 pins)**




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 185.5 | 198   | 210.5 | 223   | 235.5      |
| <b>L2</b>  | 150        | 162.5 | 175   | 175   | 187.5 | 200   | 212.5 | 225        |
| <b>L3</b>  | 129        | 139.5 | 150   | 160.5 | 171   | 181.5 | 192   | 202.5      |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5       |

| Stations n | 10 stations | 11    | 12    | 13    | 14    | 15    | 16    | 17 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 248         | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5       |
| <b>L2</b>  | 237.5       | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300         |
| <b>L3</b>  | 213         | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5       |
| <b>L4</b>  | 17.5        | 12    | 13    | 14    | 15    | 16    | 17    | 12          |

## SY3000: 9 Pins Terminal Block/Plug-in


### SS5Y3-45T1D-Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins)



Note) The L1 to L4 dimensions of **SS5Y3-45T1D-Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of **SS5Y3-45T1D-Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 148   | 160.5 | 173   | 185.5 | 198   | 210.5 | 210.5 | 223         |
| <b>L2</b>  | 137.5      | 137.5 | 150   | 162.5 | 175   | 187.5 | 200   | 200   | 212.5       |
| <b>L3</b>  | 112.5      | 123   | 133.5 | 144   | 154.5 | 165   | 175.5 | 186   | 196.5       |
| <b>L4</b>  | 17.5       | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5  | 12    | 13          |

### SS5Y3-45T1D-Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins)




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 185.5 | 198   | 210.5 | 223   | 235.5      |
| <b>L2</b>  | 150        | 162.5 | 175   | 175   | 187.5 | 200   | 212.5 | 225        |
| <b>L3</b>  | 129        | 139.5 | 150   | 160.5 | 171   | 181.5 | 192   | 202.5      |
| <b>L4</b>  | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5       |

| Stations n | 10 stations | 11    | 12    | 13    | 14    | 15    | 16    | 17 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 248         | 248   | 260.5 | 273   | 285.5 | 298   | 310.5 | 310.5       |
| <b>L2</b>  | 237.5       | 237.5 | 250   | 262.5 | 275   | 287.5 | 300   | 300         |
| <b>L3</b>  | 213         | 223.5 | 234   | 244.5 | 255   | 265.5 | 276   | 286.5       |
| <b>L4</b>  | 17.5        | 12    | 13    | 14    | 15    | 16    | 17    | 12          |

**SY5000: 18 Pins Terminal Block/Plug-in**


**SS5Y5-45T1U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins)**

<sup>C4, N3</sup>  
<sub>C6, N7</sub>




Note) The L1 to L4 dimensions of **SS5Y5-45T1U- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of **SS5Y5-45T1U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 198   | 223   | 235.5 | 248   | 273   | 285.5       |
| <b>L2</b>  | 150        | 162.5 | 175   | 187.5 | 212.5 | 225   | 237.5 | 262.5 | 275         |
| <b>L3</b>  | 126        | 142   | 158   | 174   | 190   | 206   | 222   | 238   | 254         |
| <b>L4</b>  | 17         | 15.5  | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5        |



**SS5Y5-45T1U- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins)**


<sup>C4, N3</sup>  
<sub>C6, N7</sub>



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|------------|
| <b>L1</b>  | 173        | 185.5 | 210.5 | 223   | 235.5 | 248   | 273   | 285.5      |
| <b>L2</b>  | 162.5      | 175   | 200   | 212.5 | 225   | 237.5 | 262.5 | 275        |
| <b>L3</b>  | 144        | 160   | 176   | 192   | 208   | 224   | 240   | 256        |
| <b>L4</b>  | 14.5       | 12.5  | 17    | 15.5  | 13.5  | 12    | 16.5  | 14.5       |



  

| Stations n | 10 stations | 11    | 12    | 13    | 14    | 15    | 16    | 17 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 298         | 323   | 335.5 | 348   | 360.5 | 385.5 | 398   | 410.5       |
| <b>L2</b>  | 287.5       | 312.5 | 325   | 337.5 | 350   | 375   | 387.5 | 400         |
| <b>L3</b>  | 272         | 288   | 304   | 320   | 336   | 352   | 368   | 384         |
| <b>L4</b>  | 13          | 17.5  | 15.5  | 14    | 12    | 16.5  | 15    | 13          |



## SY5000: 18 Pins Terminal Block/Plug-in


### SS5Y5-45T1D- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins) <sub>C8, N9</sub>




Note) The L1 to L4 dimensions of SS5Y5-45T1D-

Stations D-<sup>C4, N3</sup><sub>C6, N7</sub> are identical to those of  
SS5Y5-45T1D- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 160.5      | 173   | 185.5 | 198   | 223   | 235.5 | 248   | 273   | 285.5       |
| L2         | 150        | 162.5 | 175   | 187.5 | 212.5 | 225   | 237.5 | 262.5 | 275         |
| L3         | 126        | 142   | 158   | 174   | 190   | 206   | 222   | 238   | 254         |
| L4         | 17         | 15.5  | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5        |




### SS5Y5-45T1D- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (18 pins) <sub>C8, N9</sub>




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|------------|
| L1         | 173        | 185.5 | 210.5 | 223   | 235.5 | 248   | 273   | 285.5      |
| L2         | 162.5      | 175   | 200   | 212.5 | 225   | 237.5 | 262.5 | 275        |
| L3         | 144        | 160   | 176   | 192   | 208   | 224   | 240   | 256        |
| L4         | 14.5       | 12.5  | 17    | 15.5  | 13.5  | 12    | 16.5  | 14.5       |

| Stations n | 10 stations | 11    | 12    | 13    | 14    | 15    | 16    | 17 stations |
|------------|-------------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 298         | 323   | 335.5 | 348   | 360.5 | 385.5 | 398   | 410.5       |
| L2         | 287.5       | 312.5 | 325   | 337.5 | 350   | 375   | 387.5 | 400         |
| L3         | 272         | 288   | 304   | 320   | 336   | 352   | 368   | 384         |
| L4         | 13          | 17.5  | 15.5  | 14    | 12    | 16.5  | 15    | 13          |




**SY3000: PC Wiring System Compatible (Flat ribbon cable/Plug-in)**

**SS5Y3-45GU- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**




Note) The L1 to L4 dimensions of **SS5Y3-45GU- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of **SS5Y3-45GU- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| L2         | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| L3         | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| L4         | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |




**SS5Y3-45GU- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| L2         | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| L3         | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| L4         | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| L1         | 235.5       | 248   | 248   | 260.5 | 273   | 285.5       |
| L2         | 225         | 237.5 | 237.5 | 250   | 262.5 | 275         |
| L3         | 202.5       | 213   | 223.5 | 234   | 244.5 | 255         |
| L4         | 16.5        | 17.5  | 12    | 13    | 14    | 15          |




## SY3000: PC Wiring System Compatible (Flat ribbon cable/Plug-in)

### SS5Y3-45GD- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q




Note) The L1 to L4 dimensions of **SS5Y3-45GD- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q** are identical to those of **SS5Y3-45GD- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q**.



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 123        | 135.5 | 148   | 148   | 160.5 | 173   | 185.5 | 198   | 210.5       |
| L2         | 112.5      | 125   | 137.5 | 137.5 | 150   | 162.5 | 175   | 187.5 | 200         |
| L3         | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| L4         | 15.5       | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5  | 16.5  | 17.5        |

### SS5Y3-45GD- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 135.5      | 148   | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223         |
| L2         | 125        | 137.5 | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5       |
| L3         | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| L4         | 13.5       | 14.5  | 15.5  | 16.5  | 17.5  | 12.5  | 13.5  | 14.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| L1         | 235.5       | 248   | 248   | 260.5 | 273   | 285.5       |
| L2         | 225         | 237.5 | 237.5 | 250   | 262.5 | 275         |
| L3         | 202.5       | 213   | 223.5 | 234   | 244.5 | 255         |
| L4         | 16.5        | 17.5  | 12    | 13    | 14    | 15          |

**SY5000: PC Wiring System Compatible (Flat ribbon cable/Plug-in)**



**SS5Y5-45GU- Stations D-** <sup>C4, N3</sup> <sup>C6, N7-Q</sup> <sup>C8, N9</sup>

(Light/surge voltage suppressor) (Station n)----- (Station 1)




Note) The L1 to L4 dimensions of **SS5Y5-45GU-**


**Stations U-** <sup>C4, N3</sup> <sup>C6, N7-Q</sup> <sup>C8, N9</sup> are identical to those of **SS5Y5-45GU- Stations D-** <sup>C4, N3</sup> <sup>C6, N7-Q</sup> <sup>C8, N9</sup>.




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| <b>L2</b>  | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| <b>L4</b>  | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |



**SS5Y5-45GU- Stations B-** <sup>C4, N3</sup> <sup>C6, N7-Q</sup> <sup>C8, N9</sup>



| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| <b>L2</b>  | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| <b>L4</b>  | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |





## SY5000: PC Wiring System Compatible (Flat ribbon cable/Plug-in)


**SS5Y5-45GD- Stations U-** C4, N3  
C6, N7-Q  
C8, N9




Note) The L1 to L4 dimensions of **SS5Y5-45GD-**  
Stations D- C4, N3  
C6, N7-Q  
C8, N9 are identical to those of  
 SS5Y5-45GD-Stations U- C4, N3  
C6, N7-Q  
C8, N9.




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 135.5      | 148   | 160.5 | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5       |
| <b>L2</b>  | 125        | 137.5 | 150   | 175   | 187.5 | 200   | 225   | 237.5 | 250         |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| <b>L4</b>  | 15         | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17    | 15.5  | 13.5        |



**SS5Y5-45GD- Stations B-** C4, N3  
C6, N7-Q  
C8, N9




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 173   | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5       |
| <b>L2</b>  | 137.5      | 162.5 | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275         |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| <b>L4</b>  | 12.5       | 17    | 15    | 13.5  | 11.5  | 16    | 14.5  | 12.5  | 17          |



| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 298         | 310.5 | 323   | 348   | 360.5 | 373         |
| <b>L2</b>  | 287.5       | 300   | 312.5 | 337.5 | 350   | 362.5       |
| <b>L3</b>  | 267         | 283   | 299   | 315   | 331   | 347         |
| <b>L4</b>  | 15.5        | 13.5  | 12    | 16.5  | 14.5  | 13          |

## DIN Rail Manifold Exploded View

### Type 45F (D-sub Connector) Manifold



| No. | Description  | No.   |   | Note   |
|-----|--|---|---|--|
|     |  | SY3000  | SY5000  |  |
| 1   | Manifold block assembly  | Manifold block assembly part number differs according to an attached lead wire assembly based on the connector spec. Select an appropriate part number from the table of manifold block assembly part number shown below. (Gasket 7 is supplied as an accessory.) |   |  |
| 2   | SUP/EXH block assembly   | (Metric size)<br>SX3000-51-2A<br>(Inch size)<br>SX3000-51-16A   | (Metric size)<br>SX5000-51-2A<br>(Inch size)<br>SX5000-51-16A | Metric size<br>SY3000: P, R port with one-touch fitting for $\phi 8$<br>SY5000: P, R port with one-touch fitting for $\phi 10$<br><br>Inch size<br>With one-touch fitting for $\phi 5/16$ "<br>With one-touch fitting for $\phi 3/8$ " |
| 3   | End block assembly   | SX3000-52-2A-Q  | SX5000-52-2A-Q  | For D side   |
| 4   | End block assembly   | SX3000-53-2A-Q  | SX5000-53-2A-Q  | For U side   |
| 5-1 | Connector block assembly<br>(for D-sub connector)                        | SX3000-64- <sup>1A</sup> <sub>1NA</sub>   | SX5000-64- <sup>1A</sup> <sub>1NA</sub>                       | -1A: +COM<br>-1NA: -COM  |
| 5-2 | Connector block assembly<br>(for 26 pins flat cable)                     | SX3000-64- <sup>2A</sup> <sub>2NA</sub> -26   | SX5000-64- <sup>2A</sup> <sub>2NA</sub> -26                   | Note)<br>For 24 VDC  |
| 5-3 | Connector block assembly<br>(for 20 pins flat cable)                     | SX3000-64- <sup>2A</sup> <sub>2NA</sub> -20   | SX5000-64- <sup>2A</sup> <sub>2NA</sub> -20                   |  |
| 5-4 | Connector block assembly<br>(for 10 pins flat cable)                     | SX3000-64- <sup>2A</sup> <sub>2NA</sub> -10   | SX5000-64- <sup>2A</sup> <sub>2NA</sub> -10                   |  |
| 5-5 | Connector block assembly<br>(for 2 to 8 stations (T, T1) terminal block) | SX3000-64-3A  | SX5000-64-3A  | In common between +COM and -COM.   |
| 5-6 | Connector block assembly<br>(for 9 to 17 stations (T1) terminal block)   | SX3000-64-8A  | SX5000-64-8A  |  |
| 6   | Round head<br>combination screw  | SY3000-23-4   | M3 x 26,<br>Matt nickel plated                                |  |
| 7   | Gasket   | SX3000-57-4   | SX5000-57-6   |  |
| 8   | DIN rail   | VZ1000-11-1-I□  |   | Refer to page 118.   |





Note 1) The numbers 5-1 to 4 are for 24 VDC. For 12 VDC, suffix "-12V" to the end of parts number. (Example) SX3000-64-1A-12 V  
 Note 2) Two manifold block assemblies are necessary for the double, 3 position (Dual body type).

| Style of manifold   | Manifold block assembly part no. | Note   |
|---|----------------------------------|--|
| For 45(N)F<br>(D-sub connector)                             | SX <sup>3</sup> 000-50-3A-□□-Q   | □□:<br>AB port SY3000 (metric size)<br>(inch size) |
| For 45(N) <sup>P</sup> <sub>PH</sub><br>(Flat ribbon cable) | SX <sup>3</sup> 000-50-5A-□□-Q   | A, B port SY5000 (metric size)<br>(inch size)      |
| For 45G<br>PC Wiring System compatible                      |                                  |  |
| For 45 <sup>T</sup> <sub>T1</sub><br>(Terminal block)       | SX <sup>3</sup> 000-50-7A-□□-Q   |  |

C4: With one-touch fitting for  $\phi 4$   
 C6: With one-touch fitting for  $\phi 6$   
 N3: With one-touch fitting for  $\phi 5/32$ "  
 N7: With one-touch fitting for  $\phi 1/4$ "  
 C4: With one-touch fitting for  $\phi 4$   
 C6: With one-touch fitting for  $\phi 6$   
 C8: With one-touch fitting for  $\phi 8$   
 N3: With one-touch fitting for  $\phi 5/32$ "  
 N7: With one-touch fitting for  $\phi 1/4$ "  
 N9: With one-touch fitting for  $\phi 9/16$ "

## How to Increase Manifold Bases

- 1** Loosen DIN rail holding screw (a) fixing the manifold base until it begins to turn idly. (While pressing DIN rail releasing buttons (c), at two locations, separate the manifold base from the DIN rail.)
- 2** Additional bases are to be added to the U side. Press splitting button (b) of the manifold block assembly on the U side until button (b) locks, and then separate the block assemblies.
- 3** Separate the connector block assembly in the same manner as (2), and remove the connector mounting screw shown in Fig. 1.
- 4** Loosen the valve mounting screw on the U side, remove the valve, and take out the receptacle housing. (Refer to Fig. 2.)
- 5** Insert the common wire (red) of the manifold block assembly to be added into the pin insertion section (N mark) of the receptacle housing that was taken out in (4), mount it on the manifold block, and mount the removed valve.
- 6** As shown in Fig. 3, mount the additional manifold block assembly on the DIN rail on the U side. Refer to the circuit diagram, and insert the lead wire (black) as shown in Fig. 4.
- 7** Press the blocks against each other until a click sound is produced, place the lead wire in the manifold block, and close the lid without pinching the lead wire.
- 8** While lightly holding the blocks together so that there are no gaps between them, secure them to the DIN rail by tightening the DIN rail holding screws (a).  $\Delta$  (Tightening torque: 1.4 N·m)






**Fig. 4**

**D-sub connector (45F)**

**Flat ribbon cable (45P)**

**Terminal block (45T<sub>1</sub>)**



Note) After inserting pins, lightly pull lead wire to check that pins are locked.

Note) Insert pins after removing the connector from the main unit. After inserting pins, lightly pull lead wires to check that the pins are locked.

Note) Insert tab terminals completely.

- ⚠ Caution**
1. Depending on the connector, there is a limit to the number of solenoids that can be used. Manifold bases that can be added cannot exceed the number of usable solenoids.
  2. The manifold block assembly mounting position for additional manifold bases is always on the U side, because wires are connected to respective connectors sequentially from the D side.
  3. When DIN rail holding screw (a) for the end block is not sufficiently tightened during reassembly, air leakage may result. Before supplying air, check that there is no gap between blocks and that the manifold block is firmly fixed to the DIN rail in order to ensure air supply without leakage.

## Fitting Assembly

Type 45 manifold permits change in the A and B port sizes by changing the manifold block fitting assembly. After removing the valve, remove the clip with a screwdriver, etc. For mounting a new fitting assembly, insert it and then insert a clip until it will not come out of the manifold block.


### Fitting Assembly Part No.

**Metric size**

|               |                                |                |
|---------------|--------------------------------|----------------|
| <b>SY3000</b> | One-touch fitting for $\phi 4$ | VVQ1000-50A-C4 |
|               | One-touch fitting for $\phi 6$ | VVQ1000-50A-C6 |
| <b>SY5000</b> | One-touch fitting for $\phi 4$ | VVQ1000-51A-C4 |
|               | One-touch fitting for $\phi 6$ | VVQ1000-51A-C6 |
|               | One-touch fitting for $\phi 8$ | VVQ1000-51A-C8 |

**Inch size**

|               |                                     |                |
|---------------|-------------------------------------|----------------|
| <b>SY3000</b> | One-touch fitting for $\phi 5/32$ " | VVQ1000-50A-N3 |
|               | One-touch fitting for $\phi 1/4$ "  | VVQ1000-50A-N7 |
| <b>SY5000</b> | One-touch fitting for $\phi 5/32$ " | VVQ1000-51A-N3 |
|               | One-touch fitting for $\phi 1/4$ "  | VVQ1000-51A-N7 |
|               | One-touch fitting for $\phi 5/16$ " | VVQ1000-51A-N9 |



- Note 1) P and R ports cannot be changed.  
Note 2) Use caution that O-rings must be free from scratches and dust. Otherwise, air leakage may result.

Type **45S**

# 5 Port Solenoid Valve Series SY3000/5000 Base Mounted Stacking Type/DIN Rail Mounted

## How to Order Manifold

SS5Y **3** - 45S **C** - 05 **U** - C6 -  - Q

### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

### Model

| Symbol | Specifications                                   |
|--------|--|
| O      | Without SI unit                                  |
| C      | SYSBUS wire system (OMRON Corp.)                 |
| Q      | DeviceNet and CompoBus/D (OMRON Corp.)           |
| R1     | CompoBus/S (16 outputs) compatible (OMRON Corp.) |
| R2     | CompoBus/S (8 outputs) compatible (OMRON Corp.)  |
| T2     | SI unit for ASi (8 outputs) Yellow + Black wires |
| T4     | SI unit for ASi (4 outputs) Yellow + Black wires |
| T5     | SI unit for ASi (4 outputs) Yellow wire          |
| V      | CC-link System (Mitsubishi Electric Corp.)       |

\* Even when the manifold is not equipped with a SI unit, the DIN rail is long enough for future expectancy of mounting a SI unit.

### Valve stations

| Symbol | Stations    | Note  |
|--------|-------------|---|
| 02     | 2 stations  | Single wiring spec.<br>(Applicable up to 16 solenoid valves.) |
| ⋮      | ⋮           |   |
| 16     | 16 stations |   |

\* This also includes the number of blanking plate assemblies.  
\* Two stations are necessary for the double and 3 position solenoid valves (Dual body type).

### SUP/EXH block assembly mounting position

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | (Both sides)           | 2 to 16 stations |
| M      | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification sheet.

### A, B port size

#### One-touch fitting (Metric size)

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

#### One-touch fitting (Inch size)

| Symbol | Port size  | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY3000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| M      | Mixed  |                   |
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY5000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| N9     | One-touch fitting for ø <sup>9</sup> / <sub>16</sub> " |                   |
| M      | Mixed  |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.

### Option

When a longer DIN rail is desired than the specified stations, specify the station number to be required.  
(Max. 20 stations)

#### SI Unit Part No.


| Symbol | Specifications                                   | For SS5Y□-45S | Symbol | Specifications                                   | For SS5Y□-45S |
|--------|--|---------------|--------|--|---------------|
| C      | SYSBUS wire system (OMRON Corp.)                 | EX122-STA1    | R2     | CompoBus/S (8 outputs) compatible (OMRON Corp.)  | EX122-SCS2    |
| Q      | DeviceNet and CompoBus/D (OMRON Corp.)           | EX122-SDN1    | T2     | SI unit for ASi (8 outputs) Yellow + Black wires | EX122-SAS2    |
| R1     | CompoBus/S (16 outputs) compatible (OMRON Corp.) | EX122-SCS1    | T4     | SI unit for ASi (4 outputs) Yellow + Black wires | EX122-SAS4    |
|        |  |               | T5     | SI unit for ASi (4 outputs) Yellow wire          | EX122-SAS5    |
|        |  |               | V      | CC-Link System (Mitsubishi Electric Corp.)       | EX122-SMJ1    |

## How to Order Valve Manifold Assembly (Example)

### Example

Double solenoid (24 VDC)  
SY3245-5FU-Q

Single solenoid (24 VDC)  
SY3140-5FU-Q



SS5Y3-45SC-05U-C6-Q 1 set (45S with serial unit 5 Stations  
Manifold base part number)  
\* SY3140-5FU-Q 3 sets (Single solenoid part no.)  
\* SY3245-5FU-Q 1 set (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

\* The valve arrangement is numbered as the 1st. station from D side.  
\* When ordering double solenoid valves/3 position (Dual body type), please keep in mind that they require two manifold stations.  
\* Serial unit is available only for the D-side mounting type.

## How to Order Valve

2 position single SY **3** 1 4 0 - 5 FU  - Q

Double and 3 position SY **3** **2** 4 5 - 5 FU  - Q

### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

### Type of actuation

|   |                            |
|---|----------------------------|
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

### Dual body type (Double and 3 position)


### Rated voltage

|   |        |
|---|--------|
| 5 | 24 VDC |
|---|--------|

### Manual override

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

- The serial transmission system reduces wiring work, while minimising wiring and saving space.
- 16 stations max. (Specify a model with more than 9 stations by using a manifold specification sheet.)



- The total number of stations is tabulated starting from station one on the D side.
- Maximum station: Up to 16 solenoids (16 single solenoids).

| Item                                | Specifications  |                  |
|-------------------------------------|-----------------|------------------|
| External power supply               | 24 VDC +10%/−5% |                  |
| Current consumption (Internal unit) | 0.1A            | SD, SR1, SR2, SV |
|                                     | 0.3A            | SC, SQ           |

**Type C**  
**OMRON Corporation**  
**SYSBUS Wiring System**

| LED description | Detail  |
|-----------------|---|
| RUN             | Lights up when transmission is normal and PLC is in operation mode. |
| T/R<br>ERR      | Flashes when transmission is normal; lights up when it is abnormal. |

**Note**

- SYSBUS Wire System  
 Master unit:           Type C500-RM201  
                               Type C200H-RM201
- No. of output point: 16 points

**Cable wiring**

|                             | <b>Type Q</b><br><b>DeviceNet</b>  | <b>Type R1, R2</b><br><b>OMRON Corporation</b><br><b>CompoBus/S compliant</b>  | <b>Type V</b><br><b>Mitsubishi Electric Corporation</b><br><b>CC-LINK compliant</b>  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
|-----------------------------|--|--|--|-------|---|---------|---|--|-----------------|--------|-------|---|------|---|-----|---|--|-----------------|--------|-----|---|-------|---------------------------------------|----|------------------------------|----|--------------------------------|--------|---|
| Name of terminal block, LED | <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>LED description</th> <th>Detail</th> </tr> </thead> <tbody> <tr> <td>POWER</td> <td>Green light is ON when the circuit is powered. Goes out when SI unit is not online or the circuit is not powered.</td> </tr> <tr> <td>MOD/NET</td> <td>Green light is continuously ON when SI unit is on-line and in operation.<br/>Red light flashes for connection time-out (minor communication error).<br/>Red light is continuously ON for connection time-out (major communication error) or online impossibility.</td> </tr> </tbody> </table> | LED description  | Detail   | POWER | Green light is ON when the circuit is powered. Goes out when SI unit is not online or the circuit is not powered. | MOD/NET | Green light is continuously ON when SI unit is on-line and in operation.<br>Red light flashes for connection time-out (minor communication error).<br>Red light is continuously ON for connection time-out (major communication error) or online impossibility. | <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>LED description</th> <th>Detail</th> </tr> </thead> <tbody> <tr> <td>POWER</td> <td>Lights up when transmission is ON; goes out when not powered.</td> </tr> <tr> <td>COMM</td> <td>Lights up for normal communication; goes out for abnormal communication or waiting.</td> </tr> <tr> <td>ERR</td> <td>Lights up for abnormal communication; goes out for normal communication or waiting.</td> </tr> </tbody> </table> | LED description | Detail | POWER | Lights up when transmission is ON; goes out when not powered. | COMM | Lights up for normal communication; goes out for abnormal communication or waiting. | ERR | Lights up for abnormal communication; goes out for normal communication or waiting. | <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr> <th>LED description</th> <th>Detail</th> </tr> </thead> <tbody> <tr> <td>PWR</td> <td>Lights up when transmission power; goes out when not powered.</td> </tr> <tr> <td>L RUN</td> <td>Lights up when receiving normal data.</td> </tr> <tr> <td>SD</td> <td>Lights up when sending data.</td> </tr> <tr> <td>RD</td> <td>Lights up when receiving data.</td> </tr> <tr> <td>L ERR.</td> <td>Lights up for transmission error and setting error; flashes when station or transmission speed settings are changed during operation.</td> </tr> </tbody> </table> | LED description | Detail | PWR | Lights up when transmission power; goes out when not powered. | L RUN | Lights up when receiving normal data. | SD | Lights up when sending data. | RD | Lights up when receiving data. | L ERR. | Lights up for transmission error and setting error; flashes when station or transmission speed settings are changed during operation. |
| LED description             | Detail   |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| POWER                       | Green light is ON when the circuit is powered. Goes out when SI unit is not online or the circuit is not powered.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| MOD/NET                     | Green light is continuously ON when SI unit is on-line and in operation.<br>Red light flashes for connection time-out (minor communication error).<br>Red light is continuously ON for connection time-out (major communication error) or online impossibility.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| LED description             | Detail   |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| POWER                       | Lights up when transmission is ON; goes out when not powered.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| COMM                        | Lights up for normal communication; goes out for abnormal communication or waiting.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| ERR                         | Lights up for abnormal communication; goes out for normal communication or waiting.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| LED description             | Detail   |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| PWR                         | Lights up when transmission power; goes out when not powered.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| L RUN                       | Lights up when receiving normal data.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| SD                          | Lights up when sending data.   |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| RD                          | Lights up when receiving data.   |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| L ERR.                      | Lights up for transmission error and setting error; flashes when station or transmission speed settings are changed during operation.  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| Note                        | <ul style="list-style-type: none"> <li>• DeviceNet</li> <li>• OMRON Corporation: CompoBus/D System</li> <li>  Master station unit: C200HW-DSM21</li> <li>• No. of output point: 16 points</li> </ul>   | <ul style="list-style-type: none"> <li>• CompoBus/S System</li> <li>  Master unit: C200HW-SRM21</li> <li>  Master unit: COM1-SRM21</li> <li>• No. of output point: 16 points (Type SR1)</li> <li>  No. of output point: 8 points (Type SR2)</li> </ul> | <ul style="list-style-type: none"> <li>• CC-Link System</li> <li>  Master unit: AJ61BT11</li> <li>  Master unit: A1SJ61BT11</li> <li>  Master unit: AJ61QBT11</li> <li>  Master unit: A1SJ61QBT11</li> <li>• No. of output point: 16 points</li> </ul> |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |
| Cable wiring                |  |  |  |       |   |         |   |  |                 |        |       |   |      |   |     |   |  |                 |        |     |   |       |                                       |    |                              |    |                                |        |   |



|                             | Type T2  | Type T4  | Type T5   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|-----------------------------|--|--|---|--------------|---|---------------|--|---|-------------|---|---|--------------------------------------|---|---|-----------------------------------|---|---|-------------------|--|---|---|---|---|---|--|--|--|
|                             | <b>AS-i</b>  |  |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
| Name of terminal block, LED |  |  |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Pos.</th> <th>Component:</th> <th>Description:</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>green PWR LED</td> <td>green LED for AS Interface's power supply (yellow cable)</td> </tr> <tr> <td>2</td> <td>red ERR LED</td> <td>red LED for communication error (Watch-Dog)</td> </tr> <tr> <td>3</td> <td>green EXT LED<br/>(only EX120-SAS2/4)</td> <td>green LED for valve power supply (24VDC PELV)</td> </tr> <tr> <td>4</td> <td>ADDR socket<br/>(ADDR2 only in T2)</td> <td>Socket for AS-i handheld programming device for address setting<br/>ADDR1: for As-i slave 1 / solenoid outputs 0, 1, 2 and 3<br/>ADDR2: for AS-i slave 2 / solenoid outputs 4, 5, 6 and 7</td> </tr> <tr> <td>5</td> <td>CLEAR/HOLD-Switch</td> <td>CLEAR: all valves are switched OFF in case of communication error.<br/>HOLD: all the valves remain in their current ON/OFF position in case of communication error.</td> </tr> <tr> <td>6</td> <td>AS-interface-Connection for the yellow cable (left)</td> <td>Connector for communication AS-i yellow ribbon cable.</td> </tr> <tr> <td>7</td> <td>Connection for the black cable (right)<br/>(only EX120-SAS2/4)</td> <td>Connector for external +24VDC power supply cable for the valves.</td> </tr> </tbody> </table> | Pos.   | Component:  | Description: | 1 | green PWR LED | green LED for AS Interface's power supply (yellow cable) | 2 | red ERR LED | red LED for communication error (Watch-Dog) | 3 | green EXT LED<br>(only EX120-SAS2/4) | green LED for valve power supply (24VDC PELV) | 4 | ADDR socket<br>(ADDR2 only in T2) | Socket for AS-i handheld programming device for address setting<br>ADDR1: for As-i slave 1 / solenoid outputs 0, 1, 2 and 3<br>ADDR2: for AS-i slave 2 / solenoid outputs 4, 5, 6 and 7 | 5 | CLEAR/HOLD-Switch | CLEAR: all valves are switched OFF in case of communication error.<br>HOLD: all the valves remain in their current ON/OFF position in case of communication error. | 6 | AS-interface-Connection for the yellow cable (left) | Connector for communication AS-i yellow ribbon cable. | 7 | Connection for the black cable (right)<br>(only EX120-SAS2/4) | Connector for external +24VDC power supply cable for the valves. |  |  |
|                             | Pos.   | Component:   | Description:  |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | 1  | green PWR LED  | green LED for AS Interface's power supply (yellow cable)  |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | 2  | red ERR LED  | red LED for communication error (Watch-Dog)   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | 3  | green EXT LED<br>(only EX120-SAS2/4)   | green LED for valve power supply (24VDC PELV)   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | 4  | ADDR socket<br>(ADDR2 only in T2)  | Socket for AS-i handheld programming device for address setting<br>ADDR1: for As-i slave 1 / solenoid outputs 0, 1, 2 and 3<br>ADDR2: for AS-i slave 2 / solenoid outputs 4, 5, 6 and 7 |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | 5  | CLEAR/HOLD-Switch  | CLEAR: all valves are switched OFF in case of communication error.<br>HOLD: all the valves remain in their current ON/OFF position in case of communication error.                      |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
| 6                           | AS-interface-Connection for the yellow cable (left)  | Connector for communication AS-i yellow ribbon cable.  |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
| 7                           | Connection for the black cable (right)<br>(only EX120-SAS2/4)  | Connector for external +24VDC power supply cable for the valves.                                 |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
| Note                        | <ul style="list-style-type: none"> <li>• free structure: line, tree or star.</li> <li>• no termination resistors needed.</li> <li>• no baud rate settings.</li> <li>• max. bus cable length: 100m (300m wit repeaters).</li> </ul>   |  |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             | <ul style="list-style-type: none"> <li>• 8 outputs with additional valve power supply</li> </ul>   | <ul style="list-style-type: none"> <li>• 4 outputs with additional valve power supply</li> </ul> | <ul style="list-style-type: none"> <li>• 4 outputs without additional valve power supply</li> </ul>   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
| Cable wiring                | <p><b>Communication connector</b>    External +24VDC valve power supply</p>  | <p><b>Communication connector</b>    External +24VDC valve power supply</p>                      | <p><b>Communication connector</b></p>   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |
|                             |  |  |   |              |   |               |  |   |             |   |   |                                      |   |   |                                   |   |   |                   |  |   |   |   |   |   |  |  |  |



**Series SY3000: Serial Transmission Unit/Plug-in**

**SS5Y3-45S** □ - Stations **U**-<sup>C4, N3</sup>/<sub>C6, N7</sub> -**Q** (for SI unit types C, Q, R1, R2 and V)


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 148        | 160.5 | 173   | 185.5 | 185.5 | 198   | 210.5 | 223   | 235.5       |
| <b>L2</b>  | 137.5      | 150   | 162.5 | 175   | 175   | 187.5 | 200   | 212.5 | 225         |
| <b>L3</b>  | 81         | 91.5  | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165         |
| <b>L4</b>  | 14.5       | 15.5  | 16.5  | 17.5  | 12    | 13    | 14    | 15    | 16          |

Note) For SI unit types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



**SS5Y3-45S** □ - Stations **B**-<sup>C4, N3</sup>/<sub>C6, N7</sub> -**Q** (for SI unit types C, Q, R1, R2 and V)




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 198   | 210.5 | 223   | 223   | 235.5 | 248         |
| <b>L2</b>  | 150        | 162.5 | 175   | 187.5 | 200   | 212.5 | 212.5 | 225   | 237.5       |
| <b>L3</b>  | 97.5       | 108   | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5       |
| <b>L4</b>  | 12.5       | 13.5  | 14.5  | 15.5  | 16.5  | 17.5  | 12    | 13    | 14          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 260.5       | 273   | 285.5 | 285.5 | 298   | 310.5       |
| <b>L2</b>  | 250         | 262.5 | 275   | 275   | 287.5 | 300         |
| <b>L3</b>  | 192         | 202.5 | 213   | 223.5 | 234   | 244.5       |
| <b>L4</b>  | 15          | 16    | 17    | 12    | 13    | 14          |


Note) For SI unit types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



## Series SY5000: Serial Transmission Unit/Plug-in


SS5Y5-45S□ - Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (for SI unit types C, Q, R1, R2 and V)




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 173        | 185.5 | 198   | 210.5 | 235.5 | 248   | 260.5 | 285.5 | 298         |
| L2         | 162.5      | 175   | 187.5 | 200   | 225   | 237.5 | 250   | 275   | 287.5       |
| L3         | 100        | 116   | 132   | 148   | 164   | 180   | 196   | 212   | 228         |
| L4         | 17.5       | 15.5  | 14    | 12    | 16.5  | 15    | 13    | 17.5  | 16          |

Note) For SI unit types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type | SI Unit height | SI Unit length | L1 & L2 |
|--------------|----------------|----------------|---------|
| T2, T4, T5   | 22.5 mm        | 24.3 mm        | 25 mm   |



SS5Y5-45S□ - Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (for SI unit types C, Q, R1, R2 and V)




| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| L1         | 185.5      | 198   | 223   | 235.5 | 248   | 260.5 | 285.5 | 298   | 310.5       |
| L2         | 175        | 187.5 | 212.5 | 225   | 237.5 | 250   | 275   | 287.5 | 300         |
| L3         | 118        | 134   | 150   | 166   | 182   | 198   | 214   | 230   | 246         |
| L4         | 14.5       | 13    | 17.5  | 15.5  | 14    | 12    | 16.5  | 15    | 13          |


| Stations n | 2 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|------------|-------|-------|-------|-------|-------------|
| L1         | 335.5      | 348   | 360.5 | 373   | 398   | 410.5       |
| L2         | 325        | 337.5 | 350   | 362.5 | 387.5 | 400         |
| L3         | 262        | 278   | 294   | 310   | 326   | 342         |
| L4         | 17.5       | 16    | 14    | 12.5  | 17    | 15          |

Note) For SI unit types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type | SI Unit height | SI Unit length | L1 & L2 |
|--------------|----------------|----------------|---------|
| T2, T4, T5   | 22.5 mm        | 24.3 mm        | 25 mm   |



# 5 Port Solenoid Valve Series SY3000/5000 Base Mounted Stacking Type/DIN Rail Mounted Serial Transmission Unit (Separate type)



Type **45S1**

## How to Order Manifold

SS5Y **3** - 45S1 **C** **D** - **05** **U** - **C4** - **-Q**

### Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

### Model

| Symbol    | Specifications                                   |
|-----------|--|
| <b>O</b>  | Without SI unit                                  |
| <b>C</b>  | SYSBUS wire system (OMRON Corp.)                 |
| <b>Q</b>  | DeviceNet and CompoBus/D (OMRON Corp.)           |
| <b>R1</b> | CompoBus/S (16 outputs) compatible (OMRON Corp.) |
| <b>R2</b> | CompoBus/S (8 outputs) compatible (OMRON Corp.)  |
| <b>T2</b> | SI unit for ASi (8 outputs) Yellow + Black wires |
| <b>T4</b> | SI unit for ASi (4 outputs) Yellow + Black wires |
| <b>T5</b> | SI unit for ASi (4 outputs) Yellow wire          |
| <b>V</b>  | CC-Link System (Mitsubishi Electric Corp.)       |



- Even when the manifold is not equipped with a SI unit, the DIN rail length is long enough for future expectancy of mounting a SI unit. When a shorter rail is required (same as type 45□), suffix "0" in the optional blank at the end of part number.
- For SI unit specifications, Refer to pages 166 through to 168.

### Option

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (Max. 20 stations)

### A, B port size

#### One-touch fitting (Metric size)

| Symbol    | Port size                | Applicable series |
|-----------|--------------------------|-------------------|
| <b>C4</b> | One-touch fitting for ø4 | SY3000            |
| <b>C6</b> | One-touch fitting for ø6 |                   |
| <b>M</b>  | Mixed                    |                   |
| <b>C4</b> | One-touch fitting for ø4 | SY5000            |
| <b>C6</b> | One-touch fitting for ø6 |                   |
| <b>C8</b> | One-touch fitting for ø8 |                   |
| <b>M</b>  | Mixed                    |                   |

#### One-touch fitting (Inch size)

| Symbol    | Port size                     | Applicable series |
|-----------|-------------------------------|-------------------|
| <b>N3</b> | One-touch fitting for ø 5/32" | SY3000            |
| <b>N7</b> | One-touch fitting for ø 1/4"  |                   |
| <b>M</b>  | Mixed                         |                   |
| <b>N3</b> | One-touch fitting for ø 5/32" | SY5000            |
| <b>N7</b> | One-touch fitting for ø 1/4"  |                   |
| <b>N9</b> | One-touch fitting for ø 5/16" |                   |
| <b>M</b>  | Mixed                         |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.

### SUP/EXH block assembly mounting position

| Symbol   | Mounting position      | Stations         |
|----------|------------------------|------------------|
| <b>U</b> | U side                 | 2 to 10 stations |
| <b>D</b> | D side                 | 2 to 10 stations |
| <b>B</b> | Both sides             | 2 to 16 stations |
| <b>M</b> | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification sheet.

### Valve stations

| Symbol    | Stations    | Note   |
|-----------|-------------|--|
| <b>02</b> | 2 stations  | Single wiring spec. (Applicable up to 16 solenoid valves.) |
| <b>:</b>  | :           |  |
| <b>16</b> | 16 stations |  |



- This also includes the number of blanking plate assemblies.
- Two stations are necessary for the double, and 3 position solenoid valves (Dual body type).

### SI unit mounting position

| Symbol   | Mounting position |
|----------|-------------------|
| <b>U</b> | U side            |
| <b>D</b> | D side            |

## SI Unit Part No.

| Symbol    | Specifications                                   | For SS5Y□-45S1 | Symbol    | Specifications:                                  | For SS5Y□-45S1 |
|-----------|--|----------------|-----------|--|----------------|
| <b>C</b>  | SYSBUS wire system (OMRON Corp.)                 | EX121-STA1     | <b>R2</b> | CompoBus/S (8 outputs) compatible (OMRON Corp.)  | EX121-SCS2     |
| <b>Q</b>  | DeviceNet and CompoBus/D (OMRON Corp.)           | EX121-SDN1     | <b>T2</b> | SI unit for ASi (8 outputs) Yellow + Black wires | EX121-SAS2     |
| <b>R1</b> | CompoBus/S (16 outputs) compatible (OMRON Corp.) | EX121-SCS1     | <b>T4</b> | SI unit for ASi (4 outputs) Yellow + Black wires | EX121-SAS4     |
|           |  |                | <b>T5</b> | SI unit for ASi (4 outputs) Yellow wire          | EX121-SAS5     |
|           |  |                | <b>V</b>  | CC-Link System (Mitsubishi Electric Corp.)       | EX121-SMJ1     |



\* For terminal LED descriptions and cable wiring, etc. for each SI unit, refer to pages 166 through 168.



For external pilot specifications and built-in silencer, refer to page 207.

## How to Order Valve Manifold Assembly (Example)

**Example**

SS5Y3-45S1CD-05U-C6-Q 1 set (Type 45S1 with serial unit 5 station manifold base part no.)

\* SY3140-5FU-Q 3 sets (Single solenoid part no.)

\* SY3245-5FU-Q 1 set (Double solenoid part no.)

→The asterisk denotes the symbol for assembly.  
Prefix it to the part nos. of the solenoid valve, etc.

- The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of SI unit.
- When ordering double solenoid valves/3 position (Dual body type), please keep in mind that they require two manifold stations.

## How to Order Valve

2 position single **SY** 3 1 4 0 — 5 FU   -Q

Double and 3 position **SY** 3 2 4 5 — 5 FU   -Q

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Dual body type (Double and 3 position)**

|   |        |
|---|--------|
| 5 | 24 VDC |
|---|--------|

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
|---|--------|

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**SY3000: Serial Transmission Unit/Plug-in**

**SS5Y3-45S1□U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub> -Q** (for SI unit types C, Q, R1, R2 and V)




Note) The L1 to L4 dimensions of **SS5Y3-45S1□U- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>** are identical to those of **SS5Y3-45S1□U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 198   | 198   | 210.5 | 223   | 235.5 | 248         |
| <b>L2</b>  | 150        | 162.5 | 175   | 187.5 | 187.5 | 200   | 212.5 | 225   | 237.5       |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| <b>L4</b>  | 14         | 15    | 16    | 17    | 12    | 13    | 14    | 15    | 16          |



Note) For SI unit types N, P, T2, T4, T5 and Y, the dimensions below increase by the values shown

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |




**SS5Y3-45S1□U- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub> -Q** (for SI unit types C, Q, R1, R2 and V)

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 173        | 185.5 | 198   | 210.5 | 223   | 235.5 | 235.5 | 248   | 260.5       |
| <b>L2</b>  | 162.5      | 175   | 187.5 | 200   | 212.5 | 225   | 225   | 237.5 | 250         |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| <b>L4</b>  | 12         | 13    | 14    | 15    | 16    | 17    | 12    | 13    | 14          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 273         | 285.5 | 298   | 298   | 310.5 | 323         |
| <b>L2</b>  | 262.5       | 275   | 287.5 | 287.5 | 300   | 312.5       |
| <b>L3</b>  | 202.5       | 213   | 223.5 | 234   | 244.5 | 255         |
| <b>L4</b>  | 15          | 16    | 17    | 11.5  | 12.5  | 13.5        |



Note) Width of SI unit applicable to "E": Matsushita Electric Works, Ltd. and "G": Rockwell Automation, Inc. (Allen-Bradley) widens to [24.3 mm]. For further information, please consult with SMC.



## SY3000: Serial Transmission Unit/Plug-in

**SS5Y3-45S1□D- Stations U-<sup>C4, N3</sup> C6, N7 -Q** (for SI unit types C, Q, R1, R2 and V)



Note) The L1 to L4 dimensions of **SS5Y3-45S1□D-**


**Stations D-<sup>C4, N3</sup> C6, N7** are identical to those of **SS5Y3-45S1□D- Stations U-<sup>C4, N3</sup> C6, N7**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 160.5      | 173   | 185.5 | 198   | 198   | 210.5 | 223   | 235.5 | 248         |
| <b>L2</b>  | 150        | 162.5 | 175   | 187.5 | 187.5 | 200   | 212.5 | 225   | 237.5       |
| <b>L3</b>  | 91.5       | 102   | 112.5 | 123   | 133.5 | 144   | 154.5 | 165   | 175.5       |
| <b>L4</b>  | 14         | 15    | 16    | 17    | 12    | 13    | 14    | 15    | 16          |



Note) For SI unit types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



**SS5Y3-45S1□D- Stations B-<sup>C4, N3</sup> C6, N7 -Q** (for SI unit types C, Q, R1, R2 and V)


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 173        | 185.5 | 198   | 210.5 | 223   | 235.5 | 235.5 | 248   | 260.5       |
| <b>L2</b>  | 162.5      | 175   | 187.5 | 200   | 212.5 | 225   | 225   | 237.5 | 250         |
| <b>L3</b>  | 108        | 118.5 | 129   | 139.5 | 150   | 160.5 | 171   | 181.5 | 192         |
| <b>L4</b>  | 12         | 13    | 14    | 15    | 16    | 17    | 12    | 13    | 14          |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 273         | 285.5 | 298   | 298   | 310.5 | 323         |
| <b>L2</b>  | 262.5       | 275   | 287.5 | 287.5 | 300   | 312.5       |
| <b>L3</b>  | 202.5       | 213   | 223.5 | 234   | 244.5 | 255         |
| <b>L4</b>  | 15          | 16    | 17    | 11.5  | 12.5  | 13.5        |



Note) For SI types P, T2, T4, and T5, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



**SY5000: Serial Transmission Unit/Plug-in**

**SS5Y5-45S1□U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (for SI unit types C, Q, R1, R2 and V)**  
<sup>C8, N9</sup>




Note) The L1 to L4 dimensions of **SS5Y5-45S1□U- Stations U-<sup>C4, N3</sup><sub>C6, N7</sub>** are identical to those of **SS5Y5-45S1□U- Stations D-<sup>C4, N3</sup><sub>C6, N7</sub>**.

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 173        | 185.5 | 210.5 | 223   | 235.5 | 260.5 | 273   | 285.5 | 298         |
| <b>L2</b>  | 162.5      | 175   | 200   | 212.5 | 225   | 250   | 262.5 | 275   | 287.5       |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| <b>L4</b>  | 13.5       | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |



Note) For SI unit types N, P, T2, T4, T5 and Y, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



**SS5Y5-45S1□U- Stations B-<sup>C4, N3</sup><sub>C6, N7</sub>-Q (for SI unit types C, Q, R1, R2 and V)**  
<sup>C8, N9</sup>


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 198        | 210.5 | 223   | 235.5 | 260.5 | 273   | 285.5 | 310.5 | 323         |
| <b>L2</b>  | 187.5      | 200   | 212.5 | 225   | 250   | 262.5 | 275   | 300   | 312.5       |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| <b>L4</b>  | 17         | 15.5  | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 335.5       | 348   | 373   | 385.5 | 398   | 410.5       |
| <b>L2</b>  | 325         | 337.5 | 362.5 | 375   | 387.5 | 400         |
| <b>L3</b>  | 267         | 283   | 299   | 315   | 331   | 347         |
| <b>L4</b>  | 14          | 12    | 16.5  | 15    | 13    | 11.5        |



Note) For SI unit types N, P, T2, T4, T5 and Y, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |





## SY5000: Serial Transmission Unit/Plug-in

### SS5Y5-45S1 □ D - Stations <sup>C4, N3</sup> U-C6, N7 -Q (for SI unit types C, Q, R1, R2 and V)


| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 173        | 185.5 | 210.5 | 223   | 235.5 | 260.5 | 273   | 285.5 | 298         |
| <b>L2</b>  | 162.5      | 175   | 200   | 212.5 | 225   | 250   | 262.5 | 275   | 287.5       |
| <b>L3</b>  | 105        | 121   | 137   | 153   | 169   | 185   | 201   | 217   | 233         |
| <b>L4</b>  | 13.5       | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5  | 14    | 12          |

Note) For SI unit types N, P, T2, T4, T5 and Y, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



Note) The L1 to L4 dimensions of **SS5Y5-45S1 □ D - Stations D-C4, N3** are identical to those of **SS5Y5-45S1 □ D - Stations U-C6, N7 -Q**.





### SS5Y5-45S1 □ D - Stations <sup>C4, N3</sup> B-C6, N7 -Q (for SI unit types C, Q, R1, R2 and V)

| Stations n | 2 stations | 3     | 4     | 5     | 6     | 7     | 8     | 9     | 10 stations |
|------------|------------|-------|-------|-------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 198        | 210.5 | 223   | 235.5 | 260.5 | 273   | 285.5 | 310.5 | 323         |
| <b>L2</b>  | 187.5      | 200   | 212.5 | 225   | 250   | 262.5 | 275   | 300   | 312.5       |
| <b>L3</b>  | 123        | 139   | 155   | 171   | 187   | 203   | 219   | 235   | 251         |
| <b>L4</b>  | 17         | 15.5  | 13.5  | 12    | 16.5  | 14.5  | 13    | 17.5  | 15.5        |

| Stations n | 11 stations | 12    | 13    | 14    | 15    | 16 stations |
|------------|-------------|-------|-------|-------|-------|-------------|
| <b>L1</b>  | 335.5       | 348   | 373   | 385.5 | 398   | 410.5       |
| <b>L2</b>  | 325         | 337.5 | 362.5 | 375   | 387.5 | 400         |
| <b>L3</b>  | 267         | 283   | 299   | 315   | 331   | 347         |
| <b>L4</b>  | 14          | 12    | 16.5  | 15    | 13    | 11.5        |

Note) For SI unit types N, P, T2, T4, T5 and Y, the dimensions below increase by the values shown:

| SI Unit type      | SI Unit height | SI Unit length | L1 & L2 |
|-------------------|----------------|----------------|---------|
| <b>T2, T4, T5</b> | 22.5 mm        | 24.3 mm        | 25 mm   |



# 3 Port Valve

## Series SY300/500

# Mixed Mounting Type on 5 Port Valve Manifold


3 port valve can be mounted on manifold for 5 port valve.

## Applications

Possible to be mounted on all kinds of manifolds for Series SY3000/5000.  
Refer to "How to Order Manifold" for the details.

## How to Order Valve Manifold Assembly (Example)

### Example



|                         |  |
|-------------------------|--|
| <b>SS5Y3-20-05-Q</b>    | <b>1 set (Type 20, 5 station manifold base part no.)</b> |
| * <b>SY313-5G-C6-Q</b>  | <b>2 sets (3 port valve, type NC part no.)</b>           |
| * <b>SY3120-5G-C6-Q</b> | <b>1 set (5 port valve, single solenoid part no.)</b>    |
| * <b>SY3220-5G-C6-Q</b> | <b>2 sets (5 port valve, double solenoid part no.)</b>   |

→ The asterisk denotes the symbol for assembly.  
Prefix it to the part nos. of the solenoid valve, etc.

Add the valve and option part number under the manifold base part number. In the case of complex arrangement, specify them on the manifold specification sheet.

## Body Ported/How to Order Valve

### Individual Wiring: For SS5Y<sup>3</sup><sub>5</sub>-20

**SY 5 1 3 □ □ — 5 L □ □ — 01 □ — Q**

**Series**

|   |       |
|---|-------|
| 3 | SY300 |
| 5 | SY500 |

**Type of actuation**

|   |                        |
|---|------------------------|
| 1 | Normally closed (N.C.) |
| 2 | Normally open (N.O.)   |

**Solenoid type**

|   |                 |
|---|-----------------|
| - | Single solenoid |
| D | Double solenoid |

**Coil specifications**

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* Except for M5

**A port size**

**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY300             |
| 01     | 1/8       | SY500             |

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY300             |
| C6     | One-touch fitting for ø6 | SY300             |
| C6     | One-touch fitting for ø6 | SY500             |
| C8     | One-touch fitting for ø8 | SY500             |

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY300             |
| N7     | One-touch fitting for ø1/4"  | SY300             |
| N7     | One-touch fitting for ø1/4"  | SY500             |
| N9     | One-touch fitting for ø5/16" | SY500             |

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**

**Electrical entry for G, H, L, M, W**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry for D (SY500 only)**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor |
| S | With surge voltage suppressor          |
| Z | With light/surge voltage suppressor    |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Rated voltage**

| For DC |        | For AC |                   |
|--------|--------|--------|-------------------|
| 5      | 24 VDC | 1      | 100 VAC           |
| 6      | 12 VDC | 2      | 200 VAC           |
| V      | 6 VDC  | 3      | 110 VAC [115 VAC] |
| S      | 5 VDC  | 4      | 220 VAC [230 VAC] |
| R      | 3 VDC  |        |                   |

\* DC specifications of Type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D and DO type.

**Electrical entry**

| 24, 12, 6, 5, 3 VDC               |  |  | 24, 12 VDC/<br>100, 110,<br>200, 220 VAC | 24, 12,<br>6, 5, 3 VDC             |
|-----------------------------------|--|--|--|------------------------------------|
| Grommet                           | L plug connector                         | M plug connector                         | DIN terminal (SY5000 only)               | M8 connector *                     |
| <b>G:</b> Lead wire length 300 mm | <b>L:</b> With lead wire (Length 300 mm) | <b>M:</b> With lead wire (Length 300 mm) | <b>D:</b> With connector                 | <b>WO:</b> Without connector cable |
| <b>H:</b> Lead wire length 600 mm | <b>LN:</b> Without lead wire             | <b>MN:</b> Without lead wire             | <b>DO:</b> Without connector             | <b>W□:</b> With connector cable    |
|                                   | <b>LO:</b> Without connector             | <b>MO:</b> Without connector             |  | (Note 1)                           |

\* LN, MN type: with 2 sockets.  
 \* For DIN terminal of SY300 series, refer to back page 10.  
 \* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.  
 \* For connector cable of M8 connector, refer to back page 12.  
 \* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.  
 Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.

Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to page 56.)

# SY300/500

## Body Ported/How to Order Valve

Flat ribbon cable: SS5Y<sup>3</sup><sub>5</sub>-20P

**Light/surge voltage suppressor**

|   |  |
|---|--|
| Z | With light/surge voltage suppressor                  |
| U | With light/surge voltage suppressor (Non-polar type) |

Note) Z: Positive common specifications only.

**Rated voltage**

|   |        |
|---|--------|
| 5 | 24 VDC |
| 6 | 12 VDC |

**A port size**

**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY300             |
| 01     | 1/8       | SY500             |

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY300             |
| C6     | One-touch fitting for ø6 | SY500             |
| C8     | One-touch fitting for ø8 |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY300             |
| N7     | One-touch fitting for ø1/4"  | SY500             |
| N9     | One-touch fitting for ø5/16" |                   |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

\* Except for M5

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Series**

|   |       |
|---|-------|
| 3 | SY300 |
| 5 | SY500 |

**Type of actuation**

|   |                        |
|---|------------------------|
| 1 | Normally closed (N.C.) |
| 2 | Normally open (N.C.)   |

**Solenoid type**

|   |                 |
|---|-----------------|
| - | Single solenoid |
| D | Double solenoid |

**For DC: SY 5 1 3 □ 5 LO Z □ □ □ -Q**

## Base Mounted/How to Order Valve

Individual wiring: For SS5Y<sup>3</sup><sub>5</sub>-41/42/45

**Series**

|   |       |
|---|-------|
| 3 | SY300 |
| 5 | SY500 |

**Type of actuation**

|   |                        |
|---|------------------------|
| 1 | Normally closed (N.C.) |
| 2 | Normally open (N.C.)   |

**Solenoid type**

|   |                 |
|---|-----------------|
| - | Single solenoid |
| D | Double solenoid |

**Pilot type**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

\* External pilot is not available for Type 41 manifold.

**Coil specifications**

|     |   |
|-----|---|
| Nil | Standard  |
| T   | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of D, DO or W□ type.

**Rated voltage**

| For DC |        | AC |                   |
|--------|--------|----|-------------------|
| 5      | 24 VDC | 1  | 100 VAC           |
| 6      | 12 VDC | 2  | 200 VAC           |
| V      | 6 VDC  | 3  | 110 VAC [115 VAC] |
| S      | 5 VDC  | 4  | 220 VAC [230 VAC] |
| R      | 3 VDC  |    |                   |

\* DC specifications of Type D and DO is only available with 12 and 24 VDC.  
\* AC specification is only available with D and DO type.

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**Light/surge voltage suppressor**

**Electrical entry for G, H, L, M, W**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

**Electrical entry for D (SY500 only)**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor |
| S | With surge voltage suppressor          |
| Z | With light/surge voltage suppressor    |

\* DOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**


| 24, 12, 6, 5, 3 VDC        |   |   | 24, 12 VDC/<br>100, 110,<br>200, 220 VAC   | 24, 12,<br>6, 5, 3 VDC   |
|----------------------------|---|---|--|--|
| Grommet                    | L plug connector  | M plug connector  | DIN terminal (SY5000 only)                 | M8 connector *   |
| G: Lead wire length 300 mm | L: With lead wire (Length 300 mm)<br>LN: Without lead wire<br>LO: Without connector | M: With lead wire (Length 300 mm)<br>MN: Without lead wire<br>MO: Without connector | D: With connector<br>DO: Without connector | WO: Without connector cable<br>W□: With connector cable (Note 1) |

\* LN, MN type: with 2 sockets.  
\* For DIN terminal of SY300 series, refer to back page 10.  
\* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.  
\* For connector cable of M8 connector, refer to back page 12.  
\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.  
Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.


**For DC: SY 5 1 5 □ □ □ 5 L □ □ -Q**

## Base Mounted/How to Order Valve

Flat ribbon cable:  
 Connector box type: For SS5Y<sup>3</sup>/<sub>5</sub>-41P/42P/45-A







Plug-in: For SS5Y<sup>3</sup>/<sub>5</sub>-45□



# SY300/500

## Construction




### Component Parts

| No. | Description          | Material   | Note  |
|-----|----------------------|--|-------|
| 1   | Body                 | Aluminum die-casted<br>(SY3000: Zinc die-casted) | White |
| 2   | Adapter plate        | Zinc   | White |
| 3   | End plate            | Resin  | White |
| 4   | Piston               | Resin  | -     |
| 5   | Spool valve assembly | Aluminum, H-NBR                                  | -     |

### Replacement Parts

| No. | Description            | No.   |
|-----|------------------------|---|
| 6   | Pilot valve assembly   | Refer to "How to Order Pilot Valve Assembly" on page 5. |
| 7   | M5 port block assembly | Refer to "How to Order Port Block Assembly" below.      |

### How to Order M5 Port Block Assembly



#### A, B port size

Thread piping


| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY300             |
| O1     | 1/8       | SY500             |

#### One-touch fitting (Metric size)

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY300             |
| C6     | One-touch fitting for ø6 |                   |
| C4     | One-touch fitting for ø4 | SY500             |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |

#### One-touch fitting (Inch size)

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY300             |
| N7     | One-touch fitting for ø1/4"  |                   |
| N3     | One-touch fitting for ø5/32" | SY500             |
| N7     | One-touch fitting for ø1/4"  |                   |
| N9     | One-touch fitting for ø5/16" |                   |



\* Only replacement of the fittings assembly is possible.

#### Metric size

|              |                          |                |
|--------------|--------------------------|----------------|
| <b>SY300</b> | One-touch fitting for ø4 | VVQ1000-50A-C4 |
|              | One-touch fitting for ø6 | VVQ1000-50A-C6 |
|              | One-touch fitting for ø4 | VVQ1000-51A-C4 |
| <b>SY500</b> | One-touch fitting for ø6 | VVQ1000-51A-C6 |
|              | One-touch fitting for ø8 | VVQ1000-51A-C8 |

#### Inch size

|              |                              |                |
|--------------|------------------------------|----------------|
| <b>SY300</b> | One-touch fitting for ø5/32" | VVQ1000-50A-N3 |
|              | One-touch fitting for ø1/4"  | VVQ1000-50A-N7 |
| <b>SY500</b> | One-touch fitting for ø5/32" | VVQ1000-51A-N3 |
|              | One-touch fitting for ø1/4"  | VVQ1000-51A-N7 |
|              | One-touch fitting for ø5/16" | VVQ1000-51A-N9 |

**Caution** Port block assembly (cassette type)

#### Mounting screw tightening torques

**SY300 (M2) : 0.12 N·m**  
**SY500 (M3) : 0.6 N·m**

## Specifications

---

Dimensions, specifications, solenoid specifications, response time and effective area are the same as 5 port valve.

## Weight

---

### Series SY300

| Valve model       | Type of actuation | Weight (g) |                     |
|-------------------|-------------------|------------|---------------------|
|                   |                   | Grommet    | L, M plug connector |
| SY3□3-□□-M5       | Single            | 51         | 53                  |
|                   | Double            | 68         | 74                  |
| SY3□3-□□-C4<br>N3 | Single            | 56         | 59                  |
|                   | Double            | 74         | 79                  |
| SY3□3-□□-C6<br>N7 | Single            | 54         | 57                  |
|                   | Double            | 72         | 77                  |
| SY3□5-□□          | Single            | 47         | 50                  |
|                   | Double            | 65         | 70                  |


### Series SY500

| Valve model       | Type of actuation | Weight (g) |                     |              |
|-------------------|-------------------|------------|---------------------|--------------|
|                   |                   | Grommet    | L, M plug connector | DIN terminal |
| SY5□3-□□-01□      | Single            | 69         | 72                  | 93           |
|                   | Double            | 87         | 93                  | 135          |
| SY5□3-□□-C4<br>N3 | Single            | 82         | 82                  | 103          |
|                   | Double            | 100        | 102                 | 144          |
| SY5□3-□□-C6<br>N7 | Single            | 79         | 77                  | 98           |
|                   | Double            | 97         | 98                  | 140          |
| SY5□3-□□-C8<br>N9 | Single            | 75         | 84                  | 105          |
|                   | Double            | 93         | 105                 | 147          |
| SY5□5-□□          | Single            | 55         | 58                  | 79           |
|                   | Double            | 73         | 78                  | 120          |

# 5 Port Air Operated Valve

## Series SYA3000/5000/7000

### How to Order




## Specifications

|  |                   |   |
|--|-------------------|---|
| Fluid  |                   | Air   |
| Operating pressure range MPa                                       | 2 position single | 0.15 to 0.7   |
|  | 2 position double | 0.1 to 0.7  |
|  | 3 position        | 0.2 to 0.7  |
| Pilot pressure range <sup>Note 1)</sup> MPa                        | 2 position single | $(0.7 \times P + 0.1)$ to $0.7P$ : Operating pressure range |
|  | 2 position double | 0.1 to 0.7  |
|  | 3 position        | 0.2 to 0.7  |
| Ambient and fluid temperature (°C)                                 |                   | Max. 60   |
| Manual override (Manual operation)                                 |                   | Non-locking push type                                       |
| Lubrication  |                   | Not required  |
| Mounting orientation   |                   | Unrestricted  |
| Impact/Vibration resistance (m/s <sup>2</sup> ) <sup>Note 2)</sup> |                   | 150/30  |

-  Note 1) In case of single type, be certain that pressure within operating pressure range be supplied to supply port, because return pressure is introduced from supply port {1(P)} for activation.
- Note 2) Impact resistance: No malfunction resulted from the impact test using a drop impact tester. The test was performed on the axis and right angle directions of the main valve and armature, when pilot signal is ON and OFF. (Value in the initial state)
- Vibration resistance: No malfunction occurred in one sweep test between 8.3 and 2000 Hz. Test was performed to axis and right angle directions of the main valve and armature when pilot signal is ON and OFF. (Value in the initial state)

## Caution

**For Safety Instructions and Common Precautions, refer to back page 1 through to 15.**



### How to Order Manifold Base

Same manifolds as series SY (Non plug-in style) are prepared.  
(For 20, 41, 42 and 45 Types)

SS5YA<sup>3</sup><sub>5</sub><sup>7</sup> — Fill the same as SS5Y<sup>3</sup><sub>5</sub><sup>7</sup>.

\* Specify the part numbers for valves and options together beneath the manifold base part number.

<Example>


- SS5YA5-42-03-02 1 set (Type 42, 3 station manifold base part no.)
- \* SYA5140 1 set (Single air operated valve part no.)
- \* SYA5240 1 set (Double air operated valve part no.)
- \* SY5000-26-20A-Q 1 set (Blanking plate assembly part no.)

↳ The asterisk denotes the symbol for assembly.

Prefix it to the part nos. of the solenoid valve, etc.

-  Note) When single body ported air operated valves are ordered, manifold mounting bolts and gaskets are not included. Order them separately if necessary.  
(For details, refer to page 56.)

### Pilot Pressure Range (Single pilot)



# SYA3000/5000/7000

## Flow Characteristics/Weight

### Model/Series SYA3□20 (Body ported)

| Valve model | Type of actuation |        | Pilot port size (Nominal size) | Port size |                                  | Flow characteristics             |      |                                  |                                  |                              |             |             |                | Weight (g)  |             |           |     |    |
|-------------|-------------------|--------|--------------------------------|-----------|----------------------------------|----------------------------------|------|----------------------------------|----------------------------------|------------------------------|-------------|-------------|----------------|-------------|-------------|-----------|-----|----|
|             |                   |        |                                |           |                                  | 1 → 4/2 (P → A/B)                |      |                                  |                                  | 4/2 → 5/3 (A/B → EA/EB)      |             |             |                |             |             |           |     |    |
|             |                   |        |                                |           |                                  | C (dm <sup>3</sup> /(s·bar))     | b    | Cv                               | Q[l/min(ANR)]*                   | C (dm <sup>3</sup> /(s·bar)) | b           | Cv          | Q[l/min(ANR)]* |             |             |           |     |    |
| SYA3□20-M5  | 2 position        | Single | M5                             | M5        | M5                               | C4<br>(One-touch fitting for ø4) | 0.61 | 0.44                             | 0.16                             | 171                          | 0.64        | 0.45        | 0.18           | 181         | 35          |           |     |    |
|             |                   | Double |                                |           |                                  |                                  | 0.48 | 0.46                             | 0.13                             | 137                          | 0.47        | 0.43        | 0.13           | 131         | 37          |           |     |    |
|             | Closed center     | 0.47   |                                |           |                                  |                                  | 0.42 | 0.13                             | 130                              | 0.47 (0.44)                  | 0.41 (0.37) | 0.13 (0.12) | 129 (117)      | 39          |             |           |     |    |
|             | Exhaust center    |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
|             | Pressure center   |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
| SYA3□20-C4  | 2 position        | Single |                                |           |                                  |                                  | M5   | M5                               | C6<br>(One-touch fitting for ø6) | 0.72                         | 0.29        | 0.18        | 182            | 0.64        | 0.34        | 0.17      | 167 | 44 |
|             |                   | Double |                                |           |                                  |                                  |      |                                  |                                  | 0.59                         | 0.28        | 0.15        | 148            | 0.59        | 0.30        | 0.15      | 150 | 46 |
|             | Closed center     | 0.63   |                                |           |                                  |                                  |      |                                  |                                  | 0.35                         | 0.16        | 166         | 0.42 (0.41)    | 0.34 (0.37) | 0.11 (0.11) | 110 (109) | 48  |    |
|             | Exhaust center    |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
|             | Pressure center   |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
| SYA3□20-C6  | 2 position        | Single | M5                             | M5        | C6<br>(One-touch fitting for ø6) | 0.76                             |      |                                  |                                  | 0.30                         | 0.19        | 193         | 0.65           | 0.39        | 0.17        | 176       | 40  |    |
|             |                   | Double |                                |           |                                  | 0.76                             |      |                                  |                                  | 0.55                         | 0.24        | 233         | 0.60           | 0.33        | 0.16        | 156       | 42  |    |
|             | Closed center     | 0.65   |                                |           |                                  | 0.32                             |      |                                  |                                  | 0.16                         | 167         | 0.64(0.42)  | 0.31 (0.36)    | 0.17 (0.11) | 164 (111)   | 44        |     |    |
|             | Exhaust center    |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
|             | Pressure center   |        |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |
| SYA3□20-C6  | 2 position        | Single |                                |           |                                  | M5                               | M5   | C6<br>(One-touch fitting for ø6) | 0.77 (0.49)                      | 0.34 (0.43)                  | 0.21 (0.15) | 201 (136)   | 0.61           | 0.34        | 0.16        | 159       | 44  |    |
|             |                   | Double |                                |           |                                  |                                  |      |                                  |                                  |                              |             |             |                |             |             |           |     |    |



Note) ( ): denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Model/Series SYA3□40 (Base mounted)

| Valve model | Type of actuation |        | Pilot port size (Nominal size) | Port size | Flow characteristics <sup>Note 1)</sup> |      |            |                |                              |             |           |                | Weight <sup>Note 2)</sup> (g) |     |         |
|-------------|-------------------|--------|--------------------------------|-----------|---|------|------------|----------------|------------------------------|-------------|-----------|----------------|-------------------------------|-----|---------|
|             |                   |        |                                |           | 1 → 4/2 (P → A/B)                       |      |            |                | 4/2 → 5/3 (A/B → EA/EB)      |             |           |                |                               |     |         |
|             |                   |        |                                |           | C (dm <sup>3</sup> /(s·bar))            | b    | Cv         | Q[l/min(ANR)]* | C (dm <sup>3</sup> /(s·bar)) | b           | Cv        | Q[l/min(ANR)]* |                               |     |         |
| SYA3□40-01□ | 2 position        | Single | M5                             | 1/8       | 1.0                                     | 0.30 | 0.24       | 254            | 1.1                          | 0.30        | 0.26      | 280            | 69 (34)                       |     |         |
|             |                   | Double |                                |           | 0.77                                    | 0.28 | 0.18       | 193            | 0.85                         | 0.30        | 0.19      | 216            | 71 (36)                       |     |         |
|             | Closed center     | 0.73   |                                |           | 0.31                                    | 0.18 | 187        | 1.1 (0.55)     | 0.26 (0.52)                  | 0.24 (0.16) | 273 (164) | 73 (38)        |                               |     |         |
|             | Exhaust center    |        |                                |           |   |      |            |                |                              |             |           |                |                               |     |         |
|             | Pressure center   |        |                                |           |   |      |            |                |                              |             |           |                |                               |     |         |
| SYA3□40-01□ | 2 position        | Single |                                |           | M5                                      | 1/8  | 1.2 (0.51) | 0.24 (0.45)    | 0.29 (0.14)                  | 294 (144)   | 0.89      | 0.47           | 0.24                          | 255 | 73 (38) |
|             |                   | Double |                                |           |   |      |            |                |                              |             |           |                |                               |     |         |



Note 1) ( ): denotes normal position.

Note 2) [ ]: Without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

## Flow Characteristics/Weight

### Model/Series SYA5□40 (Body ported)

| Valve model | Type of actuation |                                   | Pilot port size (Nominal size) | Port size |          | Flow characteristics <sup>Note)</sup> |                                     |                              |             |                         |                 |                              |             | Weight (g)  |           |                 |     |    |
|-------------|-------------------|-----------------------------------|--------------------------------|-----------|----------|---------------------------------------|-------------------------------------|------------------------------|-------------|-------------------------|-----------------|------------------------------|-------------|-------------|-----------|-----------------|-----|----|
|             |                   |                                   |                                |           |          | 1 → 4/2 (P → A/B)                     |                                     |                              |             | 4/2 → 5/3 (A/B → EA/EB) |                 |                              |             |             |           |                 |     |    |
|             |                   |                                   |                                |           |          | P, EA, EB                             | A, B                                | C [dm <sup>3</sup> /(s·bar)] | b           | Cv                      | Q [l/min(ANR)]* | C [dm <sup>3</sup> /(s·bar)] | b           |             | Cv        | Q [l/min(ANR)]* |     |    |
| SYA5□20-01□ | 2 position        | Single                            | M5 x 0.8                       | 1/8       | Rc 1/8   | P, EA, EB                             | A, B                                | 1.9                          | 0.35        | 0.49                    | 499             | 2.4                          | 0.39        | 0.61        | 648       | 58              |     |    |
|             |                   | Double                            |                                |           |          |                                       |                                     | 1.7                          | 0.43        | 0.45                    | 473             | 1.8                          | 0.35        | 0.46        | 473       | 64              |     |    |
|             | 3 position        | Closed center                     |                                |           |          | 1.5                                   | 0.44                                | 0.41                         | 420         | 2.5 [1.5]               | 0.32 [0.43]     | 0.59 [0.40]                  | 644 [417]   | 69          |           |                 |     |    |
|             |                   | Exhaust center<br>Pressure center |                                |           |          | 2.2 [0.91]                            | 0.46 [0.58]                         | 0.61 [0.28]                  | 626 [287]   | 1.8                     | 0.38            | 0.46                         | 483         |             |           |                 |     |    |
| SYA5□20-C4  | 2 position        | Single                            |                                |           | M5 x 0.8 | 1/8                                   | C4<br>(One-touch)<br>fitting for ø4 | P, EA, EB                    | A, B        | 0.75                    | 0.43            | 0.20                         | 209         | 0.85        | 0.64      | 0.30            | 285 | 82 |
|             |                   | Double                            |                                |           |          |                                       |                                     |                              |             | 0.74                    | 0.40            | 0.19                         | 201         | 0.84        | 0.57      | 0.28            | 263 | 87 |
|             | 3 position        | Closed center                     |                                |           |          |                                       |                                     | 0.75                         | 0.36        | 0.19                    | 198             | 0.84 [0.84]                  | 0.64 [0.53] | 0.30 [0.27] | 281 [253] | 93              |     |    |
|             |                   | Exhaust center<br>Pressure center |                                |           |          |                                       |                                     | 0.78 [0.71]                  | 0.44 [0.37] | 0.21 [0.18]             | 219 [189]       | 0.84                         | 0.57        | 0.27        | 263       |                 |     |    |
| SYA5□20-C6  | 2 position        | Single                            | M5 x 0.8                       | 1/8       |          |                                       | C6<br>(One-touch)<br>fitting for ø6 | P, EA, EB                    | A, B        | 1.5                     | 0.33            | 0.33                         | 389         | 2.0         | 0.37      | 0.52            | 533 | 76 |
|             |                   | Double                            |                                |           |          |                                       |                                     |                              |             | 1.3                     | 0.31            | 0.33                         | 333         | 1.6         | 0.32      | 0.39            | 412 | 82 |
|             | 3 position        | Closed center                     |                                |           |          |                                       |                                     | 1.3                          | 0.33        | 0.33                    | 337             | 1.8 [1.4]                    | 0.35 [0.37] | 0.44 [0.35] | 473 [373] | 87              |     |    |
|             |                   | Exhaust center<br>Pressure center |                                |           |          |                                       |                                     | 1.7 [0.80]                   | 0.31 [0.47] | 0.42 [0.23]             | 435 [229]       | 1.7                          | 0.33        | 0.44        | 441       |                 |     |    |
| SYA5□20-C8  | 2 position        | Single                            |                                |           | M5 x 0.8 | 1/8                                   | C8<br>(One-touch)<br>fitting for ø8 | P, EA, EB                    | A, B        | 1.9                     | 0.21            | 0.45                         | 458         | 2.3         | 0.29      | 0.57            | 581 | 68 |
|             |                   | Double                            |                                |           |          |                                       |                                     |                              |             | 1.6                     | 0.29            | 0.39                         | 404         | 1.7         | 0.38      | 0.46            | 456 | 74 |
|             | 3 position        | Closed center                     |                                |           |          |                                       |                                     | 1.4                          | 0.38        | 0.39                    | 375             | 2.0 [1.5]                    | 0.37 [0.40] | 0.52 [0.43] | 533 [411] | 79              |     |    |
|             |                   | Exhaust center<br>Pressure center |                                |           |          |                                       |                                     | 2.2 [1.6]                    | 0.32 [0.44] | 0.56 [0.44]             | 567 [448]       | 1.8                          | 0.41        | 0.50        | 493       |                 |     |    |

Note) [ ] : denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Model/Series SYA5□40 (Base mounted)

| Valve model | Type of actuation |                                   | Pilot port size (Nominal size) | Port size |           | Flow characteristics <sup>Note 1)</sup> |            |                              |             |                         |                 |                              |             | Weight <sup>Note 2)</sup> (g) |          |
|-------------|-------------------|-----------------------------------|--------------------------------|-----------|-----------|---|------------|------------------------------|-------------|-------------------------|-----------------|------------------------------|-------------|-------------------------------|----------|
|             |                   |                                   |                                |           |           | 1 → 4/2 (P → A/B)                       |            |                              |             | 4/2 → 5/3 (A/B → EA/EB) |                 |                              |             |                               |          |
|             |                   |                                   |                                |           |           | P, EA, EB                               | A, B       | C [dm <sup>3</sup> /(s·bar)] | b           | Cv                      | Q [l/min(ANR)]* | C [dm <sup>3</sup> /(s·bar)] | b           |                               | Cv       |
| SYA5□40-02□ | 2 position        | Single                            | M5 x 0.8                       | 1/4       | P, EA, EB | A, B                                    | 2.4        | 0.41                         | 0.64        | 658                     | 2.8             | 0.29                         | 0.66        | 707                           | 105 (42) |
|             |                   | Double                            |                                |           |           |   | 1.8        | 0.47                         | 0.50        | 516                     | 1.8             | 0.40                         | 0.47        | 490                           | 110 (47) |
|             | 3 position        | Closed center                     |                                |           |           |   | 1.4        | 0.55                         | 0.44        | 430                     | 3.0 [1.2]       | 0.33 [0.48]                  | 0.72 [0.37] | 778 [347]                     | 115 (52) |
|             |                   | Exhaust center<br>Pressure center |                                |           |           |   | 3.3 [0.84] | 0.36 [0.60]                  | 0.85 [0.28] | 873 [270]               | 1.8             | 0.40                         | 0.48        | 490                           |          |

Note 1) [ ] : denotes the normal position.  
Note 2) ( ) : denotes without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Model/Series SYA7□20 (Body ported)

| Valve model | Type of actuation |                                   | Pilot port size (Nominal size) | Port size |             | Flow characteristics |                                       |                              |             |                         |                 |                              |             | Weight (g)  |             |                 |           |     |
|-------------|-------------------|-----------------------------------|--------------------------------|-----------|-------------|----------------------|---------------------------------------|------------------------------|-------------|-------------------------|-----------------|------------------------------|-------------|-------------|-------------|-----------------|-----------|-----|
|             |                   |                                   |                                |           |             | 1 → 4/2 (P → A/B)    |                                       |                              |             | 4/2 → 5/3 (A/B → EA/EB) |                 |                              |             |             |             |                 |           |     |
|             |                   |                                   |                                |           |             | P, EA, EB            | A, B                                  | C [dm <sup>3</sup> /(s·bar)] | b           | Cv                      | Q [l/min(ANR)]* | C [dm <sup>3</sup> /(s·bar)] | b           |             | Cv          | Q [l/min(ANR)]* |           |     |
| SYA7□20-02□ | 2 position        | Single                            | 1/8                            | 1/4       | P port: 1/4 | EA, EB port: 1/8     | A, B                                  | 4.1                          | 0.23        | 0.93                    | 999             | 3.3                          | 0.33        | 0.81        | 855         | 132             |           |     |
|             |                   | Double                            |                                |           |             |                      |                                       | 2.9                          | 0.31        | 0.70                    | 742             | 2.4                          | 0.38        | 0.63        | 644         | 177             |           |     |
|             | 3 position        | Closed center                     |                                |           |             |                      |                                       | 2.5                          | 0.39        | 0.65                    | 675             | 3.4 [2.1]                    | 0.35 [0.38] | 0.82 [0.54] | 893 [563]   | 186             |           |     |
|             |                   | Exhaust center<br>Pressure center |                                |           |             |                      |                                       | 4.3 [2.4]                    | 0.23 [0.32] | 0.97 [0.61]             | 1048 [618]      | 2.2                          | 0.39        | 0.58        | 594         |                 |           |     |
| SYA7□20-C8  | 2 position        | Single                            |                                |           | 1/8         | 1/4                  | C8<br>(One-touch)<br>fitting for ø8   | EA, EB port: 1/8             | A, B        | 3.2                     | 0.26            | 0.77                         | 794         | 3.2         | 0.37        | 0.82            | 852       | 138 |
|             |                   | Double                            |                                |           |             |                      |                                       |                              |             | 2.6                     | 0.24            | 0.63                         | 637         | 2.4         | 0.31        | 0.62            | 614       | 183 |
|             | 3 position        | Closed center                     |                                |           |             |                      |                                       |                              |             | 2.4                     | 0.25            | 0.57                         | 592         | 2.6 [1.9]   | 0.42 [0.46] | 0.70 [0.56]     | 718 [541] | 192 |
|             |                   | Exhaust center<br>Pressure center |                                |           |             |                      |                                       |                              |             | 3.3 [2.4]               | 0.28 [0.22]     | 0.78 [0.57]                  | 829 [581]   | 2.2         | 0.34        | 0.60            | 574       |     |
| SYA7□20-C10 | 2 position        | Single                            | 1/8                            | 3/8       |             |                      | C10<br>(One-touch)<br>fitting for ø10 | EA, EB port: 1/8             | A, B        | 3.8                     | 0.26            | 0.86                         | 943         | 3.2         | 0.34        | 0.82            | 835       | 135 |
|             |                   | Double                            |                                |           |             |                      |                                       |                              |             | 2.8                     | 0.27            | 0.67                         | 699         | 2.4         | 0.21        | 0.59            | 578       | 180 |
|             | 3 position        | Closed center                     |                                |           |             |                      |                                       |                              |             | 2.5                     | 0.25            | 0.59                         | 616         | 2.7 [2.0]   | 0.38 [0.38] | 0.70 [0.56]     | 724 [536] | 189 |
|             |                   | Exhaust center<br>Pressure center |                                |           |             |                      |                                       |                              |             | 3.8 [2.4]               | 0.25 [0.31]     | 0.89 [0.61]                  | 937 [614]   | 2.3         | 0.38        | 0.61            | 617       |     |

Note) [ ] : denotes normal position.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.

### Model/Series SYA7□40 (Base mounted)

| Valve model | Type of actuation |                                   | Pilot port size (Nominal size) | Port size |           | Flow characteristics <sup>Note 1)</sup> |           |                              |            |                         |                 |                              |            | Weight <sup>Note 2)</sup> (g) |            |                 |           |
|-------------|-------------------|-----------------------------------|--------------------------------|-----------|-----------|---|-----------|------------------------------|------------|-------------------------|-----------------|------------------------------|------------|-------------------------------|------------|-----------------|-----------|
|             |                   |                                   |                                |           |           | 1 → 4/2 (P → A/B)                       |           |                              |            | 4/2 → 5/3 (A/B → EA/EB) |                 |                              |            |                               |            |                 |           |
|             |                   |                                   |                                |           |           | P, EA, EB                               | A, B      | C [dm <sup>3</sup> /(s·bar)] | b          | Cv                      | Q [l/min(ANR)]* | C [dm <sup>3</sup> /(s·bar)] | b          |                               | Cv         | Q [l/min(ANR)]* |           |
| SYA7□40-02□ | 2 position        | Single                            | 1/8                            | 1/4       | P, EA, EB | A, B                                    | 4.1       | 0.41                         | 1.1        | 1123                    | 4.1             | 0.29                         | 1.0        | 1036                          | 240 (111)  |                 |           |
|             |                   | Double                            |                                |           |           |   | 3.0       | 0.43                         | 0.80       | 834                     | 2.6             | 0.41                         | 0.72       | 712                           | 286 (157)  |                 |           |
|             | 3 position        | Closed center                     |                                |           |           |   | 2.6       | 0.42                         | 0.71       | 718                     | 4.7 [1.7]       | 0.35 [0.48]                  | 1.1 [0.49] | 1235 [492]                    | 294 (165)  |                 |           |
|             |                   | Exhaust center<br>Pressure center |                                |           |           |   | 5.3 [2.3] | 0.39 [0.49]                  | 1.3 [0.65] | 1431 [670]              | 2.2             | 0.49                         | 0.63       | 641                           |            |                 |           |
| SYA7□40-03  | 2 position        | Single                            |                                |           | 1/8       | 3/8                                     | P, EA, EB | A, B                         | 4.9        | 0.29                    | 1.2             | 1238                         | 4.5        | 0.27                          | 1.1        | 1123            | 240 (111) |
|             |                   | Double                            |                                |           |           |   |           |                              | 3.0        | 0.40                    | 0.80            | 816                          | 2.6        | 0.45                          | 0.73       | 734             | 286 (157) |
|             | 3 position        | Closed center                     |                                |           |           |   |           |                              | 2.6        | 0.42                    | 0.71            | 718                          | 4.8 [1.7]  | 0.35 [0.48]                   | 1.1 [0.49] | 1261 [492]      | 294 (165) |
|             |                   | Exhaust center<br>Pressure center |                                |           |           |   |           |                              | 5.3 [2.3]  | 0.31 [0.51]             | 1.3 [0.64]      | 1356 [682]                   | 2.3        | 0.45                          | 0.66       | 649             |           |


Note 1) [ ] : denotes the normal position.  
Note 2) ( ) : denotes without sub-plate.

\* These values have been calculated according to ISO6358 and represent the flow rate measured in standard conditions at an upstream pressure of 0.6 MPa (relative pressure) and a differential pressure of 0.1MPa.


# SYA3000/5000/7000

## Series SYA3000: Body Ported


### 2 position single SYA3120-C4, N3 (-F2) C6, N7



### Foot bracket SYA3120-C4, N3 (-F1) C6, N7




### SYA3120-M5





## Series SYA3000: Body Ported

2 position double

SYA3220-<sup>C4, N3</sup><sub>C6, N7</sub> (-F2)





### SYA3220-M5




3 position closed center / exhaust center / pressure center

SYA3<sup>3</sup><sub>4</sub>20-<sup>C4, N3</sup><sub>C6, N7</sub> (-F2)




### SYA3<sup>3</sup><sub>4</sub>20-M5




# SYA3000/5000/7000

## Series SYA3000: Base Mounted

### 2 position single SYA3140-01□




### 2 position double SYA3240-01□



## Series SYA3000: Base Mounted

3 position closed center / exhaust center / pressure center

SYA<sup>3</sup><sub>4</sub>40-01□




# SYA3000/5000/7000

## Series SYA5000: Body Ported


### 2 position single

SYA5120-C6, N7 □ (-F2)  
C4, N3  
 C8, N9




### Foot bracket

SYA5120-C6, N7 □ -F1  
C4, N3  
 C8, N9




### SYA5120-01 □




## Series SYA5000: Body Ported

### 2 position double

C4, N3  
**SYA5220-01** □ (-F2)  
 C6, N7  
 C8, N9




**SYA5220-01** □




### 3 position closed center / exhaust center / pressure center

C4, N3  
**SYA5420-01** □ (-F2)  
 C6, N7  
 C8, N9




**SYA5420-01** □




# SYA3000/5000/7000

## Series SYA5000: Base Mounted

### 2 position single SYA5140-02□




### 2 position double SYA5240-02□



## Series SYA5000: Base Mounted

3 position closed center / exhaust center / pressure center

SYA5<sup>3</sup>/<sub>4</sub>40-02□




# SYA3000/5000/7000



## Series SYA7000: Body Ported

### 2 position single

SYA7120-C8, N9  
C10, N11 □ (-F2)





2 -  $\phi 2.2$  die-cast hole  
(For manifold gasket positioning)




### Foot bracket

SYA7120-C8, N9  
C10, N11 □ -F1




### SYA7120-02 □





## Series SYA7000: Body Ported

### 2 position double

**SYA7220-** C8, N9  
C10, N14




**SYA7220-02**





### 3 position closed center / exhaust center / pressure center

**SYA7 20-**  $\frac{3}{4}$  C8, N9  
 $\frac{5}{8}$  C10, N11




**SYA7  $\frac{3}{4}$  20-02**




# SYA3000/5000/7000

## Series SYA7000: Base Mounted

2 position single  
SYA7140-02 □







2 position double  
SYA7240-02 □



## Series SYA7000: Base Mounted

3 position closed center / exhaust center / pressure center

SYA7<sup>3</sup><sub>4</sub>40-0<sup>2</sup><sub>03</sub> □











Type **45**

# 5 Port Solenoid Valve

## Series SY3000/5000

### Made to Order

# External Pilot/Built-in Silencer



External pilot manifold bases for low-pressure/vacuum use are added to split style/DIN rail manifolds.  
The built-in silencer has materialised a clear-cut appearance.

## Individual Wiring/Connector Box Type

### How to Order Manifold

Type 45  
**SS5Y<sup>3</sup><sub>5</sub>-45(-A)-05 U R C6 -Q**

| Series |        |
|--------|--------|
| 3      | SY3000 |
| 5      | SY5000 |

#### Valve stations

| Symbol | Stations    |
|--------|-------------|
| 02     | 2 stations  |
| :      | :           |
| 20     | 20 stations |

The number of blanking plate assembly is included.

#### SUP/EXH block assembly mounting position

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 |                  |
| B      | Both sides             | 2 to 20 stations |
| M      | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification

#### SUP/EXH block assembly specifications

| Symbol | Specifications                   |
|--------|----------------------------------|
| R      | External pilot specifications    |
| S      | Internal pilot/Built-in silencer |
| RS     | External pilot/Built-in silencer |

#### A, B port size

##### One-touch fitting (Metric size)

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

##### One-touch fitting (Inch size)

| Symbol | Port size  | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY3000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| M      | Mixed  |                   |
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY5000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| N9     | One-touch fitting for ø <sup>9</sup> / <sub>16</sub> " |                   |
| M      | Mixed  |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.


#### Option

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (Max. 20 stations)

### How to Order Valve Manifold Assembly (Example)

#### Example

Single solenoid (external pilot specifications)  
SY3140R-5G-Q (5set)




**SS5Y3-45-05DRS-C6-Q 1 set (External pilot specification with built-in silencer part no.)**  
**\* SY3140R-5G-Q 5 sets (Single solenoid part no.)**

The asterisk denotes the symbol for assembly.  
Prefix it to the part nos. of the solenoid valve, etc.

The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of SUP/EXH block assembly. In ordering, specify the part nos. in the order from the 1st. station on D side. Besides, when the arrangement will be complicated, fill out the manifold specification sheet to instruct us. For manifolds with SUP/EXH block assembly at each end of the manifold, external pilot ports and silencers will be also located at each end of the manifold. The SUP/EXH block assembly (SX3/5000\_51\_1A), for special usage, as shown on page 125, can also be mounted. Please specify the mounting position, by correctly filling in the blank space on the manifold specification sheet.

How to Order Valve



Electrical entry

| 24, 12, 6, 5, 3 VDC  |  |  | 24, 12 VDC/<br>100, 110,<br>200, 220 VAC   | 24, 12, 6, 5, 3 VDC  |
|--|--|--|--|--|
| Grommet  | L plug connector   | M plug connector   | DIN terminal   | M8 connector *   |
| <b>G:</b> Lead wire length 300 mm<br><b>H:</b> Lead wire length 600 mm | <b>L:</b> With lead wire (Length 300 mm)<br><b>LN:</b> Without lead wire<br><b>LO:</b> Without connector | <b>M:</b> With lead wire (Length 300 mm)<br><b>MN:</b> Without lead wire<br><b>MO:</b> Without connector | <b>(SY5000 only)</b><br><b>D:</b> With connector<br><b>DO:</b> Without connector | <b>WO:</b> Without connector cable<br><b>W□:</b> With connector cable (Note 1) |

- \* LN, MN type: with 2 sockets.
- \* D and DO only available for SY5000.
- \* DIN terminal type "Y" which conforms to EN-175301-803C (former DIN43650C) is also available. For details, refer to page 210.
- \* Setting "-5LOU" is available only for connector box type.
- \* For connector cable of M8 connector, refer to back page 12.
- \* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.
- Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.

**Plug-in**

**How to Order Manifold**

Type 45 □

**SS5Y<sup>3</sup><sub>5</sub>-45** **F U 05 U R** □ □ □ **-Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Common specifications**

|   |                 |
|---|-----------------|
| - | Positive common |
| N | Negative common |

No symbol is used for T, T1, S□ types.

**Connector type**

| Symbol | Mounting position         |
|--------|---------------------------|
| F      | D-sub connector           |
| P      | Flat ribbon cable 26 pins |
| PG     | Flat ribbon cable 20 pins |
| PH     | Flat ribbon cable 10 pins |
| T      | Terminal block 9 pins     |
| T1     | Terminal block 18 pins    |
| S□     | Serial Transmission Type  |

\* For details, refer to page 135.

**Connector mounting position**

| Symbol | Mounting position |
|--------|-------------------|
| U      | U side            |
| D      | D side            |

**Valve stations**

| Symbol | Stations    | Note                |
|--------|-------------|---------------------|
| 02     | 2 stations  | Single wiring spec. |
| ⋮      | ⋮           |                     |
| 20     | 20 stations |                     |

- \* This also includes the number of blanking plate assemblies.
- \* Depending on the connector, the number of stations is limited. Refer to page 138.
- \* Two stations are necessary for the double, 3 position solenoid valve (Dual body type).

**SUP/EXH block assembly mounting position**

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 |                  |
| B      | (Both sides)           | 2 to 20 stations |
| M      | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification

**SUP/EXH block assembly specifications**

| Symbol | Specifications                   |
|--------|----------------------------------|
| R      | External pilot specifications    |
| S      | Internal pilot/Built-in silencer |
| RS     | External pilot/Built-in silencer |

**A, B port size**

**One-touch fitting (Metric size)**

| Symbol | Port size                | Applicable series |
|--------|--------------------------|-------------------|
| C4     | One-touch fitting for ø4 | SY3000            |
| C6     | One-touch fitting for ø6 |                   |
| M      | Mixed                    |                   |
| C4     | One-touch fitting for ø4 | SY5000            |
| C6     | One-touch fitting for ø6 |                   |
| C8     | One-touch fitting for ø8 |                   |
| M      | Mixed                    |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size  | Applicable series |
|--------|--|-------------------|
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY3000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| M      | Mixed  |                   |
| N3     | One-touch fitting for ø <sup>5</sup> / <sub>32</sub> " | SY5000            |
| N7     | One-touch fitting for ø <sup>1</sup> / <sub>4</sub> "  |                   |
| N9     | One-touch fitting for ø <sup>5</sup> / <sub>16</sub> " |                   |
| M      | Mixed  |                   |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.

**Voltage**

|     |        |
|-----|--------|
| -   | 24 VDC |
| 12V | 12 VDC |

No symbol is used for T, T1, S□ types.


**Option**

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (20 stations at maximum)

**How to Order Valve Manifold Assembly (Example)**

**Example**

Single solenoid (external pilot specifications)  
SY3140R-5FU-Q (3 sets)  
Double solenoid (external pilot specifications)  
SY3245R-5FU-Q (1 set)



**SS5Y3-45FU-05DRS-C6-Q** 1 set (External pilot specification with built-in silencer part no.)  
\* **SY3140R-5FU-Q** 3 sets (Single solenoid part no.)  
\* **SY3245R-5FU-Q** 1 set (Double solenoid part no.)

The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of SUP/EXH block assembly. In ordering, specify the part nos. in the order from the 1st. station on D side. Besides, when the arrangement will be complicated, fill out the manifold specification sheet to instruct us. For manifolds with SUP/EXH block at each end of the manifold, external pilot ports and silencers will be also located at each end of the manifold. The SUP/EXH block assembly (SX3/5000\_51\_1A), for special usage, as shown on page 264, can also be mounted. Please specify the mounting position, by correctly filling in the blank space on the manifold specification sheet. Two stations of the manifold base are necessary for the double, 3 position (Dual body type). Use caution when specifying the number of stations required for the manifold base.

**How to Order Valve**

**SY 3 1 4** □ □ **- 5 FU** □ **-Q**

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Body Option**

|   |                                     |
|---|-------------------------------------|
| 0 | Standard (Single only)              |
| 5 | Dual body type (Double, 3 position) |

**Pilot type**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

**Rated voltage**

|    |        |
|----|--------|
| 5  | 24 VDC |
| 6  | 12 VDC |
| V* | 6 VDC  |
| S* | 5 VDC  |
| R* | 3 VDC  |



\* Mark: 45T and T1 only  
S□ type is available for 24 VDC only.

**Manual override**


|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**External Pilot/Built-in Silencer**


**SY3000: SS5Y3-45- Stations DRS-<sup>C4, N3</sup><sub>C6, N7</sub> -Q**



\* The dimensions L1 to L4 are identical to those of SS5Y3-45- Stations <sup>U</sup><sub>D</sub> <sup>C4, N3</sup><sub>C6, N7</sub> -Q.





**SS5Y3-45- Stations DR-<sup>C4, N3</sup><sub>C6, N7</sub> -Q**



One-touch fitting (P, R port)  
Applicable tubing O.D.:  $\phi 8, \phi 5/16''$


One-touch fitting (PE, X port)  
Applicable tubing O.D.:  $\phi 4, \phi 5/32''$

**SY5000: SS5Y5-45- Stations DRS-<sup>C4, N3</sup><sub>C6, N7</sub> -Q  
<sup>C8, N9</sup>**




\* The dimensions L1 to L4 are identical to those of SS5Y3-45- Stations <sup>U</sup><sub>D</sub> <sup>C4, N3</sup><sub>C6, N7</sub> -Q.

\* The dimensions of SS5Y<sup>3</sup>-45- Stations URS-Q are identical to those of SS5Y<sup>2</sup>-45F- Stations DRS-Q.



**SS5Y5-45- Stations DR-<sup>C4, N3</sup><sub>C6, N7</sub> -Q  
<sup>C8, N9</sup>**





One-touch fitting (P, R port)  
Applicable tubing O.D.:  $\phi 10, \phi 3/8''$


One-touch fitting (PE, X port)  
Applicable tubing O.D.:  $\phi 4, \phi 5/32''$

**External Pilot/Built-in Silencer**



**SY3000: SS5Y3-45FU- Stations DRS-<sup>C4,N3</sup><sub>C6,N7</sub>-Q**




**SS5Y3-45FU- Stations DR-<sup>C4,N3</sup><sub>C6,N7</sub>-Q**



**SY5000: SS5Y5-45FU- Stations DRS-<sup>C4,N3</sup><sub>C6,N7</sub>-Q**



**SS5Y5-45FU- Stations DR-<sup>C4,N3</sup><sub>C6,N7</sub>-Q**



# 5 Port Solenoid Valve

## Series SY3000/5000

### Made to Order

Type **M45**

Made to Order

# Mixed Mounting Type

Non plug-in

Use SY3000 together with SY5000, which has a large Cv and is mounted only in a place where it is needed, permits a selection of economic manifold bases.

## How to Order Manifold

Type M45 (Mixed mounting style)

**SS5Y5-M45-05 U C86-Q**

Mixed mounting style

Valve stations

| Symbol | Stations    | SUP/EXH block assembly mounting position |
|--------|-------------|--|
| 02     | 2 stations  | U side                                   |
| 20     | 20 stations | D side                                   |

The number of blanking plate ass'y is included, too.

| Symbol | Mounting position      | Stations         |
|--------|------------------------|------------------|
| U      | U side                 | 2 to 10 stations |
| D      | D side                 | 2 to 10 stations |
| B      | Both sides             | 2 to 20 stations |
| M      | Special specifications |                  |

\* For special specifications, indicate separately by the manifold specification sheet.

SUP/EXH block assembly specifications

| Symbol | Specifications                         |
|--------|--|
| -      | Standard/Internal pilot specifications |
| S      | Built-in silencer                      |

\* External pilot specification is unavailable for mixed mounting style.

Option

When a longer DIN rail is desired than the specified stations, specify the station number to be required. (Max. 20 stations)

A, B port size

One-touch fitting (Metric size)

| Symbol | Port size  |
|--------|--|
| C44    | SY5000: One-touch fitting for $\phi 4$<br>SY3000: One-touch fitting for $\phi 4$ |
| C46    | SY5000: One-touch fitting for $\phi 4$<br>SY3000: One-touch fitting for $\phi 6$ |
| C64    | SY5000: One-touch fitting for $\phi 6$<br>SY3000: One-touch fitting for $\phi 4$ |
| C66    | SY5000: One-touch fitting for $\phi 6$<br>SY3000: One-touch fitting for $\phi 6$ |
| C84    | SY5000: One-touch fitting for $\phi 8$<br>SY3000: One-touch fitting for $\phi 4$ |
| C86    | SY5000: One-touch fitting for $\phi 8$<br>SY3000: One-touch fitting for $\phi 6$ |
| M      | Mixed  |


One-touch fitting (Inch size)

| Symbol | Port size  |
|--------|--|
| N33    | SY5000: One-touch fitting for $\phi 5/32$ "<br>SY3000: One-touch fitting for $\phi 5/32$ " |
| N37    | SY5000: One-touch fitting for $\phi 5/32$ "<br>SY3000: One-touch fitting for $\phi 1/4$ "  |
| N73    | SY5000: One-touch fitting for $\phi 1/4$ "<br>SY3000: One-touch fitting for $\phi 5/32$ "  |
| N77    | SY5000: One-touch fitting for $\phi 1/4$ "<br>SY3000: One-touch fitting for $\phi 1/4$ "   |
| N93    | SY5000: One-touch fitting for $\phi 5/16$ "<br>SY3000: One-touch fitting for $\phi 5/32$ " |
| N97    | SY5000: One-touch fitting for $\phi 5/16$ "<br>SY3000: One-touch fitting for $\phi 1/4$ "  |
| M      | Mixed  |

\* In the case of mixed specifications, indicate separately on the manifold specification sheet.

## How to Order Valve Manifold Assembly (Example)

Example



**SS5Y5-M45-05U-C86-Q 1 set (Type M45, manifold base part no.)**  
**\* SY3140-5G-Q 3 sets (Single solenoid part no.)**  
**\* SY5140-5G-Q 2 sets (Single solenoid part no.)**

\* The asterisk denotes the symbol for assembly. Prefix it to the part nos. of the solenoid valve, etc.

The valve arrangement is numbered as the 1st. station from D side regardless of the mounting position of SUP/EXH block assembly. In ordering, specify the part nos. in the order from the 1st. station on D side. Besides, when the arrangement will be complicated, fill out the manifold specification sheet to instruct us.

## How to Order Valve

**SY 5 2 40 □ 5 L □ -Q**

Series

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

Type of actuation

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

Coil specifications

|   |   |
|---|---|
| - | Standard  |
| T | With power saving circuit (24 VDC, 12 VDC only) |

\* Power saving circuit is not available in the case of W□ type.

Rated voltage

| For DC | Rated voltage |
|--------|---------------|
| 5      | 24 VDC        |
| 6      | 12 VDC        |
| V      | 6 VDC         |
| S      | 5 VDC         |
| R      | 3 VDC         |

\* For type W□, DC voltage is only available.

Electrical entry for G, H, L, M, W

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

\* Power saving circuit is only available in the "Z" type.

Electrical entry

| 24, 12, 6, 5, 3 VDC        |                                   |                                   |                                   |
|----------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Grommet                    | L plug connector                  | M plug connector                  | M8 connector *                    |
| G: Lead wire length 300 mm | L: With lead wire (Length 300 mm) | M: With lead wire (Length 300 mm) | WO: Without connector cable       |
| H: Lead wire length 600 mm | LN: Without lead wire             | MN: Without lead wire             | W□: With connector cable (Note 1) |
|                            | LO: Without connector             | MO: Without connector             |                                   |

\* LN, MN type: with 2 sockets.



\* For connector cable of M8 connector, refer to back page 12.

\* Connector M8 type "WA" conforming to IEC 60947-5-2 standard, is also available. For details, see page 211.

Note 1) Enter the cable length symbols in □. Please be sure to fill in the blank referring to back page 13.

**Dimensions: Mixed Mounting**

**SS5Y5-M45- Stations U-□-Q**




L dimension: Formulae for L1, L4  
 $L3 = 12.5 \times n1 + 16 \times n2 + 52$   
 $M = \left( \frac{L3}{12.5} + 1 \right)$  Omit decimals  
 $L1 = 12.5 \times M + 23$   
 $L2 = L1 - 10.5$   
 $L4 = (L1 - L3) / 2$



n1 = Number of SY3000  
 n2 = Number of SY5000



Note) The L1 to L4 dimensions of **SS5Y5-M45- Stations D-Q** are identical to those of **SS5Y5-M45- Stations U-Q**.




**SS5Y5-M45- Stations B-□-Q**



L dimension: Formulae for L1, L4  
 $L3 = 12.5 \times n1 + 16 \times n2 + 70$   
 $M = \left( \frac{L3}{12.5} + 1 \right)$  Omit decimals  
 $L1 = 12.5 \times M + 23$   
 $L2 = L1 - 10.5$   
 $L4 = (L1 - L3) / 2$

n1 = Number of SY3000  
 n2 = Number of SY5000



# 5/3 Port Solenoid Valve

## Series SY5000/7000/9000, SY500



### Made to Order

## DIN Connector Conforming to EN-175301-803C (former DIN 43650C)

DIN connector type that conforms to the 8-mm pitch standards between DIN terminals.

### How to Order Valve

**Series**

|   |       |
|---|-------|
| 5 | SY500 |
|---|-------|

**3 port valve (5 port valve mixed mounting style)**

SY 5 1 3

**5 port valve**

SY 5 2 2 0

**Series**

|   |        |
|---|--------|
| 5 | SY5000 |
| 7 | SY7000 |
| 9 | SY9000 |

**Type of actuation**

|   |                            |
|---|----------------------------|
| 1 | 2 position single          |
| 2 | 2 position double          |
| 3 | 3 position closed center   |
| 4 | 3 position exhaust center  |
| 5 | 3 position pressure center |

**Body type**

|   |                            |
|---|----------------------------|
| 2 | Body ported                |
| 4 | Base mounted               |
| 6 | Body ported, cassette type |

Note) SY9000 series is not available with body ported cassette type.

**Type of actuation**

|   |                 |
|---|-----------------|
| 1 | Normally open   |
| 2 | Normally closed |
| 3 | Body ported     |
| 5 | Base mounted    |

**Pilot type**

|    |                |
|----|----------------|
| -  | Internal pilot |
| R* | External pilot |

\* Base mounted type only.

**Rated voltage**

| For DC            |                   |
|-------------------|-------------------|
| 5                 | 24 VDC            |
| 6                 | 12 VDC            |
| For AC (50/60 Hz) |                   |
| 1                 | 100 VAC           |
| 2                 | 200 VAC           |
| 3                 | 110 VAC [115 VAC] |
| 4                 | 220 VAC [230 VAC] |

**Light/surge voltage suppressor**

|   |   |
|---|---|
| - | Without light/surge voltage suppressor            |
| S | With surge voltage suppressor                     |
| Z | With indicator light and surge voltage suppressor |

\* YOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**A port size**

| Symbol | Port size                    |
|--------|------------------------------|
| -      | Base mounted                 |
| 01     | 1/8                          |
| C4     | One-touch fitting for ø4     |
| C6     | One-touch fitting for ø6     |
| C8     | One-touch fitting for ø8     |
| N3     | One-touch fitting for ø5/32" |
| N7     | One-touch fitting for ø1/4"  |
| N9     | One-touch fitting for ø5/16" |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**A, B port size**

**For body ported Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| 01     | 1/8       | SY5000            |
| 02     | 1/8       | SY7000            |
| 03     | 3/8       | SY9000            |

**One-touch fitting (Metric size)**

| Symbol | Port size                 | Applicable series |
|--------|---------------------------|-------------------|
| C4     | One-touch fitting for ø4  | SY5000            |
| C6     | One-touch fitting for ø6  |                   |
| C8     | One-touch fitting for ø8  |                   |
| C8     | One-touch fitting for ø8  | SY7000            |
| C10    | One-touch fitting for ø10 |                   |
| C8     | One-touch fitting for ø8  | SY9000            |
| C10    | One-touch fitting for ø10 |                   |
| C12    | One-touch fitting for ø10 |                   |

**One-touch fitting (Inch size)**

| Symbol | Port size                    | Applicable series |
|--------|------------------------------|-------------------|
| N3     | One-touch fitting for ø5/32" | SY5000            |
| N7     | One-touch fitting for ø1/4"  |                   |
| N9     | One-touch fitting for ø5/16" |                   |
| N9     | One-touch fitting for ø5/16" | SY7000            |
| N11    | One-touch fitting for ø3/8"  |                   |
| N9     | One-touch fitting for ø5/16" | SY9000            |
| N11    | One-touch fitting for ø3/8"  |                   |

**For Base Mounted**

| Symbol | Port size          | Applicable series |
|--------|--------------------|-------------------|
| -      | Without sub-plate  |                   |
| 02     | 1/4 With sub-plate | SY5000<br>SY7000  |
| 03     | 3/8 With sub-plate | SY7000<br>SY9000  |
| 04     | 1/2 With sub-plate | SY9000            |

Note) When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to page 56.)

### How to Order Pilot Valve Assembly

V115 — 5 Y

**Rated voltage**

| For DC            |                   |
|-------------------|-------------------|
| 5                 | 24 VDC            |
| 6                 | 12 VDC            |
| For AC (50/60 Hz) |                   |
| 1                 | 100 VAC           |
| 2                 | 200 VAC           |
| 3                 | 110 VAC [115 VAC] |
| 4                 | 220 VAC [230 VAC] |

**Light/surge voltage suppressor**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor |
| S | With surge voltage suppressor          |
| Z | With light/surge voltage suppressor    |

\* YOZ is not available.  
\* For AC voltage valves there is no "S" option. It is already built-in to the rectifier circuit.

**Electrical entry**

|    |          |                   |
|----|----------|-------------------|
| Y  | DIN      | With connector    |
| YO | terminal | Without connector |

### DIN Connector Part No.

| Without light     | SY100-82-1     |               |
|-------------------|----------------|---------------|
| With light        |                |               |
| Rated voltage     | Voltage symbol | No.           |
| 24 VDC            | 24VN           | SY100-82-3-05 |
| 12 VDC            | 12VN           | SY100-82-3-06 |
| 100 VAC           | 100VN          | SY100-82-3-01 |
| 200 VAC           | 200VN          | SY100-82-3-02 |
| 110 VAC (115 VAC) | 110VN          | SY100-82-3-03 |
| 220 VAC (230 VAC) | 220VN          | SY100-82-3-04 |

### Caution

- Use caution in wiring because it won't meet the IP65 (enclosure) standard if you use cord other than the prescribed heavy-duty cord of size (ø3.5 to ø7.5). Also be sure to tighten the ground nut and holding screw with the prescribed torque range. Tighten the ground nut and set screw within the specified range of torque. For how to use DIN terminal (wiring procedures, procedures for changing electrical entries, precautions, applicable cable circuit diagram), refer to back page 9.
- D type DIN connector with 9.4 mm pitch between terminals if not interchangeable.
- To distinguish from the D type DIN connector, "N" is listed at the end of voltage symbol. (For connector parts without lights, "N" is not indicated. Please refer to the name plate to distinguish.)
- Dimensions are completely the same as D type DIN connector.
- When exchanging the pilot valve assembly only, "V115-□□" is interchangeable with "V115-□□". Do not replace V114 (G, L, M) to SY115 (DIN terminal), and vice versa.

# Made to Order Specifications: Series SY3000/5000/7000/9000, SY300/500 M8 Connector Conforming to IEC60947-5-2



M8 Connector type conforming to IEC60947-5-2 standard.

## How to Order Valve

**Type of actuation**

|   |              |
|---|--------------|
| 3 | Body ported  |
| 5 | Base mounted |

**Type of actuation**

|   |                 |
|---|-----------------|
| 1 | Normally open   |
| 2 | Normally closed |

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |

**A port size**

| Symbol | Port size                           | Applicable series |
|--------|-------------------------------------|-------------------|
| -      | Without sub-plate                   | -                 |
| M5     | M5                                  | SY3000            |
| O1     | 1/8                                 | SY5000            |
| C4     | One-touch fitting for $\sim 4$      | SY3000            |
| C5     | One-touch fitting for $\sim 6$      | SY3000            |
| C6     | One-touch fitting for $\sim 8$      | SY5000            |
| C8     | One-touch fitting for $\sim 8$      | SY5000            |
| N3     | One-touch fitting for $\sim 5/32$ " | SY3000            |
| N7     | One-touch fitting for $\sim 1/4$ "  | SY3000            |
| N7     | One-touch fitting for $\sim 1/4$ "  | SY5000            |
| N9     | One-touch fitting for $\sim 5/16$ " | SY5000            |

**Thread type**

|   |      |
|---|------|
| - | Rc   |
| F | G    |
| N | NPT  |
| T | NPTF |

**Series**

|   |        |
|---|--------|
| 3 | SY3000 |
| 5 | SY5000 |
| 7 | SY7000 |
| 9 | SY9000 |

**Pilot type**

|   |                |
|---|----------------|
| - | Internal pilot |
| R | External pilot |

\* Base mounted type only.

**Electrical entry**

WA: With connector cable  
WAO: Without connector cable

Note: □ is for cable length. Please refer to Specific Product Precautions 8.

**Rated voltage**

| For DC |        |
|--------|--------|
| 5      | 24 VDC |
| 6      | 12 VDC |
| V      | 6 VDC  |
| S      | 5 VDC  |
| R      | 3 VDC  |

**Thread piping**

| Symbol | Port size | Applicable series |
|--------|-----------|-------------------|
| M5     | M5        | SY3000            |
| O1     | 1/8       | SY5000            |
| O2     | 1/8       | SY7000            |
| O3     | 3/8       | SY9000            |

**One-touch fitting (Metric size)**

| Symbol | Port size                       | Applicable series |
|--------|---------------------------------|-------------------|
| C4     | One-touch fitting for $\sim 4$  | SY3000            |
| C6     | One-touch fitting for $\sim 6$  | SY3000            |
| C6     | One-touch fitting for $\sim 6$  | SY5000            |
| C8     | One-touch fitting for $\sim 8$  | SY5000            |
| C8     | One-touch fitting for $\sim 8$  | SY7000            |
| C10    | One-touch fitting for $\sim 10$ | SY7000            |
| C8     | One-touch fitting for $\sim 8$  | SY9000            |
| C10    | One-touch fitting for $\sim 10$ | SY9000            |
| C12    | One-touch fitting for $\sim 10$ | SY9000            |

**Light/surge voltage suppressor**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor                             |
| S | With surge voltage suppressor                                      |
| Z | With indicator light and surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)                     |
| U | With indicator light and surge voltage suppressor (Non-polar type) |

**Manual override**

|   |                                |
|---|--------------------------------|
| - | Non-locking push type          |
| D | Push-turn locking slotted type |
| E | Push-turn locking lever type   |

**3 port valve (5 port valve mixed mounting style)** SY 5 1 3

**5 port valve** SY 5 2 2 0

**Body type**

|   |                            |
|---|----------------------------|
| 2 | Body ported                |
| 4 | Base mounted               |
| 6 | Body ported, cassette type |

Note) SY9000 series is not available with body ported cassette type.

**Note)** When placing an order for body ported solenoid valve as a single unit, mounting bolt for manifold and gasket are not attached. Order them separately, if necessary. (For details, refer to page 56.)

## How to Order Pilot Valve Assembly

V111 — 5 WAO □

**Rated voltage**

| For DC |        |
|--------|--------|
| 5      | 24 VDC |
| 6      | 12 VDC |
| V      | 6 VDC  |
| S      | 5 VDC  |
| R      | 3 VDC  |

**Electrical entry**

|      |                         |
|------|-------------------------|
| WAO  | Without connector cable |
| WAO□ | With connector cable    |

Note: □ is for cable length. Please refer to Specific Product Precautions 8.

**Light/surge voltage suppressor**

|   |  |
|---|--|
| - | Without light/surge voltage suppressor               |
| S | With surge voltage suppressor                        |
| Z | With light/surge voltage suppressor                  |
| R | With surge voltage suppressor (Non-polar type)       |
| U | With light/surge voltage suppressor (Non-polar type) |

# 5 Port Solenoid Valve

## Series SY3000/5000/7000/9000

Made to Order Body Ported

# External Pilot/Fluoro Rubber for Main Value



### Body Ported External Pilot

Applicable solenoid valves: Series SY3□<sup>2</sup>/<sub>6</sub>0, SY5□<sup>2</sup>/<sub>6</sub>0, SY7□<sup>2</sup>/<sub>6</sub>0

Model no. SY<sup>3</sup>/<sub>5</sub><sup>2</sup>/<sub>7</sub>□<sup>2</sup>/<sub>6</sub>0 - X20-Q

● Entry is the same as standard products.

Operating pressure range (MPa)

|                          |                 |
|--------------------------|-----------------|
| Operating pressure range | -100 kPa to 0.7 |
| Pilot pressure range     | 0.25 to 0.7     |


Dimensions: For SY3□<sup>20</sup>/<sub>60</sub>60, SY5□<sup>20</sup>/<sub>60</sub>60, SY7□<sup>20</sup>/<sub>60</sub>60

Dimensions SY3000 becomes 6.5 mm longer  
SY5000 and SY7000 becomes 10 mm longer.

### External pilot port

| Series                             | Port size |
|------------------------------------|-----------|
| SY3000                             | M3        |
| SY <sup>5</sup> / <sub>7</sub> 000 | M5        |

Dimensions: For SY3□60, SY5□60, SY7□60




### Dimensions/External Pilot Port Position

| Series | L1 dimensions | L2 dimensions |
|--------|---------------|---------------|
| SY3000 | 41.5          | 6.5           |
| SY5000 | 60.4          | 9             |
| SY7000 | 71.9          | 9             |


### JIS Symbol

Body ported


2 position single




3 position closed center




2 position double



3 position exhaust center



3 position pressure center



### Main Valve Fluoro Rubber Specifications

Fluoro rubber is used for rubber parts of the main valve to allow use in applications such as the following.

- When using a lubricant other than the recommended turbine oil, and there is a possibility of malfunction due to swelling of the spool valve seals.

Applicable solenoid valves: Series SY3□<sup>2</sup>/<sub>6</sub>0, SY5□<sup>2</sup>/<sub>6</sub>0, SY7□<sup>2</sup>/<sub>6</sub>0, SY9□<sup>2</sup>/<sub>4</sub>0

Model no. SY<sup>3</sup>/<sub>5</sub><sup>20</sup>/<sub>7</sub>□<sup>2</sup>/<sub>6</sub>0 - X90-Q

● Entry is the same as standard products.

Specifications and performance are the same as standard products.



# Series SY Safety Instructions

These safety instructions are intended to prevent a hazardous situation and/or equipment damage. These instructions indicate the level of potential hazard by a label of “Caution”, “Warning” or “Danger”. To ensure safety, be sure to observe ISO 4414 <sup>Note 1)</sup>, JIS B 8370 <sup>Note 2)</sup> and other safety practices.

 **Caution:** Operator error could result in injury or equipment damage.

 **Warning:** Operator error could result in serious injury or loss of life.

 **Danger:** In extreme conditions, there is a possible result of serious injury or loss of life.

Note 1) ISO 4414: Pneumatic fluid power — General rules relating to systems.

Note 2) JIS B 8370: General Rules for Pneumatic Equipment

## Warning

### **1. The compatibility of pneumatic equipment is the responsibility of the person who designs the pneumatic system or decides its specifications.**

Since the products specified here are used in various operating conditions, their compatibility for the specific pneumatic system must be based on specifications or after analysis and/or tests to meet your specific requirements. The expected performance and safety assurance will be the responsibility of the person who has determined the compatibility of the system. This person should continuously review the suitability of all items specified, referring to the latest catalogue information with a view to giving due consideration to any possibility of equipment failure when configuring a system.

### **2. Only trained personnel should operate pneumatically operated machinery and equipment.**

Compressed air can be dangerous if an operator is unfamiliar with it. Assembly, handling or repair of pneumatic systems should be performed by trained and experienced operators.

### **3. Do not service machinery/equipment or attempt to remove components until safety is confirmed.**

1. Inspection and maintenance of machinery/equipment should only be performed once measures to prevent falling or runaway of the driven objects have been confirmed.
2. When equipment is to be removed, confirm the safety process as mentioned above. Cut the supply pressure for this equipment and exhaust all residual compressed air in the system.
3. Before machinery/equipment is restarted, take measures to prevent shooting-out of cylinder piston rod, etc.

### **4. Contact SMC if the product is to be used in any of the following conditions:**

1. Conditions and environments beyond the given specifications, or if product is used outdoors.
2. Installation on equipment in conjunction with atomic energy, railway, air navigation, vehicles, medical equipment, food and beverages, recreation equipment, emergency stop circuits, clutch and brake circuits in press applications, or safety equipment.
3. An application which has the possibility of having negative effects on people, property, or animals, requiring special safety analysis.



# 4/5 Port Solenoid Valves/Common Precautions 1

Be sure to read before handling.

## Design

### Warning

#### 1. Actuator drive

When an actuator, such as a cylinder, is to be driven using a valve, take appropriate measures to prevent potential danger caused by actuator operation

#### 2. Intermediate stopping

When a 3 position closed center valve is used to stop a cylinder at an intermediate position, accurate stopping of the piston in a predetermined position is not possible due to the compressibility of air. Furthermore, since valves and cylinders are not guaranteed for zero air leakage, it may not be possible to hold a stopped position for an extended length of time. Contact SMC if it is necessary to hold a stopped position for an extended time.

#### 3. Effect of back pressure when using a manifold

Use caution when valves are used on a manifold, as actuator malfunction due to back-pressure may occur.

Special caution must be taken when using 3 position exhaust center valve or when driving a single acting cylinder. To prevent a malfunction, implement counter measures such as using a single EXH spacer assembly or an individual exhaust manifold.

#### 4. Holding of pressure (including vacuum)

Since valves are subject to air leakage, they cannot be used for applications such as holding pressure (including vacuum) in a pressure vessel.

#### 5. Cannot be used as an emergency shut off valve, etc.

The valves presented in this catalogue are not designed for safety applications such as an emergency shut off valve. If the valves are used in this type of system, other reliable safety assurance measures should also be adopted.

#### 6. Maintenance space

The installation should allow sufficient space for maintenance activities (removal of valve, etc.).

#### 7. Release of residual pressure

Provide a residual pressure release function for maintenance purpose. Especially in case of 3 position closed center valve or perfect valve, ensure the release of residual pressure between valve and cylinder.

#### 8. Vacuum applications

When a valve is used for vacuum switching, etc., take measures against the suction of external dust or other contaminants from vacuum pads and exhaust ports, etc. Moreover, an external pilot type valve should be used in this case. Contact SMC in case of an internal pilot type or air operated valve, etc.

#### 9. About using the double solenoid type

When using the double solenoid type for the first time, actuators may travel in an unexpected direction depending on the switching position of a valve. Implement countermeasures not to occur any danger by the actuator's operation.

## Design

#### 10. About ventilation

When it is used inside a sealed control panel, etc., provide ventilation to prevent a pressure increase caused by exhausted air inside the control panel or temperature rise caused by the heat generated by valve.

## Selection

### Warning

#### 1. Confirm the specification

The products presented in this catalogue are designed only for use in compressed air systems (including vacuum). Do not operate at pressures or temperatures, etc., beyond the range of specifications, as this can cause damage or malfunction. (Refer to specifications.)

Contact SMC when using a fluid other than compressed air (including vacuum).

#### 2. Extended periods of continuous energisation

- Continuous energisation of the valve for extended periods of time may have an adverse effect on the solenoid valve performance and the peripheral equipment due to temperature rises caused by the heat generation of the coil. Consult with SMC if valves will be continuously energised for extended periods of time or the energised period per day will be longer than the de-energised period. It is also possible to shorten the energisation period by using valves of the N.O. (normally open) type.

- When solenoid valves are mounted in a control panel, employ measures to radiate excess heat, so that temperatures remain within the valve specification range. Use special caution when three or more stations sequentially aligned on the manifold are continuously energised since this will cause a drastic temperature rise. (As for AC specifications, since the applicable merchandises are ready to provide separately, contact SMC.)



# 4/5 Port Solenoid Valves/Common Precautions 2

Be sure to read before handling.

## Selection


### ⚠ Caution

#### 1. Momentary energisation

If a double solenoid valve will be operated with momentary energisation, it should be energised for at least 0.1 second. However, depending on the secondary load conditions, it should be energised until the cylinder reaches the stroke end position, as there is a possibility of malfunction otherwise.

#### 2. Leakage voltage

When using a resistor in parallel with the switching element or using a C-R element (surge voltage suppressor) for protection of the switching element, note that leakage voltage will increase due to leakage current flowing through the resistor or C-R element. Limit the amount of residual leakage voltage to the following values:



**DC coil** Should be 3% or less of the rated voltage

**AC coil** Should be 8% or less of the rated voltage

#### 3. Solenoid valve drive for AC with solid state output (SSR, TRIAC output, etc.)

##### 1) Voltage leakage

When using a snubber circuit (C-R element) for surge protection of the output element, very small electric current will still continue to flow in spite of the OFF state. This results in the valve not returning. In the cases when exceeding the tolerance as shown above, take measures to install a bleeder resistor.

##### 2) Minimum allowable load (Min. load current)

When the consumption current of a valve is equal or less than the output element's the minimum allowable load volume or the margin is small, the output element may not be switched normally. Please confirm SMC.

#### 4. Surge voltage suppressor

If a surge protection circuit contains non-ordinary diodes such as Varistor, a residual voltage that is in proportion to the protective elements and the rated voltage will remain. Therefore, give consideration to surge voltage protection of the controller. In the case of diodes, the residual voltage is approximately 1 V.

#### 5. Low temperature operation

Unless otherwise indicated in the specifications for each valve, operation is possible to  $-10^{\circ}\text{C}$ , but appropriate measures should be taken to avoid solidification or freezing of drainage and moisture, etc.

#### 6. Using for air blow

When using a solenoid valve for air blow, use an external pilot type. Take note that when internal pilots and external pilots are used on the same manifold, the pressure drop caused by the air blowing can have an effect on the internal pilot type valves.

Moreover, when compressed air within the pressure range of the established specifications is supplied to the external pilot port, and a double solenoid valve is used for air blowing, the solenoids should normally be energised when air is being blown.

## Selection

#### 7. Mounting orientation

Rubber seal: Refer to the specifications of each series.

## Mounting

### ⚠ Warning

#### 1. If air leakage increases or equipment does not operate properly, stop operation.

Check mounting conditions when air and power supplies are connected. Initial function and leakage tests should be performed after installation.

#### 2. Instruction manual

Mount and operate the product after reading the manual carefully and understanding its contents.

Also keep the manual where it can be referred to as necessary.

#### 3. Painting and coating

Warnings or specifications printed or pasted on the product should not be erased, removed or covered up.

Consult with SMC if paint is to be applied to resinous parts, as this may have an adverse effect due to the paint solvent.

## Piping


### ⚠ Caution

#### 1. Preparation before piping

Before piping is connected, it should be thoroughly blown out with air (flushing) or washed to remove chips, cutting oil and other debris from inside the pipe.

#### 2. Wrapping of sealant tape

When connecting pipes and fittings, etc., be sure that chips from the pipe thread and sealing materials do not get inside the valve. Furthermore, when pipe tape is used, leave 1.5 to 2 thread ridges exposed at the end of the threads.



#### 3. Closed center valves

When using closed center type valves, check carefully to be sure there are no air leaks from the piping between the valves and cylinders.



# 4/5 Port Solenoid Valves/Common Precautions 3

Be sure to read before handling.

## Piping

### Caution

#### 4. Screwing in

When connecting fittings to valves, tighten as indicated below.

- 1) For M3, M5 types
  1. When using SMC fittings, follow the guidelines below.  
After tightening by hand, tighten an additional 1/4 (M3), 1/6 (M5) turn with a tightening tool. However, if miniature fittings are used, tighten an additional 1/4 turn with a tightening tool after tightening by hand. For fittings with gaskets in 2 locations, e.g., universal elbow or universal tee, tighten an additional 1/2 turn.
  - Note) If fittings are over-tightened, air leakage may result due to breaking of fitting threads or deformation of the gaskets. However, if fittings are not tightened sufficiently, loosening of the threads and air leakage and may occur.
  2. When fittings other than SMC fittings are used, follow the instructions of the respective fitting manufacturer.

#### 2) For Rc threads

Fasten with the proper tightening torques as shown below.

#### Tightening Torque for Piping

| Connection threads | Proper tightening torque N·m |
|--------------------|------------------------------|
| 1/8                | 7 to 9                       |
| 1/4                | 12 to 14                     |
| 3/8                | 22 to 24                     |
| 1/2                | 28 to 30                     |
| 3/4                | 28 to 30                     |
| 1                  | 36 to 38                     |
| 1 1/4              | 40 to 42                     |
| 1 1/2              | 48 to 50                     |
| 2                  | 48 to 50                     |

#### 5. Connection of piping to products

When connecting piping to a product, refer to its instruction manual to avoid mistakes regarding the supply port, etc.

## Wiring

### Caution

#### 1. Polarity

When connecting power to a DC specification solenoid valve equipped with (indicator light) surge voltage suppressor, confirm whether or not there is polarity. If there is polarity, take note of the following points.

Without built-in diode to protect polarity (including any power saving circuit):

If a mistake is made regarding polarity, the diode in the valve, the control device switching element or power supply equipment, etc., may burn out.

With diode to protect polarity:

If a mistake is made regarding polarity, it will not be possible to switch the valve.

## Wiring

#### 2. Applied voltage

When electric power is connected to a solenoid valve, be careful to apply the proper voltage. Improper voltage may cause malfunction or burn out the coil.

#### 3. Confirm the connections.

After completing the wiring, confirm that the connections are correct.

## Lubrication

### Caution

#### 1. Lubrication

[Rubber seal]

1. The valve has been lubricated for life at the factory, and does not require any further lubrication.
2. In the event that it is lubricated, use class 1 turbine oil (without additives), ISO VG32.  
However, once lubrication is applied it must be continued, as loss of the original lubricant may lead to malfunction.  
Contact SMC regarding class 2 turbine oil (with additives), ISO VG32.

## Air Supply

### Warning

#### 1. Use clean air.

Do not use compressed air which contains chemicals, synthetic oils containing organic solvents, salts or corrosive gases, etc., as this can cause damage or malfunction.

### Caution

#### 1. Install air filters.

Install air filters close to valves at their upstream side. A filtration degree of 5 µm or less should be selected.

#### 2. Install an air dryer, after cooler or Drain Catch (water separator), etc.

Air that includes excessive drainage may cause malfunction of valves and other pneumatic equipment. To prevent this, install an air dryer, after-cooler or water separator, etc.

#### 3. If excessive carbon dust is generated, eliminate it by installing mist separators at the upstream side of valves.

If excessive carbon dust is generated by the compressor, it may adhere to the inside of valves and cause malfunction.

Refer to "SMC Best Pneumatics" catalogue for compressed air quality.



# 4/5 Port Solenoid Valves/Common Precautions 4

Be sure to read before handling.

## Operating Environment

### Warning

1. Do not use valves in atmospheres of corrosive gases, chemicals, salt water, water or steam or where there is direct contact with any of these.
2. Products with IP65 enclosures (based on IEC60529) are protected against dust and water, however, these products cannot be used in water.  
Take measures to prevent water and dust from coming from the exhaust port.
3. Products compliant to IP65 satisfy the specifications by mounting each product properly. Be sure to read the Specific Product Precautions for each product.
4. Do not use in an explosive atmosphere.
5. Do not use in locations subject to vibration or impact. Confirm the specifications in the main section of this catalogue.
6. A protective cover, etc., should be used to shield valves from direct sunlight.
7. Shield valves from radiated heat generated by nearby heat sources.
8. Employ suitable protective measures in locations where there is contact with water droplets, oil or welding spatter, etc.
9. When solenoid valves are mounted in a control panel or are energised for extended periods of time, employ measures to radiate excess heat, so that temperatures remain within the valve specification range.

## Maintenance

### Warning

1. Perform maintenance procedures as shown in the instruction manual.  
If handled improperly, malfunction or damage of machinery or equipment may occur.
2. Equipment removal and supply/exhaust of compressed air  
When equipment is removed, first confirm that measures are in place to prevent dropping of work pieces and run-away of equipment, etc. Then cut the supply pressure and power, and exhaust all compressed air from the system using its residual pressure release function.  
Furthermore, in the case of 3 position closed center type valves, compressed air will remain between valves and cylinders, and must be exhausted similarly.  
When the equipment is to be started again after remounting or replacement, first confirm that measures are in place to prevent lurching of actuators, etc., and then confirm that the equipment is operating normally.
3. Low frequency operation  
Valves should be switched at least once every 30 days to prevent malfunction. (Use caution regarding the air supply.)
4. Manual override operation  
When the manual override is operated, connected equipment will be actuated. Confirm safety before operating.

### Caution

1. Drain flushing  
Remove drainage from air filters regularly.



# Series SY Specific Product Precautions 1

Be sure to read before handling.


Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## Manual Override Operation

### ⚠ Warning

#### ■ Non-locking push type [Standard]


Press in the direction of the arrow




#### ■ Push-turn locking slotted type [Type D]

While pressing, turn in the direction of the arrow.

If it is not turned, it can be operated the same way as the non-locking type.



Locked position



### ⚠ Caution


When operating the locking type D with a screw driver, turn it gently using a watchmakers screw driver.

[Torque: Less than 0.1 N·m]


#### ■ Push-turn locking lever type [Type E]

While pressing, turn it the direction of the arrow.

If it is not turned, it can be operated the same way as the non-locking type.



Locked position



### ⚠ Caution

When locking the manual override on the push-turn locking types (D, E), be sure to push it down before turning.

Turning without first pushing it down can cause damage to the manual override and trouble such as air leakage, etc.

## Solenoid Valve for 200, 220 VAC Specifications

### ⚠ Warning

Solenoid valves with DIN terminal and L/M type plug connector AC specifications have a built-in rectifier circuit in the pilot section to operate the DC coil.

With 200 V, 220 VAC specification pilot valves, this built-in rectifier generates heat when energised. The surface may become hot depending on the energised condition; therefore, do not touch the solenoid valves.

## Exhaust Throttle

### ⚠ Caution

With series SY, the pilot valve and main valve share a common exhaust inside the valve. Therefore, do not block the exhaust port when arranging the piping.

## Series SY3000/5000/7000/9000 Used as a 3-Port Valve

### ⚠ Caution

#### In case of using a 5-port valve as a 3-port valve

Series SY3000/5000/7000/9000 can be used as normally closed (N.C.) or normally open (N.O.) 3-port port valves by closing one of the cylinder ports (A or B) with a plug. However, they should be used with the exhaust ports kept open. (Refer to pages 117 to 182 for dedicated 3-port solenoid valve.)

| Plug position       | Configuration | B port | A port |
|---------------------|---------------|--------|--------|
|                     |               | N.C.   | N.O.   |
| Number of solenoids | Single        |        |        |
|                     | Double        |        |        |



# Series SY Specific Product Precautions 2

Be sure to read before handling.


Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## How to Use Plug Connector

### ⚠ Caution


#### 1. Attaching and detaching connectors

- To attach a connector, hold the lever and connector unit between your fingers and insert straight onto the pins of the solenoid valve so that the lever's pawl is pushed into the groove and locks.
- To detach a connector, remove the pawl from the groove by pushing the lever downward with your thumb, and pull the connector straight out.



#### 2. Crimping connection of lead wire and socket

Strip 3.2 to 3.7 mm at the end of lead wires, insert the end of the core wires evenly into the sockets, and then crimp it by a crimping tool. When this is done, take care that the coverings of the lead wires do not enter the core wire crimping area. (Crimping tool: Model no. DXT170-75-1)



#### 3. Attaching and detaching lead wires with sockets

##### • Attaching


Insert the sockets into the square holes of the connector (+, - indication), and continue to push the sockets all the way in until they lock by hooking into the seats in the connector.

(When they are pushed in, their hooks open and they are locked automatically.) Then confirm that they are locked by pulling lightly on the lead wires.

##### • Detaching

To detach a socket from a connector, pull out the lead wire while pressing the socket's hook with a stick having a thin tip (approx. 1 mm).

If the socket will be used again, first spread the hook outward.




## Surge Voltage Suppressor


### ⚠ Caution

<For DC>  
Grommet, L/M Plug Connector


#### ■ Standard type (With polarity) With surge voltage suppressor (□S)




#### With light/surge voltage suppressor (□Z)



#### ■ Non-polar type With surge voltage suppressor (□R)




#### With light/surge voltage suppressor (□U)



- Connect the standard type in accordance with the +, - polarity indication. (The non-polar type can be used with the connections made either way.)
- Since voltage specifications other than standard 24 V and 12 VDC do not have diodes for polarity protection, be careful not to make errors in the polarity.
- Please use caution regarding the allowable voltage fluctuation because there is about a 1 volt drop for a valve with polarity protection. (For details, refer to the solenoid specifications for the individual valve.)
- When wiring is done at the factory, positive (+) is red and negative (-)

#### ■ With power saving circuit

Power consumption is decreased by 1/4 by reducing the wattage required to hold the valve in an energised state. (Effective energising time is over 62 ms at 24 VDC.)




## Operating Principle

With the above circuit, the current consumption when holding is reduced to save energy. Please refer to the electric wave data below.

- Please be careful not to reverse the polarity, since a diode to prevent the reversed current is not provided for the power saving circuit.
- Please use caution regarding the allowable voltage fluctuation because there is about a 0.5 volt drop due to the transistor. (For details, refer to the solenoid specifications for the individual valve.)

(In the case of SY<sup>3</sup>/<sub>9</sub>\*OT, the electric wave form of energy saving type)






# Series SY Specific Product Precautions 3

Be sure to read before handling.


Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## Surge Voltage Suppressor


### DIN Terminal



#### With surge voltage suppressor (DS)




#### With light/surge voltage suppressor (DZ)





DIN terminal has no polarity.

### M8 Connector





Solenoid valve side pin wiring diagram (For W type)

#### Standard type (without polarity) With surge voltage suppressor (□S)





Solenoid valve side pin wiring diagram (For WA type)

#### With light/surge voltage suppressor (□Z)




Solenoid valve side pin wiring diagram (For W type)

#### Non-polar type With surge voltage suppressor (□R)



Solenoid valve side pin wiring diagram (For WA type)


#### With light/surge voltage suppressor (□U)



- In the case of standard type, connect + to 1 and - to 3 for W type, and connect + to 4 and - to 3 for WA type, according to the polarity.
- For DC voltages other than 12 V and 24 V, incorrect wiring will cause damage to the surge suppressor circuit.
- Please use caution regarding the allowable voltage fluctuation because there is about a 1 volt drop for a valve with polarity protection. (For details, refer to the solenoid specifications for the individual valve.)

### Plug-in

#### Circuit for non-polar (FU)




Plug-in valve has no polarity, so its possible to use for both manifold bases for positive (SS5Y<sub>s</sub><sup>3</sup>-45□) and negative its common (SS5Y<sub>s</sub><sup>3</sup>-45N□) types.

#### <For AC>

(There is no "S" option, because the generation of surge voltage is prevented by a rectifier.)

### DIN Terminal

#### With light (DZ)



Note) Surge voltage suppressor of varistor has residual voltage corresponding to the protective element and rated voltage; therefore, protect the controller side from the surge voltage. The residual voltage of the diode is approximately 1 V.



# Series SY Specific Product Precautions 4

Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## Plug Connector Lead Wire Length

### ⚠ Caution

Standard length is 300mm, but the following lengths are also available.

### How to Order Connector Assembly

For DC: **SY100-30-4A** 

Without lead wire: **SY100-30-A**

(with connector and 2 of sockets only)

#### • How to Order

Specify the part numbers of the solenoid valve without connector and the connector assembly with protective cover separately.

<Example> Lead wire length 2000 mm

**For DC**  
**SY3120-5LO-M5**  
**SY100-30-4A-20**

#### • Lead wire length

|    |         |
|----|---------|
| -  | 300 mm  |
| 6  | 600 mm  |
| 10 | 1000 mm |
| 15 | 1500 mm |
| 20 | 2000 mm |
| 25 | 2500 mm |
| 30 | 3000 mm |
| 50 | 5000 mm |

## How to Use DIN Terminal

### ⚠ Caution

#### Connection

1. Loosen the holding screw and pull the connector out of the solenoid valve terminal block.
2. After removing the holding screw, insert a flat head screwdriver, etc. into the notch on the bottom of the terminal block and pry it open, separating the terminal block and the housing.
3. Loosen the terminal screws (slotted screws) on the terminal block, insert the cores of the lead wires into the terminals according to the connection method, and fasten them securely with the terminal screws.
4. Secure the cord by fastening the ground nut.

#### ⚠ Caution

When making connections, take note that using other than the supported size ( $\phi 3.5$  to  $\phi 7$ ) heavy duty cord will not satisfy IP65 (enclosure) standards. Also, be sure to tighten the ground nut and holding screw within their specified torque ranges.

#### Changing the entry direction

After separating the terminal block and housing, the cord entry can be changed by attaching the housing in the desired direction (4 directions at 90° intervals).

\* When equipped with a light, be careful not to damage the light with the cord's lead wires.


#### Precautions

Plug in and pull out the connector vertically without tilting to one side.

#### Compatible cable

Cord O.D.:  $\phi 3.5$  to  $\phi 7$

(Reference)  $0.5\text{mm}^2$ , 2-core or 3-core, equivalent to JIS C 3306





# Series SY Specific Product Precautions 5


Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## Series SY300, SY3000 How to Use DIN Terminal Connector

### ⚠ Caution

- SMC can provide a DIN style terminal connector (body ported type, sub-plate type) for the series SY300 and SY3000. This cannot be assembled to a standard manifold since the DIN connector width (15.8mm) exceeds that of the valve body (10mm). Contact SMC if you wish to use with a manifold. Please also note: that brackets F1, F2 cannot be mounted.



## DIN Connector Part No.

### ⚠ Caution


Without light

SY100-61-1

### With light

| Rated voltage | Voltage symbol | No.           |
|---------------|----------------|---------------|
| 24 VDC        | 24 V           | SY100-61-3-05 |
| 12 VDC        | 12 V           | SY100-61-3-06 |
| 100 VAC       | 100 V          | SY100-61-2-01 |
| 200 VAC       | 200 V          | SY100-61-2-02 |
| 110 VAC       | 110 V          | SY100-61-2-03 |
| 220 VAC       | 220 V          | SY100-61-2-04 |

### Circuit Diagram with Light



Note) Refer to page 212 for DIN connector (Y) conforming to EN-175301-803C (former DIN 43650C).

## Connector Assembly with Cover

### ⚠ Caution

Connector assembly with dust proof protective cover.

- Effective to prevention of short circuit failure due to the entry of foreign matter into the connector.
- Chloroprene rubber for electrical use, which provides outstanding weather resistance and electrical insulation, is used for the cover material. However, do not allow contact with cutting oil, etc.
- Simple and unencumbered appearance by adopting round-shaped cord.


### How to Order

SY100-68-A-

• Lead wire length (L)

|    |         |
|----|---------|
| -  | 300 mm  |
| 6  | 600 mm  |
| 10 | 1000 mm |
| 15 | 1500 mm |
| 20 | 2000 mm |
| 25 | 2500 mm |
| 30 | 3000 mm |
| 50 | 5000 mm |

## Connector Assembly with Cover: Dimensions



### How to Order

Enter the part number for a plug connector solenoid valve without connector together with the part number for a connector assembly with cover.

<Example 1> Lead wire length of 2000 mm

SY3120-5LOZ-M5-Q  
SY100-68-A-20

<Example 2> Lead wire length of 300 mm (standard)

SY3120-5LPZ-M5-Q

Symbol for connector assembly with cover

\* In this case, the part number for the connector assembly with cover is not required.



# Series SY Specific Product Precautions 6

Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## Plug-in

### ⚠ Caution

- When using a double solenoid valve (Dual body type: SY<sup>3</sup>245-□FU) on the plug-in style manifold (SS5Y<sup>3</sup>-45(N)□), two manifold stations are required per valve.


Output to A/B ports will be made through the manifold block on the side indicated by an arrow on the top of the solenoid valve. Therefore, arrange the piping on the side indicated by the arrow.

Although the "T" side will not be used, plugs will not be necessary since it is sealed with the valve.

(However, insert a plug into the A/B ports if dust intrusion is possible. Refer to page 138.)


### Manifold valve

#### SS5Y<sup>3</sup>-45 (N)□




Plug-in type solenoid valves consist of a non-polar solenoid valve and a plug-in socket. When ordering them separately, refer to the following part numbers.

#### [Single solenoid]



#### [Double, 3 position] Dual body type



Note) Using a valve other than a non-polar type may cause trouble.

## DIN Rail for Series SY7000/9000

### ⚠ Caution

The DIN rail used with Series SY7000 and SY9000 is stronger than that used with Series SY3000 and SY5000. Use this exclusive DIN rail with Series SY7000 and SY9000. Furthermore, if using a DIN rail other than that supplied by SMC, refer to the manifold mounting section below, and mount using the same method as prescribed for side facing and rear facing, regardless of the mounting orientation.

## Manifold Mounting

### ⚠ Caution

For Type 23, 43, 45, 45□ and 60 DIN rail mounting, when attaching a manifold to a mounting surface, etc., with bolts, if the entire bottom surface of the DIN rail contacts the mounting surface in a horizontal mounting, it can be used by simply securing both ends of the DIN rail. However, for any other mounting method or for side facing and rear facing, etc., secure the DIN rail with bolts at uniform intervals using the following as a guide: 2 to 5 stations at 2 locations, 6 to 10 stations at 3 locations, 11 to 15 stations at 4 locations, and 16 to 20 stations at 5 locations. In addition, even in the case of a horizontal mounting, if the mounting surface is subject to vibration, etc., take the same measures indicated above. If secured at fewer than the specified number of locations, warping or twisting may occur in the DIN rail and manifold, causing trouble such as air leakage.

Also, when using mounting screws for the DIN rail on the bottom side (L3 dimension in the dimension table) of the manifold valve body, the height of the screw head has to be as follows.


Type 23, 43 (SY9000): 8 mm or less

Type 45 (SY3000, 5000): 5.8 mm or less

For type 60:

SY3000: 4.7 mm or less

SY5000: 5.8 mm or less



[This is the case for type 60.]



# Series SY Specific Product Precautions 7

Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## One-touch Fittings

### ⚠ Caution

The pitch determined for each of the series SY piping ports (P, A, B, etc.) is based on the assumption that series KJ one-touch fittings will be used. For this reason, other pipe fittings may interfere with each other depending on their type and size. Dimensions should be confirmed in a pipe fitting catalogue before they are used.

#### • Tubing attachment/detachment for One-touch fittings

##### 1) Attaching of tubing

1. Take a tubing having no flaws on its periphery and cut it off at a right angle. When cutting the tubing, use tubing cutters TK-1, 2 or 3. Do not use pinchers, nippers or scissors, etc. If cutting is done with tools other than tubing cutters, the tubing may be cut diagonally or become flattened, etc., making a secure installation impossible, and causing problems such as the tubing pulling out after installation or air leakage. Allow some extra length in the tubing.
2. Grasp the tubing and push it in slowly, inserting it securely all the way into the fitting.
3. After inserting the tubing, pull on it lightly to confirm that it will not come out. If it is not installed securely all the way into the fitting, this can cause problems such as air leakage or the tubing pulling out.

##### 2) Detaching of tubing

1. Push in the release button sufficiently, pushing its collar equally around the circumference.
2. Pull out the tubing while holding down the release button so that it does not come out. If the release button is not pressed down sufficiently, there will be increased bite on the tubing and it will become more difficult to pull it out.
3. When the removed tubing is to be used again, cut off the portion which has been chewed before reusing it. If the chewed portion of the tubing is used as is, this can cause trouble such as air leakage or difficulty in removing the tubing.

- The pitch determined for each of the series SY piping ports (A, B, etc.) is based on the assumption that series KJ one-touch fittings will be used. For this reason, other pipe fittings may interfere with each other depending on their type and size. Dimensions should be confirmed in a pipe fitting catalogue before they are used.

## Other Tubing Brands

### ⚠ Caution

**1. When using other than SMC brand tubing, confirm that the following specifications are satisfied with respect to the outside diameter tolerance of the tubing.**

- |                        |   |
|------------------------|---|
| 1) Nylon tubing        | within $\pm 0.1$ mm                     |
| 2) Soft nylon tubing   | within $\pm 0.1$ mm                     |
| 3) Polyurethane tubing | within $+0.15$ mm,<br>within $-0.2$ mm. |

Do not use tubing which do not meet these outside diameter tolerances. It may not be possible to connect them, or they may cause other trouble, such as air leakage or the tubing pulling out after connection.

## M8 Connector


### ⚠ Caution

1. M8 connector types have an IP65 (enclosure) rating, offering protection from dust and water. However please note: these products are not intended for use in water. Select a SMC connector cable (V100-49-1-□) or a FA sensor type connector, with M8 threaded 3 pin specifications conforming to Nippon Electric Control Equipment Association Standard, NECA4202 (IEC60947-5-2). Make sure the connector O.D. is 10.5mm or less when used with the Series SY3000 manifold. If more than 10.5mm, it cannot be mounted due to the size.
2. Do not use a tool to mount the connector, as this may cause damage. Only tighten by hand. (0.4 to 0.6 N·m)
3. The excessive stress on the cable connector will not be able to satisfy the IP65 rating. Please use caution and do not apply a stress of 30 N or greater.

### ⚠ Caution

Failure to meet IP65 performance may result if using alternative connectors than those shown above, or when insufficiently tightened.

#### Connector cable mounting



Note) Connector cable should be mounted in the correct direction.

Make sure that the arrow symbol on the connector is facing the triangle symbol on the valve when using SMC connector cable (V100-49-1-□).

Be careful not to squeeze it in the wrong direction, as problems such as pin damage may occur.



# Series SY Specific Product Precautions 8

Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

## M8 Connector

### ⚠ Caution

#### ■ Connector cable

- Connector cable for M8 can be ordered as follows:

#### How to Order

- To order solenoid valve and connector cable at the same time.  
(Connector cable will be included in the shipment of the solenoid valve.)

SY<sup>3</sup><sub>5</sub><sub>7</sub><sub>9</sub> □ □ □ - □ □ □ □ □ - □ □ □ - Q

Electrical entry

**W1, WA1:** Cable length 300 mm

**W2, WA2:** Cable length 500 mm

**W3, WA3:** Cable length 1000 mm


**W4, WA4:** Cable length 2000 mm

**W7, WA7:** Cable length 5000 mm

Ex. 1) Cable length: 300mm  
SY312-5W1ZE-C4-Q


Symbol for electrical entry

- To order connector cable only



| Cable length (L) | No.         |
|------------------|-------------|
| 300 mm           | V100-49-1-1 |
| 500 mm           | V100-49-1-2 |
| 1000 mm          | V100-49-1-3 |
| 2000 mm          | V100-49-1-4 |
| 5000 mm          | V100-49-1-7 |

### [Dimensions when installed]



## Solenoid Valve Mounting

### ⚠ Caution

Mount it so that there is no slippage or deformation in gaskets, and tighten with the tightening torque as shown below.


| Model  | Thread size | Tightening torque |
|--------|-------------|-------------------|
| SY3000 | M2          | 0.16 N·m          |
| SY5000 | M3          | 0.8 N·m           |
| SY7000 | M4          | 1.4 N·m           |
| SY9000 | M3          | 0.8 N·m           |

## Replacement of Pilot Valve


### ⚠ Caution

Pilot valves in this series are improved to provide excellent energy saving results. However following this improvement, these new valves are no longer compatible with the conventional pilot valve used at the interface. Consult with SMC when you need to exchange these pilot valves, in the case of manual override (marked in orange) of the adapter plate.

#### New type



#### Conventional type





# Series SY

## Specific Product Precautions 9

Be sure to read before handling.

Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

### Interface Regulator

#### ⚠ Caution

#### Specifications

| Interface regulator model                      | ARBY3000-□-P-2      | ARBY3000-□-A <sup>1</sup> <sub>B<sup>1</sup></sub> -2 | ARBY5000-□-P-2       | ARBY5000-□-A <sup>1</sup> <sub>B<sup>1</sup></sub> -2 | ARBY7000-□-P-2       | ARBY7000-□-A <sup>1</sup> <sub>B<sup>1</sup></sub> -2 |
|--|---------------------|---|----------------------|---|----------------------|---|
| Applicable solenoid valve model                | SY3□40(R)           |   | SY5□40(R)            |   | SY7□40(R)            |   |
| Regulated port                                 | P                   | A B   | P                    | A B   | P                    | A B   |
| Set pressure range                             | 0.1 to 0.7 MPa      |   |                      |   |                      |   |
| Maximum operating pressure                     | 0.7 MPa             |   |                      |   |                      |   |
| Fluid  | Air                 |   |                      |   |                      |   |
| Ambient and fluid temperature                  | Max. 50°C           |   |                      |   |                      |   |
| Connection port of pressure gauge              | M5                  |   |                      |   |                      |   |
| Weight W (g)                                   | With pressure gauge | 46 g (05), 50 g (06)                                  |                      | 66.8 g  | 110.8 g              |   |
|  | With plug           | 20 g  |                      | 60.4 g  | 103.2 g              |   |
| Supply side effective area <sup>Note 3)</sup>  | P→A,B               | —   | 2.45 mm <sup>2</sup> | —   | 7.61 mm <sup>2</sup> | 13.54 mm <sup>2</sup>                                 |
| Exhaust side effective area <sup>Note 3)</sup> | A,B→EA,EB           | 4.05 mm <sup>2</sup>                                  | 3.91 mm <sup>2</sup> | 11.1 mm <sup>2</sup>                                  | 10.1 mm <sup>2</sup> | 15.71 mm <sup>2</sup>                                 |


Note 1) Pressurise the interface regulator from P port on the base.

Note 2) With closed center and pressure center valves, the pressure can be regulated through P port only.


Note 3) Effective area, excluding the regulated port, when a primary pressure of 0.5 MPa is supplied with regulators mounted on the solenoid valves (2 positions) and sub-plate. Refer to "Flow Characteristics" regarding the regulated port.

Note 4) Valves for weight include gasket and mounting screws.

Note 5) With A, B ports regulated (P port controlled A, B ports regulated), the effective area (Cv factor) for the regulated port and unregulated passage (P to B or P to A) decreases as shown in the graph below when the set pressure is 0.25 MPa or less.




#### JIS Symbol



#### How to Order Interface Regulator

### ARBY3000-05-P-2



- Regulated port
 

|    |   |
|----|---|
| P  | P port                                  |
| A1 | A port (P controlled, A port regulated) |
| B1 | B port (P controlled, B port regulated) |
- Pressure gauge connection port
 

|    |   |
|----|---|
| 05 | Pressure gauge (G15-10-01) [for odd number stations]  |
| 06 | Pressure gauge (G15-10-01) [for even number stations] |
| M1 | Plug (M-5P)   |

Note) For series ARBY3000 with pressure gauge, note that the part numbers for odd number and even number stations differ to prevent interference between the pressure gauges when installing on the manifold.

### ARBY5000-00-P-2




- Regulated port
 

|    |   |
|----|---|
| P  | P port                                  |
| A1 | A port (P controlled, A port regulated) |
| B1 | B port (P controlled, B port regulated) |
- Pressure gauge connection port
 

|    |                            |
|----|----------------------------|
| 00 | Pressure gauge (G15-10-01) |
| M1 | Plug (M-5P)                |

### ARBY7000-00-P-2



- Regulated port
 

|    |   |
|----|---|
| P  | P port                                  |
| A1 | A port (P controlled, A port regulated) |
| B1 | B port (P controlled, B port regulated) |
- Pressure gauge connection port
 

|    |                            |
|----|----------------------------|
| 00 | Pressure gauge (G15-10-01) |
| M1 | Plug (M-5P)                |



# Series SY

## Specific Product Precautions 10

Be sure to read before handling.


Refer to back page 1 through to 5 for Safety Instruction and Common Precautions.

### Flow Characteristics


(Conditions: Inlet pressure 0.7 MPa when 2 position solenoid valve is mounted.)

#### ARBY3000

P port regulated (P→A, B)




A1 port regulated (P→A),  
B1 port regulated (P→B)




#### ARBY5000

P port regulated (P→A, B)




A1 port regulated (P→A),  
B1 port regulated (P→B)




#### ARBY7000

P port regulated (P→A, B)



A1 port regulated (P→A),  
B1 port regulated (P→B)







## EUROPEAN SUBSIDIARIES:



### Austria

SMC Pneumatik GmbH (Austria).  
Girakstrasse 8, A-2100 Korneuburg  
Phone: +43 2262-62280, Fax: +43 2262-62285  
E-mail: office@smc.at  
http://www.smc.at



### France

SMC Pneumatique, S.A.  
1, Boulevard de Strasbourg, Parc Gustave Eiffel  
Bussy Saint Georges F-77607 Marne La Vallée Cedex 3  
Phone: +33 (0)1-6476 1000, Fax: +33 (0)1-6476 1010  
E-mail: contact@smc-france.fr  
http://www.smc-france.fr



### Netherlands

SMC Pneumatics BV  
De Ruyterkade 120, NL-1011 AB Amsterdam  
Phone: +31 (0)20-5318888, Fax: +31 (0)20-5318880  
E-mail: info@smcpneumatics.nl  
http://www.smcpneumatics.nl



### Spain

SMC España, S.A.  
Zuazobidea 14, 01015 Vitoria  
Phone: +34 945-184 100, Fax: +34 945-184 124  
E-mail: post@smc.smces.es  
http://www.smces.es



### Belgium

SMC Pneumatics N.V./S.A.  
Nijverheidsstraat 20, B-2160 Wommelgem  
Phone: +32 (0)3-355-1464, Fax: +32 (0)3-355-1466  
E-mail: info@smcpneumatics.be  
http://www.smcpneumatics.be



### Germany

SMC Pneumatik GmbH  
Boschring 13-15, D-63329 Egelsbach  
Phone: +49 (0)6103-4020, Fax: +49 (0)6103-402139  
E-mail: info@smc-pneumatik.de  
http://www.smc-pneumatik.de



### Norway

SMC Pneumatics Norway A/S  
Vollsveien 13 C, Granfos Næringspark N-1366 Lysaker  
Tel: +47 67 12 90 20, Fax: +47 67 12 90 21  
E-mail: post@smc-norge.no  
http://www.smc-norge.no



### Sweden

SMC Pneumatics Sweden AB  
Ekhagsvägen 29-31, S-141 71 Huddinge  
Phone: +46 (0)8-603 12 00, Fax: +46 (0)8-603 12 90  
E-mail: post@smcpneumatics.se  
http://www.smc.nu



### Bulgaria

SMC Industrial Automation Bulgaria EOOD  
16 Kliment Ohridski Blvd., fl.13 BG-1756 Sofia  
Phone: +359 2 9744492, Fax: +359 2 9744519  
E-mail: office@smc.bg  
http://www.smc.bg



### Greece

SMC Hellas EPE  
Anagenisseos 7-9 - P.C. 14342. N. Philadelphia, Athens  
Phone: +30-210-2717265, Fax: +30-210-2717766  
E-mail: sales@smchellas.gr  
http://www.smchellas.gr



### Poland

SMC Industrial Automation Polska Sp.z.o.o.  
ul. Poloneza 89, PL-02-826 Warszawa,  
Phone: +48 22 211 9600, Fax: +48 22 211 9617  
E-mail: office@smc.pl  
http://www.smc.pl



### Switzerland

SMC Pneumatik AG  
Dorfstrasse 7, CH-8484 Weisslingen  
Phone: +41 (0)52-396-3131, Fax: +41 (0)52-396-3191  
E-mail: info@smc.ch  
http://www.smc.ch



### Croatia

SMC Industrijska automatika d.o.o.  
Cromerec 12, 10000 ZAGREB  
Phone: +385 1 377 66 74, Fax: +385 1 377 66 74  
E-mail: office@smc.hr  
http://www.smc.hr



### Hungary

SMC Hungary Ipari Automatizálási Kft.  
Budafoki út 107-113, H-1117 Budapest  
Phone: +36 1 371 1343, Fax: +36 1 371 1344  
E-mail: office@smc.hu  
http://www.smc.hu



### Portugal

SMC Sucursal Portugal, S.A.  
Rua de Engº Ferreira Dias 452, 4100-246 Porto  
Phone: +351 22-610-89-22, Fax: +351 22-610-89-36  
E-mail: postpt@smc.smces.es  
http://www.smces.es



### Turkey

Entek Pnömatik San. ve Tic Ltd. Sti.  
Perpa Tic. Merkezi Kat: 11 No: 1625, TR-80270 Okmeydanı Istanbul  
Phone: +90 (0)212-221-1512, Fax: +90 (0)212-221-1519  
E-mail: smc-entek@entek.com.tr  
http://www.entek.com.tr



### Czech Republic

SMC Industrial Automation CZ s.r.o.  
Hudcova 78a, CZ-61200 Brno  
Phone: +420 5 414 24611, Fax: +420 5 412 18034  
E-mail: office@smc.cz  
http://www.smc.cz



### Ireland

SMC Pneumatics (Ireland) Ltd.  
2002 Citywest Business Campus, Naas Road, Saggart, Co. Dublin  
Phone: +353 (0)1-403 9000, Fax: +353 (0)1-464-0500  
E-mail: sales@smcpneumatics.ie  
http://www.smcpneumatics.ie



### Romania

SMC Romania srl  
Str Frunzei 29, Sector 2, Bucharest  
Phone: +40 213205111, Fax: +40 213261489  
E-mail: smcromania@smcromania.ro  
http://www.smcromania.ro



### UK

SMC Pneumatics (UK) Ltd  
Vincent Avenue, Crownhill, Milton Keynes, MK8 0AN  
Phone: +44 (0)800 1382930 Fax: +44 (0)1908-555064  
E-mail: sales@smcpneumatics.co.uk  
http://www.smcpneumatics.co.uk



### Denmark

SMC Pneumatik A/S  
Knudsminde 4B, DK-8300 Odder  
Phone: +45 70252900, Fax: +45 70252901  
E-mail: smc@smc-pneumatik.dk  
http://www.smc.dk.com



### Italy

SMC Italia S.p.A  
Via Garibaldi 62, I-20061 Carugate, (Milano)  
Phone: +39 (0)2-92711, Fax: +39 (0)2-9271365  
E-mail: mailbox@smcitalia.it  
http://www.smcitalia.it



### Russia

SMC Pneumatik LLC.  
4B Sverdlovskaja nab, St. Petersburg 195009  
Phone: +7 812 718 5445, Fax: +7 812 718 5449  
E-mail: info@smc-pneumatik.ru  
http://www.smc-pneumatik.ru



### Estonia

SMC Pneumatics Estonia OÜ  
Laki 12, 106 21 Tallinn  
Phone: +372 6510370, Fax: +372 65110371  
E-mail: smc@smcpneumatics.ee  
http://www.smcpneumatics.ee



### Latvia

SMC Pneumatics Latvia SIA  
Smerla 1-705, Riga LV-1006  
Phone: +371 781-77-00, Fax: +371 781-77-01  
E-mail: info@smclv.lv  
http://www.smclv.lv



### Slovakia

SMC Priemyselná Automatizácia, s.r.o.  
Námestie Matina Benku 10, SK-81107 Bratislava  
Phone: +421 2 444 56725, Fax: +421 2 444 56028  
E-mail: office@smc.sk  
http://www.smc.sk



### Finland

SMC Pneumatics Finland Oy  
PL72, Tiistiniityntie 4, SF-02231 ESPOO  
Phone: +358 207 513513, Fax: +358 207 513595  
E-mail: smcfi@smc.fi  
http://www.smc.fi



### Lithuania

SMC Pneumatics Lietuva, UAB  
Oslo g.1, LT-04123 Vilnius  
Phone: +370 5 264 81 26, Fax: +370 5 264 81 26



### Slovenia

SMC industrijska Avtomatika d.o.o.  
Mirska cesta 7, SLO-8210 Trebnje  
Phone: +386 7 3885412 Fax: +386 7 3885435  
E-mail: office@smc.si  
http://www.smc.si



## OTHER SUBSIDIARIES WORLDWIDE:

ARGENTINA, AUSTRALIA, BOLIVIA, BRASIL, CANADA, CHILE,  
CHINA, HONG KONG, INDIA, INDONESIA, MALAYSIA, MEXICO,  
NEW ZEALAND, PHILIPPINES, SINGAPORE, SOUTH KOREA,  
TAIWAN, THAILAND, USA, VENEZUELA

<http://www.smc.eu>  
<http://www.smcworld.com>