



PLUG-IN RELAY COMPLETE UNIT DC 24V,  
4 CO CONTACT LED MODULE RED STANDARD PLUG-IN  
SOCKET SCREW TERMINAL 3.5 MM PINNING

**General technical details:**

<b>type of voltage</b>		DC
<b>Control supply voltage</b>		
• for DC / rated value		
• minimum	V	24
• maximum	V	24
<b>Number of NC contacts</b>		
• for auxiliary contacts		0
<b>Number of NO contacts</b>		
• for auxiliary contacts		0
<b>Number of changeover contacts</b>		
• for auxiliary contacts		4
<b>Operating current / of the auxiliary contacts</b>		
• at DC-13		
• at 24 V	A	6
• at AC-15		
• at 230 V	A	4
<b>Design of the switching function</b>		
• guided		changeover switch
		No
<b>Switching behaviour</b>		monostable

### Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		Yes
Width	mm	28
Height	mm	72
Depth	mm	74

### Certificates/approvals:

General Product Approval

other



GOST

[Declaration of Conformity](#)

### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/LZS:PT5A5L24/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=LZS:PT5A5L24](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZS:PT5A5L24)

last change:

Feb 25, 2013