

Powered by



## Rechargeable Li-ion battery pack – 1691.01.001.1 Configuration: 2S2P



### Dimensions:

**Length:** 37 ±1mm

**Width:** 39 ±1mm

**Height:** 68,5 ±1mm

### Data for pack

Nominal Voltage	7.3V		
Rated Capacity	5.34Ah		
Used cell in Pack	4pcs	INR18650-29E	
Internal resistance pack	100mΩ	±10%	
Max charge voltage	8.4V	25°C	
Charge current	standard	2.75A	25°C
	rapid	3A	25°C
Discharge	standard	1.1A	25°C
	max. cont.	3A	25°C
	max. Peak	5A	25°C t<70s
Short Circuit current	60A	t<450μs	
Cable length	150mm	± 5mm	
Weight	190g	±10g	
Watt-hour rating	39Wh		
Charge temperature	standard	0°C - 45°C	
	rapid	10°C - 40°C	
Discharge temperature	standard	-20°C - 60°C	
Storage temperature	1 year	0~23°C	
Note 1: Self discharge <1% / month			
Note 2: Delivery SOC approx. 30%			

### Limitations by Safety Unit (SU)

Over Voltage (per cell)	cut off	4.35V	±0.025
	release	4.05V	±0.05
Under Voltage (per cell)	cut off	2.4V	±0.08
	release	3V	±0.075
Current Limit 1 by SU		5A	t~70s
Current Limit 2 by SU		8A	t~20ms
Power Consumption	active		