

Powered by



Rechargeable Li-ion battery pack – 1698.01.001.1 Configuration: 4S1P



Dimensions:

Length: 74 ±1mm

Width: 22 ±1mm

Height: 69 ±1mm

Data for pack

Nominal Voltage	14.6V		
Rated Capacity	2.67Ah		
Used cell in Pack	4pcs	INR18650-29E	
Internal resistance pack	230mΩ	±10%	
Max charge voltage	16.8V	25°C	
Charge current	standard	1.37A	25°C
	rapid	2A	-
Discharge	standard	0.5A	25°C
	max. cont.	2A	25°C
	max. Peak	4.5A	25°C
Short Circuit current	73A		t<1ms
Cable length	150mm	±5mm	
Weight	200g	±10g	
Watt-hour rating	39Wh		
Charge temperature	standard	0°C - 45°C	
	rapid	10°C - 40°C	
Discharge temperature	standard	-20°C - 60°C	
Storage temperature	1 year	0~23°C	
Note 1: Self discharge <1% / month			
Note 2: Delivery SOC approx. 30%			

Limitations by Safety Unit (SU)

Over Voltage (per cell)	cut off	4.35V	±0.025
	release	4.15V	±0.05
Under Voltage (per cell)	cut off	2.4V	±0.08
	release	3.0V	±0.1
Current Limit 1 by SU		4.5A	t~15s
Current Limit 2 by SU		5.3A	t~60ms
Power Consumption	active		