

Powered by



Rechargeable Li-ion battery pack – 1699.01.001.1 Configuration: 4S2P



Dimensions:

Length: 74,5 ±1mm

Width: 40 ±1mm

Height: 68 ±1mm

Data for pack

Nominal Voltage	14.6V		
Rated Capacity	5.54Ah		
Used cell in Pack	8pcs	INR18650-29E	
Internal resistance pack	155mΩ	±10%	
Max charge voltage	16.8V	25°C	
Charge current	standard	2.75A	25°C
	rapid	3.3A	25°C
Discharge	standard	1.1A	25°C
	max. cont.	3.3A	25°C
	max. Peak	4.5A	25°C t<60s
Short Circuit current	115A	t<1ms	
Cable length	150mm	± 5mm	
Weight	385g	±10g	
Watt-hour rating	81Wh		
Charge temperature	standard	0°C - 45°C	
	rapid	10°C - 40°C	
Discharge temperature	standard	-20°C - 60°C	
Storage temperature	1 year	0~23°C	
Note 1: Self discharge <1% / month			
Note 2: Delivery SOC aprox. 30%			

Limitations by Safety Unit (SU)

Over Voltage (per cell)	cut off	4.35V	±0.025
	release	4.15V	±0.05
Under Voltage (per cell)	cut off	2.4V	±0.08
	release	3.0V	±0.1
Current Limit 1 by SU		4.5A	t~60s
Current Limit 2 by SU		5.5A	t~70ms
Power Consumption	active		