



Specification:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug
	AC/DC-CL-DT 12/7	12	0	7	+/- 5	>87	84	<150	2,1x5,5X11
input	voltage				100 - 240V				
	voltage range				90 - 264V				
	frequency min. / max				47 - 63 Hz				
	frequency				60HZ / 50Hz				
	current				1.8Amax				
	inrush current				60Amax@240VAC				
protection	OCP				Overload				
	OVP				Over voltage				
	SC				Short circuit				
	insulation				Class II				
	min. load requirement				No				
others	MTBF				50000h				
	efficiency				> 87 %				
	dimensions / weight				116 x 56x 34 mm / 330 g				
environmental	operating temp.				0 ~40 deg C				
	storage temp.				-10 ~80 deg C				
	relative humidity				5 ~90% RH				
	storage relative humidity				5% ~90% RH				
safety	CE				EN60950-1				
	TUV - GS				EN60950-1				
EMC	EMI				Meet the limits EN 55022 CLASS B rules				
	EMS				EN 61000-3-2, EN 61000-3-3				
					EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003				