

FEATURES:

Super Slim Model (22 mm)

MTBF – 50 000 h

Meets energy star level V

Universal AC input / full range



SPECIFICATION:

| output | Model | Voltage DC [V] | Current min [A] | Current max. [A] | Tolerance [%] | Efficiency [%] | Power max. [W] | Ripple & noise [mV] | DC plug [mm] |
|---------------|---|---|-----------------|------------------|---------------|----------------|----------------|---------------------|------------------|
| | Cellevia AC/DC-CL-DT 19.5/4.6-5074 | 19.5 | 0.05 | 4.6 | +/- 5 | >87 | 90 | 300 | 5.0x7.4 for DELL |
| input | voltage | 100 - 240V | | | | | | | |
| | voltage range | 90 - 264V | | | | | | | |
| | frequency min. / max | 47 - 63 Hz | | | | | | | |
| | frequency | 60HZ / 50Hz | | | | | | | |
| | current | 1.3 Amax @ 100 VAC | | | | | | | |
| | inrush current | 80 Amax @ 264 VAC | | | | | | | |
| protection | OCP | Overload | | | | | | | |
| | OVP | Over voltage | | | | | | | |
| | SC | Short circuit | | | | | | | |
| | insulation | Class II | | | | | | | |
| | min. load requirement | 0.05A | | | | | | | |
| others | MTBF | 50000h | | | | | | | |
| | efficiency [%] | >87 | | | | | | | |
| | dimensions / weight | 130 x 64 x 22.5 mm / 241g (50pcs/cartoon) | | | | | | | |
| environmental | operating temp. | 0 ~40 deg C | | | | | | | |
| | storage temp. | -40 ~80 deg C | | | | | | | |
| | relative humidity | 5 ~90% RH | | | | | | | |
| | storage relative humidity | 5% ~90% RH | | | | | | | |
| safety | CE | EN60950-1 | | | | | | | |
| | TUV - GS | EN60950-1 | | | | | | | |