

FEATURES:



Meets energy star level VI

MTBF – 50 000 h

DC Cable - L=1200mm

OCP / OVP / SC



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug
	CLD-3015-T2	15	0	2	+/- 5	>86	30	200	2.1x5.5x11
input	voltage				100 - 240V				
	voltage range				90 - 264V				
	frequency min. / max				47 - 63 Hz				
	frequency				60HZ / 50Hz				
	variation Frequency				47-63Hz				
	current				0.75Amax @ 115VAC				
	inrush current				50 Amax @ 230VAC				
leakage current				0,25mA @ 264WAC					
protection	OCP				Overload				
	OVP				Over voltage				
	SC				Short circuit				
	insulation				Class II				
	min. load requirement				No				
others	MTBF				50000h				
	efficiency				> 86 %				
	dimensions / weight				105 x 45 x 28 mm / 191g				
environmental	operating temp.				0 ~40 deg C				
	storage temp.				-10 ~85 deg C				
	relative humidity				25 ~75% RH				
	storage relative humidity				5% ~90% RH				
safety	CE				EN 60950-1				
	TUV - GS				EN 60950-1				
EMC	EMI				EN 55022 CLASS B				
	EMS				EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN 61000-4-5, EN 61000-4-6 EN 61000-4-8, EN 61000-4-11				