

Slim wall socket housing

2 years warranty period

MTBF – 50 000 h

Meets energy star level V

Universal AC input / full range



output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug		
	ESPE 1512	12	0	1,25	+/- 5	>75	15	120	2,1x5,5X11		
input	voltage					100 - 240V					
	voltage range					90 - 264V					
	frequency min. / max					47 - 63 Hz					
	frequency					60HZ / 50Hz					
	current					0,5Amax@115VAC					
	inrush current					30Amax@230VAC					
protection	OCP					Overload					
	OVP					Over voltage					
	SC					Short circuit					
	insulation					Class II					
	min. load requirement					No					
others	MTBF					35000h					
	efficiency					> 75 %					
	dimensions / weight					73 x 28 x 42 mm / 155 g (120pcs/cartoon)					
environmental	operating temp.					0 ~40 deg C					
	storage temp.					-20 ~85 deg C					
	relative humidity					20 ~90% RH					
	storage relative humidity					20% ~90% RH					
safety	CE					EN60950-1					
	TUV - GS					EN60950-1					
EMC	EN 55022:1998, +A1:2000 +A2:2003, CLASS B										
	EMI	CISPR 22:2003, CLASS B									
		AS/NZS CISPR22: 2004, CLASS B									
	EMS	EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN61000-4-5, EN61000-4-6 EN 61000-4-8, EN 61000-4-11									