

FEATURES:

Slim wall socket housing

MTBF – 50 000 h

Meets energy star level V



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug
	ESPE 0605-P-iUSB	5	0.01	1.2	+/- 5	>68	6	100	socket USB
input	voltage				220 - 240V				
	voltage range				200 - 264V				
	frequency min. / max				47 – 53 Hz				
	frequency				60HZ / 50Hz				
	current				0.12 Amax				
	inrush current				20Amax@240VAC				
protection	OCP				Overload				
	OVP				Over voltage				
	SC				Short circuit				
	insulation				Class II				
	min. load requirement				0,01				
others	MTBF				50000h				
	efficiency				> 68 %				
	dimensions / weight				48 x 38.1 x 20.3 mm / 27g (200pcs/cartoon)				
environmental	operating temp.				0 ~40 deg C				
	storage temp.				-10 ~80 deg C				
	relative humidity				25 ~75% RH				
	storage relative humidity				25% ~75% RH				
saferty	CE				EN60950-1				
	TUV - GS				EN60950-1				
EMC	EMI				EN 55022:1998, +A1:2000 +A2:2003, CLASS B CISPR 22:2003, CLASS B AS/NZS CISPR22: 2004, CLASS B				
	EMS				EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN61000-4-5, EN61000-4-6 EN 61000-4-8, EN 61000-4-11				