

FEATURES:

- Slim wall socket housing*
- 2 years warranty period*
- MTBF – 50 000 h*
- Meets energy star level V*
- Widel AC input / full range*



SPECIFICATION:

output	Model	Voltage DC [V]	Current min [A]	Current max. [A]	Tolerance [%]	Efficiency [%]	Power max. [W]	Ripple & noise [mV]	DC plug
	ESPE 1512L H2E	12	0	1.2	+/- 5	>78.8	15	120	2,1x5,5x11 L
input	voltage	100 - 240V							
	voltage range	90 - 264V							
	frequency min. / max	47 - 63 Hz							
	frequency	60HZ / 50Hz							
	current	0.5 Amax @ 100 - 240 VAC							
	inrush current	30 Amax @ 264 VAC							
protection	OCP	Overload							
	OVP	Over voltage							
	SC	Short circuit							
	insulation	Class II							
	min. load requirement	No							
others	MTBF	50000h							
	efficiency	> 78.8 %							
	dimensions (LxWxH) / weight	60 x 30 x 74 mm / 144g (120pcs/cartoon)							
environmental	operating temp.	0 ~40 deg C							
	storage temp.	-20 ~80 deg C							
	relative humidity	10 ~90% RH							
	storage relative humidity	5% ~95% RH							
safety	CE	EN60950-1							
	TUV - GS	EN60950-1							
EMC	EMI	EN 55022:1998, +A1:2000 +A2:2003, CLASS B							
		CISPR 22:2003, CLASS B							
		AS/NZS CISPR22: 2004, CLASS B							
	EMS	EN 61000-3-2, EN 61000-3-3, EN 61000-4-2, EN 6100-4-3, EN 6100-4-4, EN61000-4-5, EN61000-4-6 EN 61000-4-8, EN 61000-4-11							