

 $\textbf{EMERGENCY POWER SUPPLY | UPS} \underline{\text{https://www.qoltec.com/product/emergency-power-supply-ups/uninterruptible-power-supply-strip/uninterruptible-power-supply-monolith-650va-390w-2xustantions and the product of the$



Uninterruptible Power Supply | Monolith | 650VA | 390W | 2xUSB

Product code: 53965

High quality uninterruptible power supplies ensure stable operation of connected electronic devices even in the case of power failure.

Power: 390W

Sockets: 3 x SCHUKO Backup and Surge Protection

3 x SCHUKO Surge Protection

2 x USB (5V, 2A)

TECHNICAL DATA

USABLE POWER	390 W
RATED CAPACITY	650 VA
POWER FACTORY	0.6
LOAD TYPE	Personal computer and other PC peripheral devices
AC VOLTAGE RANGE	140Vac ~ 290Vac
AC FREQUENCY	50Hz 10%
OUTPUT RANGE (LINE)	220Vac 10%
OUTPUT FREQUENCY (LINE)	50Hz 10%
OUTPUT VOLTAGE (BATTERY)	220Vac ~ 230Vac 5%
OUTPUT FREQUENCY (BATTERY)	50Hz - 60Hz 1Hz
OUTPUT SOCKETS	3 x SCHUKO Backup and Surge Protection 3 x SCHUKO Surge Protection 2 x USB (5V, 2A)
BACKUP TIME	10 - 20 min
BUILT-IN BATTERY	1 x 12V/7Ah
CHARGING TIME	6 to 8 hours
STORAGE TEMPERATURES	-15°C to 45°C
OPERATING TEMPERATURE	20°C to +40°C
ENVIRONMENT HUMIDITY	0% - 95%

WWW.QOLTEC.COM 1 / 2

RELATIVE HUMIDITY	0% - 90%
SAFETY	Overload protection Short Circuit Protection Overheat Protection High / Iow Voltage Protection Input Fuses Protection
USAGE	Home and office applications
ADDITIONAL INFORMATION	2 USB ports Note: Uninterruptible Power Supplies are not intended for use with medical devices, including life support or health equipment.
PACKAGE CONTENTS	UPS Power cable (1 x SCHUKO) 1.2m User manual
NOISE	Less than 40dB
DIMENSIONS	185 x 280 x 95 mm
WEIGHT	5.5 kg
WARRANTY	24 months
WAVE FORM	Simulated sine wave
FUNCTIONS	Microprocessor - based digital control Automatic voltage regulator Alarm with configuration capability Power on self-test Auto restart when mains power is restored Cold start Simulated sine wave output Intelligent battery management Automatic charging in OFF mode
EAN CODE	5901878539652

WWW.QOLTEC.COM 2 / 2