



Uninterruptible power supply | Monolith | 650VA | 360W

Product code: 53970

Qoltec offline UPS emergency power supply is a modern and economical device that ensures stable operation of connected electronic devices even in the event of a power failure. The duration of a power supply with a 100W load is 14 minutes. The UPS protects connected devices against loss and voltage drop in the network and excludes the possibility of damage in the event of overvoltages in the electricity network, also protects against overloads and short circuits.

The Qoltec offline UPS will meet the requirements of anyone who wants to have control over the stable operation of their devices regardless of fluctuations in the mains supply. Thanks to the highest quality and wide range of operation, it is an ideal solution for powering desktops and other peripheral devices at home or in the enterprise, as well as in educational institutions and offices.

TECHNICAL DATA

INPUT VOLTAGE	110 VAC to 120 VAC or 220 VAC to 230 VAC
OUTPUT VOLTAGE	110 VAC to 120 VAC or 220 VAC to 230 VAC
WAVE FORM	Simulated sine wave
RUNTIME (100W)	14 min
USABLE POWER	360 W
RATED CAPACITY	650 VA
LOAD TYPE	Personal computer and other PC peripheral devices
AC VOLTAGE RANGE	140-300 VAC
AC FREQUENCY	50 Hz to 60 Hz (Auto sensing)
OUTPUT FREQUENCY (BATTERY)	50 Hz to 60 Hz 1 Hz
TRANSFER TIME	2-6 ms
OUTPUT SOCKETS	2 x french
BATTERY	Lead-acid battery
BATTERY VOLTAGE	13.7 V
BUILT-IN BATTERY	1x12V / 7Ah

CHARGING TIME 4-6 hours recover to 90% capacity

STORAGE TEMPERATURES -15 C to +45 C

OPERATING TEMPERATURE 0°C to 40°C

RELATIVE HUMIDITY 0% to 90%

SAFETY Overload
Discharge
Overcharge
Short Circuit Protection
Under/Overvoltage Protection

USAGE PC, terminal, small load devices

ADDITIONAL INFORMATION Compact size and ergonomic design: it can be placed on a desktop or other convenient location
Stylish case with LED indicators
Perfect protection for overload, short circuit, over voltage, low voltage and overheating
Double boost and AVR for voltage stabilization
Excellent microprocessor control optimizes reliability
Off mode charging and cold start function
The fastest charging capacity
Line mode, battery mode and fault alarm
Auto restart while AC is recovering
Eco friendly and user friendly
Low transfer time <5ms
Frequency auto adaptive
Low maintenance cost
Wide input range
Easy installation

NOISE 35dB (1 meter from front panel)

DIMENSIONS 279 x 101 x 142 mm

WEIGHT 4.2 kg

WARRANTY 24 months

EAN CODE 5901878539706