



Uninterruptible power supply | Monolith | 1500VA | 900W

Product code: 53974

Qoltec offline UPS emergency power supply is a modern and economical device that ensures stable operation of connected electronic devices even in the event of a power failure. The duration of a power supply with a 100W load is 50 minutes. The UPS protects connected devices against loss and voltage drop in the network and excludes the possibility of damage in the event of overvoltages in the electricity network, also protects against overloads and short circuits.

The Qoltec offline UPS will meet the requirements of anyone who wants to have control over the stable operation of their devices regardless of fluctuations in the mains supply. Thanks to the highest quality and wide range of operation, it is an ideal solution for powering desktops and other peripheral devices at home or in the enterprise, as well as in educational institutions and offices.

TECHNICAL DATA

INPUT VOLTAGE	140 VAC do 290 VAC
OUTPUT VOLTAGE	220 VAC to 230 VAC
RUNTIME (100W)	50 min
USABLE POWER	900 W
RATED CAPACITY	1500 VA
LOAD TYPE	Personal computer and other PC peripheral devices
AC VOLTAGE RANGE	170-280 VAC
AC FREQUENCY	50 Hz
OUTPUT FREQUENCY (BATTERY)	50 Hz 1 Hz
TRANSFER TIME	2-6 ms
OUTPUT SOCKETS	2 x french 1 x IEC
BATTERY	Lead-acid battery
BUILT-IN BATTERY	2 x 12V / 9Ah
CHARGING TIME	4-6 hours recover to 90% capacity
STORAGE TEMPERATURES	-15 C to +45 C

OPERATING TEMPERATURE	0°C to 40°C
RELATIVE HUMIDITY	0% to 90%
SAFETY	<ul style="list-style-type: none"> Overload Discharge Overcharge Short Circuit Protection Under/Overvoltage Protection Overheat Protection
USAGE	PC, terminal, small load devices
ADDITIONAL INFORMATION	<ul style="list-style-type: none"> Double boost and AVR for voltage stabilization Built-in smart charger makes charging time shorten Excellent microprocessor control optimizes reliability Off mode charging Cold start function Auto restart while AC is recovering Simulated sine wave Compact size and ergonomic design: it can be placed on a desktop or other convenient location Perfect protection for overload, short circuit, over voltage, low voltage and overheating Excellent microprocessor control optimizes reliability The fastest charging capacity Eco friendly and user friendly Low maintenance cost Wide input range Easy installation
NOISE	Less than 40dB
DIMENSIONS	370 x 135 x 165 mm
WEIGHT	10.5 kg
WARRANTY	24 months
EAN CODE	5901878539744