

**PRO ECO 120W 24V 5A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



You are looking for a reliable power supply with basic functions.  
 With PROeco we can offer you affordable switched-mode power supply units with high efficiency and system capability. Let's connect. Particularly in the series production of machines, switched-mode power supply units with above-average performance values can deliver genuine competitive advantages.  
 The low-cost PROeco series offers all the basic functions and delivers impressively high performance and flexibility. Our PROeco switched-mode power supply units feature a compact design, high efficiency and are extremely easy to service. Thanks to temperature protection, short-circuit strength and overload resistance, they can be universally used in all applications.

Wide-ranging safety functions and the combinability with our diode and capacitance modules as well as UPS components for setting up a redundant power supply, characterise solutions with PROeco.

**General ordering data**

Type	PRO ECO 120W 24V 5A
Order No.	<a href="#">1469480000</a>
Version	Power supply, switch-mode power supply unit, 24 V
GTIN (EAN)	4050118275476
Qty.	1 pc(s).

**PRO ECO 120W 24V 5A**
**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	40 mm	Height	125 mm
Depth	100 mm	Weight	0.6 kg
Net weight	0.58 g		

**Temperatures**

Operating temperature	Storage temperature	-40 °C...+85 °C
-----------------------	---------------------	-----------------

**Input**

AC current consumption	1.2 A @ 230 V AC / 2.4 A @ 115 V AC	AC input voltage range	85...264 V AC (Derating @ 100 V AC)
Connection system [Input]	Screw connection	DC current consumption	0.4 A @ 370 V DC / 1.2 A @ 120 V DC
DC input voltage range	80...370 V DC (Derating @ 120 V DC)	Frequency range AC	47...63 Hz
Input frequency	47...63 Hz	Input fuse (internal)	Yes
Inrush current	max. 40 A	Recommended back-up fuse	4 A / DI, safety fuse 6 A, Char. B, circuit breaker 3...5 A, Char. C, circuit breaker
rated input voltage	100...240 V AC (wide-range input)		

**output**

Connection system [Output]	Screw connection	Output voltage	24 V
Output voltage	22...28 V DC (einstellbar über Potentiometer in der Front)	Overload protection	Yes
Parallel connection option	yes, max. 5	Powerboost @ 24 V DC, 60 °C	3.6 A for 1 min, ED = 5 %
Protection against inverse voltage	Yes	Ramp-up time	≤ 100 ms
Rated (nominal) output current @ U <sub>Nom</sub>	5 A at 55 °C	continuous output current @ 24 V DC	5 A @ 55 °C
rated output voltage	24 V DC ± 1 %	residual ripple, breaking spikes	< 50 mV <sub>SS</sub> @ 24 V DC, I <sub>N</sub>

**General data**

AC failure bridging time @ I <sub>Nom</sub>	> 100 ms @ 230 V AC / > 20 ms @ 115 V AC	Degree of efficiency	88%
Earth leakage current, max.	1 mA	Housing version	Metal, corrosion resistant
MTBF	> 500,000 h acc. to IEC 1709 (SN29500)	Max. perm. air humidity (operational)	5 %...95 % RH
Mounting position, installation notice	Horizontal on TS35 mounting rail, with 50 mm of clearance at top and bottom for air circulation. Can be mounted side by side with no space in between.	Operating temperature	
Protection against over-heating	Yes	Short-circuit protection	Yes
Weight	0.6 kg		

**PRO ECO 120W 24V 5A****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****EMC / shock / vibration**

Limiting of mains voltage harmonic currents	in accordance with EN 61000-3-2	Noise emission acc. to EN55022	Class B
Vibration resistance IEC 60068-2-6		Interference immunity test acc. to	EN 61000-4-2 (ESD), EN 61000-4-3 (RS), EN 61000-4-4 (burst), EN 61000-4-5 (surge), EN 61000-4-6 (conducted), EN61000-4-8 (Fields), EN61000-4-11 (Dips)
	1 g according to EN50178		
Shock resistance IEC 60068-2-27	15 g In all directions		

**Insulation coordination**

Class of protection	I, with PE connection	Insulation voltage, input/output	3 kV
Pollution severity	2		

**Electrical safety (applied standards)**

Electrical machine equipment	Acc. to EN60204	For use with electronic equipment	Acc. to EN50178 / VDE0160
Protection against dangerous shock currents	Acc. to VDE0106-101	Protective separation protection against electrical shock	VDE0100-410 / acc. to DIN57100-410
Safety extra-low voltage	SELV acc. to EN60950, PELV acc. to EN60204	Safety transformers for switch-mode power supplies	Acc. to EN 61558-2-17

**Connection data (input)**

Conductor cross-section, AWGcmil , max.	12	Conductor cross-section, AWGcmil , min.	26
Conductor cross-section, flexible , min.	0.5 mm <sup>2</sup>	Conductor cross-section, rigid , max.	6 mm <sup>2</sup>
Conductor cross-section, rigid , min.	0.5 mm <sup>2</sup>	Connection system [Input]	Screw connection
Number of terminals [Input]	3 for L/N/PE	Tightening torque, max.	0.6 Nm
Tightening torque, min.	0.5 Nm	Wire connection cross section, flexible (input), max.	2.5 mm <sup>2</sup>

**Connection data (output)**

Conductor cross-section, AWGcmil , max.	12	Conductor cross-section, AWGcmil , min.	26
Conductor cross-section, flexible , max.	2.5 mm <sup>2</sup>	Conductor cross-section, flexible , min.	0.5 mm <sup>2</sup>
Conductor cross-section, rigid , max.	6 mm <sup>2</sup>	Conductor cross-section, rigid , min.	0.5 mm <sup>2</sup>
Connection system [Output]	Screw connection	Tightening torque, max.	0.6 Nm
Tightening torque, min.	0.5 Nm		

**Signalling**

Contact load (NO contact)	max. 30 V DC / 0,5 A	Floating contact	Yes
Relay on/off	Output voltage > 21.6 V / < 20.4 V		

**Classifications**

eClass 6.2	27-04-90-04
------------	-------------

**Approvals**

ROHS	Conform
------	---------

Creation date February 26, 2014 2:54:47 PM CET

Catalogue status 15.11.2013 / We reserve the right to make technical changes.

**PRO ECO 120W 24V 5A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Drawings**

**Electric symbol**

