Product datasheet Characteristics

NSYDLA66G

Modular distribution chassis 66 modules for NSYPLM75,NSYS3D75,NSYCRN75,NSYS3X75



Price*: 84.48 GBP



Main

IVIAIII		•
Range	Spacial	
Accessory / separate part category	Mounting accessory	
Application	Multi-purpose Modular distribution application	
Product or component type	Chassis	
Device short name	DLA	
For enclosure nominal dimensions	H: -	
Mounting location	Front of enclosure	
Range compatibility	Spacial CRN Spacial S3D Spacial S3X Thalassa PLM	44
Device composition	1 chassis structure 2 finish cover 1 neutral/earth strip 2 x 16 mm ² 5 x 6 mm ² 3 front panels with 35 mm DIN rail 1 plain front panel with mounting plate	
Quantity per set	Set of 1	

Complementary

Complementary		
Material	Self-extinguishing insulating for front panel Steel for chassis structure and rails	
Colour	Front panel : grey RAL 7035	
Fixing mode	By fixing element - on front with supports location	
Adjustment	In height from 40 to 85 mm for DIN rail	
Number of horizontal rows	4	
Total number of 18 mm modules	66	
Type of front plate	Plain and cut-out plates	
Number of cut-out	4 cut-outs	

Height	680 mm
Width	460 mm

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product Environmental Profile
Product end of life instructions	Need no specific recycling operations