

Price* : 160.52 GBP



Main

Range	Spacial
Product or component type	Drive flush mounting kit
Accessory category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Spacial SF and SM enclosures: H: \geq 600 mm x W: \geq 300 mm Spacial S3D enclosure: H: \geq 600 mm x W: \geq 300 mm Altivar variable speed drive ATV630 Altivar variable speed drive ATV930
Compatibility for Altivar Process 630-930, size:	3
Motor power kW	7.5 kW 220/240 V 11 kW 220/240 V 15 kW 380/480 V 18.5 kW 380/480 V 22 kW 380/480 V
Mounting location	Mode 2 : inside enclosure Mode 1 : back of enclosure on mounting plate
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing by screws and nuts 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic.

Complementary

Permanent permissible load	14.3 kg
Colour	Grey RAL 7035
Height	External : 555 mm Cut-out : 503 mm
Width	External : 295 mm Cut-out : 250 mm
Depth	Wall-enclosure separation : 22 mm
Product weight	2.1 kg
Services	Configuration of enclosure pre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0810 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
