



JUNCTION BOX

# Abox 025-L



## Abox 025-L

Junction box

**CUSTOMIZABLE**

80 x 80 x 52 mm  
Article number: 80290701

Junction box acc. to DIN EN 60670 (VDE 0606), Ui=690V, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

Grey, without terminal



## Technical data

### Measures

Width:	80 mm
Length:	80 mm
Height:	52 mm

### Material:

Cover:	polystyrene
material:	polystyrene
Box:	polystyrene, membrane out of TPE

### Entries

Pre-embossings, top:	2 x M20
Pre-embossings, left/right:	2 x M20
Pre-embossings, bottom:	1 x M20
Pre-embossings, rear side:	1 x M20

## Certificates



## Accessory

- Abox 025/040 KLS-2,5²/4² - Terminal block
- BST M20/sw - Ventilation seal
- Abox PST - Sealing kit
- AST M20 - Attachment bushes
- BST M20 - Ventilation seal
- DMS M20 - Double-membrane seals
- KS M20 - Combi set
- KVR M20-GDB/MGM - Cable gland
- KVR M20-MGM - Cable gland
- MPS-KRI - Mounting plate
- RST M20 - Conduit connector
- SNI M20 - Stepped nipple
- VST M20 - Sealing plugs



JUNCTION BOX

**Abox 025-L**

**Other attributes**

Entries:	8
Rated cross section:	2,5 mm <sup>2</sup>
Tackable:	No
Rated insulation voltage AC:	690 V
Functional integrity:	none
sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. to EN 60529 / DIN VDE 0470-1
weatherproof:	No
Combustion behaviour acc. to UL 94:	HB acc. UL94
Combustion behaviour acc. to VDE:	650°C acc. VDE 0471/ EN 60695
Equipment:	None
Color:	Grey
Cover screw torque:	1 N m

WNI M20 - Twist nipple

WST M20 - Twist plug

**Environmental attributes**

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%