

EK EKPL 180 G



Sample photo

Order symbol: EKPL 180 G
Product nbr: 2538061
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074013644
EI. number:
 Finland: 3425430
 Electric No. Italy: 7501060
 Electric No. Sweden: 2538061

Including: Flanged Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:				Accessories:	
	Length	Width	Height		
mm:	380	280	180	EKPL	Base, PC
inch:	15.0	11.0	7.1	EKP 30-G	Cover
Materials:				EKP 80-G	Cover
Material:	Polycarbonate			EKP 30-T	Cover
Base colour:	RAL 7035 -light grey			EKP 80-T	Cover
Cover screws material:	Polyamide			EKPVT	Mounting plate
Cover colour:	RAL 7035 -light grey			EKPXT	Mounting plate isolated
Cover screws colour:	Grey			EKV 22	DIN-35 Mounting rail
Gasket material:	Polyurethane			EKV 32	DIN-35 Mounting rail
Temperatures:				EKPZR	Extension frame
Temperature °C (short term):	-40 ... 120 °C			Rating:	
Temperature °C (continuous):	-40 ... 80 °C			Ingress Protection (EN 60529): IP66/IP67	
Temperature °F (short term):	-40 ... 250 °F			Impact Resistance (EN 62262): IK08	
Temperature °F (continuous):	-40 ... 175 °F			Electrical insulation: Totally insulated	
Accessories:				Halogen free (DIN/VDE 0472, Part 815): 1	
EKPK	Base, PC			UV resistance: UL 508	
				Flammability Rating: UL 746C 5"	
				Glow Wire Test (IEC 695-2-1) °C: 960	
				NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12	
				Certificates:	
				Germanischer Lloyd (GL)	
				SGS Fimko	
				Lloyds Register of Shipping (LR)	
				Gost R	

