

EK EKH 180 T



Sample photo

Order symbol: EKH 180 T
Product nbr: 2538173
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074013941
EI. number:
 Finland: 3425486
 Electric No. Italy: 7502070
 Electric No. Sweden: 2538173

Including: Flanged Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:		Length	Width	Height	Accessories:	
mm:		560	380	180	EKH	Base, PC
inch:		22.0	15.0	7.1	EKUN	Base, PC
Materials:					EKU 30-G	Cover
Material:		Polycarbonate			EKU 30-T	Cover
Base colour:		RAL 7035 -light grey			EKUVT	Mounting plate
Cover screws material:		Polyamide			EKUXT	Mounting plate isolated
Cover colour:		Clear transparent			EKV 32	DIN-35 Mounting rail
Cover screws colour:		Grey			EKUZR	Extension frame
Gasket material:		Polyurethane			Rating:	
Temperatures:					Ingress Protection (EN 60529): IP66/IP67	
Temperature °C (short term):		-40 ... 120 °C			Impact Resistance (EN 62262): IK08	
Temperature °C (continuous):		-40 ... 80 °C			Electrical insulation: Totally insulated	
Temperature °F (short term):		-40 ... 250 °F			Halogen free (DIN/VDE 0472, Part 815): 1	
Temperature °F (continuous):		-40 ... 175 °F			UV resistance: UL 508	
Accessories:					Flammability Rating: UL 746C 5"	
EKUM		Base, PC			Glow Wire Test (IEC 695-2-1) °C: 960	
					NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12	
Certificates:					Germanischer Lloyd (GL)	
					SGS Fimko	
					Lloyds Register of Shipping (LR)	
					Gost R	

