

CAB CAB PC 405020 G



Order symbol: CAB PC 405020 G
Product nbr: 8113361
Description: Cabinet, PC
Remarks: Latches on the short side

EAN: 6418074020345
EI. number:
 Finland: 3424122
 Electric No. Denmark: 8212020443
 Electric No. Italy: 7821050
 Electric No. Sweden: 2539979

Including: Cabinet base, door with PUR gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Sample photo

Dimensions:			Accessories:		
Length	Width	Height			
mm:	500	400	200	EKIV 37	DIN-35 Mounting rail
inch:	19.7	15.7	7.9	DS35370E1	DIN-35 Mounting rail
Materials:			EKIV 47	DIN-35 Mounting rail	
Material:	Polycarbonate		DS35470E1	DIN-35 Mounting rail	
Base colour:	RAL 7035 -light grey		FP A 54	Swing-out door/Front plate	
Cover colour:	RAL 7035 -light grey		MB 12225 AL	Swing door set	
Gasket material:	Polyurethane		FP 54	Front plate	
Temperatures:			FP 18X2-54	Front plate	
Temperature °C (short term):	-40 ... 120 °C		DRF 54	DIN rail frame set	
Temperature °C (continuous):	-40 ... 80 °C				
Temperature °F (short term):	-40 ... 250 °F		Rating:		
Temperature °F (continuous):	-40 ... 175 °F		Ingress Protection (EN 60529):	IP65	
Accessories:			Impact Resistance (EN 62262):	IK08	
EKIV 54	Mounting plate		Electrical insulation:	Totally insulated	
			Halogen free (DIN/VDE 0472, Part 815):	1	
			UV resistance:	UL 508	
			Flammability Rating:	UL 746C 5"	
			Glow Wire Test (IEC 695-2-1) °C:	960	
			Certificates:		
			Germanischer Lloyd (GL)		
			SGS Fimko		
			Lloyds Register of Shipping (LR)		
			Gost R		

