

**ARCA 604021**

**Order symbol:** ARCA 604021  
**Product nbr:** 8120012  
**Description:** Cabinet, PC  
**Remarks:** 2-point locking

**EAN:** 6418074079237  
**EI. number:**  
 Finland: 3423100  
 Electric No. 8212091100  
 Denmark:  
 Electric No. Sweden: 2500118



Sample photo

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height	Accessories:	
mm:	600	400	210	MPP ARCA 6040	Mounting plate perforated (550x350x2 mm - 26x11 mm)
inch:	23.6	15.7	8.3	MPMP ARCA 6040	Mounting plate multiperforated (550x350x2 mm - □3.6 mm)
Materials:				MPX ARCA 6040	Mounting plate (550x350 mm)
<b>Material:</b>	Polycarbonate			DRS ARCA 604021	DIN rail frame set
<b>Base colour:</b>	RAL 7035 -light grey			DRS ARCA 604030	DIN rail frame set
<b>Cover colour:</b>	RAL 7035 -light grey			IDS ARCA 6040	Inner door set
<b>Gasket material:</b>	Polyurethane			PMK ARCA 40	Pole mounting kit
Temperatures:				RCS ARCA 6040	Rain canopy set
<b>Temperature °C (short term):</b>	-40 ... 120 °C			SBK ARCA 40	Support bar kit
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			SBK ARCA 60	Support bar kit
<b>Temperature °F (short term):</b>	-40 ... 250 °F			DSP ARCA VLS	Door stopper ARCA, vertical, left, small
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			DSP ARCA VRS	Door stopper ARCA, vertical, right, small

Accessories:	
MPS ARCA 6040	Mounting plate (550x350x2 mm)

**Rating:**  
 Ingress Protection (EN 60529): IP66  
 Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C  
 Electrical insulation: Totally insulated  
 Halogen free (DIN/VDE 0472, Part 815): 1  
 UV resistance: UL 508  
 Flammability Rating: UL 94 5VA  
 Glow Wire Test (IEC 695-2-1) °C: 960

**Certificates:**

SGS Fimko  
 Gost R

