

**SOLID PC 3819 18 T-2FSH**



Sample photo

**Order symbol:** PC 3819 18 T-2FSH  
**Product nbr:** 2539545  
**Description:** Enclosure, PC  
**Remarks:** Transparent hinged cover

**EAN:** 6418074052919  
**El. number:**  
**Finland:** 3435762  
**Electric No. Sweden:** 2539545

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

Dimensions:				Accessories:	
	Length	Width	Height		
<b>mm:</b>	378	188	180	EKMXT	Mounting plate isolated
<b>inch:</b>	14.9	7.4	7.1	EKV 12	DIN-35 Mounting rail
<b>Materials:</b>				EKV 32	DIN-35 Mounting rail
<b>Material:</b>	Polycarbonate			EKMZR	Extension frame
<b>Base colour:</b>	RAL 7035 -light grey			<b>Rating:</b>	
<b>Cover screws material:</b>	Polyamide			Ingress Protection (EN 60529): IP65	
<b>Cover colour:</b>	Clear transparent			Impact Resistance (EN 62262): IK08/IK09	
<b>Cover screws colour:</b>	Grey			Electrical insulation: Totally insulated	
<b>Gasket material:</b>	Polyurethane			Halogen free (DIN/VDE 0472, Part 815): 1	
<b>Temperatures:</b>				UV resistance: UL 508	
<b>Temperature °C (short term):</b>	-40 ... 120 °C			Flammability Rating: UL 746C 5"	
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			Glow Wire Test (IEC 695-2-1) °C: 960	
<b>Temperature °F (short term):</b>	-40 ... 250 °F			<b>Certificates:</b>	
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			SGS Fimko	
<b>Accessories:</b>				Gost R	
EKMVT	Mounting plate				

