

**MNX PC 175/100 HG**



Sample photo

**Order symbol:** PC 175/100 HG  
**Product nbr:** 6011321  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074022226  
**EI. number:**  
 Finland: 3420363  
 Electric No. 8212022218  
 Denmark:  
 Electric No. Italy: 7351115  
 Electric No. Sweden: 2535566

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:		
Length	Width	Height			
mm:	180	180	100	MIN 15	DIN-15 Mounting rail
inch:	7.1	7.1	3.9	MIV 15	DIN-35 Mounting rail
<b>Materials:</b>			<b>Rating:</b>		
<b>Material:</b>	Polycarbonate		FP A 175/180	Front plate (Aluminium)	
<b>Base colour:</b>	RAL 7035 -light grey		HFP 180	Front plate hinge series	
<b>Cover screws material:</b>	Polyamide		FP 22046	Wall fastening lug (4 pcs)	
<b>Cover colour:</b>	RAL 7035 -light grey				
<b>Cover screws colour:</b>	Grey				
<b>Gasket material:</b>	TPE				
<b>Temperatures:</b>			Ingress Protection (EN 60529): IP66/IP67		
<b>Temperature °C (short term):</b>	-40 ... 120 °C		Impact Resistance (EN 62262): IK08		
<b>Temperature °C (continuous):</b>	-40 ... 80 °C		Electrical insulation: Totally insulated		
<b>Temperature °F (short term):</b>	-40 ... 250 °F		Halogen free (DIN/VDE 0472, Part 815): 1		
<b>Temperature °F (continuous):</b>	-40 ... 175 °F		UV resistance: UL 508		
<b>Accessories:</b>			Flammability Rating: UL 746C 5"		
MIV 175	Mounting plate (Galvanized steel)		Glow Wire Test (IEC 695-2-1) °C: 960		
			NEMA Class: NEMA 1, 4, 4X, 6, 12, 13		
			<b>Certificates:</b>		
			Germanischer Lloyd (GL)		
			SGS Fimko		
			Gost R		

