

MNX PC 200/125 XHT



Sample photo

Order symbol: PC 200/125 XHT
Product nbr: 6013927
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074021946
EI. number:
 Finland: 3421686
 Electric No. Denmark: 8212022661
 Electric No. Italy: 7352150
 Electric No. Sweden: 6013927

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	Length	Width	Height	Accessories:
mm:	255	180	125	MIN 15 DIN-15 Mounting rail
inch:	10.0	7.1	4.9	MIN 20 DIN-15 Mounting rail MIV 15 DIN-35 Mounting rail MIV 20 DIN-35 Mounting rail

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover screws material:	Polyamide
Cover colour:	Smoked grey
Cover screws colour:	Black
Gasket material:	Polyurethane

Accessories:

FP A 200/180	Front plate (Aluminium)
HFP 180	Front plate hinge series
FP 22046	Wall fastening lug (4 pcs)

Temperatures:

Temperature °C (short term):	-40 ... 120 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 250 °F
Temperature °F (continuous):	-40 ... 175 °F

Rating:

Ingress Protection (EN 60529):	IP66/IP67
Impact Resistance (EN 62262):	IK08
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
UV resistance:	UL 508
Flammability Rating:	UL 746C 5"
Glow Wire Test (IEC 695-2-1) °C:	960
NEMA Class:	NEMA 1, 4, 4X, 6, 12, 13

Accessories:

MIV 200	Mounting plate (Galvanized steel)
---------	-----------------------------------

Certificates:

Germanischer Lloyd (GL)
SGS Fimko
Gost R

