



Sample photo

**Order symbol:** PCTQ3 153410  
**Product nbr:** 7025700  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover (quick-locking)

**EAN:** 6418074099143  
**EI. number:**  
**Finland:** 3424199

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and quick-locking cover screws.

| Dimensions:                         |                      |       |        | Accessories:                             |                                       |
|-------------------------------------|----------------------|-------|--------|--|---------------------------------------|
|                                     | Length               | Width | Height |  |                                       |
| <b>mm:</b>                          | 340                  | 150   | 101    | TRH 34                                   | DIN-35 Mounting rail                  |
| <b>inch:</b>                        | 13.4                 | 5.9   | 4.0    | TRH 15                                   | DIN-35 Mounting rail                  |
| <b>Materials:</b>                   |                      |       |        | TF 28037                                 | Wall fastening lug (4 pcs)            |
| <b>Material:</b>                    | Polycarbonate        |       |        | TH A                                     | Grey plastic hinges (2 pcs)           |
| <b>Base colour:</b>                 | RAL 7035 -light grey |       |        | EU 3 QuickLock set 60                    | QuickLock screws (60 pcs)             |
| <b>Cover screws material:</b>       | Stainless steel      |       |        | MR 28036EU Set 60                        | Mounting screws (60 pcs)              |
| <b>Cover colour:</b>                | Clear transparent    |       |        | EU 3 Plug set 60/30                      | EU 3 Cover screw plug set 60/30       |
| <b>Gasket material:</b>             | Polyurethane         |       |        | EU 3 Plug set 60/30 BL                   | EU 3 Cover screw plug set 60/30 black |
| <b>Temperatures:</b>                |                      |       |        | <b>Rating:</b>                           |                                       |
| <b>Temperature °C (short term):</b> | -40 ... 120 °C       |       |        | Ingress Protection (EN 60529): IP66/IP67 |                                       |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C        |       |        | Impact Resistance (EN 62262): IK07/IK08  |                                       |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F       |       |        | Electrical insulation: Totally insulated |                                       |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F       |       |        | Halogen free (DIN/VDE 0472, Part 815): 1 |                                       |
| <b>Accessories:</b>                 |                      |       |        | Glow Wire Test (IEC 695-2-1) °C: 960     |                                       |
| TM 1534                             | Mounting plate       |       |        | <b>Certificates:</b>                     |                                       |
|                                     |                      |       |        | SGS Fimko                                |                                       |
|                                     |                      |       |        | Gost R                                   |                                       |

