



Sample photo

Order symbol: PCTQ3 163610
Product nbr: 7025750
Description: Enclosure, PC
Remarks: Smoked transparent cover (quick-locking)

EAN: 6418074099327
EI. number:
Finland: 3424261

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and quick-locking cover screws.

Dimensions:		Length	Width	Height	Accessories:		
mm:		360	160	95	ARM 0615	DIN-15 Mounting rail	
inch:		14.2	6.3	3.7	DH-3	DIN-35 Mounting rail	
Materials:					TRH 2036	DIN-35 Mounting rail	
Material:		Polycarbonate		TF 28037	Wall fastening lug (4 pcs)		
Base colour:		RAL 7035 -light grey		TH A	Grey plastic hinges (2 pcs)		
Cover screws material:		Stainless steel		EU 3 QuickLock set 60	QuickLock screws (60 pcs)		
Cover colour:		Clear transparent		MR 28036EU Set 60	Mounting screws (60 pcs)		
Gasket material:		Polyurethane		EU 3 Plug set 60/30	EU 3 Cover screw plug set 60/30		
Temperatures:					EU 3 Plug set 60/30 BL	EU 3 Cover screw plug set 60/30 black	
Temperature °C (short term):		-40 ... 120 °C		Rating:			
Temperature °C (continuous):		-40 ... 80 °C		Ingress Protection (EN 60529): IP66/IP67			
Temperature °F (short term):		-40 ... 250 °F		Impact Resistance (EN 62262): IK07			
Temperature °F (continuous):		-40 ... 175 °F		Electrical insulation: Totally insulated			
Accessories:					Halogen free (DIN/VDE 0472, Part 815): 1		
TM 1636		Mounting plate		Glow Wire Test (IEC 695-2-1) °C: 650			
Certificates:					SGS Fimko		
					Gost R		

