



Sample photo

**Order symbol:** P 254012  
**Product nbr:** 7094400  
**Description:** Enclosure  
**Remarks:** Polyester

**EAN:** 6418074004437  
**EI. number:**  
 Finland: 3423677  
 Electric No. Denmark: 8212005701  
 Electric No. Italy: 7331060  
 Electric No. Sweden: 2536233

Including: Base, cover with EPDM gasket and stainless steel cover screws.

Dimensions:				Rating:
	Length	Width	Height	
<b>mm:</b>	402	250	120	Ingress Protection (EN 60529): IP66
<b>inch:</b>	15.8	9.8	4.7	Impact Resistance (EN 62262): IK08
<b>Materials:</b>				Electrical insulation: Totally insulated
<b>Material:</b>	Polyester			Halogen free (DIN/VDE 0472, Part 815): 1
<b>Base colour:</b>	RAL 7001			UV resistance: UL 508
<b>Cover screws material:</b>	Stainless steel			Flammability Rating: UL 94 V0
<b>Cover colour:</b>	RAL 7001			Glow Wire Test (IEC 695-2-1) °C: 960
<b>Gasket material:</b>	EPDM			NEMA Class: NEMA 1, 4, 4X, 12, 13
<b>Temperatures:</b>				
<b>Temperature °C (short term):</b>	-50 ... 120 °C			
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			
<b>Temperature °F (short term):</b>	-60 ... 250 °F			
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			

