

**QUICK CAB PCQ 603017 T**



Sample photo

**Order symbol:** CAB PCQ 603017 T  
**Product nbr:** 8113068  
**Description:** Cabinet, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074024626  
**EI. number:**  
 Finland: 3421934  
 Electric No. Italy: 7682055  
 Electric No. Sweden: 2539210

Including: Base with screws for mounting plate/DIN-rail, internal corner plugs, cover with PUR gasket and CS 12137 cover screws.

Dimensions:		Length	Width	Height	Accessories:		
mm:		600	300	170	FA 12053	Spacer 14 mm	
inch:		23.6	11.8	6.7	EKIV 33	Mounting plate	
<b>Materials:</b>					EKIV 27	DIN-35 Mounting rail	
<b>Material:</b>		Polycarbonate		FP A 63	Swing-out door/Front plate		
<b>Base colour:</b>		RAL 7035 -light grey		MB 12225 AL	Swing door set		
<b>Cover screws material:</b>		Polyamide		DRF 33	DIN rail frame set		
<b>Cover colour:</b>		Smoked grey		PAT 12040	Hinge set		
<b>Cover screws colour:</b>		RAL 5023		<b>Rating:</b>			
<b>Gasket material:</b>		Polyurethane		Ingress Protection (EN 60529): IP66/IP67			
<b>Temperatures:</b>					Impact Resistance (EN 62262): IK08		
<b>Temperature °C (short term):</b>		-40 ... 120 °C		Electrical insulation: Totally insulated			
<b>Temperature °C (continuous):</b>		-40 ... 80 °C		Halogen free (DIN/VDE 0472, Part 815): 1			
<b>Temperature °F (short term):</b>		-40 ... 250 °F		UV resistance: UL 508			
<b>Temperature °F (continuous):</b>		-40 ... 175 °F		Flammability Rating: UL 746C 5"			
<b>Accessories:</b>					Glow Wire Test (IEC 695-2-1) °C: 960		
EKIV 63		Mounting plate		NEMA Class: NEMA 1, 4, 4X, 12, 13			
					<b>Certificates:</b>		
					Germanischer Lloyd (GL)		
					SGS Fimko		
					Lloyds Register of Shipping (LR)		
					Gost R		

