

**QUICK CAB PCQ 403023 T**



Sample photo

**Order symbol:** CAB PCQ 403023 T  
**Product nbr:** 8113158  
**Description:** Cabinet, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074011107  
**EI. number:**  
 Finland: 3421930  
 Electric No. Italy: 7682045  
 Electric No. Sweden: 2539200

Including: Base with screws for mounting plate/DIN-rail, internal corner plugs, cover with PUR gasket and CS 12137 cover screws.

Dimensions:				Accessories:	
	Length	Width	Height		
<b>mm:</b>	400	300	230	EKIV 27	DIN-35 Mounting rail
<b>inch:</b>	15.7	11.8	9.1	EKIV 37	DIN-35 Mounting rail
<b>Materials:</b>				FP A 43	Swing-out door/Front plate
<b>Material:</b>	Polycarbonate			MB 12225 AL	Swing door set
<b>Base colour:</b>	RAL 7035 -light grey			FP 12x2-43	Front plate
<b>Cover screws material:</b>	Polyamide			FP 12x3-43	Front plate
<b>Cover colour:</b>	Smoked grey			DRF 43/44	DIN rail frame set
<b>Cover screws colour:</b>	RAL 5023			PAT 12040	Hinge set
<b>Gasket material:</b>	Polyurethane			<b>Rating:</b>	
<b>Temperatures:</b>				Ingress Protection (EN 60529): IP66/IP67	
<b>Temperature °C (short term):</b>	-40 ... 120 °C			Impact Resistance (EN 62262): IK08	
<b>Temperature °C (continuous):</b>	-40 ... 80 °C			Electrical insulation: Totally insulated	
<b>Temperature °F (short term):</b>	-40 ... 250 °F			Halogen free (DIN/VDE 0472, Part 815): 1	
<b>Temperature °F (continuous):</b>	-40 ... 175 °F			UV resistance: UL 508	
<b>Accessories:</b>				Flammability Rating: UL 746C 5"	
EKIV 43	Mounting plate			Glow Wire Test (IEC 695-2-1) °C: 960	
				NEMA Class: NEMA 1, 4, 4X, 12, 13	
				<b>Certificates:</b>	
				Germanischer Lloyd (GL)	
				SGS Fimko	
				Lloyds Register of Shipping (LR)	
				Gost R	

